

CENNTRO AUTOMOTIVE CORPORATION

RF TEST REPORT

Report Type:

FCC Part 15.225 & ISED RSS-210 RF report

Model:

DCC130C130, DCC160C130, DCC160C160,
DCC190C160, DCC190C190

REPORT NUMBER:

230600383SHA-002

ISSUE DATE:

November 2, 2023

DOCUMENT CONTROL NUMBER:

TTRF15.225_V1 © 2018 Intertek



TEST REPORT

Report no.: 230600383SHA-002

Applicant: CENNTR AUTOMOTIVE CORPORATION
501 OKERSON RD FREEHOLD, NJ 07728, USA

Manufacturer: CENNTR AUTOMOTIVE CORPORATION
501 OKERSON RD FREEHOLD, NJ 07728, USA

Factory: Powercore Technology Co., Ltd.
Zone A, No.1 Yuansi Road, Jiangbei New District, Nanjing City, Jiangsu
Province, P.R. China

FCC ID: 2BBQD-DC1001

SUMMARY:


The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 15 (2021): Radio Frequency Devices (Subpart C)

ANSI C63.10 (2020): American National Standard of Procedures for Compliance Testing of Unlicensed
Wireless Devices

RSS-210 Issue 10 (December 2019): Licence-Exempt Radio Apparatus: Category I Equipment

RSS-Gen Issue 5, Amendment 1 (March 2019): General Requirements for Compliance of Radio Apparatus

PREPARED BY:

Project Engineer
Sky Yang

REVIEWED BY:

Reviewer
Eric Li

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT**Content**

| | |
|--|-----------|
| REVISION HISTORY | 4 |
| MEASUREMENT RESULT SUMMARY | 5 |
| 1 GENERAL INFORMATION | 6 |
| 1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) | 6 |
| 1.2 TECHNICAL SPECIFICATION | 6 |
| 1.3 DESCRIPTION OF TEST FACILITY | 7 |
| 2 TEST SPECIFICATIONS | 8 |
| 2.1 STANDARDS OR SPECIFICATION | 8 |
| 2.2 MODE OF OPERATION DURING THE TEST..... | 8 |
| 2.3 TEST SOFTWARE LIST | 8 |
| 2.4 TEST PERIPHERALS LIST | 8 |
| 2.5 TEST ENVIRONMENT CONDITION:..... | 8 |
| 2.6 INSTRUMENT LIST | 9 |
| 2.7 MEASUREMENT UNCERTAINTY | 10 |
| 3 FUNDAMENTAL EMISSION | 11 |
| 3.1 LIMIT | 11 |
| 3.2 MEASUREMENT PROCEDURE | 11 |
| 3.3 TEST CONFIGURATION | 12 |
| 3.4 TEST RESULTS OF FUNDAMENTAL EMISSIONS | 13 |
| 4 SPURIOUS EMISSION | 14 |
| 4.1 LIMIT | 14 |
| 4.2 MEASUREMENT PROCEDURE | 14 |
| 4.3 TEST RESULTS OF RADIATED EMISSIONS | 16 |
| 5 FREQUENCY STABILITY (TEMPERATURE VARIATION) | 19 |
| 5.1 TEST LIMIT | 19 |
| 5.2 TEST CONFIGURATION | 19 |
| 5.3 TEST PROCEDURE AND TEST SETUP | 20 |
| 5.4 TEST PROTOCOL | 20 |
| 6 FREQUENCY STABILITY (VOLTAGE VARIATION) | 21 |
| 6.1 TEST LIMIT | 21 |
| 6.2 TEST CONFIGURATION | 21 |
| 6.3 TEST PROCEDURE AND TEST SETUP | 21 |
| 6.4 TEST PROTOCOL | 22 |
| 7 CONDUCTED EMISSIONS | 23 |
| 7.1 LIMIT | 23 |
| 7.2 TEST CONFIGURATION | 23 |
| 7.3 MEASUREMENT PROCEDURE | 24 |
| 7.4 TEST RESULTS OF CONDUCTED EMISSIONS..... | 25 |
| 8 20DB BANDWIDTH | 28 |
| 8.1 LIMIT..... | 28 |
| 8.2 TEST CONFIGURATION | 28 |
| 8.3 TEST PROCEDURE AND TEST SET UP | 29 |
| 8.4 TEST PROTOCOL | 30 |
| 9 ANTENNA REQUIREMENT | 31 |

TEST REPORT**Revision History**

| Report No. | Version | Description | Issued Date |
|------------------|---------|-------------------------|------------------|
| 230600383SHA-002 | Rev. 01 | Initial issue of report | November 2, 2023 |
| | | | |
| | | | |

TEST REPORT**Measurement result summary**

| TEST ITEM | FCC REFERENCE | IC REFERENCE | RESULT |
|------------------------|-------------------|-------------------------------|--------|
| Fundamental emission | 15.225(a) (b) (c) | RSS 210 B.6 | Pass |
| Spurious emission | 15.225(d) | RSS 210 B.6 | Pass |
| Frequency stability | 15.225(e) | RSS 210 B.6 | Pass |
| Conducted emissions | 15.207 | RSS-Gen Issue 5 Clause 8.8 | Pass |
| 99% and 20dB Bandwidth | 15.215(c) | RSS-Gen Issue 5 Clause 6.6 | Pass |
| Antenna requirement | 15.203 | RSS-GEN 6.8 | Pass |

Notes: 1: NA =Not Applicable

2: Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

TEST REPORT**1 GENERAL INFORMATION****1.1 Description of Equipment Under Test (EUT)**

| | |
|-----------------------|---|
| Product name: | DC Electric Vehicle Charging Station |
| Type/Model: | DCC130C130, DCC160C130, DCC160C160, DCC190C160, DCC190C190 |
| Description of EUT: | The EUT is electric vehicle DC charger. It contains two certified modules, the WIFI/Bluetooth module FCC ID is 2AC7Z-ESPWROOM32UE(grant date:01/25/2022), the LTE module FCC ID is XMR201903EG25G. All models are electric identical except the rated power. We test DCC190C190 as representative and list the result in this report. |
| Rating: | DCC130C130: Input: 480VAC \pm 10%, 50/60Hz, 76A Output: 150-1000VDC, 200ADC Max DCC160C130: Input: 480VAC \pm 10%, 50/60Hz, 114A Output: 150-1000VDC, 200ADC Max DCC160C160: Input: 480VAC \pm 10%, 50/60Hz, 152A Output: 150-1000VDC, 200ADC Max DCC190C160: Input: 480VAC \pm 10%, 50/60Hz, 190A Output: 150-1000VDC, 200ADC Max DCC190C190: Input: 480VAC \pm 10%, 50/60Hz, 228A Output: 150-1000VDC, 200ADC Max |
| EUT type: | <input type="checkbox"/> Table top <input checked="" type="checkbox"/> Floor standing |
| Software Version: | - |
| Hardware Version: | - |
| Serial numbers: | 0231016-29 |
| Sample received date: | October 16, 2023 |
| Date of test: | October 16, 2023 ~ October 19, 2023 |

1.2 Technical Specification

| | |
|------------------|-----------------------|
| Frequency Range: | 13.56 MHz ~ 13.56 MHz |
| Modulation: | ASK |
| Antenna: | PCB antenna |

TEST REPORT**1.3 Description of Test Facility**

| | |
|------------|--|
| Name: | Intertek Testing Services Shanghai |
| Address: | Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China |
| Telephone: | 86 21 61278200 |
| Telefax: | 86 21 54262353 |

| | |
|---|--|
| The test facility is recognized, certified, or accredited by these organizations: | CNAS Accreditation Lab Registration No. CNAS L0139 |
| | FCC Accredited Lab Designation Number: CN0175 |
| | IC Registration Lab CAB identifier.: CN0014 |
| | VCCI Registration Lab Member No.: 3598 (Registration No.: R-14243, G-10845, C-14723, T-12252) |
| | A2LA Accreditation Lab Certificate Number: 3309.02 |

Fundamental emission, Spurious emission and Conducted emissions tests were sub-contracted.

| | |
|---|---|
| Name: | Shenzhen Academy of Metrology and Quality Inspection |
| Address: | NETC Building, No.4 Tongfa Road Xili, Nanshan, Guangdong, China |
| Telephone: | +86-13600419320 |
| The test facility is recognized, certified, or accredited by these organizations: | FCC Accredited Lab Designation Number: CN1165 |
| | IC Registration Lab CAB identifier.: CN0009 |

TEST REPORT**2 TEST SPECIFICATIONS****2.1 Standards or specification**

47CFR Part 15 (2021)
ANSI C63.10 (2020)
RSS-210 Issue 10 (December 2019)
RSS-Gen Issue 5, Amendment 1 (March 2019)

2.2 Mode of operation during the test

While testing, the internal modulation and continuously transmission was applied.

2.3 Test software list

| Test Items | Software | Manufacturer | Version |
|--------------------|----------|--------------|---------|
| Conducted emission | ESxS-K1 | R&S | V2.1.0 |
| Radiated emission | ES-K1 | R&S | V1.71 |

2.4 Test peripherals list

| Item No | Description | Band and Model | S/No |
|---------|-------------|----------------|------|
| | | | |
| | | | |

2.5 Test environment condition:

| Test items | Temperature | Humidity |
|-------------------------------|-------------|----------|
| Radiated emission | 26°C | 53% RH |
| Power line conducted emission | 27°C | 53% RH |

TEST REPORT**2.6 Instrument list**

| Used | Equipment | Manufacturer | Type | Internal no. | Due date |
|------|---------------------|--------------|-----------|--------------|------------|
| ☒ | Test Receiver | R&S | ESW8 | SB21192 | 2024-7-25 |
| ☒ | LISN | schwarzbeck | NNLK8130 | SB21542 | 2024-4-16 |
| ☒ | Test Receiver | R&S | ESI26 | SB3436 | 2023-10-19 |
| ☒ | Loop Antenna | Schwarzbeck | FMZB1519B | SB19178 | 2023-11-30 |
| ☒ | Broadband Antenna | Schwarzbeck | VULB9163 | SB19658/01 | 2024-8-6 |
| ☒ | Active loop antenna | Schwarzbeck | FMZB1519 | EC 5345 | 2024-07-16 |
| ☒ | Spectrum Analyzer | Keysight | N9030B | EC 6078 | 2024-06-15 |
| ☒ | Climate chamber | GWS | MT3065 | EC 6021 | 2024-03-06 |
| ☒ | Thermo-Hygrograph | ZJ1-2A | S.M.I.F. | EC 3783 | 2024-03-24 |

TEST REPORT**2.7 Measurement uncertainty**

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

| Measurement | Frequency | Expanded Uncertainty (k=2) |
|-----------------------------------|----------------|----------------------------|
| Conducted emission at mains ports | 9kHz ~ 150kHz | 3.52 dB |
| | 150kHz ~ 30MHz | 3.19 dB |
| Radiated Emissions up to 1 GHz | 30MHz ~ 1GHz | 3.06 dB |
| Radiated Emissions above 1 GHz | 1GHz ~ 6GHz | 5.02 dB |
| | 6GHz ~ 18GHz | 5.28 dB |

TEST REPORT**3 Fundamental Emission****Test result:** **Pass****3.1 Limit**


| Frequencies (MHz) | Limit at 30m (dBuV/m) | Limit at 3m (dBuV/m) |
|----------------------|--------------------------|-------------------------|
| 13.110 – 13.410 | 40.50 | 80.50 |
| 13.410 – 13.553 | 50.50 | 90.50 |
| 13.553 – 13.567 | 84.00 | 124.00 |
| 13.567 – 13.710 | 50.50 | 90.50 |
| 13.710 – 14.010 | 40.50 | 80.50 |


3.2 Measurement Procedure

- a) The EUT was placed on a 0.1m plank above the ground at a 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) Both X and Y axes of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to PK Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

TEST REPORT**3.3 Test Configuration**

TEST REPORT
3.4 Test Results of Fundamental Emissions


| Antenna Polarization | Frequency (MHz) | Corrected Reading (dBuV/m) | Correct Factor (dB/m) | Limit (dBuV/m) | Margin | Detector |
|----------------------|-----------------|----------------------------|-----------------------|----------------|--------|----------|
| X | 13.56 | 52.1 | 20.4 | 124.00 | 71.9 | PK |
| Y | 13.56 | 50.3 | 20.4 | 124.00 | 73.7 | PK |

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
 2. Corrected Reading = Original Receiver Reading + Correct Factor
 3. Margin = Limit - Corrected Reading

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
 Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,
 Limit = 40.00dBuV/m.
 Then Correct Factor = $30.20 + 2.00 - 32.00 = 0.20$ dB/m;
 Corrected Reading = $10\text{dBuV} + 0.20\text{dB/m} = 10.20\text{dBuV/m}$;
 Margin = $40.00\text{dBuV/m} - 10.20\text{dBuV/m} = 29.80\text{dB}$.

TEST REPORT

4 Spurious Emission

Test result: Pass

4.1 Limit

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490 | 2400/F(kHz) | 300 |
| 0.490 ~ 1.705 | 24000/F(kHz) | 30 |
| 1.705 ~ 30.0 | 30 | 30 |
| 30 ~ 88 | 100 | 3 |
| 88 ~ 216 | 150 | 3 |
| 216 ~ 960 | 200 | 3 |
| Above 960 | 500 | 3 |

4.2 Measurement Procedure

For Radiated emission below 30MHz:

- f) The EUT was placed on a 0.1m plank above the ground at a 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- g) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- h) Both X and Y axes of the antenna are set to make the measurement.
- i) For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- j) The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz:

- a) The EUT was placed on a 0.1m plank above the ground at a 10 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

TEST REPORT

- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:



1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. All modes of operation were evaluated and the worst-case emissions were reported

TEST REPORT**4.3 Test Results of Radiated Emissions**

The EUT has been tested in all two orthogonal planes, it has the worst case when it is in horizontal position for both below 30MHz & above 30MHz.

Test data below 30MHz:

| Frequency | Limit (dBuV/m) | Corrected Reading (dBuV/m) | Margin | Detector | Polarity |
|------------|-------------------|----------------------------------|--------|----------|----------|
| 496.500kHz | 73.7 | 44.4 | -29.3 | PK | X |
| 636.000kHz | 71.5 | 45.5 | -26.0 | PK | X |
| 5.717MHz | 69.5 | 32.2 | -37.3 | PK | X |
| 9.551MHz | 69.5 | 34.5 | -35.0 | PK | X |
| 15.365MHz | 69.5 | 31.4 | -38.1 | PK | X |
| 22.934MHz | 69.5 | 33.0 | -36.5 | PK | Y |
| 631.500kHz | 71.6 | 44.7 | -26.9 | PK | Y |
| 5.744MHz | 69.5 | 41.9 | -27.6 | PK | Y |
| 7.445MHz | 69.5 | 44.3 | -25.2 | PK | Y |
| 9.596MHz | 69.5 | 37.9 | -31.6 | PK | Y |
| 15.365MHz | 69.5 | 37.1 | -32.4 | PK | Y |
| 22.682MHz | 69.5 | 31.8 | -37.7 | PK | Y |

TEST REPORT**H****V**

TEST REPORT
Test data from 30MHz to 1000MHz:

| Antenna Polarization | Frequency | Limit (dBuV/m) | Corrected Reading (dBuV/m) | Margin | Detector |
|----------------------|-----------|----------------|----------------------------|--------|----------|
| H | 59.127 | 39.0 | 23.4 | 15.6 | QP |
| H | 89.950 | 43.5 | 23.6 | 19.9 | QP |
| H | 161.708 | 43.5 | 21.5 | 22.0 | QP |
| H | 251.994 | 46.4 | 34.0 | 12.5 | QP |
| H | 350.007 | 46.4 | 35.2 | 11.2 | QP |
| H | 419.916 | 46.4 | 33.0 | 13.4 | QP |
| V | 31.997 | 39.0 | 20.9 | 18.1 | QP |
| V | 32.100 | 39.0 | 23.2 | 15.8 | QP |
| V | 66.904 | 39.0 | 30.7 | 8.3 | QP |
| V | 84.015 | 39.0 | 37.5 | 1.5 | QP |
| V | 146.476 | 43.5 | 27.9 | 15.6 | QP |
| V | 226.757 | 46.4 | 38.6 | 7.8 | QP |
| V | 350.000 | 46.4 | 40.5 | 5.9 | QP |

Remark:

1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
2. Corrected Reading = Original Receiver Reading + Correct Factor
3. Margin = Limit - Corrected Reading
4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB, Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV, Limit = 40.00dBuV/m.

Then Correct Factor = $30.20 + 2.00 - 32.00 = 0.20$ dB/m;

Corrected Reading = $10\text{dBuV} + 0.20\text{dB/m} = 10.20\text{dBuV/m}$;


Margin = $40.00\text{dBuV/m} - 10.20\text{dBuV/m} = 29.80\text{dB}$.

TEST REPORT**5 Frequency Stability (Temperature Variation)**

Test result: PASS

5.1 Test limit

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage.

5.2 Test Configuration

TEST REPORT**5.3 Test procedure and test setup**

Test Procedure as per ANSI 63.10 clause 6.8.1.

5.4 Test protocol


| Voltage (V) | Temp (°C) | Freq measured (MHz) | Freq nominal (MHz) | Tolerance (%) | Limit (%) |
|----------------|--------------|------------------------|-----------------------|---------------|--------------|
| 480 | -20 | 13.5593 | 13.56 | -0.005 | ±.01 |
| | -10 | 13.5597 | | -0.002 | |
| | 0 | 13.5600 | | 0 | |
| | 10 | 13.5600 | | 0 | |
| | 20 | 13.5600 | | 0 | |
| | 30 | 13.5602 | | 0.001 | |
| | 40 | 13.5592 | | -0.006 | |
| | 50 | 13.5596 | | -0.003 | |

TEST REPORT**6 Frequency Stability (Voltage Variation)**

Test result: PASS

6.1 Test limit

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

6.2 Test Configuration**6.3 Test procedure and test setup**

Test Procedure as per ANSI 63.10 clause 6.8.2.


TEST REPORT**6.4 Test protocol**

| Temp (°C) | Voltage (V) | Freq Measured (MHz) | Freq nominal (MHz) | Tolerance (%) | Limit (%) |
|--------------|----------------|------------------------|-----------------------|---------------|--------------|
| 20 | 432 | 13.5604 | 13.56 | 0.003 | ±0.01 |
| | 480 | 13.5600 | | 0 | |
| | 528 | 13.5603 | | 0.002 | |

TEST REPORT**7 Conducted emissions**Test result: **Pass****7.1 Limit**

| Frequency of Emission (MHz) | Conducted Emissions Limit (dBuV) | |
|-----------------------------|----------------------------------|----|
| | QP | AV |
| 0.15 ~ 0.5 | 79 | 66 |
| 0.5 ~ 30 | 73 | 60 |

* Decreases with the logarithm of the frequency.

7.2 Test Configuration

TEST REPORT**7.3 Measurement Procedure**

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the $50\ \Omega$ LISN port (to which the EUT is connected), where permitted, terminated into a $50\ \Omega$ measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the $50\ \Omega$ measuring port is terminated by a measuring instrument having $50\ \Omega$ input impedance. All other ports are terminated in $50\ \Omega$ loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.


The bandwidth of the test receiver is set at 9 kHz.

TEST REPORT

7.4 Test Results of Conducted Emissions

Test Voltage: 480VAC/60Hz

L1 Line




| Frequency [MHz] | Level [dBμV] | Limit [dBμV] | Delta [dB] | Detector |
|-----------------|--------------|--------------|------------|----------|
| 0.2035 | 58.80 | 79.00 | 20.20 | QP |
| 0.2035 | 46.73 | 66.00 | 19.27 | AV |
| 1.2144 | 32.02 | 73.00 | 40.98 | QP |
| 1.2144 | 26.63 | 60.00 | 33.37 | AV |
| 2.5404 | 36.76 | 73.00 | 36.24 | QP |
| 2.5404 | 28.02 | 60.00 | 31.98 | AV |
| 3.3835 | 34.26 | 73.00 | 38.74 | QP |
| 3.3835 | 22.19 | 60.00 | 37.81 | AV |
| 13.5602 | 54.57 | 73.00 | 18.43 | QP |
| 13.5602 | 53.33 | 60.00 | 6.67 | AV |
| 16.4325 | 51.59 | 73.00 | 21.41 | QP |
| 16.4325 | 49.54 | 60.00 | 10.46 | AV |

Remark:

1. Correct Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.
2. Level = Original Receiver Reading + Correct Factor
3. Delta = Limit - Level
4. If the PK Level is lower than AV limit, the AV test can be elided.

TEST REPORT




| Frequency [MHz] | Level [dBμV] | Limit [dBμV] | Delta [dB] | Detector |
|-----------------|--------------|--------------|------------|----------|
| 0.2028 | 58.39 | 79.00 | 20.61 | QP |
| 0.2028 | 45.28 | 66.00 | 20.72 | AV |
| 1.3737 | 34.19 | 73.00 | 38.81 | QP |
| 1.3737 | 23.27 | 60.00 | 36.73 | AV |
| 2.9555 | 34.14 | 73.00 | 38.86 | QP |
| 2.9555 | 24.17 | 60.00 | 35.83 | AV |
| 13.5593 | 46.09 | 73.00 | 26.91 | QP |
| 13.5593 | 44.98 | 60.00 | 15.02 | AV |
| 16.4201 | 46.39 | 73.00 | 26.61 | QP |
| 16.4201 | 44.11 | 60.00 | 15.89 | AV |
| 27.9743 | 46.46 | 73.00 | 26.54 | QP |
| 27.9743 | 41.99 | 60.00 | 18.01 | AV |

Remark:

1. Correct Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.
2. Level = Original Receiver Reading + Correct Factor
3. Delta = Limit - Level
4. If the PK Level is lower than AV limit, the AV test can be elided.

TEST REPORT

L3 Line



| Frequency [MHz] | Level [dBμV] | Limit [dBμV] | Delta [dB] | Detector |
|-----------------|--------------|--------------|------------|----------|
| 0.1975 | 57.80 | 79.00 | 21.20 | QP |
| 0.1975 | 45.72 | 66.00 | 20.28 | AV |
| 1.2689 | 42.99 | 73.00 | 30.01 | QP |
| 1.2689 | 31.52 | 60.00 | 28.48 | AV |
| 2.1126 | 44.99 | 73.00 | 28.01 | QP |
| 2.1126 | 26.89 | 60.00 | 33.11 | AV |
| 2.5305 | 45.48 | 73.00 | 27.52 | QP |
| 2.5305 | 29.16 | 60.00 | 30.84 | AV |
| 13.5598 | 53.17 | 73.00 | 19.83 | QP |
| 13.5598 | 52.13 | 60.00 | 7.87 | AV |
| 16.4122 | 48.78 | 73.00 | 24.22 | QP |
| 16.4122 | 46.62 | 60.00 | 13.38 | AV |

Remark:


1. Correct Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.
2. Level = Original Receiver Reading + Correct Factor
3. Delta = Limit - Level
4. If the PK Level is lower than AV limit, the AV test can be elided.

TEST REPORT**8 20dB Bandwidth**

Test result: Pass

8.1 Limit

The 20dB bandwidth should be fallen in the allocated operating frequency range.
No limit for 99% bandwidth.

8.2 Test configuration

TEST REPORT**8.3 Test procedure and test set up**

The measurement was applied in a 3m semi-anechoic chamber.


The center of the loop antenna shall be 1 m above the horizontal metal ground plane.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set RBW = 1 % to 5 % of the OBW
3. Set VBW $\geq 3 \cdot$ RBW
4. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
5. Use the 99 % power bandwidth function of the instrument (if available).
6. the 20dB bandwidth is also measured with the same setting.

TEST REPORT
8.4 Test protocol

| | Lower point (MHz) | Higher point (MHz) | Bandwidth (kHz) | Allocated bandwidth (MHz) |
|-----------------------|----------------------|-----------------------|--------------------|------------------------------|
| 20dB Bandwidth | 13.560278 | 13.561141 | 0.863 | 13.553 ~ 13.567 |
| Occupied bandwidth | 13.559209 | 13.562081 | 2.872 | 13.553 ~ 13.567 |



TEST REPORT

9 Antenna requirement

Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Result:

EUT uses permanently attached antenna to the intentional radiator, so it can comply with the provisions of this section.

***** END *****