

Label outline
(represented in green)



Bleed (+1.5 mm)

Area for DataMatrix
(18x18 mm max)

Layout source file:

225862_KEYSTONE LABEL LAYOUT_ed_2024-11-04.svg

Blank label:

Article no. 313525 (50 x 30 mm, white)

Label content specification:

Thermal transfer printing, in black, compliant to RoHS & REACH

White markings on black background, acc. to layout above

Graphic safety margin: 1.5 mm on the periphery, and all around the DataMatrix

Texts: font Arial 6 (regular and bold)

Height of regulatory symbols:

- CE, FCC, UKCA: 5 mm
- WEEE (crossed-out dustbin with bar): 7 mm

Variable fields (" "):

- "KEYSTONE X" acc. to the product commercial name (e.g. KEYSTONE 6)
- "HBKXXXXXXXXXXXXXXXX" acc. to the product designation, without spaces if necessary, (e.g. HBK0620005ALUTANPUM80)
- PN "XXXXX" acc. to the product number
- SN "0000-0000000-00000000" serial number, made up of: Production site-Work order-PCBA SN
- FCC ID "2BBS9-XXXXX" acc. to the registered FCC product identification code:
(first portion of the FCC ID is the grantee code, and second portion is the product code)
 - HBK06 for KEYSTONE 6 hub
 - HBK04 for KEYSTONE 4 hub
- DATE OF MFR "MM-YYYY" acc. to current month and year
- MADE IN "SWITZERLAND" acc. to the production country
- DataMatrix ECC200 code, containing fields PN, SN, and DATE OF MFR

Title: LABEL KEYSTONE HUB	Designation: KEYSTONE mixed		Creation:	02-Sep-22	JDN
	State: SERIE		Drawn:	15-Nov-24	JDN
			Controlled:	15-Nov-24	DPZ
	Scale:		Change No.:	CN00068	
 Fischer Fischer Connectors SA Ch. du Glapin 20 CH - 1162 Saint-Prex	1:1		Sheet:	ERP No.:	Revision:
			1/1	225862	7
CONFIDENTIAL - THIS DRAWING IS OUR PROPERTY AND CANNOT BE DIFFUSE WITHOUT OUR PRIOR WRITTEN CONSENT			PLM No.:	225862	