

## FCC RF Exposure

EUT Description: Electronic Knob Door Lock

ModelNo.:ES0001, ES0011, ES0021, ES0031, ES0041

FCC ID: 2BBSH-AST2017

Equipment type: portable equipment

According to KDB 447498 and part 2.1093, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numericasimulation, is not required when the corresponding SAR Test Exclusion Thresholocondition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances < 50 mm, the 1-g and 10-g SAR testexclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance mm})] \cdot [f(\text{GHz})] < 3.0$  for 1-g SAR, and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

$$\text{EIRP} = \text{E}_{\text{Meas}} + 20 \log(\text{d}_{\text{meas}}) - 104.7$$

EIRP is the equivalent isotropically radiated power,

$\text{E}_{\text{Meas}}$  in dBm is the field strength of the emission at the measurement distance, in dB u V/m

$\text{d}_{\text{meas}}$  is the measurement distance, in m

Field strength(dBuV/m)	EIRP(dBm)	Max tune-up(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
93.61	-1.5476	0.7002	2402	5	0.217	3.0
93.52	-1.7076	0.6749	2440	5	0.211	3.0
91.82	-3.3376	0.4637	2480	5	0.146	3.0

Conclusion : SAR exempted