



Shenzhen CTL Testing Technology Co., Ltd.
Tel: +86-755-89486194 E-mail: ctl@ctl-lab.com

TEST REPORT

FCC PART 15 SUBPART E 15.407

Report Reference No. : CTL2401122031-WF04

Compiled by:
(position+printed name+signature)

Happy Guo
(File administrators)

Tested by:
(position+printed name+signature)

Snow Tang
(Test Engineer)

Approved by:
(position+printed name+signature)

Ivan Xie
(Manager)



Product Name : ADTH NEXTGEN TV Box

Model/Type reference : X23A3U-Z2

List Model(s) : X23A3U-XX

Trade Mark : ADTH

FCC ID : 2BBTW-X23A3U-Z1

Applicant's name : Atlanta DTH, Inc.

Address of applicant : 40 Technology Parkway South, Suite 210,
Peachtree Corners, GA 30092

Test Firm : Shenzhen CTL Testing Technology Co., Ltd.

Address of Test Firm : Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road,
Nanshan District, Shenzhen, China 518055

Test specification :

Standard : 47 CFR FCC Part 15 Subpart E 15.407

TRF Originator : Shenzhen CTL Testing Technology Co., Ltd.

Master TRF : Dated 2011-01

Date of receipt of test item : Feb.26, 2024

Date of Test Date : Feb.26, 2024-Mar.06, 2024

Date of Issue : Mar.07, 2024

Result : Pass

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

TEST REPORT

Test Report No. :	CTL2401122031-WF04	Mar.07, 2024
		Date of issue

Equipment under Test : ADTH NEXTGEN TV Box

Sample No : CTL2401122031

Model /Type : X23A3U-Z2

Listed Models : X23A3U-XX

Applicant : **Atlanta DTH, Inc.**

Address : 40 Technology Parkway South, Suite 210,
Peachtree Corners, GA 30092

Manufacturer : **Atlanta DTH, Inc.**

Address : 40 Technology Parkway South, Suite 210,
Peachtree Corners, GA 30092

Test result	Pass *
--------------------	---------------

* In the configuration tested, the EUT complied with the standards specified page 5.

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.

** Modified History **

Table of Contents

	Page
1. SUMMARY	5
1.1. TEST STANDARDS	5
1.2. TEST DESCRIPTION	5
1.3. TEST FACILITY	6
1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY	6
1.5. AUXILIARY TEST EQUIPMENT INFORMATION	7
2. GENERAL INFORMATION	8
2.1. ENVIRONMENTAL CONDITIONS	8
2.2. GENERAL DESCRIPTION OF EUT	8
2.3. DESCRIPTION OF TEST MODES AND TEST FREQUENCY	9
2.4. EQUIPMENTS USED DURING THE TEST	10
2.5. RELATED SUBMITTAL(S) / GRANT (S)	10
2.6. MODIFICATIONS	10
3. TEST CONDITIONS AND RESULTS	11
3.1. CONDUCTED EMISSIONS TEST	11
3.2. RADIATED EMISSIONS	14
3.3. ANTENNA REQUIREMENT	19
4. TEST SETUP PHOTOS OF THE EUT	20
5. PHOTOS OF THE EUT	21

1. SUMMARY

1.1. TEST STANDARDS

The tests were performed according to following standards:

FCC Rules Part 15 Subpart E—Unlicensed National Information Infrastructure Devices

ANSI C63.10: 2013: American National Standard for Testing Unlicensed Wireless Devices

KDB789033 D02: General UNII Test Procedures New Rules v02r01

v01r03 and KDB 662911 D01 Multiple Transmitter Output v02r01 is required to be used for this kind of FCC 15.407 UII device.

1.2. Test Description

FCC Requirement		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.407(a)	Emission Bandwidth(26dB Bandwidth)	N/A
FCC Part 15.407(e)	Minimum Emission Bandwidth(6dB Bandwidth)	N/A
FCC Part 15.407(a)	Maximum Conducted Output Power	N/A
FCC Part 15.407(a)	Peak Power Spectral Density	N/A
FCC Part 15.407(g)	Frequency Stability	N/A
FCC Part 15.407(b)	Undesirable emission	N/A
FCC Part 15.407(b)/15.205/15.209	Radiated Emissions	PASS
FCC Part 15.203	Antenna Requirement	N/A

1.3. Test Facility

1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co.,Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L7497

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No. 4343.01

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

IC Registration No.: 9618B

CAB identifier: CN0041

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Registration No.: 9618B on Jan. 22, 2019.

FCC-Registration No.: 399832

Designation No.: CN1216

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 399832, December 08, 2017.

1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Measurement Uncertainty	Notes
Transmitter power conducted	±0.57 dB	(1)
Transmitter power Radiated	±2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	±2.20 dB	(1)
Occupied Bandwidth	±0.01ppm	(1)
Radiated Emission9KHz~30MHz	±3.66dB	(1)
Radiated Emission 30~1000MHz	±4.10dB	(1)
Radiated Emission Above 1GHz	±4.32dB	(1)
Conducted Disturbance0.15~30MHz	±3.20dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.5. Auxiliary test equipment information

Manufacturer	Description	Model	Serial Number
TPV Display Technology (Xiamen) Co. LTD	LCD TV	T1951MD	LYSL3YA000234 NG
GUANGDONG SENEASY INTELLIGENT TECHNOLOGY CO.,LTD	Remote Control	B19AG	---

2. GENERAL INFORMATION

2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

2.2. General Description of EUT

Product Name:	ADTH NEXTGEN TV Box			
Model/Type reference:	X23A3U-Z2			
Power supply:	Input: 100-240V~ 50/60Hz 0.6A Output: 12V-1.5A			

5G WIFI :

	20MHz system	40MHz system	80MHz system	160MHz system
Supported type:	802.11a 802.11n 802.11ac	802.11n 802.11ac	802.11ac	N/A
Operation frequency:	5180-5240MHz 5745-5825MHz	5190 - 5230MHz 5755MHz,5795MHz	5210MHz 5775MHz	N/A
Modulation:	OFDM	OFDM	OFDM	N/A
Channel number:	11	4	2	N/A
Channel separation:	20MHz	40MHz	80MHz	N/A
Antenna type:	Ant 1: PIFA Antenna Ant 2: PCB Antenna			
Antenna gain:	Ant 1: 5.39dBi Ant 2: 4.24dBi MIMO(Antenna 1+Antenna 2) Directional Gain (dBi): 7.84dBi			

Note1: For more details, please refer to the user's manual of the EUT.

Note2: Antenna gain provided by the applicant.

Note3: This report is only for 5G WIFI.

Note4: Directional gain= $10\log[(10^{G1/20}+10^{G2/20}+\dots+10^{GN/20})^2/N_{ANT}]$ dBi [Note the "20" s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]

2.3. Description of Test Modes and Test Frequency

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing.

All test performed at the low, middle and high of operational frequency range of each mode.

Operation Frequency List WIFI on 5G Band:

Operating band	20MHz		40MHz		80MHz	
	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
U-NII 1 (5150MHz-5250MHz)	36	5180	38	5190	42	5210
	40	5200				
	44	5220				
	48	5240	46	5230		
	136	5680				
	140	5700				
U-NII 3 (5725MHz-5850MHz)	149	5745	151	5755	155	5775
	153	5765				
	157	5785	159	5795		
	161	5805				
	165	5825	--	--	--	--

Note:

- "Means no channel(s) available any more.
- The line display in grey is those Channels/Frequencies select to test in this report for each operation mode.

Data Rate Used:

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate
Maximum Conducted Output Power Power Spectral Density Emission Bandwidth(26dBm Bandwidth) Minimum Emission Bandwidth(6dBm Bandwidth) Undesirable emission Frequency Stability	11a/OFDM	6 Mbps
	11n(20MHz), 11ac(20MHz)/OFDM	7.2 Mbps
	11n(40MHz), 11ac(40MHz)/OFDM	15.0Mbps
	11ac(80MHz)/OFDM	65.0Mbps

2.4. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ESH2-Z5	860014/010	2023/05/04	2024/05/03
Double cone logarithmic antenna	Schwarzbeck	VULB 9168	824	2023/02/13	2026/02/12
Horn Antenna	Ocean Microwave	OBH100400	26999002	2021/12/22	2024/12/21
EMI Test Receiver	R&S	ESCI	1166.5950.03	2023/05/04	2024/05/03
Spectrum Analyzer	Agilent	E4407B	MY41440676	2023/05/05	2024/05/04
Spectrum Analyzer	Agilent	N9020A	UE22220290	2023/05/05	2024/05/04
Spectrum Analyzer	Keysight	N9020A	MY53420874	2023/05/05	2024/05/04
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2021/12/23	2024/12/22
Active Loop Antenna	Da Ze	ZN30900A	/	2021/05/13	2024/05/12
Amplifier	Agilent	8449B	3008A02306	2023/05/04	2024/05/03
Amplifier	Agilent	8447D	2944A10176	2023/05/04	2024/05/03
Amplifier	Brief&Smart	LNA-4018	2104197	2023/05/05	2024/05/04
Temperature/Humidity Meter	Ji Yu	MC501	/	2023/05/09	2024/05/08
Power Sensor	Agilent	U2021XA	MY55130004	2023/05/05	2024/05/04
Power Sensor	Agilent	U2021XA	MY55130006	2023/05/05	2024/05/04
Power Sensor	Agilent	U2021XA	MY54510008	2023/05/05	2024/05/04
Power Sensor	Agilent	U2021XA	MY55060003	2023/05/05	2024/05/04
Spectrum Analyzer	RS	FSP	1164.4391.38	2023/05/05	2024/05/04
LISN	R&S	ESH2-Z5	860014/010	2023/05/04	2024/05/03
Test Software					
Name of Software		Version			
TST-PASS		V1.1.0			
EZ_EMC(Below 1GHz)		V1.1.4.2			
EZ_EMC((Above 1GHz)		V1.1.4.2			

The calibration interval was one year

2.5. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.

2.6. Modifications

No modifications were implemented to meet testing criteria.

3. TEST CONDITIONS AND RESULTS

3.1. Conducted Emissions Test


LIMIT

According to FCC CFR Title 47 Part 15 Subpart C Section 15.207, AC Power Line Conducted Emissions Limits for Licence-Exempt Radio Apparatus as below:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a Laser Projector op system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10:2013.
2. Support equipment, if needed, was placed as per ANSI C63.10:2013.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2013.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST RESULTS

Remark: 802.11a / 802.11n (HT20) / 802.11ac (HT20) / 802.11n (HT40) / 802.11ac (HT40) / 802.11ac (HT80) mode all have been tested, only worse case is reported

Test Mode	WIFI	Line:	L																																																
<p>SCAN TABLE: "Voltage (9K-30M) FIN" Short Description: 150K-30M Voltage</p>																																																			
<p>MEASUREMENT RESULT: "CTL240304023_fin"</p>																																																			
<p>3/5/2024 12:15AM</p> <table><thead><tr><th>Frequency MHz</th><th>Level dBpV</th><th>Transad dB</th><th>Limit dBpV</th><th>Margin dB</th><th>Detector</th><th>Line</th><th>PE</th></tr></thead><tbody><tr><td>0.172500</td><td>39.60</td><td>10.0</td><td>65</td><td>25.2</td><td>QP</td><td>L1</td><td>GND</td></tr><tr><td>0.195000</td><td>37.70</td><td>10.0</td><td>64</td><td>26.1</td><td>QP</td><td>L1</td><td>GND</td></tr><tr><td>0.312000</td><td>32.90</td><td>10.0</td><td>60</td><td>27.0</td><td>QP</td><td>L1</td><td>GND</td></tr><tr><td>0.343500</td><td>39.40</td><td>10.0</td><td>59</td><td>19.7</td><td>QP</td><td>L1</td><td>GND</td></tr><tr><td>25.705500</td><td>31.60</td><td>10.5</td><td>60</td><td>28.4</td><td>QP</td><td>L1</td><td>GND</td></tr></tbody></table>				Frequency MHz	Level dBpV	Transad dB	Limit dBpV	Margin dB	Detector	Line	PE	0.172500	39.60	10.0	65	25.2	QP	L1	GND	0.195000	37.70	10.0	64	26.1	QP	L1	GND	0.312000	32.90	10.0	60	27.0	QP	L1	GND	0.343500	39.40	10.0	59	19.7	QP	L1	GND	25.705500	31.60	10.5	60	28.4	QP	L1	GND
Frequency MHz	Level dBpV	Transad dB	Limit dBpV	Margin dB	Detector	Line	PE																																												
0.172500	39.60	10.0	65	25.2	QP	L1	GND																																												
0.195000	37.70	10.0	64	26.1	QP	L1	GND																																												
0.312000	32.90	10.0	60	27.0	QP	L1	GND																																												
0.343500	39.40	10.0	59	19.7	QP	L1	GND																																												
25.705500	31.60	10.5	60	28.4	QP	L1	GND																																												
<p>MEASUREMENT RESULT: "CTL240304023_fin2"</p>																																																			
<p>3/5/2024 12:15AM</p> <table><thead><tr><th>Frequency MHz</th><th>Level dBpV</th><th>Transad dB</th><th>Limit dBpV</th><th>Margin dB</th><th>Detector</th><th>Line</th><th>PE</th></tr></thead><tbody><tr><td>0.339000</td><td>32.10</td><td>10.0</td><td>49</td><td>17.1</td><td>AV</td><td>L1</td><td>GND</td></tr><tr><td>0.343500</td><td>37.80</td><td>10.0</td><td>49</td><td>11.3</td><td>AV</td><td>L1</td><td>GND</td></tr><tr><td>0.636000</td><td>20.00</td><td>10.0</td><td>46</td><td>26.0</td><td>AV</td><td>L1</td><td>GND</td></tr><tr><td>12.678000</td><td>24.20</td><td>10.9</td><td>50</td><td>25.8</td><td>AV</td><td>L1</td><td>GND</td></tr><tr><td>13.114500</td><td>24.10</td><td>11.0</td><td>50</td><td>25.9</td><td>AV</td><td>L1</td><td>GND</td></tr></tbody></table>				Frequency MHz	Level dBpV	Transad dB	Limit dBpV	Margin dB	Detector	Line	PE	0.339000	32.10	10.0	49	17.1	AV	L1	GND	0.343500	37.80	10.0	49	11.3	AV	L1	GND	0.636000	20.00	10.0	46	26.0	AV	L1	GND	12.678000	24.20	10.9	50	25.8	AV	L1	GND	13.114500	24.10	11.0	50	25.9	AV	L1	GND
Frequency MHz	Level dBpV	Transad dB	Limit dBpV	Margin dB	Detector	Line	PE																																												
0.339000	32.10	10.0	49	17.1	AV	L1	GND																																												
0.343500	37.80	10.0	49	11.3	AV	L1	GND																																												
0.636000	20.00	10.0	46	26.0	AV	L1	GND																																												
12.678000	24.20	10.9	50	25.8	AV	L1	GND																																												
13.114500	24.10	11.0	50	25.9	AV	L1	GND																																												

Test Mode	WIFI	Line:	N																																																
SCAN TABLE: "Voltage (9K-30M).FIN" Short Description: 150K-30M Voltage																																																			
MEASUREMENT RESULT: "CTL240304022_fin" 3/5/2024 12:12AM																																																			
<table><thead><tr><th>Frequency MHz</th><th>Level dBpV</th><th>Transd dB</th><th>Limit dBpV</th><th>Margin dB</th><th>Detector</th><th>Line</th><th>PE</th></tr></thead><tbody><tr><td>0.172500</td><td>39.90</td><td>10.0</td><td>65</td><td>24.9</td><td>QP</td><td>N</td><td>GND</td></tr><tr><td>0.186000</td><td>38.00</td><td>10.0</td><td>64</td><td>26.2</td><td>QP</td><td>N</td><td>GND</td></tr><tr><td>0.190500</td><td>38.00</td><td>10.0</td><td>64</td><td>26.0</td><td>QP</td><td>N</td><td>GND</td></tr><tr><td>12.750000</td><td>33.10</td><td>10.9</td><td>60</td><td>26.9</td><td>QP</td><td>N</td><td>GND</td></tr><tr><td>27.492000</td><td>34.50</td><td>10.3</td><td>60</td><td>25.5</td><td>QP</td><td>N</td><td>GND</td></tr></tbody></table>				Frequency MHz	Level dBpV	Transd dB	Limit dBpV	Margin dB	Detector	Line	PE	0.172500	39.90	10.0	65	24.9	QP	N	GND	0.186000	38.00	10.0	64	26.2	QP	N	GND	0.190500	38.00	10.0	64	26.0	QP	N	GND	12.750000	33.10	10.9	60	26.9	QP	N	GND	27.492000	34.50	10.3	60	25.5	QP	N	GND
Frequency MHz	Level dBpV	Transd dB	Limit dBpV	Margin dB	Detector	Line	PE																																												
0.172500	39.90	10.0	65	24.9	QP	N	GND																																												
0.186000	38.00	10.0	64	26.2	QP	N	GND																																												
0.190500	38.00	10.0	64	26.0	QP	N	GND																																												
12.750000	33.10	10.9	60	26.9	QP	N	GND																																												
27.492000	34.50	10.3	60	25.5	QP	N	GND																																												
MEASUREMENT RESULT: "CTL240304022_fin2" 3/5/2024 12:12AM																																																			
<table><thead><tr><th>Frequency MHz</th><th>Level dBpV</th><th>Transd dB</th><th>Limit dBpV</th><th>Margin dB</th><th>Detector</th><th>Line</th><th>PE</th></tr></thead><tbody><tr><td>0.343500</td><td>34.00</td><td>10.0</td><td>49</td><td>15.1</td><td>AV</td><td>N</td><td>GND</td></tr><tr><td>0.640500</td><td>18.40</td><td>10.0</td><td>46</td><td>27.6</td><td>AV</td><td>N</td><td>GND</td></tr><tr><td>0.910500</td><td>17.90</td><td>10.1</td><td>46</td><td>28.1</td><td>AV</td><td>N</td><td>GND</td></tr><tr><td>12.750000</td><td>24.30</td><td>10.9</td><td>50</td><td>25.7</td><td>AV</td><td>N</td><td>GND</td></tr></tbody></table>				Frequency MHz	Level dBpV	Transd dB	Limit dBpV	Margin dB	Detector	Line	PE	0.343500	34.00	10.0	49	15.1	AV	N	GND	0.640500	18.40	10.0	46	27.6	AV	N	GND	0.910500	17.90	10.1	46	28.1	AV	N	GND	12.750000	24.30	10.9	50	25.7	AV	N	GND								
Frequency MHz	Level dBpV	Transd dB	Limit dBpV	Margin dB	Detector	Line	PE																																												
0.343500	34.00	10.0	49	15.1	AV	N	GND																																												
0.640500	18.40	10.0	46	27.6	AV	N	GND																																												
0.910500	17.90	10.1	46	28.1	AV	N	GND																																												
12.750000	24.30	10.9	50	25.7	AV	N	GND																																												

3.2. Radiated Emissions

Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Undesirable emission limits

Requirement	Limit(EIRP)	Limit (Field strength at 3m) <small>Note1</small>
15.407(b)(1)	PK:-27(dBm/MHz)	PK:68.2(dB μ V/m)
15.407(b)(2)		
15.407(b)(3)		
15.407(b)(4)		

Note1: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m}, \text{ where } P \text{ is the eirp (Watts)}$$


- (5) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209
- (6) In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



Test Procedure

1. Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 40GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Bilog Antenna	3
1GHz-18GHz	Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:


Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak


TEST RESULTS

Remark:

1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
2. All 802.11a / 802.11n (HT20) / 802.11ac (HT20) / 802.11n (HT40) / 802.11ac (HT40) / 802.11ac (HT80) modes have been tested for below 1GHz test, only the worst case 802.11n (HT20) low channel of U-NII 1 band was recorded.
3. All 802.11a / 802.11n (HT20) / 802.11ac (HT20) / 802.11n (HT40) / 802.11ac (HT40) / 802.11ac (HT80) modes have been tested for above 1GHz test, only the worst case 802.11n (HT20) was recorded.
4. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

For 30MHz-1GHz





3.3. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited


And according to FCC 47 CFR Section 15.407 (a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance


The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction

The maximum gain of Antenna 1 was 5.39dBi and Antenna 2 was 4.24 dBi



4. Test Setup Photos of the EUT



5. Photos of the EUT

Reference to the test report No. CTL2401122031-WF01

***** End of Report *****