



SAR Test Report

For

Applicant Name: M/s Linkwell Telesystems Pvt. Ltd.
Address: B-45 & 46, Electronics Complex, Kushaiguda, Hyderabad-500062, Telangana, India
EUT Name: Tablet
Model Number: VT 31
Brand Name: VISIONTEK

Issued By

Company Name: BTF Testing Lab (Shenzhen) Co., Ltd.
Address: F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Report Number: BTF230529R00101
Test Standards: 47 CFR Part 2.1093 IEEE1528-2013 IEEE C95.1-2019 KDB 447498 D01 KDB 865664 D01 KDB 865664 D02 KDB 941225 D01 KDB 941225 D05 KDB 941225 D06 KDB 248227 D01 KDB 616217 D04 KDB 690783 D01
FCC ID: 2BBV2-VT31
Test Conclusion: Pass
Test Date: 2023-06-14 to 2023-06-15
Date of Issue: 2023-06-16

Prepared By: Monica Zhou
Date: 2023-06-16
Approved By: Ryan.CJ
Date: 2023-06-16



Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.

Revision History		
Version	Issue Date	Revisions Content
R_V0	2023-06-16	Original
<i>Note:</i>		<i>Once the revision has been made, then previous versions reports are invalid.</i>

Table of Contents

1. Introduction	4
1.1 Identification of Testing Laboratory	4
1.2 Identification of the Responsible Testing Location	4
1.3 Laboratory Condition	4
1.4 Announcement	4
2. Product Information	5
2.1 Application Information	5
2.2 Manufacturer Information	5
2.3 Factory Information	5
2.4 General Description of Equipment under Test (EUT)	5
2.5 Equipment under Test Ancillary Equipment	5
2.6 Technical Information	5
3. Summary of Test Results	6
3.1 Test Standards	6
3.2 Device Category and SAR Limit	7
3.3 Test Result Summary	7
3.4 Test Uncertainty	8
4. Measurement System	10
4.1 Specific Absorption Rate (SAR) Definition	10
4.2 MVG SAR System	10
5. System Verification	14
5.1 Purpose of System Check	14
5.2 System Check Setup	15
6. TEST POSITION CONFIGURATIONS	15
6.1 Head Exposure Conditions	15
6.2 Body-worn Position Conditions	17
6.3 Hotspot Mode Exposure Position Conditions	18
6.4 Product Specific 10g Exposure Consideration	18
7. Measurement Procedure	19
7.1 Measurement Process Diagram	19
7.2 SAR Scan General Requirement	20
7.3 Measurement Procedure	21
7.4 Area & Zoom Scan Procedure	21
8. Conducted RF Output Power	22
8.1 GSM	22
8.2 LTE	23
8.3 Wi-Fi	28
8.4 Bluetooth	29
9. Test Exclusion Consideration	30
9.1 SAR Test Exclusion Consideration Table	30
10. Test Result	31
Body 1g SAR Data	31
11. SAR Measurement Variability	32
12. Simultaneous Transmission	33
12.1 Simultaneous Transmission Mode Considerations	33
12.2 Sum SAR of Simultaneous Transmission	33
13. Test Equipment List	34
ANNEX A Simulating Liquid Verification Result	35
ANNEX B System Check Result	35
ANNEX C Test Data	48
ANNEX D SAR Test Setup Photos	66
ANNEX E EUT External and Internal Photos	67
ANNEX F Calibration Information	67

1. Introduction

1.1 Identification of Testing Laboratory

Company Name:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Phone Number:	+86-0755-23146130
Fax Number:	+86-0755-23146130

1.2 Identification of the Responsible Testing Location

Test Location:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Description:	All measurement facilities used to collect the measurement data are located at F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
FCC Registration Number	518915
Designation Number	CN1330

1.3 Laboratory Condition

Ambient Temperature:	21°C to 25°C
Ambient Relative Humidity:	48% to 59%
Ambient Pressure:	100 kPa to 102 kPa

1.4 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2. Product Information

2.1 Application Information

Company Name:	M/s Linkwell Telesystems Pvt. Ltd.
Address:	B-45 & 46, Electronics Complex, Kushaiguda, Hyderabad-500062, Telangana, India

2.2 Manufacturer Information

Company Name:	M/s Linkwell Telesystems Pvt. Ltd.
Address:	B-45 & 46, Electronics Complex, Kushaiguda, Hyderabad-500062, Telangana, India

2.3 Factory Information

Company Name:	M/s Linkwell Telesystems Pvt. Ltd.
Address:	B-45 & 46, Electronics Complex, Kushaiguda, Hyderabad-500062, Telangana, India

2.4 General Description of Equipment under Test (EUT)

EUT Name	Tablet
Under Test Model Name	VT 31
Sample No.	BTFSN230526E004-1/1

2.5 Equipment under Test Ancillary Equipment

Ancillary Equipment 1	Rechargeable Battery	
	Capacity	5100mAh
	Rated Voltage	3.8V

2.6 Technical Information

Network and Wireless connectivity	2G Network GSM/GPRS/EGPRS 850/1900 MHz 4G Network FDD LTE Band 5 TDD LTE Band 38/40/41 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20/40) 5G WIFI 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40) Bluetooth (EDR+BLE)
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	GSM, LTE, WLAN, Bluetooth		
Frequency Range	GSM 850	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	GSM 1900	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	LTE Band 5	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	LTE Band 38	2570 ~ 2620 MHz	
	LTE Band 40	2305 ~ 2315 MHz, 2350 ~ 2360 MHz	
	LTE Band 41	2496 ~ 2690 MHz	
	802.11b/g/n(HT20)	2412 ~ 2462 MHz	
	802.11n(HT40)	2422 ~ 2452 MHz	
	802.11a/802.11n(HT20/40) /802.11ac(VHT20/40)	5150 ~ 5250 MHz	
		5725 ~ 5850 MHz	
	Bluetooth	2402 ~ 2480 MHz	
Antenna Type	WWAN: PIFA Antenna WLAN: PIFA Antenna BT: PIFA Antenna		
Hotspot Function	Support		
Power Reduction	Not Support		
Exposure Category	General Population/Uncontrolled exposure		
EUT Stage	Portable Device		
Product	Type		
	☐ Production unit	☒ Identical prototype	

3. Summary of Test Results

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices
2	IEEE1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate in the Human Head from Wireless Communications Devices: Measurement Techniques
3	IEEE C95.1-2019	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz
4	KDB 447498 D01	General RF Exposure Guidance v06
5	KDB 865664 D01	SAR measurement 100MHz to 6GHz v01r04
6	KDB 865664 D02	RF Exposure Reporting v01r02
7	KDB 941225 D01	3G SAR Procedures v03r01
8	KDB 941225 D05	SAR for LTE Devices v02r05
9	KDB 941225 D06	Hotspot Mode v02r01
10	KDB 248227 D01	802.11 Wi-Fi SAR v02r02
11	KDB 616217 D04	SAR for laptop and tablets v01r02
12	KDB 690783 D01	SAR Listings on Grant v01r03

3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

Body Position	SAR Value (W/Kg)	
	General Population/ Uncontrolled Exposure	Occupational/ Controlled Exposure
Whole-Body SAR (averaged over the entire body)	0.08	0.4
Partial-Body SAR (averaged over any 1 gram of tissue)	1.60	8.0
SAR for hands, wrists, feet and ankles (averaged over any 10 grams of tissue)	4.0	20.0

NOTE:

General Population/Uncontrolled Exposure: Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment- related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Occupational/Controlled Exposure: Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure. In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

3.3 Test Result Summary

The maximum results of Specific Absorption Rate (SAR) found during test as bellows:

<Highest Reported standalone SAR Summary>

Exposure Position	Frequency Band	Reported SAR (W/kg)	Equipment Class	Highest Reported SAR (W/kg)	
Body 1-g SAR (0 mm Gap)	GSM 850	0.460	PCT	0.791	
	GSM 1900	0.737			
	LTE Band 5	0.625			
	LTE Band 38	0.554			
	LTE Band 40	0.401			
	LTE Band 41	0.480	DTS		
	WLAN 2.4 GHz	0.248			
	WLAN 5.2 GHz	0.272	NII		
	WLAN 5.8 GHz	0.791			

This device is in compliance with Specific Absorption Rate(SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC47 CFR part 2(2.1093) and ANSI/IEEE C95.1-2019, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013.

<Highest Reported Simultaneous SAR>

Exposure Position	Simultaneous Configuration	Highest Reported Simultaneous Transmission SAR (W/kg)	Limit (W/kg)	Verdict
Body 1-g SAR (0 mm Gap)	GSM 1900 + 5G WIFI	1.528	1.6	Pass

3.4 Test Uncertainty

3.4.1 Measurement uncertainty evaluation for SAR test

Measurement uncertainty evaluation for SAR test (300MHz to 6GHz)

Uncertainty Component	Tol (+-%)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10 g Ui (+-%)	Vi veff
Measurement System								
Probe calibration	5.8	N	1	1	1	5.80	5.80	∞
Axial Isotropy	3.5	R	√3	√0.5	√0.5	1.43	1.43	∞
Hemispherical Isotropy	5.9	R	√3	√0.5	√0.5	2.41	2.41	∞
Boundary effect	1.0	R	√3	1	1	0.58	0.58	∞
Linearity	4.7	R	√3	1	1	2.71	2.71	∞
System detection limits	1.0	R	√3	1	1	0.58	0.58	∞
Modulation response	3.0	R	√3	1	1	1.73	1.73	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	√3	1	1	0.00	0.00	∞
Integration Time	1.4	R	√3	1	1	0.81	0.81	∞
RF ambient Conditions - Noise	3.0	R	√3	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	3.0	R	√3	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	1.4	R	√3	1	1	0.81	0.81	∞
Probe positioning with respect to Phantom Shell	1.4	R	√3	1	1	0.81	0.81	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	2.3	R	√3	1	1	1.33	1.33	∞
Test sample Related								
Test sample positioning	2.6	N	1	1	1	2.60	2.60	11
Device Holder Uncertainty	3.0	N	1	1	1	3.00	3.00	7
Output power Variation - SAR drift measurement	5.0	R	√3	1	1	2.89	2.89	∞
SAR scaling	2.0	R	√3	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom Shell Uncertainty - Shape, Thickness and Permittivity	4	R	√3	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviation in permittivity and conductivity	2.0	N	1	1	0.84	2.00	1.68	∞
Liquid conductivity measurement	4.0	N	1	0.78	0.71	3.12	2.84	5
Liquid permittivity measurement	5.0	N	1	0.23	0.26	1.15	1.30	5
Liquid Conductivity - Temperature Uncertainty	2.5	R	√3	0.78	0.71	1.13	1.02	∞
Liquid permittivity - Temperature Uncertainty	2.5	R	√3	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty		RSS				10.47	10.34	
Expanded Uncertainty (95% Confidence interval)		k				20.95	20.69	

* This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.4.2 Measurement uncertainty evaluation for system check

Uncertainty Component	Tol (+-%)	Prob. Dist.	Div.	Ci (1g)	Ci (10 g)	1g Ui (+-%)	10 g Ui (+-%)	Vi veff
Measurement System								
Probe calibration	5.8	N	1	1	1	5.80	5.80	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	1	1	2.02	2.02	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Boundary effect	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
System detection limits	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	0	N	$\sqrt{3}$	0	0	0.00	0.00	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	0	0	0.00	0.00	∞
RF ambient Conditions - Noise	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to Phantom Shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Dipole								
Deviation of experimental source from numerical source	5	N	1	1	1	5.00	5.00	∞
Input Power and SAR drift measurement	0.5	R	$\sqrt{3}$	1	1	0.29	0.29	∞
Dipole Axis to Liquid Dist.	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom Shell Uncertainty - Shape, Thickness and Permittivity	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviation in permittivity and conductivity	2.0	N	1	1	0.84	2.00	1.68	∞
Liquid conductivity measurement	4	N	1	0.78	0.71	3.12	2.84	5
Liquid permittivity measurement	5.0	N	1	0.23	0.26	1.15	1.30	5
Liquid Conductivity - Temperature Uncertainty	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid permittivity - Temperature Uncertainty	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty		RSS				10.16	10.03	
Expanded Uncertainty (95% Confidence interval)		k				20.32	20.06	

4.2.2 Robot



A standard high precision 6-axis robot (Denso) with teaches pendant with Scanning System

- It must be able to scan all the volume of the phantom to evaluate the tridimensional distribution of SAR.
- Must be able to set the probe orthogonal of the surface of the phantom ($\pm 30^\circ$).
- Detects stresses on the probe and stop itself if necessary to keep the integrity of the probe.

4.2.3 E-Field Probe

For the measurements, the Specific Dosimetric SSE2 E-Field Probe with following specifications is used:

- Dynamic range: 0.01-100 W/kg
- Tip diameter: 2mm for SSE2
- Distance between probe tip and sensor centre: 1mm for SSE2
- Distance between sensor centre and the inner phantom surface: 2mm for $f \geq 4\text{GHz}$.
- Probe linearity: $<0.25\text{dB}$.
- Axial Isotropy: $<0.25\text{dB}$.
- Spherical Isotropy: $<0.50\text{dB}$.
- Calibration range: 150 to 6000 MHz for head & body simulating liquid
- Angle between probe axis (evaluation axis) and surface normal line: less than 20° .



4.2.4 Phantoms

SAM Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The probe scanning of the E-Field is done in the 2 halves of the normalized head. The normalized shape of the phantom corresponds to the dimensions of 90% of an adult head size. It enables the dosimetric evaluation of left and right-hand phone usage and includes an additional flat phantom part for the simplified body performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.



SAM Phantom

The thickness of the phantom amounts to $2\text{ mm} \pm 0.2\text{ mm}$. The materials for the phantom do not affect the radiation of the device under test (DUT) : $\epsilon_r' < 5$
The head is filled with tissue simulating liquid. The hand do not have to be modeled.

TWIN SAM phantom

	Mechanical	Electrical	
Overall thickness	$2 \pm 0.2\text{ mm}$ (except ear area)	Relative permittivity	3.4
Dimensions	1000 mm(L) x 500 mm(W) x 200 mm(H)	Loss tangent	0.02
Maximum volume	27 L		
Material	Fiberglass based		

ELLIPTICAL Phantom

The phantom is for Body performance check filled with tissue-equivalent liquid to a depth of at least 150 mm, whose shell material is resistant to damage or reaction with tissue-equivalent liquid chemicals.



ELLI Phantom

The shape of the phantom is an ellipse with length $600\text{ mm} \pm 5\text{ mm}$ and width $400\text{ mm} \pm 5\text{ mm}$.
The phantom shell is made of low-loss and low-permittivity material, having loss tangent $\tan \delta \leq 0.05$ and relative permittivity:
 $\epsilon_r' \leq 5$ for $f \leq 3\text{ GHz}$
 $3 \leq \epsilon_r' \leq 5$ for $f > 3\text{ GHz}$
The thickness of the bottom-wall of the flat phantom is 2.0 mm with a tolerance of $\pm 0.2\text{ mm}$.

Technical & mechanical characteristics

Shell thickness	$2\text{ mm} \pm 0.2\text{ mm}$
Filling volume	25 L
Dimensions	600 mm x 400 mm x 200mm
Permittivity	4.4
Loss tangent	0.017

4.2.5 Device Holder



System Material	Permittivity	Loss tangent
Delrin	3.7	0.005

(The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1°.)

System Material	Permittivity	Loss tangent
PMMA	2.9	0.028


4.2.6 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.

Head Liquid Depth



Body Liquid Depth



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.


Head (Reference IEEE1528)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.4	40.0
2450	55.0	0	0	0.1	0	44.9	1.80	39.2
2600	54.9	0	0	0.1	0	45.0	1.96	39.0
Frequency (MHz)	Water (%)	Hexyl Carbitol (%)			Triton X-100 (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	62.52	17.24			17.24		4.66	36.0
5800	62.52	17.24			17.24		5.27	35.3
Body (From instrument manufacturer)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0.1	0	31.3	1.95	52.7
2600	68.2	0	0	0.1	0	31.7	2.16	52.5
Frequency(MHz)	Water	DGBE (%)			Salt (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	78.60	21.40			/		5.30	49.00
5800	78.50	21.40			0.1		6.00	48.20

5. System Verification

5.1 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. The setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

5.2 System Check Setup



6. TEST POSITION CONFIGURATIONS


According to KDB 648474 D04 Handset, handsets are tested for SAR compliance in head, body-worn accessory and other use configurations described in the following subsections.

6.1 Head Exposure Conditions

Head exposure is limited to next to the ear voice mode operations. Head SAR compliance is tested according to the test positions defined in IEEE Std 1528-2013 using the SAM phantom illustrated as below.

6.1.1 Two Imaginary Lines on the Handset

- (a) The vertical center line passes through two points on the front side of the handset - the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.
- (b) The horizontal line is perpendicular to the vertical center line and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- (c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical center line is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




6.1.2 Two Imaginary Lines on the Handset

- To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost.



6.1.3 Titled Position

- To position the device in the “cheek” position described above.
- While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost.




6.2 Body-worn Position Conditions

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB 447498 are used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode. When the reported SAR for a body-worn accessory.

Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.

Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required. A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by users of consumer handsets is used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer, according to the requirements of Supplement C 01-01. Devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, will be tested using a conservative minimum test separation distance ≤ 5 mm to support compliance.



6.3 Hotspot Mode Exposure Position Conditions

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing functions, the relevant hand and body exposure conditions are tested according to the hotspot SAR procedures in KDB 941225. A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge. When the form factor of a handset is smaller than 9 cm x 5 cm, a test separation distance of 5 mm (instead of 10 mm) is required for testing hotspot mode. When the separation distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).



6.4 Product Specific 10g Exposure Consideration


According with FCC KDB 648474 D04, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, unless it is confirmed otherwise through KDB inquiries, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance;

The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

7. Measurement Procedure

7.1 Measurement Process Diagram

Body SAR



7.2 SAR Scan General Requirement

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1 g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013.

			≤3GHz	>3GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5±1 mm	½ δ·ln(2)±0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30°±1°	20°±1°
Maximum area scan spatial resolution: Δx Area , Δy Area			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3–4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx Zoom , Δy Zoom			≤ 2 GHz: ≤ 8 mm 2–3 GHz: ≤ 5 mm*	3–4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: Δz Zoom (n)		≤ 5 mm	3–4 GHz: ≤ 4 mm
				4–5 GHz: ≤ 3 mm
				5–6 GHz: ≤ 2 mm
	graded grid	Δz Zoom (1): between 1st two points closest to phantom surface	≤ 4 mm	3–4 GHz: ≤ 3 mm
				4–5 GHz: ≤ 2.5 mm
				5–6 GHz: ≤ 2 mm
		≤ 1.5·Δz Zoom (n-1)		
Minimum zoom scan volume	x, y, z		≥30 mm	3–4 GHz: ≥ 28 mm
				4–5 GHz: ≥ 25 mm
				5–6 GHz: ≥ 22 mm
Note:				
1. δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528- 2011 for details.				
2. * When zoom scan is required and the reported SAR from the area scan based 1 g SAR estimation procedures of KDB				
447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

7.3 Measurement Procedure

The following steps are used for each test position

- a. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- b. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- c. Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- d. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

7.4 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r04 quoted below.

When the 1 g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

8. Conducted RF Output Power

8.1 GSM

Mode: GSM850		Maximum Tune-up(dBm)	Burst Average Power (dBm)			Division Factors	Frame-Average Power (dBm)		
			CH128	CH190	CH251		CH128	CH190	CH251
			824.2MHz	836.6MHz	848.8MHz		824.2MHz	836.6MHz	848.8MHz
GSM		33.50	33.04	32.75	32.74	-9.03	24.01	23.72	23.71
GPRS (GMSK)	1Tx slot	33.00	32.74	32.76	32.75	-9.03	23.71	23.73	23.72
	2Tx slots	32.50	31.99	31.94	32.27	-6.02	25.97	25.92	26.25
	3Tx slots	30.50	30.02	30.42	30.06	-4.26	25.76	26.16	25.80
	4Tx slots	29.50	29.40	28.93	28.97	-3.01	26.39	25.92	25.96
EGPRS (8PSK)	1Tx slot	33.50	33.08	32.76	33.07	-9.03	24.05	23.73	24.04
	2Tx slots	32.50	32.28	32.00	32.30	-6.02	26.26	25.98	26.28
	3Tx slots	30.50	30.43	30.02	30.45	-4.26	26.17	25.76	26.19
	4Tx slots	29.50	29.37	28.95	28.95	-3.01	26.36	25.94	25.94
Mode: GSM1900		Maximum Tune-up(dBm)	Burst Average Power (dBm)			Division Factors	Frame-Average Power (dBm)		
			CH512	CH661	CH810		CH512	CH661	CH810
			1850.2MHz	1880.0MHz	1909.8MHz		1850.2MHz	1880.0MHz	1909.8MHz
GSM		30.00	29.62	29.77	29.92	-9.03	20.59	20.74	20.89
GPRS (GMSK)	1Tx slot	30.00	29.63	29.80	29.95	-9.03	20.60	20.77	20.92
	2Tx slots	29.00	28.53	28.65	28.85	-6.02	22.51	22.63	22.83
	3Tx slots	27.00	26.29	26.45	26.66	-4.26	22.03	22.19	22.40
	4Tx slots	26.00	25.19	25.39	25.56	-3.01	22.18	22.38	22.55
EGPRS (8PSK)	1Tx slot	25.00	24.23	24.12	24.74	-9.03	15.20	15.09	15.71
	2Tx slots	24.00	23.44	23.50	23.56	-6.02	17.42	17.48	17.54
	3Tx slots	22.00	21.46	21.76	21.71	-4.26	17.20	17.50	17.45
	4Tx slots	21.00	20.75	20.60	20.57	-3.01	17.74	17.59	17.56
Note: 1) Division Factors To average the power, the division factor is as follows: 1Tx-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB 2Tx-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB 3Tx-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB 4Tx-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB									

8.2 LTE

Band 5

LTE-FDD Band 5				Maximum Tune-up(dBm)	Conducted Power(dBm)				
Bandwidth	Modulation	RB allocation	RB offset		20407	20525	20643		
					824.7MHz	836.5MHz	848.3MHz		
1.4MHz	QPSK	1	0	22.50	22.33	22.42	22.43		
			2	22.50	22.41	22.49	22.48		
			5	22.50	22.40	22.46	22.41		
		3	0	23.00	22.49	22.64	22.63		
			2	23.00	22.43	22.63	22.58		
			3	23.00	22.53	22.65	22.57		
		6	0	22.00	21.57	21.73	21.72		
		16QAM	1	0	22.00	21.69	21.81	21.54	
				2	22.00	21.68	21.83	21.53	
	5			22.00	21.76	21.85	21.52		
	3		0	22.50	21.92	22.05	21.99		
			2	22.50	21.92	22.08	21.98		
			3	22.50	21.91	22.15	21.95		
	6		0	21.50	20.99	21.16	21.14		
	Bandwidth		Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20415	20525	20635
							825.5MHz	836.5MHz	847.5MHz
	3MHz	QPSK	1	0	22.50	22.17	22.37	22.45	
				7	22.50	22.30	22.40	22.49	
14				22.50	22.29	22.47	22.43		
8			0	22.00	21.71	21.83	21.93		
			4	22.00	21.75	21.89	21.93		
			7	22.00	21.79	21.93	21.86		
15			0	22.00	21.76	21.87	21.92		
16QAM			1	0	22.00	21.88	21.79	21.60	
				7	22.00	21.94	21.85	21.50	
		14		22.00	21.98	21.92	21.51		
		8	0	21.50	21.02	21.12	21.17		
			4	21.50	21.02	21.16	21.13		
			7	21.50	21.02	21.17	21.11		
		15	0	21.50	21.06	21.13	21.24		

LTE-FDD Band 5				Maximum Tune-up(dBm)	Conducted Power(dBm)				
Bandwidth	Modulation	RB allocation	RB offset		20425	20525	20625		
					826.5MHz	836.5MHz	846.5MHz		
5MHz	QPSK	1	0	23.00	22.42	22.52	22.78		
			13	23.00	22.53	22.62	22.72		
			24	23.00	22.52	22.70	22.62		
		12	0	22.50	21.86	21.92	22.06		
			6	22.50	21.91	21.99	22.03		
			13	22.50	21.83	22.08	21.98		
		25	0	22.50	21.90	22.02	22.06		
			16QAM	1	0	23.00	22.03	22.09	22.57
					13	23.00	22.12	22.14	22.55
	24	22.50			22.11	22.26	22.42		
	12	0		21.50	21.09	21.20	21.35		
		6		21.50	21.10	21.26	21.33		
		13		21.50	21.08	21.35	21.27		
	25	0		21.50	21.19	21.26	21.34		

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20450	20525	20600
					829.0MHz	836.5MHz	844.0MHz
10MHz	QPSK	1	0	23.00	22.54	22.50	22.77
			25	23.00	22.60	22.63	22.86
			49	23.00	22.64	22.88	22.69
		25	0	22.50	21.95	21.89	22.19
			13	22.50	21.90	22.04	22.17
			25	22.50	21.93	22.14	22.04
		50	0	22.50	21.98	22.05	22.16
	16QAM	1	0	22.50	21.60	22.19	22.17
			25	22.50	21.65	22.23	22.30
			49	23.00	21.73	22.52	22.09
		25	0	21.50	21.22	21.19	21.44
			13	21.50	21.19	21.30	21.43
			25	21.50	21.19	21.42	21.33
		50	0	21.50	21.24	21.30	21.44

Band 38

LTE-TDD Band 38					Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	37775	38000	38225
					2572.5MHz	2595.0MHz	2617.5MHz
5MHz	QPSK	1	0	20.50	18.86	18.49	20.09
			12	20.00	18.82	18.45	19.96
			24	20.50	18.79	18.40	20.19
		12	0	18.50	18.19	17.72	17.89
			6	18.50	18.14	17.71	17.92
			13	18.50	18.14	17.71	17.91
		25	0	18.50	18.15	17.77	17.93
	16QAM	1	0	19.00	18.73	18.05	18.11
			12	19.00	18.66	17.96	18.04
			24	19.00	18.72	17.93	18.23
		12	0	17.50	17.43	16.96	17.19
			6	17.50	17.45	16.91	17.21
			13	17.50	17.42	16.95	17.22
		25	0	17.50	17.41	17.07	17.15
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	37800	38000	38200
10MHz	QPSK	1	0	20.50	18.91	18.68	20.05
			24	20.50	18.83	18.45	20.08
			49	20.50	18.86	18.44	20.28
		25	0	18.50	18.15	17.83	17.81
			12	18.50	18.14	17.77	17.88
			25	18.50	18.14	17.79	17.95
		50	0	18.50	18.19	17.85	17.88
	16QAM	1	0	19.00	18.63	18.01	17.67
			24	19.00	18.54	17.78	17.79
			49	19.00	18.59	17.80	17.91
		25	0	17.50	17.48	17.11	17.08
			12	17.50	17.46	17.07	17.16
			25	17.50	17.45	17.06	17.26
		50	0	17.50	17.44	17.14	17.15

LTE-TDD Band 38				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		37825	38000	38175
					2577.5MHz	2595.0MHz	2612.5MHz
15MHz	QPSK	1	0	20.00	18.87	18.71	19.98
			37	20.00	18.71	18.48	19.99
			74	20.50	18.85	18.32	20.30
		37	0	18.50	18.02	17.77	17.64
			18	18.00	17.99	17.68	17.75
			38	18.50	18.09	17.62	17.88
		75	0	18.50	18.04	17.70	17.72
	16QAM	1	0	18.50	18.23	18.10	18.07
			37	18.50	18.04	17.84	18.13
			74	18.50	18.22	17.71	18.42
		37	0	17.50	17.36	16.97	16.91
			18	17.50	17.34	16.88	17.05
			38	17.50	17.39	16.83	17.15
		75	0	17.50	17.24	16.95	16.98
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	37850	38000	38150
					2580.0MHz	2595.0MHz	2610.0MHz
20MHz	QPSK	1	0	19.00	18.77	18.68	18.22
			49	20.00	18.84	18.45	19.96
			99	20.50	18.65	19.98	20.25
		50	0	18.50	18.18	17.89	17.64
			25	18.50	18.20	17.85	17.87
			50	18.50	18.17	17.82	17.99
		100	0	18.50	18.16	17.80	17.81
	16QAM	1	0	18.50	18.32	18.16	17.62
			49	18.50	18.36	17.87	17.88
			99	18.50	18.16	17.76	18.09
		50	0	17.50	17.49	17.15	16.90
			25	17.50	17.49	17.10	17.12
			50	18.00	17.50	17.05	17.27
		100	0	17.50	17.41	17.08	17.08

Band 40

LTE-TDD Band 40				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		39175	39200	39225
					2352.5MHz	2355.0MHz	2757.5MHz
5MHz	QPSK	1	0	21.50	20.09	20.03	21.02
			12	21.50	20.02	19.99	21.10
			24	21.50	20.03	20.98	21.03
		12	0	20.50	20.46	19.40	20.39
			6	20.50	20.41	19.37	20.37
			13	21.50	21.47	20.44	20.42
		25	0	23.00	22.50	20.46	20.45
	16QAM	1	0	22.00	20.67	19.64	21.92
			12	21.00	20.59	19.63	20.95
			24	22.00	21.62	20.63	20.95
		12	0	21.00	19.70	20.71	19.70
			6	21.00	19.64	20.67	18.67
			13	21.00	19.73	20.76	18.73
		25	0	21.00	19.86	20.75	19.74

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	39200
					2355.0MHz
10MHz	QPSK	1	0	21.50	21.12
			24	21.50	21.06
			49	21.50	21.04
		25	0	20.50	20.47
			12	20.50	20.46
			25	21.00	20.53
		50	0	21.00	20.54
	16QAM	1	0	21.00	20.88
			24	21.00	20.72
			49	20.00	19.83
		25	0	19.00	18.78
			12	19.00	18.79
			25	19.00	18.88
		50	0	19.00	18.84

LTE-TDD Band 40				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		38725	38750	38775
					2307.5MHz	2310.0MHz	2312.5MHz
5MHz	QPSK	1	0	20.00	19.72	19.65	19.58
			12	20.00	19.62	19.71	19.61
			24	20.00	19.65	14.61	19.55
		12	0	19.50	19.18	14.06	19.06
			6	20.50	19.08	20.00	19.97
			13	20.50	19.10	20.03	20.05
		25	0	20.50	19.18	20.10	20.04
	16QAM	1	0	20.50	19.60	20.23	20.23
			12	21.50	19.56	20.26	21.29
			24	21.50	19.59	21.14	20.19
		12	0	22.00	18.74	21.61	21.64
			6	21.00	18.68	20.56	20.63
			13	21.00	18.67	20.57	20.63
		25	0	21.00	18.72	19.66	20.55
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	38750		
					2310.0MHz		
10MHz	QPSK	1	0	21.00	20.75		
			24	23.00	22.62		
			49	22.00	21.65		
		25	0	20.50	20.17		
			12	20.50	20.07		
			25	20.50	20.10		
		50	0	20.50	20.20		
	16QAM	1	0	22.00	21.50		
			24	22.50	22.27		
			49	21.50	21.39		
		25	0	22.00	21.74		
			12	22.00	21.71		
			25	22.00	21.71		
		50	0	22.00	21.74		

Band 41

LTE-TDD Band 41				Maximum Tune-up(dBm)	Conducted Power(dBm)							
Bandwidth	Modulation	RB allocation	RB offset		39675	40148	40620	41093	41565			
					2498.5MHz	2545.8MHz	2593.0MHz	2640.3MHz	2687.5MHz			
5MHz	QPSK	1	0	21.00	20.92	18.89	18.53	19.64	20.24			
			13	21.50	21.03	18.81	18.51	19.57	20.05			
			24	20.50	20.00	18.85	18.42	19.60	20.24			
		12	0	20.00	18.32	18.30	17.82	19.04	19.65			
			6	22.00	21.55	18.17	20.77	18.90	19.61			
			13	20.00	19.84	18.11	17.78	18.84	19.65			
		25	0	20.00	18.39	18.24	17.83	18.97	19.65			
			16QAM	1	0	20.50	18.93	18.41	18.13	19.14	20.05	
					13	20.00	19.24	18.33	18.11	19.06	19.85	
	24	20.50			19.92	18.37	18.00	19.10	20.05			
	12	0		20.50	20.05	17.83	17.11	18.55	20.16			
		6		18.50	18.23	17.70	17.06	18.41	17.16			
		13		22.50	19.38	17.65	22.07	18.36	20.17			
	25	0		21.00	20.97	17.77	17.09	18.48	19.18			
		Bandwidth		Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	39700	40160	40620	41080	41540
								2501.0MHz	2547MHz	2593.0MHz	2639.0MHz	2685MHz
	10MHz	QPSK	1	0	20.50	18.38	18.84	19.71	19.65	20.38		
25				21.00	18.39	18.77	20.54	19.58	20.25			
49				20.50	18.08	18.80	19.53	19.61	20.34			
25			0	21.00	19.58	18.26	20.90	19.04	20.73			
			13	20.00	19.90	18.12	18.83	18.91	19.70			
			25	21.00	18.98	18.07	18.85	18.85	20.71			
50			0	21.00	20.61	18.19	20.92	18.98	19.78			
			16QAM	1	0	20.00	18.38	18.36	19.05	19.15	19.53	
					25	21.50	19.60	18.29	18.89	19.07	21.41	
49		21.00			20.52	18.32	18.85	19.11	19.51			
25		0		19.50	19.35	17.79	18.22	18.56	18.29			
		13		32.00	20.55	17.66	18.14	18.42	17.25			
		25		20.50	20.16	17.61	18.13	18.36	18.25			
50		0		20.50	20.11	17.73	17.21	18.49	17.27			

LTE-TDD Band 41				Maximum Tune-up(dBm)	Conducted Power(dBm)					
Bandwidth	Modulation	RB allocation	RB offset		39725	40173	40620	41068	41515	
					2503.5MHz	2548.3MHz	2593.0MHz	2637.8MHz	2682.5MHz	
15MHz	QPSK	1	0	21.00	18.10	18.86	18.73	19.62	20.52	
			38	21.50	18.19	18.79	18.60	19.54	21.22	
			74	20.50	18.92	18.82	20.08	19.58	20.36	
		36	0	20.00	20.00	18.28	17.82	19.01	19.74	
			18	23.00	20.36	18.14	17.74	18.87	22.60	
			39	21.00	20.66	18.09	17.71	18.82	19.64	
		75	0	20.50	20.10	18.21	17.76	18.94	19.68	
		16QAM	1	0	20.00	18.40	18.38	18.10	19.12	19.93
				38	20.00	19.33	18.30	17.95	19.04	19.58
	74			20.00	19.63	18.34	19.81	19.08	19.76	
	36		0	19.50	19.02	17.81	18.16	18.52	17.27	
			18	20.50	19.49	17.68	20.07	18.39	20.18	
			39	21.00	20.89	17.62	20.03	18.33	17.16	
	75		0	21.00	20.83	17.74	19.99	18.46	20.27	

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	39750	40185	40620	41055	41490
					2506.0MHz	2549.5MHz	2593.0MHz	2636.5MHz	2680.0MHz
20MHz	QPSK	1	0	20.50	18.99	18.93	18.71	19.68	20.48
			50	20.50	19.10	18.85	18.56	19.60	20.35
			99	21.00	20.89	18.89	20.02	19.64	20.27
		50	0	20.50	20.14	18.34	19.98	19.07	20.02
			25	20.50	20.19	18.21	20.93	18.93	19.85
			50	20.00	19.06	18.15	17.90	18.87	19.79
		100	0	20.50	20.01	18.28	20.91	19.00	19.88
	16QAM	1	0	21.50	21.33	18.44	18.14	19.18	19.94
			50	20.00	19.27	18.37	17.99	19.10	19.79
			99	20.00	19.29	18.41	22.81	19.13	19.75
		50	0	19.00	18.21	17.87	17.30	18.58	17.58
			25	20.50	20.31	17.74	17.23	18.44	18.44
			50	19.50	19.28	17.69	20.20	18.39	17.33
		100	0	21.00	20.86	17.81	17.15	18.51	20.45

8.3 Wi-Fi

Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
2.4 (2.4~2.4835)	802.11b	1	2412	10.98	11.00	No
		6	2437	11.35	11.50	Yes
		11	2462	8.83	9.00	No
	802.11g	1	2412	10.56	11.00	No
		6	2437	11.18	11.50	No
		11	2462	8.67	9.00	No
	802.11n(HT20)	1	2412	10.40	10.50	No
		6	2437	11.19	11.50	No
		11	2462	8.37	8.50	No
	802.11n(HT40)	3	2422	9.93	10.00	No
		6	2437	10.92	11.00	No
		9	2452	8.32	8.50	No

Note: SAR is not required for the following 2.4 GHz OFDM conditions as the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is $\leq 1.2W/kg$.

Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-1 (5.150~5.250)	802.11a	36	5180	11.48	11.50	No
		40	5200	12.03	12.50	No
		44	5220	11.49	11.50	No
	802.11n(HT20)	36	5180	12.37	12.50	No
		40	5200	16.65	17.00	Yes
		44	5220	13.11	13.50	No
	802.11ac(VHT20)	36	5180	11.65	12.00	No
		40	5200	12.02	12.50	No
		44	5220	12.46	12.50	No
	802.11n(HT40)	38	5190	14.36	14.50	No
		46	5230	11.83	12.00	No
	802.11ac(VHT40)	38	5190	12.96	13.00	No
		46	5230	13.58	14.00	No

Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-3 (5.725~5.850)	802.11a	149	5745	10.59	11.00	Yes
		157	5785	9.59	10.00	No
		165	5825	8.41	8.50	No
	802.11n(HT20)	149	5745	10.29	10.50	No
		157	5785	9.50	10.00	No
		165	5825	8.27	8.50	No
	802.11ac(VHT20)	149	5745	10.32	10.50	No
		157	5785	9.33	9.50	No
		165	5825	8.28	8.50	No
	802.11n(HT40)	151	5755	10.16	10.50	No
		159	5795	5.20	5.50	No
	802.11ac(VHT40)	151	5755	9.86	10.00	No
		159	5795	5.10	5.50	No

8.4 Bluetooth

EDR	Mode	Maximum Tune-up(dBm)	Average Conducted Output Power (dBm)		
			0	39	78
			2402MHz	2441MHz	2480MHz
	GFSK	-1.00	-1.91	-1.25	-1.33
	$\pi/4$ QPSK	0.00	-1.10	-0.43	-0.49
BLE	8DPSK	0.00	-0.65	-0.03	-0.06
	Mode	Maximum Tune-up(dBm)	Average Conducted Output Power (dBm)		
			0	20	39
			2402MHz	2440MHz	2480MHz
	1Mbps	-0.50	-1.37	-0.72	-0.72

Channel	Frequency (GHz)	Max. Tune-up Power (dBm)	Max. Power (mW)	Test distance (mm)	Exclusion thresholds for 1-g SAR(mW)	RF exposure evaluation required
39	2.441	0.00	1.00	0	10	No

Note

- Per KDB 447498 D01 General RF Exposure Guidance v06, the 1-g SAR test exclusion thresholds for 300 MHz to 6 GHz at *test separation distances* ≤ 40 cm are determined by:

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

*When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine estimated SAR.

- Per KDB 248227 D01 v02r02, choose the highest output power channel to test SAR and determine further SAR exclusion.
- The output power of all data rate were prescan, just the worst case (the lowest data rate) of all mode were shown in report.

9. Test Exclusion Consideration

Antenna information:



WWAN Main Antenna	GSM/WCDMA/LTE TX/RX
WLAN/BT Antenna	WLAN/BT TX/RX
Note: 1. KDB 447498 D01v06, particular DUT edges were not required to be evaluated for SAR if the antenna-to-edge distance is greater than 2.5cm. 2. KDB 616217 D04 SAR for laptop and tablets v01r02, it doesn't require SAR evaluation for the front surface of a tablet. 3. Per KDB648474 D04, 10-g extremity SAR is not required when Body-Worn mode 1-g reported SAR<1.2W/Kg.	

Distance of The Antenna to the EUT surface and edge (mm)						
Antenna	Front Side (mm)	Back Side (mm)	Left Edge (mm)	Right Edge (mm)	Top Edge (mm)	Bottom Edge (mm)
WWAN	<25	<25	65	55	200	<25
Wifi/BT	<25	<25	87	33	<25	200
Positions for SAR tests						
Antenna	Front Side (mm)	Back Side (mm)	Left Edge (mm)	Right Edge (mm)	Top Edge (mm)	Bottom Edge (mm)
WWAN	No	Yes	No	No	No	Yes
Wifi/BT	No	Yes	No	No	Yes	No

9.1 SAR Test Exclusion Consideration Table

Per KDB 447498 requires when the standalone SAR test exclusion of section 4.3.1 is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following format to determine simultaneous transmission SAR test exclusion:

$$(\text{max.power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})} / x]$$

W/kg for test separation distances ≤ 50 mm;

where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.

Mode	Channel	Frequency (GHz)	Max tune-up power (dBm)	Max. Power (mW)	Exposure Position	Body
					Test Dist.(mm)	5
BT	39	2.441	0.00	1.00	Estimated SAR(W/kg)	0.042

10. Test Result

Body 1g SAR Data

Body(10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Reported SAR (W/kg)	Meas. No.
GPRS 850+4slots	Back	128	824.2	-2.130	0.450	100.00	1.000	29.40	29.50	1.023	0.460	1#
	Bottom	128	824.2	-1.580	0.238	100.00	1.000	29.40	29.50	1.023	0.243	/
Body(10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Reported SAR (W/kg)	Meas. No.
GPRS 1900+2slots	Back	810	1909.8	2.060	0.712	100.00	1.000	28.85	29.00	1.035	0.737	2#
	Bottom	810	1909.8	2.640	0.365	100.00	1.000	28.85	29.00	1.035	0.378	/

Body(10mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Reported SAR (W/kg)	Meas. No.
Band 5 (BW: 10MHz)	1RB	Back	20525	836.5	-0.960	0.608	100.00	1.000	22.88	23.00	1.028	0.625	3#
		Bottom	20525	836.5	3.250	0.352	100.00	1.000	22.88	23.00	1.028	0.362	/
	50%RB	Back	20525	836.5	-0.671	0.512	100.00	1.000	22.14	22.50	1.086	0.556	/
		Bottom	20525	836.5	3.629	0.203	100.00	1.000	22.14	22.50	1.086	0.220	/
Body(10mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Reported SAR (W/kg)	Meas. No.
Band 38 (BW: 20MHz)	1RB	Back	38150	2610.0	-2.900	0.523	100.00	1.000	20.25	20.50	1.059	0.554	4#
		Bottom	38150	2610.0	3.250	0.246	100.00	1.000	20.25	20.50	1.059	0.261	/
	50%RB	Back	38150	2610.0	-0.671	0.336	100.00	1.000	17.99	18.00	1.002	0.337	/
		Bottom	38150	2610.0	3.629	0.128	100.00	1.000	17.99	18.00	1.002	0.128	/
Body(10mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Reported SAR (W/kg)	Meas. No.
Band 40 (BW: 20MHz)	1RB	Back	38750	2310.0	-2.050	0.366	100.00	1.000	22.60	23.00	1.096	0.401	5#
		Bottom	38750	2310.0	3.250	0.182	100.00	1.000	22.60	23.00	1.096	0.199	/
	50%RB	Back	38750	2310.0	-0.671	0.254	100.00	1.000	20.17	20.50	1.079	0.274	/
		Bottom	38750	2310.0	3.629	0.147	100.00	1.000	20.17	20.50	1.079	0.159	/
Body(10mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Reported SAR (W/kg)	Meas. No.
Band 41 (BW: 20MHz)	1RB	Back	39750	2506.0	-2.200	0.468	100.00	1.000	20.89	21.00	1.026	0.480	6#
		Back	40185	2549.5	-0.681	0.289	100.00	1.000	18.89	19.00	1.026	0.297	/
		Back	40620	2593.0	-3.064	0.412	100.00	1.000	20.02	20.50	1.117	0.460	/
		Back	41055	2636.5	1.955	0.338	100.00	1.000	19.64	20.00	1.086	0.367	/
		Back	41490	2680.0	2.051	0.437	100.00	1.000	20.27	20.50	1.054	0.461	/
		Bottom	39750	2506.0	0.798	0.421	100.00	1.000	20.89	21.00	1.026	0.432	/
		Bottom	40185	2549.5	-1.339	0.264	100.00	1.000	18.89	19.00	1.026	0.271	/
		Bottom	40620	2593.0	4.005	0.361	100.00	1.000	20.02	20.50	1.117	0.403	/
		Bottom	41055	2636.5	-0.810	0.307	100.00	1.000	19.64	20.00	1.086	0.333	/
		Bottom	41490	2680.0	3.150	0.399	100.00	1.000	20.27	20.50	1.054	0.421	/
	50%RB	Back	39750	2506.0	3.760	0.325	100.00	1.000	20.19	20.50	1.074	0.349	/
		Bottom	39750	2506.0	2.660	0.115	100.00	1.000	20.19	20.50	1.074	0.124	/

Body(10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Reported SAR (W/kg)	Meas. No.
2.4g (2.4~2.4835)	Back	6	2437	-1.510	0.240	100.00	1.000	11.35	11.50	1.035	0.248	7#
	Top	6	2437	1.830	0.085	100.00	1.000	11.35	11.50	1.035	0.088	/
Body(10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Reported SAR (W/kg)	Meas. No.
U-NII-1 (5.150~5.250) 802.11n(HT20)	Back	40	5200	2.230	0.418	100.00	1.000	16.65	17.00	1.084	0.453	8#
	Top	40	5200	-1.050	0.211	100.00	1.000	16.65	17.00	1.084	0.229	/
Body(10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Reported SAR (W/kg)	Meas. No.
U-NII-3 (5.725~5.850) 802.11a	Back	149	5745	1.510	0.720	100.00	1.000	10.59	11.00	1.099	0.791	9#
	Top	149	5745	4.110	0.539	100.00	1.000	10.59	11.00	1.099	0.592	/

Note:

- Per KDB 447498 D01 v06, for each exposure position, if the highest output power channel Reported SAR ≤ 0.8 W/kg, other channels SAR testing is not necessary.
- Per KDB 447498 D01 v06, body use is evaluated with the device positioned at 0mm from a flat phantom respectively filled with body tissue-equivalent medium.
- Per KDB 616217 D04 where SAR test considerations for tablets are based on a composite test separation distance of 0 mm from the back and edges of the device with antennas 2.5 cm or closer to the edge of the device, determined from general mixed use conditions for this type of devices.
- Per KDB 447498 D01 v06, the report SAR is measured SAR value adjusted for maximum tune-up tolerance. Scaling Factor= $10^{[(\text{tune-up limit power (dBm)} - \text{Ave. power power (dBm)})/10]}$, where tune-up limit is the maximum rated power among all production units.
Reported SAR(W/kg)=Measured SAR (W/kg)*Scaling Factor.

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 31 of 67

BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

11. SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Note: For 1g SAR, the highest measured 1g SAR is $0.720 < 0.80$ W/kg, repeated measurement is not required.

12. Simultaneous Transmission

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR 1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR 1g 1.6 W/kg), SAR test exclusion is determined by the SAR to Peak Location Ratio (SPLSR).

12.1 Simultaneous Transmission Mode Considerations

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. The device has 2 Tx antennas, WWAN main antenna, Wifi/BT antenna supports 2.4G/5G Wi-Fi & BT. The 2 antennas can always transmit simultaneously. The work mode combination is showed as below table.

Application Simultaneous Transmission information:

NO.	Configuration	Body
1	WWAN+WIFI(2.4g)	Yes
2	WWAN+WIFI(5g)	Yes
3	WWAN+BT	Yes

12.2 Sum SAR of Simultaneous Transmission

Body

Band	Test Position	Reported SAR(W/kg)				Σ SAR (W/kg) WWAN + WIFI 2.4G	Σ SAR (W/kg) WWAN + WIFI 5G	Σ SAR (W/kg) WWAN + BT	SPLSR	Remark
		WWAN	WIFI 2.4G	WIFI 5G	BT					
GSM850 (GPRS 4slots)	Back	0.460	0.248	0.791	0.042	0.708	1.251	0.502	N/A	N/A
	Top	/	0.088	0.592	0.042	0.088	0.592	0.042	N/A	N/A
	Bottom	0.243	/	/	/	0.243	0.243	0.243	N/A	N/A
GSM1900 (GPRS 2slots)	Back	0.737	0.248	0.791	0.042	0.985	1.528	0.779	N/A	N/A
	Top	/	0.088	0.592	0.042	0.088	0.592	0.042	N/A	N/A
	Bottom	0.378	/	/	/	0.378	0.378	0.378	N/A	N/A

Band	Test Position	RB allocation	Reported SAR(W/kg)				Σ SAR (W/kg) WWAN + WIFI 2.4G	Σ SAR (W/kg) WWAN + WIFI 5G	Σ SAR (W/kg) WWAN + BT	SPLSR	Remark
			WWAN	WIFI 2.4G	WIFI 5G	Bluetooth					
LTE Band 5 (10MHz)	Back	1RB	0.625	0.248	0.791	0.042	0.873	1.416	0.667	N/A	N/A
	Top		/	0.088	0.592	0.042	0.088	0.592	0.042	N/A	N/A
	Bottom		0.362	/	/	/	0.362	0.362	0.362	N/A	N/A
	Back	50%RB	0.556	0.248	0.791	0.042	0.804	1.347	0.598	N/A	N/A
	Top		/	0.088	0.592	0.042	0.088	0.592	0.042	N/A	N/A
	Bottom		0.220	/	/	/	0.220	0.220	0.220	N/A	N/A
LTE Band 38 (20MHz)	Back	1RB	0.554	0.248	0.791	0.042	0.802	1.345	0.596	N/A	N/A
	Top		/	0.088	0.592	0.042	0.088	0.592	0.042	N/A	N/A
	Bottom		0.261	/	/	/	0.261	0.261	0.261	N/A	N/A
	Back	50%RB	0.337	0.248	0.791	0.042	0.585	1.128	0.379	N/A	N/A
	Top		/	0.088	0.592	0.042	0.088	0.592	0.042	N/A	N/A
	Bottom		0.128	/	/	/	0.128	0.128	0.128	N/A	N/A
LTE Band 40 (20MHz)	Back	1RB	0.401	0.248	0.791	0.042	0.649	1.192	0.443	N/A	N/A
	Top		/	0.088	0.592	0.042	0.088	0.592	0.042	N/A	N/A
	Bottom		0.199	/	/	/	0.199	0.199	0.199	N/A	N/A
	Back	50%RB	0.274	0.248	0.791	0.042	0.522	1.065	0.316	N/A	N/A
	Top		/	0.088	0.592	0.042	0.088	0.592	0.042	N/A	N/A
	Bottom		0.159	/	/	/	0.159	0.159	0.159	N/A	N/A
LTE Band 41 (20MHz)	Back	1RB	0.480	0.248	0.791	0.042	0.728	1.271	0.522	N/A	N/A
	Top		/	0.088	0.592	0.042	0.088	0.592	0.042	N/A	N/A
	Bottom		0.432	/	/	/	0.432	0.432	0.432	N/A	N/A
	Back	50%RB	0.349	0.248	0.791	0.042	0.597	1.14	0.391	N/A	N/A
	Top		/	0.088	0.592	0.042	0.088	0.592	0.042	N/A	N/A
	Bottom		0.124	/	/	/	0.124	0.124	0.124	N/A	N/A

13. Test Equipment List

Description	Manufacturer	Model	Serial No./Version	Cal. Date	Cal. Due
E-Field Probe	MVG	SSE2	04/22 EPG0365	2023/02/06	2024/02/05
6 1/2 Digital Multimeter	Keithley	DMM6500	4527164	2022/11/24	2023/11/23
Wideband Radio Communication Tester	ROHDE & SCHWARZ	CMW500	161997	2022/11/24	2023/11/23
MXG Vector Signal Generator	Agilent	N5182A	MY46240163	2022/11/24	2023/11/23
E-Series Avg. Power Sensor	KEYSIGHT	E9300A	MY55050017	2023/03/24	2024/03/23
EPM Series Power Meter	KEYSIGHT	E4418B	MY41293435	2023/03/24	2024/03/23
10dB Attenuator	MIDWEST MICROWAVE	263-10dB	/	2023/03/24	2024/03/23
Coupler	MERRIMAC	CWM-10R-10.8G	LOT-83391	2023/03/24	2024/03/23
835MHz Validation Dipole	MVG	SID835	07/22 DIP 0G835-656	2023/02/06	2024/02/05
1900MHz Validation Dipole	MVG	SID1900	07/22 DIP 1G900-658	2023/02/06	2024/02/05
2450MHz Validation Dipole	MVG	SID2450	07/22 DIP 2G450-662	2023/02/06	2024/02/05
2600MHz Validation Dipole	MVG	SID2600	07/22 DIP 2G600-663	2023/02/06	2024/02/05
5200MHz-5800MHz Validation Dipole	MVG	SID5000	07/22 DIP5G000-670	2023/02/06	2024/02/05
LIMESAR Dielectric Probe	MVG	SCLMP	06/22 OCPG88	/	/
ENA Series Network Analyzer	Agilent	E5071B	MY42301221	2022/11/24	2023/11/23
Thermometer	Riters	DT-232	21A11	2023/03/24	2024/03/23
Antenna network emulator	MVG	ANTA 74	07/22 ANTA 74	/	/
SAM Phantom	MVG	SAM	07/22 SAM149	/	/
Mobile Phone Positioning System	MVG	MSH 118	07/22 MSH 118	/	/
Mechanical Calibration Kit	PNA	/	/	/	/
Open SAR test software	MVG	/	V5.3.5	/	/
Note: For dipole antennas, BTF has adopted 3 years as calibration intervals, and on annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria: 1. There is no physical damage on the dipole; 2. System validation with specific dipole is within 10% of calibrated value; 3. Return-loss in within 20% of calibrated measurement. 4. Impedance (real or imaginary parts) in within 5 Ohms of calibrated measurement.					

ANNEX A Simulating Liquid Verification Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an SCLMP Dielectric Probe Kit.

Dielectric performance of tissue simulating liquid									
Frequency (MHz)	ϵ_r		$\sigma(s/m)$		Delta (ϵ_r)	Delta (σ)	Limit	Temp ($^{\circ}C$)	Date
	Target	Measured	Target	Measured					
835	41.50	41.41	0.90	0.87	0.22%	3.33%	$\pm 5\%$	20.0	14/6/2023
1900	40.00	39.88	1.40	1.41	0.30%	-0.71%	$\pm 5\%$	20.0	14/6/2023
2450	39.20	39.08	1.80	1.81	0.31%	-0.56%	$\pm 5\%$	20.0	15/6/2023
2600	39.00	38.88	1.96	1.97	0.31%	-0.51%	$\pm 5\%$	20.0	15/6/2023
5200	36.00	35.88	4.66	4.70	0.33%	-0.86%	$\pm 5\%$	20.0	15/6/2023
5800	35.30	35.18	5.27	5.31	0.34%	-0.76%	$\pm 5\%$	20.0	15/6/2023

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 $^{\circ}C$ of the conditions expected during the SAR evaluation to satisfy protocol requirements.

ANNEX B System Check Result

Comparing to the original SAR value provided by MVG, the validation data should be within its specification of 10 % (for 10 g).

Frequency (MHz)	Input Power (mW)	1g SAR (W/Kg)	10g SAR (W/Kg)	1g SAR 1W input power normalized (W/Kg)	10g SAR 1W input power normalized (W/Kg)	1g SAR Standard target (1W) (W/Kg)	10g SAR Standard target (1W) (W/Kg)	1g SAR Deviation	10g SAR Deviation
835	16	0.163	0.106	10.19	6.63	9.79	6.17	4.06%	7.37%
1900	16	0.630	0.322	39.38	20.13	40.97	20.7	-3.89%	-2.78%
2450	16	0.793	0.352	49.56	22.00	54.4	23.86	-8.89%	-7.80%
2600	16	0.866	0.421	54.13	26.31	57.14	24.48	-5.28%	7.49%
5200	13	0.294	0.998	23.35	79.27	21.60	76.50	-7.97%	1.19%
5800	13	1.023	0.280	78.69	21.54	74.21	21.50	6.04%	0.18%

System Performance Check Data (835 MHz)

System check at 835 MHz

Date of measurement: 14/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW835
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	835.000
Relative permittivity (real part)	41.410
Relative permittivity (imaginary part)	19.490
Conductivity (S/m)	0.870

C. SAR Surface and Volume




Maximum location: X=-1.00, Y=-3.00 ; SAR Peak: 0.26 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.106
SAR 1g (W/Kg)	0.163
Variation (%)	-3.390
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.059	0.173	0.115	0.061	0.072



F. 3D Image



System Performance Check Data (1900 MHz)

System check at 1900 MHz

Date of measurement: 14/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	1900.000
Relative permittivity (real part)	39.880
Relative permittivity (imaginary part)	13.380
Conductivity (S/m)	1.410

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 1.18 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.322
SAR 1g (W/Kg)	0.630
Variation (%)	-2.080
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.201	0.759	0.402	0.239	0.156



F. 3D Image



System Performance Check Data (2450 MHz)

System check at 2450 MHz

Date of measurement: 15/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.36
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	2450.000
Relative permittivity (real part)	39.080
Relative permittivity (imaginary part)	13.340
Conductivity (S/m)	1.810

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 1.47 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.352
SAR 1g (W/Kg)	0.793
Variation (%)	-2.570
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.466	0.900	0.477	0.261	0.158



F. 3D Image



System Performance Check Data (2600 MHz)

System check at 2600 MHz

Date of measurement: 15/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.40
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW2600
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	2600.000
Relative permittivity (real part)	38.880
Relative permittivity (imaginary part)	12.690
Conductivity (S/m)	1.970

C. SAR Surface and Volume




Maximum location: X=0.00, Y=-1.00 ; SAR Peak: 1.02 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.421
SAR 1g (W/Kg)	0.866
Variation (%)	2.980
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.020	0.655	0.359	0.187	0.091



F. 3D Image



System Performance Check Data (5200 MHz)

System check at 5200 MHz

Date of measurement: 15/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5200
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	5200.000
Relative permittivity (real part)	35.880
Relative permittivity (imaginary part)	16.250
Conductivity (S/m)	4.700

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 3.38 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.294
SAR 1g (W/Kg)	0.998
Variation (%)	-3.400
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	3.268	1.889	1.021	0.523	0.266	0.142	0.085	0.060	0.052



F. 3D Image



System Performance Check Data (5800 MHz)

System check at 5800 MHz

Date of measurement: 15/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.04
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5800
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	5800.000
Relative permittivity (real part)	35.180
Relative permittivity (imaginary part)	16.480
Conductivity (S/m)	5.310

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 4.17 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.280
SAR 1g (W/Kg)	1.023
Variation (%)	0.490
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	3.948	2.037	0.915	0.361	0.135	0.055	0.033	0.037	0.059



F. 3D Image



ANNEX C Test Data

1-Body with back position in dist. 0mm on Channel 128 in GPRS850+4slots

SAR Measurement at GPRS850 (Body, Validation Plane)

Date of measurement: 14/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	GPRS850
Channels	Lower (128)
Signal	TDMA (GPRS)
Modulation	GMSK (CS-1)
TX-slots	4

B. Permittivity

Frequency (MHz)	824.200
Relative permittivity (real part)	41.427
Relative permittivity (imaginary part)	19.473
Conductivity (S/m)	0.864

C. SAR Surface and Volume




Maximum location: X=-1.00, Y=0.00 ; SAR Peak: 0.83 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.228
SAR 1g (W/Kg)	0.450
Variation (%)	-2.130
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.834	0.473	0.220	0.104	0.056



F. 3D Image



2-Body with back position in dist. 0mm on Channel 810 in GPRS1900+2slots

SAR Measurement at GPRS1900 (Body, Validation Plane)

Date of measurement: 14/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	GPRS1900
Channels	Higher (810)
Signal	TDMA (GPRS)
Modulation	GMSK (CS-1)
TX-slots	2

B. Permittivity

Frequency (MHz)	1909.800
Relative permittivity (real part)	39.866
Relative permittivity (imaginary part)	13.394
Conductivity (S/m)	1.417

C. SAR Surface and Volume




Maximum location: X=-1.00, Y=-11.00 ; SAR Peak: 1.68 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.304
SAR 1g (W/Kg)	0.712
Variation (%)	2.060
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.673	0.947	0.447	0.224	0.139



F. 3D Image



3-Body with back position in dist. 0mm on Channel 20525 in LTE band 5

SAR Measurement at LTE band 5 (Body, Validation Plane)

Date of measurement: 14/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 5
Channels	Middle (20525)
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	49
RB size	1

B. Permittivity

Frequency (MHz)	840.910
Relative permittivity (real part)	41.401
Relative permittivity (imaginary part)	19.499
Conductivity (S/m)	0.873

C. SAR Surface and Volume




Maximum location: X=5.00, Y=-23.00 ; SAR Peak: 0.89 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.302
SAR 1g (W/Kg)	0.608
Variation (%)	-0.960
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.893	0.581	0.334	0.196	0.123



F. 3D Image



4-Body with back position in dist. 0mm on Channel 38150 in LTE band 38

SAR Measurement at LTE band 38 (Body, Validation Plane)

Date of measurement: 15/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.40
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 38
Channels	Higher (38150)
Signal	LTE TDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	99
RB size	1
Subframe configuration	0
Special subframe configuration	0
Cyclic prefix	Normal
Duty Cycle (%)	0.61

B. Permittivity

Frequency (MHz)	2618.910
Relative permittivity (real part)	38.855
Relative permittivity (imaginary part)	12.715
Conductivity (S/m)	1.990

C. SAR Surface and Volume




Maximum location: X=8.00, Y=-8.00 ; SAR Peak: 1.09 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.239
SAR 1g (W/Kg)	0.523
Variation (%)	-2.900
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.076	0.547	0.207	0.072	0.028



F. 3D Image



5-Body with back position in dist. 0mm on Channel 38750 in LTE band 40

SAR Measurement at LTE band 40 (Body, Validation Plane)

Date of measurement: 15/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.36
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 40
Channels	Lower (38750)
Signal	LTE TDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	0
RB size	1
Subframe configuration	0
Special subframe configuration	0
Cyclic prefix	Normal
Duty Cycle (%)	0.61

B. Permittivity

Frequency (MHz)	2310.000
Relative permittivity (real part)	41.418
Relative permittivity (imaginary part)	13.350
Conductivity (S/m)	1.708

C. SAR Surface and Volume




Maximum location: X=2.00, Y=-25.00 ; SAR Peak: 0.54 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.195
SAR 1g (W/Kg)	0.366
Variation (%)	-2.050
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.540	0.352	0.205	0.124	0.083



F. 3D Image



6-Body with back position in dist. 0mm on Channel 39750 in LTE band 41

SAR Measurement at LTE band 41 (Body, Validation Plane)

Date of measurement: 15/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.40
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 41
Channels	Lower (39750)
Signal	LTE TDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	99
RB size	1
Subframe configuration	0
Special subframe configuration	0
Cyclic prefix	Normal
Duty Cycle (%)	0.61

B. Permittivity

Frequency (MHz)	2506.090
Relative permittivity (real part)	41.315
Relative permittivity (imaginary part)	13.097
Conductivity (S/m)	1.870

C. SAR Surface and Volume




Maximum location: X=6.00, Y=-8.00 ; SAR Peak: 0.97 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.216
SAR 1g (W/Kg)	0.468
Variation (%)	-2.200
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.962	0.490	0.190	0.072	0.033



F. 3D Image



7-Body with back position in dist. 0mm on Channel 6 in IEEE 802.11b ISM

SAR Measurement at IEEE 802.11b ISM (Body, Validation Plane)

Date of measurement: 15/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.36
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11b ISM
Channels	Middle (6)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	2437.000
Relative permittivity (real part)	39.097
Relative permittivity (imaginary part)	13.396
Conductivity (S/m)	1.796

C. SAR Surface and Volume




Maximum location: X=8.00, Y=7.00 ; SAR Peak: 0.46 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.121
SAR 1g (W/Kg)	0.240
Variation (%)	-1.510
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.455	0.260	0.126	0.067	0.046



F. 3D Image



8-Body with back position in dist. 0mm on Channel 40 in IEEE 802.11n U-NII

SAR Measurement at IEEE 802.11n U-NII (Body, Validation Plane)

Date of measurement: 15/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11n U-NII
Channels	Middle (40)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	5200.000
Relative permittivity (real part)	35.880
Relative permittivity (imaginary part)	16.250
Conductivity (S/m)	4.700

C. SAR Surface and Volume




Maximum location: X=10.00, Y=0.00 ; SAR Peak: 0.55 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.251
SAR 1g (W/Kg)	0.418
Variation (%)	2.230
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.534	0.324	0.164	0.078	0.036



F. 3D Image



9-Body with back position in dist. 0mm on Channel 149 in IEEE 802.11a U-NII

SAR Measurement at IEEE 802.11a U-NII (Body, Validation Plane)

Date of measurement: 15/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.04
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11a U-NII
Channels	Higher (149)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	5745.000
Relative permittivity (real part)	35.235
Relative permittivity (imaginary part)	16.565
Conductivity (S/m)	5.255

C. SAR Surface and Volume




Maximum location: X=8.00, Y=-1.00 ; SAR Peak: 1.66 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.376
SAR 1g (W/Kg)	0.720
Variation (%)	1.510
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.620	0.947	0.459	0.220	0.113



F. 3D Image



ANNEX D SAR Test Setup Photos


Reference Photo: simulation liquid depth 15cm




Reference Photos



Back (dist. 0mm)



Top (dist. 0mm)



Bottom (dist. 0mm)

ANNEX E EUT External and Internal Photos

Please refer to RF Report.

ANNEX F Calibration Information

Please refer to the document "Calibration.pdf".



BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street,
Bao'an District, Shenzhen, China

www.btf-lab.com

--END OF REPORT--