


TEST REPORT

FCC ID.	2BBVL-AION7XX01	
Test Report No.	TCT240523E022	
Date of issue	Jul. 22, 2024	
Testing laboratory	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name	TES Touch Embedded Solutions Inc. Taiwan Branch	
Address	7F., No.141, Sec. 3, Ren ai Rd., Da an Dist., Taipei City 106, Taiwan, 222106 China	
Manufacturer's name ...	TES Touch Embedded Solutions Inc. Taiwan Branch	
Address	7F., No.141, Sec. 3, Ren ai Rd., Da an Dist., Taipei City 106, Taiwan, 222106 China	
Standard(s)	FCC CFR Title 47 Part 15 Subpart E Section 15.407 KDB 662911 D01 Multiple Transmitter Output v02r01 KDB 789033 D02 General U-NII Test Procedures New Rules v02r01	
Product Name	AIO Core Board module	
Trade Mark	TES/MicroTouch 	
Model/Type reference	AION7XX01	
Rating(s)	DC 4.2V	
Date of receipt of test item	May 23, 2024	
Date (s) of performance of test	May 23, 2024 ~ Jul. 22, 2024	
Tested by (+signature) ...	Aaron MO	
Check by (+signature)	Beryl ZHAO	
Approved by (+signature):	Tomsin	

General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1. General Product Information	3
1.1. EUT description	3
1.2. Model(s) list.....	3
1.3. Test Frequency	4
2. Test Result Summary	5
3. General Information.....	6
3.1. Test environment and mode.....	6
3.2. Description of Support Units	7
4. Facilities and Accreditations	8
4.1. Facilities	8
4.2. Location	8
4.3. Measurement Uncertainty.....	8
5. Test Results and Measurement Data	9
5.1. Antenna requirement	9
5.2. Conducted Emission.....	10
5.3. Band edge	14
5.4. Unwanted Emissions	29

Appendix B: Photographs of Test Setup

Appendix C: Photographs of EUT

1. General Product Information

1.1. EUT description

Product Name:	AIO Core Board module
Model/Type reference:	AION7XX01
Sample Number:	TCT240523E013-0101
Operation Frequency	Band 1: 5180 MHz~5240 MHz Band 2A: 5260 MHz~5320 MHz Band 2C: 5500 MHz~5700 MHz Band 3: 5745 MHz~5825 MHz
Channel Bandwidth:	802.11a: 20MHz 802.11n: 20MHz, 40MHz 802.11ac: 20MHz, 40MHz, 80MHz 802.11ax: 20MHz, 40MHz, 80MHz
Modulation Technology	Orthogonal Frequency Division Multiplexing(OFDM)
Modulation Type	256QAM, 64QAM, 16QAM, BPSK, QPSK
Antenna Type:	External Antenna
Antenna Gain:	Support two antenna: Antenna a: Band 1: Antenna 0: -5.36dBi, Antenna 1: -6.01dBi Band 2A: Antenna 0: -5.36dBi, Antenna 1: -6.01dBi Band 2C: Antenna 0: -5.78dBi, Antenna 1: -5.74dBi Band 3: Antenna 0: -5.23dBi, Antenna 1: -5.56dBi Antenna b: Band 1: Antenna 0: 3.28dBi, Antenna 1: -5.36dBi Band 2A: Antenna 0: 3.27dBi, Antenna 1: -5.36dBi Band 2C: Antenna 0: 3.45dBi, Antenna 1: -5.78dBi Band 3: Antenna 0: 5.09dBi, Antenna 1: -5.23dBi
Rating(s):	DC 4.2V

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

None.

1.3. Test Frequency

Band 1

20MHz		40MHz		80MHz	
Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180	38	5190	42	5210
40	5200	46	5230		
48	5240				

Band 2A

20MHz		40MHz		80MHz	
Channel	Frequency	Channel	Frequency	Channel	Frequency
52	5260	54	5270	58	5290
60	5300	62	5310		
64	5320				

Band 2C

20MHz		40MHz		80MHz	
Channel	Frequency	Channel	Frequency	Channel	Frequency
100	5500	102	5510	106	5530
120	5600	118	5590	122	5610
140	5700	134	5670		

Band 3

20MHz		40MHz		80MHz	
Channel	Frequency	Channel	Frequency	Channel	Frequency
149	5745	151	5755	155	5775
157	5785	159	5795		
165	5825				

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203	PASS
AC Power Line Conducted Emission	§15.207	PASS
Maximum Conducted Output Power	§15.407(a)	PASS
6dB Emission Bandwidth	§15.407(a)	PASS
26dB Emission Bandwidth & 99% Occupied Bandwidth	§15.407(a)	PASS
Power Spectral Density	§15.407(a)	PASS
Restricted Bands around fundamental frequency	§15.407(b)	PASS
Radiated Emission	§15.407(b)	PASS
Frequency Stability	§15.407(g)	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.
5. For the band 5.15-5.25GHz, EUT meet the requirements of 15.407(a)(ii).
6. Those test results (Maximum Conducted Output Power, 6dB Emission Bandwidth, 26dB Emission Bandwidth & 99% Occupied Bandwidth, Power Spectral Density, Frequency Stability) was based on FCC ID: 2BBVL-AION7XX01; Change antenna.

3. General Information

3.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Voltage:	DC 4.2V by Mainboard (Mainboard power by adapter)
Test Software:	
Software Information:	ADB Tool
Power Level:	20M P=7/10 40M P=8/12 80M P=10/14
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations with max. duty cycle.
The sample was placed 0.8m/1.5m for blow/above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	Data rate
802.11a(SISO)	6 Mbps
802.11n(HT20) (MIMO)	6.5 Mbps
802.11n(HT40) (MIMO)	13.5 Mbps
802.11ac(VHT20) (MIMO)	6.5 Mbps
802.11ac(VHT40) (MIMO)	13.5 Mbps

802.11ac(VHT80) (MIMO)	29.3 Mbps
802.11ax(HE20) (MIMO)	6.5 Mbps
802.11ax(HE40) (MIMO)	13.5 Mbps
802.11ax(HE80) (MIMO)	29.3 Mbps
Final Test Mode:	
Operation mode:	Keep the EUT in continuous transmitting with modulation

3.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
BOX PC	TBX-100N7020011002	/	/	MicroTouch
Media Player	IDX-300	/	/	MicroTouch

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

4. Facilities and Accreditations

4.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

4.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339


4.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	± 3.10 dB
2	RF power, conducted	± 0.12 dB
3	Spurious emissions, conducted	± 0.11 dB
4	All emissions, radiated(<1 GHz)	± 4.56 dB
5	All emissions, radiated(1 GHz - 18 GHz)	± 4.22 dB
6	All emissions, radiated(18 GHz- 40 GHz)	± 4.36 dB

5. Test Results and Measurement Data

5.1. Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
E.U.T Antenna:	
The EUT test with two external antennas for maximum gain which are detachable, and the gain is shown below.	
	
Refer to KDB 662911 D01 Multiple Transmitter Output v02r01: Unequal antenna gains, with equal transmit powers, if transmit signals are correlated, then antenna a: Directional gain of B1= $10\log[(10^{-5.36/20}+10^{-6.01/20})^2/2] = -2.67\text{dBi}$; Directional gain of B2A = $10\log[(10^{-5.36/20}+10^{-6.01/20})^2/2] = -2.67\text{dBi}$; Directional gain of B2C = $10\log[(10^{-5.78/20}+10^{-5.74/20})^2/2] = -2.75\text{dBi}$; Directional gain of B3 = $10\log[(10^{-5.23/20}+10^{-5.56/20})^2/2] = -2.38\text{dBi}$. antenna b: Directional gain of B1= $10\log[(10^{3.28/20}+10^{-5.36/20})^2/2] = 3.00\text{dBi}$; Directional gain of B2A = $10\log[(10^{3.27/20}+10^{-5.36/20})^2/2] = 3.00\text{dBi}$; Directional gain of B2C = $10\log[(10^{3.45/20}+10^{-5.78/20})^2/2] = 3.02\text{dBi}$; Directional gain of B3 = $10\log[(10^{5.09/20}+10^{-5.23/20})^2/2] = 4.39\text{dBi}$.	
Note: Above directional gain not applicable to power measurements.	

5.2. Conducted Emission

5.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	Reference Plane 40cm E.U.T AC power Test table/Insulation plane 80cm LISN Filter AC power EMI Receiver Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m														
Test Mode:	Transmitting Mode														
Test Procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.														
Test Result:	PASS														


5.2.2. Test Instruments

Conducted Emission Shielding Room Test Site (843)				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCI3	100898	Jun. 26, 2025
LISN	Schwarzbeck	NSLK 8126	8126453	Jan. 31, 2025
Attenuator	N/A	10dB	164080	Jun. 26, 2025
Line-5	TCT	CE-05	/	Jun. 26, 2025
EMI Test Software	EZ EMC	EMEC-3A1	1.1.4.2	/

5.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room

Phase: L1

Temperature: 22.8 (°C)

Humidity: 49 %

Limit: FCC Part 15C Conduction(QP)

Power: DC 4.2 V

No.	Mk.	Freq. MHz	Reading Level dBμV	Correct Factor dB	Measure- ment dBμV	Limit dBμV	Over dB	Detector	Comment
1	*	0.4060	32.20	9.42	41.62	57.73	-16.11	QP	
2		0.4060	22.05	9.42	31.47	47.73	-16.26	AVG	
3		1.0339	26.09	8.87	34.96	56.00	-21.04	QP	
4		1.0339	13.92	8.87	22.79	46.00	-23.21	AVG	
5		2.0419	24.95	10.03	34.98	56.00	-21.02	QP	
6		2.0419	14.97	10.03	25.00	46.00	-21.00	AVG	
7		3.7580	26.28	10.27	36.55	56.00	-19.45	QP	
8		3.7580	15.56	10.27	25.83	46.00	-20.17	AVG	
9		5.9618	24.92	10.45	35.37	60.00	-24.63	QP	
10		5.9618	13.37	10.45	23.82	50.00	-26.18	AVG	
11		14.6500	21.39	10.61	32.00	60.00	-28.00	QP	
12		14.6500	11.03	10.61	21.64	50.00	-28.36	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard


Margin (dB) = Measurement (dBμV) – Limits (dBμV)

Q.P. =Quasi-Peak

AVG =average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room

Phase: **N**

Temperature: 22.8 (°C)

Humidity: 49 %

Limit: FCC Part 15C Conduction(QP)

Power: DC 4.2 V

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.4168	34.88	9.39	44.27	57.51	-13.24	QP	
2		0.4168	24.14	9.39	33.53	47.51	-13.98	AVG	
3		0.7378	28.52	9.09	37.61	56.00	-18.39	QP	
4		0.7378	14.68	9.09	23.77	46.00	-22.23	AVG	
5		1.8020	27.30	9.96	37.26	56.00	-18.74	QP	
6		1.8020	16.34	9.96	26.30	46.00	-19.70	AVG	
7		3.8860	25.60	10.20	35.80	56.00	-20.20	QP	
8		3.8860	14.16	10.20	24.36	46.00	-21.64	AVG	
9		5.4100	21.67	10.35	32.02	60.00	-27.98	QP	
10		5.4100	10.63	10.35	20.98	50.00	-29.02	AVG	
11		15.3500	26.69	10.58	37.27	60.00	-22.73	QP	
12		15.3500	19.18	10.58	29.76	50.00	-20.24	AVG	

Note1: Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard

Margin (dB) = Measurement (dBμV) – Limits (dBμV)

Q.P. =Quasi-Peak

AVG =average


* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

Note2: Measurements were conducted in all three channels (high, middle, low) and all modulation (802.11a, 802.11n(HT20), 802.11n(HT40), 802.11ac(VHT20), 802.11ac(VHT40), 802.11ac(VHT80), 802.11ax(HE20), 802.11ax(HE40), 802.11ax(HE80)) and the worst case Mode (Channel 48 and 802.11ax(HE20) transmit with antenna 1) was submitted only.

Antenna a and Antenna b have been tested, but the test data only show the worst case model (Antenna b) in this report.

5.3. Band edge

5.3.1. Test Specification

Test Requirement:	FCC CFR47 Part 15E Section 15.407																				
Test Method:	ANSI C63.10 2013																				
Limit:	In un-restricted band: For Band 1&2A&2C: -27dBm/MHz For Band 3:																				
	<table><tr><th>Frequency (MHz)</th><th>Limit (dBm/MHz)</th><th>Frequency (MHz)</th><th>Limit (dBm/MHz)</th></tr><tr><td>< 650</td><td>-27</td><td>5850~5855</td><td>27~15.6</td></tr><tr><td>5650~5700</td><td>-27~10</td><td>5855~5875</td><td>15.6~10</td></tr><tr><td>5700~5720</td><td>10~15.6</td><td>5875~5925</td><td>10~-27</td></tr><tr><td>5720~5725</td><td>15.6~27</td><td>> 5925</td><td>-27</td></tr></table>	Frequency (MHz)	Limit (dBm/MHz)	Frequency (MHz)	Limit (dBm/MHz)	< 650	-27	5850~5855	27~15.6	5650~5700	-27~10	5855~5875	15.6~10	5700~5720	10~15.6	5875~5925	10~-27	5720~5725	15.6~27	> 5925	-27
	Frequency (MHz)	Limit (dBm/MHz)	Frequency (MHz)	Limit (dBm/MHz)																	
	< 650	-27	5850~5855	27~15.6																	
	5650~5700	-27~10	5855~5875	15.6~10																	
	5700~5720	10~15.6	5875~5925	10~-27																	
5720~5725	15.6~27	> 5925	-27																		
E[dBμV/m] = EIRP[dBm] + 95.2 @3m																					
In restricted band:																					
<table><tr><th>Detector</th><th>Limit@3m</th></tr><tr><td>Peak</td><td>74dBμV/m</td></tr><tr><td>AVG</td><td>54dBμV/m</td></tr></table>	Detector	Limit@3m	Peak	74dBμV/m	AVG	54dBμV/m															
Detector	Limit@3m																				
Peak	74dBμV/m																				
AVG	54dBμV/m																				
Test Setup:																					
Test Mode:	Transmitting mode with modulation																				
Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold																				


	Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasipeak or average method as specified and then reported in a data sheet.
Test Result:	PASS

5.3.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCI7	100529	Jan. 31, 2025
Spectrum Analyzer	R&S	FSQ40	200061	Jun. 26, 2025
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 26, 2025
Pre-amplifier	SKET	LNPA_0118G-45	SK2021012102	Jan. 31, 2025
Pre-amplifier	SKET	LNPA_1840G-50	SK202109203500	Jan. 31, 2025
Pre-amplifier	HP	8447D	2727A05017	Jun. 26, 2025
Loop antenna	Schwarzbeck	FMZB1519B	00191	Jun. 26, 2025
Broadband Antenna	Schwarzbeck	VULB9163	340	Jun. 28, 2025
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Jun. 28, 2025
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Feb. 02, 2025
Coaxial cable	SKET	RE-03-D	/	Jun. 26, 2025
Coaxial cable	SKET	RE-03-M	/	Jun. 26, 2025
Coaxial cable	SKET	RE-03-L	/	Jun. 26, 2025
Coaxial cable	SKET	RE-04-D	/	Jun. 26, 2025
Coaxial cable	SKET	RE-04-M	/	Jun. 26, 2025
Coaxial cable	SKET	RE-04-L	/	Jun. 26, 2025
Antenna Mast	Keleto	RE-AM	/	/
EMI Test Software	EZ_EMCC	FA-03A2 RE+	1.1.4.2	/

5.3.3. Test Data

AX20-5180



Site: 3m Anechoic Chamber

Polarization: **Horizontal**


Temperature: 23.4(°C)

Humidity: 53 %

Limit: FCC part 15.407 band edge (PK)

Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5150.000	59.78	-9.24	50.54	74.00	-23.46	peak	P	



Site: 3m Anechoic Chamber

Polarization: **Vertical**

Temperature: 23.4(°C)


Humidity: 53 %

Limit: FCC part 15.407 band edge (PK)

Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5150.000	56.97	-9.24	47.73	74.00	-26.27	peak	P	

AX40-5190




Site: 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 23.4(°C) Humidity: 53 %

Limit: FCC part 15.407 band edge (PK)

Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5150.000	56.79	-9.24	47.55	74.00	-26.45	peak	P	




Site: 3m Anechoic Chamber Polarization: **Vertical** Temperature: 23.4(°C) Humidity: 53 %

Limit: FCC part 15.407 band edge (PK)

Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5150.000	55.31	-9.24	46.07	74.00	-27.93	peak	P	

AX80-5210




Site: 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 23.4(°C) Humidity: 53 %

Limit: FCC part 15.407 band edge (PK)

Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5150.000	59.27	-9.24	50.03	74.00	-23.97	peak	P	





Site: 3m Anechoic Chamber Polarization: **Vertical** Temperature: 23.4(°C) Humidity: 53 %

Limit: FCC part 15.407 band edge (PK)


Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5150.000	55.57	-9.24	46.33	74.00	-27.67	peak	P	

AX20-5320



AX40-5310




Site: 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 23.4(°C) Humidity: 53 %

Limit: FCC part 15.407 band edge (PK)

Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5350.000	58.55	-8.15	50.40	74.00	-23.60	peak	P	





Site: 3m Anechoic Chamber Polarization: **Vertical** Temperature: 23.4(°C) Humidity: 53 %

Limit: FCC part 15.407 band edge (PK)


Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5350.000	52.28	-8.15	44.13	74.00	-29.87	peak	P	

AX80-5290



AX20-5500



Site: 3m Anechoic Chamber

Polarization: **Horizontal**


Temperature: 23.4(°C)

Humidity: 53 %

Limit: FCC part 15.407 band edge (PK)

Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5460.000	51.12	-8.20	42.92	68.20	-25.28	peak	P	



Site: 3m Anechoic Chamber

Polarization: **Vertical**

Temperature: 23.4(°C)


Humidity: 53 %

Limit: FCC part 15.407 band edge (PK)

Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5460.000	49.43	-8.20	41.23	68.20	-26.97	peak	P	

AX40-5510




Site: 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 23.4(°C) Humidity: 53 %

Limit: FCC part 15.407 band edge (PK)

Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5460.000	56.10	-8.20	47.90	68.20	-20.30	peak	P	




Site: 3m Anechoic Chamber Polarization: **Vertical** Temperature: 23.4(°C) Humidity: 53 %

Limit: FCC part 15.407 band edge (PK)

Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5460.000	48.43	-8.20	40.23	68.20	-27.97	peak	P	

AX80-5530



Site: 3m Anechoic Chamber

Polarization: **Horizontal**


Temperature: 23.4(°C)

Humidity: 53 %

Limit: FCC part 15.407 band edge (PK)

Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5460.000	55.74	-8.20	47.54	68.20	-20.66	peak	P	



Site: 3m Anechoic Chamber

Polarization: **Vertical**

Temperature: 23.4(°C)


Humidity: 53 %

Limit: FCC part 15.407 band edge (PK)

Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5460.000	52.84	-8.20	44.64	68.20	-23.56	peak	P	

AX20-5825




Site: 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 23.4(°C) Humidity: 53 %

Limit: FCC part 15.407 band edge (PK)

Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5901.780	52.70	-6.99	45.71	68.20	-22.49	peak	P	




Site: 3m Anechoic Chamber Polarization: **Vertical** Temperature: 23.4(°C) Humidity: 53 %

Limit: FCC part 15.407 band edge (PK)

Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5903.120	49.89	-6.98	42.91	68.20	-25.29	peak	P	


AX40-5795



Site: 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 23.4(°C) Humidity: 53 %

Limit: FCC part 15.407 band edge (PK) Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5904.275	49.14	-6.97	42.17	68.20	-26.03	peak	P	




Site: 3m Anechoic Chamber Polarization: **Vertical** Temperature: 23.4(°C) Humidity: 53 %

Limit: FCC part 15.407 band edge (PK) Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5907.975	48.65	-6.96	41.69	68.20	-26.51	peak	P	

AX80-5775




Site: 3m Anechoic Chamber Polarization: **Horizontal** Temperature: 23.4(°C) Humidity: 53 %

Limit: FCC part 15.407 band edge (PK)

Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5924.160	48.77	-6.89	41.88	68.20	-26.32	peak	P	



Site: 3m Anechoic Chamber Polarization: **Vertical** Temperature: 23.4(°C) Humidity: 53 %

Limit: FCC part 15.407 band edge (PK)

Power: DC 4.2 V


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5906.520	48.42	-6.97	41.45	68.20	-26.75	peak	P	


Note: 1. All modulation (802.11a, 802.11n, 802.11ac, 802.11ax) have been tested, only the worst case in 802.11ax be reported.

2. Antenna a and Antenna b have been tested, but the test data only show the worst case model (Antenna b) in this report.


5.4. Unwanted Emissions

5.4.1. Test Specification

Test Requirement:	FCC CFR47 Part 15 Section 15.407 & 15.209 & 15.205				
Test Method:	KDB 789033 D02 v02r01				
Frequency Range:	9kHz to 40GHz				
Measurement Distance:	3 m				
Antenna Polarization:	Horizontal & Vertical				
Operation mode:	Transmitting mode with modulation				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit:	Unwanted spurious emissions fallen in restricted bands per FCC Part15.205 shall comply with the general field strength limits set forth in § 15.209 as below table, In restricted bands:				
	Frequency	Detector	Limit@3m		
	Above 1G	Peak	74dB μ V/m		
		AVG	54dB μ V/m		
	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)		
	0.009-0.490	2400/F(KHz)	300		
	0.490-1.705	24000/F(KHz)	3		
	1.705-30	30	30		
	30-88	100	3		
	88-216	150	3		
	216-960	200	3		
	Above 960	500	3		
In un-restricted bands: 68.2dB μ V/m					
Test setup:	For radiated emissions below 30MHz				
					
30MHz to 1GHz					



Above 1GHz



Test Procedure:

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotating table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


Test results:

PASS

5.4.2. Test Data

Please refer to following diagram for individual
Below 1GHz

Horizontal:



Site: 3m Anechoic Chamber1

Polarization: **Horizontal**


Temperature: 25.1(C) Humidity: 53 %

Limit: FCC Part 15C RE_3m

Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	38.0783	28.17	-12.13	16.04	40.00	-23.96	QP	P	
2	61.3463	28.34	-12.86	15.48	40.00	-24.52	QP	P	
3	100.9339	31.45	-15.32	16.13	43.50	-27.37	QP	P	
4 *	157.0074	34.88	-11.28	23.60	43.50	-19.90	QP	P	
5	346.8092	33.89	-10.06	23.83	46.00	-22.17	QP	P	
6	670.4893	26.88	-4.24	22.64	46.00	-23.36	QP	P	

Vertical:



Site: 3m Anechoic Chamber1

Polarization: **Vertical**

Temperature: 25.1(C)

Humidity: 53 %

Limit: FCC Part 15C RE_3m

Power: DC 4.2 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	30.0000	45.92	-13.00	32.92	40.00	-7.08	QP	P	
2	35.0048	43.91	-12.57	31.34	40.00	-8.66	QP	P	
3	63.9828	35.95	-13.27	22.68	40.00	-17.32	QP	P	
4	103.0800	39.59	-15.09	24.50	43.50	-19.00	QP	P	
5	157.0074	36.94	-11.28	25.66	43.50	-17.84	QP	P	
6	295.1469	33.17	-10.99	22.18	46.00	-23.82	QP	P	

- Note:**
- The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported
 - Measurements were conducted in all three channels (high, middle, low) and all modulation (802.11a, 802.11n(HT20), 802.11n(HT40), 802.11ac(VHT20), 802.11ac(VHT40), 802.11ac(VHT80), 802.11ax(HE20), 802.11ax(HE40), 802.11ax(HE80)) and the worst case Mode (Channel 48 and 802.11ax(HE20) transmit with antenna 1) was submitted only.
Antenna a and Antenna b have been tested, but the test data only show the worst case model (Antenna b) in this report.
 - Measurement (dBμV) = Reading level + Correction Factor, correction Factor= Antenna Factor + Cable loss – Pre-amplifier.

Modulation Type: Band 1									
11a CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	38.04	---	8.02	46.06	---	68.2	---	-22.14
15540	H	37.69	---	9.87	47.56	---	74	54	-6.44
---	H	---	---	---	---	---	---	---	---
10360	V	38.15	---	8.02	46.17	---	68.2	---	-22.03
15540	V	37.47	---	9.87	47.34	---	74	54	-6.66
---	V	---	---	---	---	---	---	---	---
11a CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	39.28	---	7.97	47.25	---	68.2	---	-20.95
15600	H	38.51	---	9.83	48.34	---	74	54	-5.66
---	H	---	---	---	---	---	---	---	---
10400	V	40.14	---	7.97	48.11	---	68.2	---	-20.09
15600	V	38.86	---	9.83	48.69	---	74	54	-5.31
---	V	---	---	---	---	---	---	---	---
11a CH48: 5240MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	38.21	---	7.97	46.18	---	68.2	---	-22.02
15720	H	37.96	---	9.83	47.79	---	74	54	-6.21
---	H	---	---	---	---	---	---	---	---
10480	V	38.64	---	7.97	46.61	---	68.2	---	-21.59
15720	V	36.05	---	9.83	45.88	---	74	54	-8.12
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	41.36	---	8.02	49.38	---	68.2	---	-18.82
15540	H	37.58	---	9.87	47.45	---	74	54	-6.55
---	H	---	---	---	---	---	---	---	---
10360	V	42.12	---	8.02	50.14	---	68.2	---	-18.06
15540	V	37.74	---	9.87	47.61	---	74	54	-6.39
---	V	---	---	---	---	---	---	---	---

11n(HT20) CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	40.56	---	7.97	48.53	---	68.2	---	-19.67
15600	H	38.31	---	9.83	48.14	---	74	54	-5.86
---	H	---	---	---	---	---	---	---	---
10400	V	40.02	---	7.97	47.99	---	68.2	---	-20.21
15600	V	37.78	---	9.83	47.61	---	74	54	-6.39
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH48: 5240MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	41.25	---	7.97	49.22	---	68.2	---	-18.98
15720	H	38.86	---	9.83	48.69	---	74	54	-5.31
---	H	---	---	---	---	---	---	---	---
10480	V	40.12	---	7.97	48.09	---	68.2	---	-20.11
15720	V	38.39	---	9.83	48.22	---	74	54	-5.78
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH38: 5190MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10380	H	39.78	---	7.75	47.53	---	68.2	---	-20.67
15570	H	37.15	---	9.87	47.02	---	74	54	-6.98
---	H	---	---	---	---	---	---	---	---
10380	V	40.69	---	7.75	48.44	---	68.2	---	-19.76
15570	V	37.02	---	9.87	46.89	---	74	54	-7.11
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH46: 5230MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10460	H	41.96	---	7.97	49.93	---	68.2	---	-18.27
15690	H	38.45	---	9.83	48.28	---	74	54	-5.72
---	H	---	---	---	---	---	---	---	---
10460	V	41.21	---	7.97	49.18	---	68.2	---	-19.02
15690	V	38.04	---	9.83	47.87	---	74	54	-6.13
---	V	---	---	---	---	---	---	---	---

11ac(VHT20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	40.63	---	8.02	48.65	---	68.2	---	-19.55
15540	H	37.47	---	9.87	47.34	---	74	54	-6.66
---	H	---	---	---	---	---	---	---	---
10360	V	38.15	---	8.02	46.17	---	68.2	---	-22.03
15540	V	39.22	---	9.87	49.09	---	74	54	-4.91
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	39.56	---	7.97	47.53	---	68.2	---	-20.67
15600	H	38.91	---	9.83	48.74	---	74	54	-5.26
---	H	---	---	---	---	---	---	---	---
10400	V	39.67	---	7.97	47.64	---	68.2	---	-20.56
15600	V	38.48	---	9.83	48.31	---	74	54	-5.69
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH48:5240									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	37.17	---	7.97	45.14	---	68.2	---	-23.06
15720	H	37.39	---	9.83	47.22	---	74	54	-6.78
---	H	---	---	---	---	---	---	---	---
10480	V	38.82	---	7.97	46.79	---	68.2	---	-21.41
15720	V	38.04	---	9.83	47.87	---	74	54	-6.13
---	V	---	---	---	---	---	---	---	---
11ac(VHT40) CH38:5190									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10380	H	40.28	---	7.75	48.03	---	68.2	---	-20.17
15570	H	39.47	---	9.87	49.34	---	74	54	-4.66
---	H	---	---	---	---	---	---	---	---
10380	V	38.93	---	7.75	46.68	---	68.2	---	-21.52
15570	V	38.15	---	9.87	48.02	---	74	54	-5.98
---	V	---	---	---	---	---	---	---	---

11ac(VHT40) CH46:5230									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10460	H	38.15	---	7.97	46.12	---	68.2	---	-22.08
15690	H	38.99	---	9.83	48.82	---	74	54	-5.18
---	H	---	---	---	---	---	---	---	---
10460	V	39.24	---	7.97	47.21	---	68.2	---	-20.99
15690	V	37.36	---	9.83	47.19	---	74	54	-6.81
---	V	---	---	---	---	---	---	---	---
11ac(VHT80) CH42:5210									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10420	H	41.88	---	7.96	49.84	---	68.2	---	-18.36
15630	H	39.45	---	9.84	49.29	---	74	54	-4.71
---	H	---	---	---	---	---	---	---	---
10420	V	41.12	---	7.96	49.08	---	68.2	---	-19.12
15630	V	39.95	---	9.84	49.79	---	74	54	-4.21
---	V	---	---	---	---	---	---	---	---
11ax(HE20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	39.69	---	8.02	47.71	---	68.2	---	-20.49
15540	H	37.44	---	9.87	47.31	---	74	54	-6.69
---	H	---	---	---	---	---	---	---	---
10360	V	38.71	---	8.02	46.73	---	68.2	---	-21.47
15540	V	38.25	---	9.87	48.12	---	74	54	-5.88
---	V	---	---	---	---	---	---	---	---
11ax(HE20) CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	39.66	---	7.97	47.63	---	68.2	---	-20.57
15600	H	38.14	---	9.83	47.97	---	74	54	-6.03
---	H	---	---	---	---	---	---	---	---
10400	V	39.87	---	7.97	47.84	---	68.2	---	-20.36
15600	V	38.01	---	9.83	47.84	---	74	54	-6.16
---	V	---	---	---	---	---	---	---	---

11ax(HE20) CH48:5240									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	37.99	---	7.97	45.96	---	68.2	---	-22.24
15720	H	37.58	---	9.83	47.41	---	74	54	-6.59
---	H	---	---	---	---	---	---	---	---
10480	V	38.46	---	7.97	46.43	---	68.2	---	-21.77
15720	V	38.31	---	9.83	48.14	---	74	54	-5.86
---	V	---	---	---	---	---	---	---	---
11ax(HE40) CH38:5190									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10380	H	40.33	---	7.75	48.08	---	68.2	---	-20.12
15570	H	39.85	---	9.87	49.72	---	74	54	-4.28
---	H	---	---	---	---	---	---	---	---
10380	V	38.14	---	7.75	45.89	---	68.2	---	-22.31
15570	V	38.69	---	9.87	48.56	---	74	54	-5.44
---	V	---	---	---	---	---	---	---	---
11ax(HE40) CH46:5230									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10460	H	38.47	---	7.97	46.44	---	68.2	---	-21.76
15690	H	38.23	---	9.83	48.06	---	74	54	-5.94
---	H	---	---	---	---	---	---	---	---
10460	V	39.86	---	7.97	47.83	---	68.2	---	-20.37
15690	V	37.15	---	9.83	46.98	---	74	54	-7.02
---	V	---	---	---	---	---	---	---	---

11ax(HE80) CH42:5210									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10420	H	41.57	---	7.96	49.53	---	68.2	---	-18.67
15630	H	39.23	---	9.84	49.07	---	74	54	-4.93
---	H	---	---	---	---	---	---	---	---
10420	V	41.66	---	7.96	49.62	---	68.2	---	-18.58
15630	V	39.71	---	9.84	49.55	---	74	54	-4.45
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. Antenna a and Antenna b have been tested, but the test data only show the worst case model (Antenna b) in this report.

Modulation Type: Band 2A									
11a CH52: 5260MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10520	H	38.51	---	7.97	46.48	---	68.2	---	-21.72
15780	H	36.23	---	9.83	46.06	---	74	54	-7.94
---	H	---	---	---	---	---	---	---	---
10520	V	41.07	---	7.97	49.04	---	68.2	---	-19.16
15780	V	38.65	---	9.83	48.48	---	74	54	-5.52
---	V	---	---	---	---	---	---	---	---
11a CH60: 5300MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10600	H	38.98	---	7.98	46.96	---	74	54	-7.04
15900	H	36.24	---	9.85	46.09	---	74	54	-7.91
---	H	---	---	---	---	---	---	---	---
10600	V	39.71	---	7.98	47.69	---	74	54	-6.31
15900	V	37.36	---	9.85	47.21	---	74	54	-6.79
---	V	---	---	---	---	---	---	---	---
11a CH64: 5320MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10640	H	40.35	---	7.98	48.33	---	74	54	-5.67
15960	H	37.47	---	9.85	47.32	---	74	54	-6.68
---	H	---	---	---	---	---	---	---	---
10640	V	39.66	---	7.98	47.64	---	74	54	-6.36
15960	V	35.82	---	9.85	45.67	---	74	54	-8.33
---	V	---	---	---	---	---	---	---	---
11n(HT20) C52: 5260MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10520	H	41.87	---	7.97	49.84	---	68.2	---	-18.36
15780	H	38.12	---	9.83	47.95	---	74	54	-6.05
---	H	---	---	---	---	---	---	---	---
10520	V	38.55	---	7.97	46.52	---	68.2	---	-21.68
15780	V	35.26	---	9.83	45.09	---	74	54	-8.91
---	V	---	---	---	---	---	---	---	---

11n(HT20) CH60: 5300MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10600	H	38.58	---	7.98	46.56	---	74	54	-7.44
15900	H	35.14	---	9.85	44.99	---	74	54	-9.01
---	H	---	---	---	---	---	---	---	---
10600	V	40.99	---	7.98	48.97	---	74	54	-5.03
15900	V	38.32	---	9.85	48.17	---	74	54	-5.83
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH64: 5320MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10640	H	37.71	---	7.98	45.69	---	74	54	-8.31
15960	H	35.16	---	9.85	45.01	---	74	54	-8.99
---	H	---	---	---	---	---	---	---	---
10640	V	39.34	---	7.98	47.32	---	74	54	-6.68
15960	V	37.89	---	9.85	47.74	---	74	54	-6.26
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH54: 5270MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10540	H	41.74	---	7.97	49.71	---	68.2	---	-18.49
15810	H	37.25	---	9.83	47.08	---	74	54	-6.92
---	H	---	---	---	---	---	---	---	---
10540	V	37.56	---	7.97	45.53	---	68.2	---	-22.67
15810	V	36.39	---	9.83	46.22	---	74	54	-7.78
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH62: 5310MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10620	H	40.86	---	7.98	48.84	---	74	54	-5.16
15930	H	37.47	---	9.85	47.32	---	74	54	-6.68
---	H	---	---	---	---	---	---	---	---
10620	V	38.61	---	7.98	46.59	---	74	54	-7.41
15930	V	35.23	---	9.85	45.08	---	74	54	-8.92
---	V	---	---	---	---	---	---	---	---

11ac(VHT20) C52: 5260MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10520	H	40.25	---	7.97	48.22	---	68.2	---	-19.98
15780	H	39.04	---	9.83	48.87	---	74	54	-5.13
---	H	---	---	---	---	---	---	---	---
10520	V	40.77	---	7.97	48.74	---	68.2	---	-19.46
15780	V	37.82	---	9.83	47.65	---	74	54	-6.35
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH60: 5300MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10600	H	38.45	---	7.98	46.43	---	74	54	-7.57
15900	H	35.12	---	9.85	44.97	---	74	54	-9.03
---	H	---	---	---	---	---	---	---	---
10600	V	37.56	---	7.98	45.54	---	74	54	-8.46
15900	V	34.38	---	9.85	44.23	---	74	54	-9.77
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH64: 5320MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10640	H	40.14	---	7.98	48.12	---	74	54	-5.88
15960	H	37.36	---	9.85	47.21	---	74	54	-6.79
---	H	---	---	---	---	---	---	---	---
10640	V	40.98	---	7.98	48.96	---	74	54	-5.04
15960	V	35.72	---	9.85	45.57	---	74	54	-8.43
---	V	---	---	---	---	---	---	---	---
11ac(VHT40) CH54: 5270MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10540	H	40.57	---	7.97	48.54	---	68.2	---	-19.66
15810	H	37.12	---	9.83	46.95	---	74	54	-7.05
---	H	---	---	---	---	---	---	---	---
10540	V	39.45	---	7.97	47.42	---	68.2	---	-20.78
15810	V	37.68	---	9.83	47.51	---	74	54	-6.49
---	V	---	---	---	---	---	---	---	---

11ac(VHT40) CH62: 5310MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10620	H	38.15	---	7.98	46.13	---	74	54	-7.87
15930	H	36.67	---	9.85	46.52	---	74	54	-7.48
---	H	---	---	---	---	---	---	---	---
10620	V	39.38	---	7.98	47.36	---	74	54	-6.64
15930	V	37.42	---	9.85	47.27	---	74	54	-6.73
---	V	---	---	---	---	---	---	---	---
11ac(VHT80) C58:5290MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10580	H	41.58	---	7.98	49.56	---	74	54	-4.44
15870	H	38.24	---	9.85	48.09	---	74	54	-5.91
---	H	---	---	---	---	---	---	---	---
10580	V	40.81	---	7.98	48.79	---	74	54	-5.21
15870	V	37.99	---	9.85	47.84	---	74	54	-6.16
---	V	---	---	---	---	---	---	---	---
11ax(HE20) C52: 5260MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10520	H	40.54	---	7.97	48.51	---	68.2	---	-19.69
15780	H	39.98	---	9.83	49.81	---	74	54	-4.19
---	H	---	---	---	---	---	---	---	---
10520	V	40.27	---	7.97	48.24	---	68.2	---	-19.96
15780	V	37.46	---	9.83	47.29	---	74	54	-6.71
---	V	---	---	---	---	---	---	---	---
11ax(HE20) CH60: 5300MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10600	H	38.63	---	7.98	46.61	---	74	54	-7.39
15900	H	36.27	---	9.85	46.12	---	74	54	-7.88
---	H	---	---	---	---	---	---	---	---
10600	V	37.45	---	7.98	45.43	---	74	54	-8.57
15900	V	35.82	---	9.85	45.67	---	74	54	-8.33
---	V	---	---	---	---	---	---	---	---

11ax(HE20) CH64: 5320MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10640	H	40.35	---	7.98	48.33	---	74	54	-5.67
15960	H	37.47	---	9.85	47.32	---	74	54	-6.68
---	H	---	---	---	---	---	---	---	---
10640	V	40.61	---	7.98	48.59	---	74	54	-5.41
15960	V	35.72	---	9.85	45.57	---	74	54	-8.43
---	V	---	---	---	---	---	---	---	---
11ax(HE40) CH54: 5270MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10540	H	40.99	---	7.97	48.96	---	68.2	---	-19.24
15810	H	37.51	---	9.83	47.34	---	74	54	-6.66
---	H	---	---	---	---	---	---	---	---
10540	V	39.68	---	7.97	47.65	---	68.2	---	-20.55
15810	V	37.12	---	9.83	46.95	---	74	54	-7.05
---	V	---	---	---	---	---	---	---	---
11ax(HE40) CH62: 5310MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10620	H	38.15	---	7.98	46.13	---	74	54	-7.87
15930	H	36.46	---	9.85	46.31	---	74	54	-7.69
---	H	---	---	---	---	---	---	---	---
10620	V	39.68	---	7.98	47.66	---	74	54	-6.34
15930	V	37.93	---	9.85	47.78	---	74	54	-6.22
---	V	---	---	---	---	---	---	---	---

11ax(HE80) C58:5290MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10580	H	41.45	---	7.98	49.43	---	74	54	-4.57
15870	H	39.23	---	9.85	49.08	---	74	54	-4.92
---	H	---	---	---	---	---	---	---	---
10580	V	40.66	---	7.98	48.64	---	74	54	-5.36
15870	V	37.87	---	9.85	47.72	---	74	54	-6.28
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. Antenna a and Antenna b have been tested, but the test data only show the worst case model (Antenna b) in this report.

Modulation Type: Band 2C									
11a CH100: 5500MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11000	H	39.45	---	8.03	47.48	---	74	54	-6.52
16500	H	39.32	---	9.76	49.08	---	68.2	---	-19.12
---	H	---	---	---	---	---	---	---	---
11000	V	40.59	---	8.03	48.62	---	74	54	-5.38
16500	V	40.87	---	9.76	50.63	---	68.2	---	-17.57
---	V	---	---	---	---	---	---	---	---
11a CH120: 5600MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11200	H	40.51	---	8.04	48.55	---	74	54	-5.45
16800	H	40.47	---	9.74	50.21	---	68.2	---	-17.99
---	H	---	---	---	---	---	---	---	---
11200	V	38.88	---	8.04	46.92	---	74	54	-7.08
16800	V	39.23	---	9.74	48.97	---	68.2	---	-19.23
---	V	---	---	---	---	---	---	---	---
11a CH140: 5700MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11400	H	38.82	---	8.05	46.87	---	74	54	-7.13
17100	H	40.56	---	9.72	50.28	---	68.2	---	-17.92
---	H	---	---	---	---	---	---	---	---
11400	V	38.21	---	8.05	46.26	---	74	54	-7.74
17100	V	40.45	---	9.72	50.17	---	68.2	---	-18.03
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH100: 5500MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11000	H	40.66	---	8.03	48.69	---	74	54	-5.31
16500	H	39.23	---	9.76	48.99	---	68.2	---	-19.21
---	H	---	---	---	---	---	---	---	---
11000	V	38.41	---	8.03	46.44	---	74	54	-7.56
16500	V	41.98	---	9.76	51.74	---	68.2	---	-16.46
---	V	---	---	---	---	---	---	---	---

11n(HT20) CH120: 5600MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11200	H	39.33	---	8.04	47.37	---	74	54	-6.63
16800	H	40.51	---	9.74	50.25	---	68.2	---	-17.95
---	H	---	---	---	---	---	---	---	---
11200	V	38.04	---	8.04	46.08	---	74	54	-7.92
16800	V	39.87	---	9.74	49.61	---	68.2	---	-18.59
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH140: 5700MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11400	H	39.46	---	8.05	47.51	---	74	54	-6.49
17100	H	40.52	---	9.72	50.24	---	68.2	---	-17.96
---	H	---	---	---	---	---	---	---	---
11400	V	38.69	---	8.05	46.74	---	74	54	-7.26
17100	V	39.14	---	9.72	48.86	---	68.2	---	-19.34
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH102: 5510MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11020	H	39.01	---	8.03	47.04	---	74	54	-6.96
16530	H	39.89	---	9.76	49.65	---	68.2	---	-18.55
---	H	---	---	---	---	---	---	---	---
11020	V	39.32	---	8.03	47.35	---	74	54	-6.65
16530	V	37.76	---	9.76	47.52	---	68.2	---	-20.68
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH118: 5590MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11180	H	39.88	---	8.04	47.92	---	74	54	-6.08
16770	H	39.23	---	9.74	48.97	---	68.2	---	-19.23
---	H	---	---	---	---	---	---	---	---
11180	V	37.97	---	8.04	46.01	---	74	54	-7.99
16770	V	41.12	---	9.74	50.86	---	68.2	---	-17.34
---	V	---	---	---	---	---	---	---	---

11n(HT40) CH134: 5670MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11340	H	40.98	---	8.05	49.03	---	74	54	-4.97
17010	H	41.41	---	9.72	51.13	---	68.2	---	-17.07
---	H	---	---	---	---	---	---	---	---
11340	V	39.86	---	8.05	47.91	---	74	54	-6.09
17010	V	38.33	---	9.72	48.05	---	68.2	---	-20.15
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH100: 5500MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11000	H	37.24	---	8.03	45.27	---	74	54	-8.73
16500	H	39.78	---	9.76	49.54	---	68.2	---	-18.66
---	H	---	---	---	---	---	---	---	---
11000	V	39.13	---	8.03	47.16	---	74	54	-6.84
16500	V	39.07	---	9.76	48.83	---	68.2	---	-19.37
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH120: 5600MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11200	H	40.58	---	8.04	48.62	---	74	54	-5.38
16800	H	39.04	---	9.74	48.78	---	68.2	---	-19.42
---	H	---	---	---	---	---	---	---	---
11200	V	39.39	---	8.04	47.43	---	74	54	-6.57
16800	V	39.21	---	9.74	48.95	---	68.2	---	-19.25
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH140: 5700MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11400	H	39.47	---	8.05	47.52	---	74	54	-6.48
17100	H	38.61	---	9.72	48.33	---	68.2	---	-19.87
---	H	---	---	---	---	---	---	---	---
11400	V	40.22	---	8.05	48.27	---	74	54	-5.73
17100	V	39.53	---	9.72	49.25	---	68.2	---	-18.95
---	V	---	---	---	---	---	---	---	---

11ac(VHT40) CH102: 5510MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11020	H	38.59	---	8.03	46.62	---	74	54	-7.38
16530	H	39.23	---	9.76	48.99	---	68.2	---	-19.21
---	H	---	---	---	---	---	---	---	---
11020	V	41.66	---	8.03	49.69	---	74	54	-4.31
16530	V	38.71	---	9.76	48.47	---	68.2	---	-19.73
---	V	---	---	---	---	---	---	---	---
11ac(VHT40) CH118: 5590MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11180	H	38.05	---	8.04	46.09	---	74	54	-7.91
16770	H	36.47	---	9.74	46.21	---	68.2	---	-21.99
---	H	---	---	---	---	---	---	---	---
11180	V	38.18	---	8.04	46.22	---	74	54	-7.78
16770	V	37.39	---	9.74	47.13	---	68.2	---	-21.07
---	V	---	---	---	---	---	---	---	---
11ac(VHT40) CH134: 5670MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11340	H	37.21	---	8.05	45.26	---	74	54	-8.74
17010	H	36.99	---	9.72	46.71	---	68.2	---	-21.49
---	H	---	---	---	---	---	---	---	---
11340	V	37.47	---	8.05	45.52	---	74	54	-8.48
17010	V	39.63	---	9.72	49.35	---	68.2	---	-18.85
---	V	---	---	---	---	---	---	---	---
11ac(VHT80) CH106: 5530MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11060	H	39.88	---	8.03	47.91	---	74	54	-6.09
16590	H	40.12	---	9.75	49.87	---	68.2	---	-18.33
---	H	---	---	---	---	---	---	---	---
11060	V	40.36	---	8.03	48.39	---	74	54	-5.61
16590	V	41.41	---	9.75	51.16	---	68.2	---	-17.04
---	V	---	---	---	---	---	---	---	---

11ac(VHT80) CH122: 5610MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11220	H	40.63	---	8.05	48.68	---	74	54	-5.32
16830	H	38.21	---	9.72	47.93	---	68.2	---	-20.27
---	H	---	---	---	---	---	---	---	---
11220	V	39.78	---	8.05	47.83	---	74	54	-6.17
16830	V	39.04	---	9.72	48.76	---	68.2	---	-19.44
---	V	---	---	---	---	---	---	---	---
11ax(HE20) CH100: 5500MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11000	H	37.41	---	8.03	45.44	---	74	54	-8.56
16500	H	39.28	---	9.76	49.04	---	68.2	---	-19.16
---	H	---	---	---	---	---	---	---	---
11000	V	39.53	---	8.03	47.56	---	74	54	-6.44
16500	V	39.67	---	9.76	49.43	---	68.2	---	-18.77
---	V	---	---	---	---	---	---	---	---
11ax(HE20) CH120: 5600MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11200	H	40.08	---	8.04	48.12	---	74	54	-5.88
16800	H	39.14	---	9.74	48.88	---	68.2	---	-19.32
---	H	---	---	---	---	---	---	---	---
11200	V	39.35	---	8.04	47.39	---	74	54	-6.61
16800	V	39.78	---	9.74	49.52	---	68.2	---	-18.68
---	V	---	---	---	---	---	---	---	---
11ax(HE20) CH140: 5700MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11400	H	39.16	---	8.05	47.21	---	74	54	-6.79
17100	H	38.23	---	9.72	47.95	---	68.2	---	-20.25
---	H	---	---	---	---	---	---	---	---
11400	V	40.69	---	8.05	48.74	---	74	54	-5.26
17100	V	39.07	---	9.72	48.79	---	68.2	---	-19.41
---	V	---	---	---	---	---	---	---	---

11ax(HE40) CH102: 5510MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11020	H	38.35	---	8.03	46.38	---	74	54	-7.62
16530	H	39.78	---	9.76	49.54	---	68.2	---	-18.66
---	H	---	---	---	---	---	---	---	---
11020	V	41.04	---	8.03	49.07	---	74	54	-4.93
16530	V	38.12	---	9.76	47.88	---	68.2	---	-20.32
---	V	---	---	---	---	---	---	---	---
11ax(HE40) CH118: 5590MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11180	H	38.39	---	8.04	46.43	---	74	54	-7.57
16770	H	36.88	---	9.74	46.62	---	68.2	---	-21.58
---	H	---	---	---	---	---	---	---	---
11180	V	38.52	---	8.04	46.56	---	74	54	-7.44
16770	V	37.41	---	9.74	47.15	---	68.2	---	-21.05
---	V	---	---	---	---	---	---	---	---
11ax(HE40) CH134: 5670MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11340	H	37.62	---	8.05	45.67	---	74	54	-8.33
17010	H	36.13	---	9.72	45.85	---	68.2	---	-22.35
---	H	---	---	---	---	---	---	---	---
11340	V	37.78	---	8.05	45.83	---	74	54	-8.17
17010	V	39.55	---	9.72	49.27	---	68.2	---	-18.93
---	V	---	---	---	---	---	---	---	---
11ax(HE80) CH106: 5530MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11060	H	39.38	---	8.03	47.41	---	74	54	-6.59
16590	H	40.04	---	9.75	49.79	---	68.2	---	-18.41
---	H	---	---	---	---	---	---	---	---
11060	V	40.26	---	8.03	48.29	---	74	54	-5.71
16590	V	41.59	---	9.75	51.34	---	68.2	---	-16.86
---	V	---	---	---	---	---	---	---	---

11ax(HE80) CH122: 5610MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11220	H	40.61	---	8.05	48.66	---	74	54	-5.34
16830	H	38.45	---	9.72	48.17	---	68.2	---	-20.03
---	H	---	---	---	---	---	---	---	---
11220	V	39.38	---	8.05	47.43	---	74	54	-6.57
16830	V	39.03	---	9.72	48.75	---	68.2	---	-19.45
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. Antenna a and Antenna b have been tested, but the test data only show the worst case model (Antenna b) in this report.

Modulation Type: Band 3									
11a CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	37.87	---	8.09	45.96	---	74	54	-8.04
17235	H	37.25	---	9.67	46.92	---	68.2	---	-21.28
---	H	---	---	---	---	---	---	---	---
11490	V	40.41	---	8.09	48.5	---	74	54	-5.5
17235	V	38.97	---	9.67	48.64	---	68.2	---	-19.56
---	V	---	---	---	---	---	---	---	---
11a CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	39.14	---	8.10	47.24	---	74	54	-6.76
17355	H	38.67	---	9.65	48.32	---	68.2	---	-19.88
---	H	---	---	---	---	---	---	---	---
11570	V	38.58	---	8.10	46.68	---	74	54	-7.32
17355	V	39.02	---	9.65	48.67	---	68.2	---	-19.53
---	V	---	---	---	---	---	---	---	---
11a CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	37.54	---	8.12	45.66	---	74	54	-8.34
17475	H	36.71	---	9.62	46.33	---	68.2	---	-21.87
---	H	---	---	---	---	---	---	---	---
11650	V	38.36	---	8.12	46.48	---	74	54	-7.52
17475	V	38.92	---	9.62	48.54	---	68.2	---	-19.66
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	38.25	---	8.09	46.34	---	74	54	-7.66
17235	H	38.81	---	9.67	48.48	---	68.2	---	-19.72
---	H	---	---	---	---	---	---	---	---
11490	V	39.34	---	8.09	47.43	---	74	54	-6.57
17235	V	37.01	---	9.67	46.68	---	68.2	---	-21.52
---	V	---	---	---	---	---	---	---	---

11n(HT20) CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	38.56	---	8.10	46.66	---	74	54	-7.34
17355	H	39.21	---	9.65	48.86	---	68.2	---	-19.34
---	H	---	---	---	---	---	---	---	---
11570	V	38.99	---	8.10	47.09	---	74	54	-6.91
17355	V	39.64	---	9.65	49.29	---	68.2	---	-18.91
---	V	---	---	---	---	---	---	---	---
11n(HT20) CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	38.12	---	8.12	46.24	---	74	54	-7.76
17475	H	37.36	---	9.62	46.98	---	68.2	---	-21.22
---	H	---	---	---	---	---	---	---	---
11650	V	38.51	---	8.12	46.63	---	74	54	-7.37
17475	V	39.49	---	9.62	49.11	---	68.2	---	-19.09
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH151: 5755MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11510	H	40.37	---	8.09	48.46	---	74	54	-5.54
17265	H	37.62	---	9.67	47.29	---	68.2	---	-20.91
---	H	---	---	---	---	---	---	---	---
11510	V	41.85	---	8.09	49.94	---	74	54	-4.06
17265	V	38.24	---	9.67	47.91	---	68.2	---	-20.29
---	V	---	---	---	---	---	---	---	---
11n(HT40) CH159: 5795MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11590	H	38.13	---	8.10	46.23	---	74	54	-7.77
17385	H	38.47	---	9.65	48.12	---	68.2	---	-20.08
---	H	---	---	---	---	---	---	---	---
11590	V	38.62	---	8.10	46.72	---	74	54	-7.28
17385	V	37.08	---	9.65	46.73	---	68.2	---	-21.47
---	V	---	---	---	---	---	---	---	---

11ac(VHT20) CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	40.36	---	8.09	48.45	---	74	54	-5.55
17235	H	37.14	---	9.67	46.81	---	68.2	---	-21.39
---	H	---	---	---	---	---	---	---	---
11490	V	40.88	---	8.09	48.97	---	74	54	-5.03
17235	V	38.25	---	9.67	47.92	---	68.2	---	-20.28
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	38.56	---	8.10	46.66	---	74	54	-7.34
17355	H	36.23	---	9.65	45.88	---	68.2	---	-22.32
---	H	---	---	---	---	---	---	---	---
11570	V	37.37	---	8.10	45.47	---	74	54	-8.53
17355	V	38.18	---	9.65	47.83	---	68.2	---	-20.37
---	V	---	---	---	---	---	---	---	---
11ac(VHT20) CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	40.42	---	8.12	48.54	---	74	54	-5.46
17475	H	38.36	---	9.62	47.98	---	68.2	---	-20.22
---	H	---	---	---	---	---	---	---	---
11650	V	38.51	---	8.12	46.63	---	74	54	-7.37
17475	V	40.02	---	9.62	49.64	---	68.2	---	-18.56
---	V	---	---	---	---	---	---	---	---
11ac(VHT40) CH151: 5755MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11510	H	39.05	---	8.09	47.14	---	74	54	-6.86
17265	H	37.71	---	9.67	47.38	---	68.2	---	-20.82
---	H	---	---	---	---	---	---	---	---
11510	V	40.66	---	8.09	48.75	---	74	54	-5.25
17265	V	36.42	---	9.67	46.09	---	68.2	---	-22.11
---	V	---	---	---	---	---	---	---	---

11ac(VHT40) CH159: 5795MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11590	H	40.23	---	8.10	48.33	---	74	54	-5.67
17385	H	37.71	---	9.65	47.36	---	68.2	---	-20.84
---	H	---	---	---	---	---	---	---	---
11590	V	39.65	---	8.10	47.75	---	74	54	-6.25
17385	V	38.34	---	9.65	47.99	---	68.2	---	-20.21
---	V	---	---	---	---	---	---	---	---
11ac(VHT80) CH155: 5775MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11550	H	40.58	---	8.09	48.67	---	74	54	-5.33
17325	H	38.23	---	9.66	47.89	---	68.2	---	-20.31
---	H	---	---	---	---	---	---	---	---
11550	V	41.89	---	8.09	49.98	---	74	54	-4.02
17325	V	38.12	---	9.66	47.78	---	68.2	---	-20.42
---	V	---	---	---	---	---	---	---	---
11ax(HE20) CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	40.32	---	8.09	48.41	---	74	54	-5.59
17235	H	37.47	---	9.67	47.14	---	68.2	---	-21.06
---	H	---	---	---	---	---	---	---	---
11490	V	40.89	---	8.09	48.98	---	74	54	-5.02
17235	V	38.12	---	9.67	47.79	---	68.2	---	-20.41
---	V	---	---	---	---	---	---	---	---
11ax(HE20) CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	38.14	---	8.10	46.24	---	74	54	-7.76
17355	H	36.67	---	9.65	46.32	---	68.2	---	-21.88
---	H	---	---	---	---	---	---	---	---
11570	V	37.34	---	8.10	45.44	---	74	54	-8.56
17355	V	38.47	---	9.65	48.12	---	68.2	---	-20.08
---	V	---	---	---	---	---	---	---	---

11ax(HE20) CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	40.24	---	8.12	48.36	---	74	54	-5.64
17475	H	38.79	---	9.62	48.41	---	68.2	---	-19.79
---	H	---	---	---	---	---	---	---	---
11650	V	38.16	---	8.12	46.28	---	74	54	-7.72
17475	V	40.05	---	9.62	49.67	---	68.2	---	-18.53
---	V	---	---	---	---	---	---	---	---
11ax(HE40) CH151: 5755MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11510	H	39.37	---	8.09	47.46	---	74	54	-6.54
17265	H	37.61	---	9.67	47.28	---	68.2	---	-20.92
---	H	---	---	---	---	---	---	---	---
11510	V	40.85	---	8.09	48.94	---	74	54	-5.06
17265	V	36.46	---	9.67	46.13	---	68.2	---	-22.07
---	V	---	---	---	---	---	---	---	---
11ax(HE40) CH159: 5795MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11590	H	40.95	---	8.10	49.05	---	74	54	-4.95
17385	H	37.84	---	9.65	47.49	---	68.2	---	-20.71
---	H	---	---	---	---	---	---	---	---
11590	V	39.56	---	8.10	47.66	---	74	54	-6.34
17385	V	38.71	---	9.65	48.36	---	68.2	---	-19.84
---	V	---	---	---	---	---	---	---	---

11ax(HE80) CH155: 5775MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11550	H	40.38	---	8.09	48.47	---	74	54	-5.53
17325	H	38.21	---	9.66	47.87	---	68.2	---	-20.33
---	H	---	---	---	---	---	---	---	---
11550	V	41.93	---	8.09	50.02	---	74	54	-3.98
17325	V	38.56	---	9.66	48.22	---	68.2	---	-19.98
---	V	---	---	---	---	---	---	---	---

Note:

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.
5. Data of measurement shown “---“in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
6. Antenna a and Antenna b have been tested, but the test data only show the worst case model (Antenna b) in this report.

Appendix B: Photographs of Test Setup

Refer to the test report No. TCT240523E013

Appendix C: Photographs of EUT

Refer to the test report No. TCT240523E013

*******END OF REPORT*******