

**FCC ID: 2BBVM-ALW1**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $<$  5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BLE

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
BLE-1M	2.402	4.74	2.98	5 $\pm$ 1	6	3.98	<5	1.23400	3.00	YES
	2.440	4.94	3.12	5 $\pm$ 1	6	3.98	<5	1.24373	3.00	YES
	2.480	5.34	3.42	5 $\pm$ 1	6	3.98	<5	1.25388	3.00	YES
BLE-2M	2.402	4.76	2.99	5 $\pm$ 1	6	3.98	<5	1.23400	3.00	YES
	2.440	4.96	3.13	5 $\pm$ 1	6	3.98	<5	1.24373	3.00	YES
	2.480	5.34	3.42	5 $\pm$ 1	6	3.98	<5	1.25388	3.00	YES

**Conclusion:**

For the max result :  $1.25388 \leq 3.0$  for 1g SAR, SAR is not required.



**Signature:**

**Date:** 2023-07-24

**NAME AND TITLE** (Please print or type): Alex li /Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.