

PARTIAL Test Report

23-1-0035501T003a-C01

Number of pages:	24	Date of Report:	2024-Sep-03
Testing company:	cetecom advanced GmbH Untertuerkheimer Str. 6-10 66117 Saarbruecken GERMANY	Applicant:	Schmitz Cargobull AG
Product:	Telematic Device	Model:	CTU-Pro
FCC ID:	2BBVQ-CTUPRO	IC:	N/A
Testing has been carried out in accordance with:	FCC Regulations Title 47 CFR, Chapter I, Subchapter A Part 15, Subpart C Intentional Radiators § 15.209 Radiated emission limits; general requirements Title 47 CFR, Chapter I, Subchapter B Part 22, Subpart H Cellular Radiotelephone Service Part 24, Subpart E Paging and Radiotelephone Service		
Tested Technology:	GSM		
Test Results:	<input checked="" type="checkbox"/> The EUT complies with the requirements in respect of selected parameters subject to the test. The test results relate only to devices specified in this document The current version of Test Report "TR23-1-0035501T003a-C01" replaces the test report "TR23-1-0035501T003a" dated 2024-Jul-19. The replaced test report is herewith invalid.		
Signatures:	B.Eng. Martin Nunier Supervisor Radio Services Authorization of test report	Timo Franke Testing Manager Responsible of test report	

B.Eng. Martin Nunier
Supervisor Radio Services
Authorization of test report

Timo Franke
Testing Manager
Responsible of test report

Table of Contents

Table of Annex.....	3
1 General information	4
1.1 Disclaimer and Notes.....	4
1.3 Summary of Test Results	5
1.4 Summary of Test Methods	6
2 Administrative Data.....	7
2.1 Identification of the Testing Laboratory.....	7
2.2 General limits for environmental conditions.....	7
2.3 Test Laboratories sub-contracted.....	7
2.4 Organizational Items	7
2.5 Applicant's details	7
2.6 Manufacturer's details	7
2.7 Equipment under Test (EUT)	8
2.8 Untested Variant (VAR)	8
2.9 Auxiliary Equipment (AE).....	8
2.10 Connected cables (CAB).....	8
2.11 Software (SW).....	8
2.12 EUT set-ups.....	8
2.13 EUT operation modes	9
3 Equipment under test (EUT)	10
3.1 General Data of Main EUT as Declared by Applicant.....	10
3.2 Detailed Technical data of Main EUT as Declared by Applicant	10
3.3 Modifications on Test sample.....	10
4 Measurements.....	11
4.1 Conducted RF output power	11
4.2 Radiated field strength emissions below 30 MHz	13
4.3 Radiated spurious emissions	17
4.4 Radiated Band Edge.....	19
4.5 Equipment lists	20
5 Results from external laboratory	22
6 Opinions and interpretations.....	22
7 List of abbreviations	22
8 Measurement Uncertainty valid for conducted/radiated measurements	23
9 Versions of test reports (change history)	24

Table of Annex			
Annex No.	Contents	Reference Description	Total Pages
Annex 1	Test result diagrams	TR23-1-0035501T003a-A1-C01	14
Annex 2	Internal photographs of EUT	To be provided by applicant	--
Annex 3	External photographs of EUT	TR23-1-0035501T003a-A3-C01	5
Annex 4	Test set-up photographs	TR23-1-0035501T003a-A4-C01	4
Annex 5	Declaration of applicant of model differences	TR23-1-0035501T003a-A5-C01	2
The listed attachments are separate documents.			

1 General information

1.1 Disclaimer and Notes

The test results of this test report relate exclusively to the test item specified in this test report as specified in chapter 2. cetecom advanced does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of cetecom advanced.

The testing service provided by cetecom advanced has been rendered under the current "General Terms and Conditions for cetecom advanced".

cetecom advanced will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the cetecom advanced test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the cetecom advanced test report include or imply any product or service warranties from cetecom advanced , including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by cetecom advanced.

All rights and remedies regarding vendor's products and services for which cetecom advanced has prepared this test report shall be provided by the party offering such products or services and not by cetecom advanced.

In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 10 years at cetecom advanced.

Also we refer on special conditions which the applicant should fulfill according §2.927 to §2.948, special focus regarding modification of the equipment and availability of sample equipment for market surveillance tests.

1.3 Summary of Test Results

Test case in GSM850 band	Reference Clause FCC	Page	Remark	Result
AC-Power Lines Conducted Emissions	§15.207(a)	--	--	NP
Conducted RF output power	§2.1046(a)	12	--	PASSED
Radiated RF output power	§22.913(a)	--	--	NP
Occupied Channel Bandwidth 99%	§22.917(b), §2.202(a), §2.1049(h)	--	--	NP
26dB Emission bandwidth	§22.917(b), §2.202(a), §2.1049(h)	--	--	NP
Radiated Band Edge	§2.1053(a), §2.1057(a)(1) §22.917(a)(b)	19	--	PASSED
Conducted RF Band Edge	§22.917(a)(b)(c)(d) §2.1051, §2.1057(a)(1)	--	--	NP
Peak to Average ratio (PAPR)	§2.1046(a)	--	--	NP
Radiated field strength emissions below 30 MHz	§15.205, §15.209	16	--	PASSED
Spurious emissions at antenna terminals	§22.917(a)(b)(c)(d) §2.1051, §2.1057(a)(1)	--	--	NP
Radiated spurious emissions	§2.1053(a), §2.1057(a)(1) §22.917(a)(b)	18	--	PASSED
Frequency stability, temperature variation	§22.355, §2.1055(a)(1) (d)	--	--	NP
Frequency stability, voltage variation	§22.355, §2.1055(a)(1) (d)	--	--	NP

Test case in GSM1900 band	Reference Clause FCC	Page	Remark	Result
AC-Power Lines Conducted Emissions	§15.207(a)	--	--	NP
Conducted RF output power	§2.1046(a)	12	--	PASSED
Radiated RF output power	§24.232(b)	--	--	NP
Occupied Channel Bandwidth 99%	§24.238(b), §2.202(a), §2.1049(h)	--	--	NP
26dB Emission bandwidth	§24.238(b), §2.202(a), §2.1049(h)	--	--	NP
Radiated Band Edge	§2.1053(a), §2.1057(a)(1) §24.238(a)(b)	19	--	PASSED
Conducted RF Band Edge	§24.238(a)(b)(c)(d) §2.1051, §2.1057(a)(1)	--	--	NP
Peak to Average ratio (PAPR)	§2.1046(a)	--	--	NP
Radiated field strength emissions below 30 MHz	§15.205, §15.209	16	--	PASSED
Spurious emissions at antenna terminals	§24.238(a)(b)(c)(d) §2.1051, §2.1057(a)(1)	--	--	NP
Radiated spurious emissions	§2.1053(a), §2.1057(a)(1) §24.238(a)(b)	18	--	PASSED
Frequency stability, temperature variation	§24.235, §2.1055(a)(1) (d)	--	--	NP
Frequency stability, voltage variation	§24.235, §2.1055(a)(1) (d)	--	--	NP

PASSED

The EUT complies with the essential requirements in the standard.

FAILED

The EUT does not comply with the essential requirements in the standard.

N/A

Test case does not apply to the test object.

NP

The test was not performed by the cetecom advanced laboratory.

Decision Rule: cetecom advanced GmbH follows [ILAC G8:2019 chapter 4.2.1 \(Simple Acceptance Rule\)](#).

Remarks:

- Please check the module report "MDE_UBLOX_2029_FCC_01" issued on 2021-Dec-10 by 7 layers GmbH, for not performed measurements by the cetecom advanced laboratory.

1.4 Summary of Test Methods

Test case	Test method
AC-Power Lines Conducted Emissions	ANSI C63.4-2014, §7, ANSI C63.10-2013 §6.2
Conducted RF output power	ANSI C63.26:2015, §5.2, KDB 971168 D01 v03r01
Radiated RF output power	ANSI C63.26:2015, §5.2.7, KDB 971168 D01 v03r01
Occupied Channel Bandwidth 99%	ANSI C63.26:2015, §5.4.4, KDB 971168 D01 v03r01
26dB Emission bandwidth	ANSI C63.26:2015, §5.4.3, KDB 971168 D01 v03r01
Modulation characteristics	ANSI C63.26:2015, §5.3
Radiated Band Edge	ANSI C63.26:2015, §5.5, KDB 971168 D01 v03r01
Conducted RF Band Edge	ANSI C63.26:2015, §5.7, KDB 971168 D01 v03r01
Peak to Average ratio (PAPR)	ANSI C63.26:2015, §5.2.6 Result calculated with measured conducted RF-power value and stated/measured antenna gain for band of interest
Radiated field strength emissions below 30 MHz	ANSI C63.4-2014 §5.3, §8.2.1, §8.3.1.1+§8.3.2.1
Spurious emissions at antenna terminals	ANSI C63.26:2015, §5.7, KDB 971168 D01 v03r01
Radiated spurious emissions	ANSI C63.26:2015, §5.5, KDB 971168 D01 v03r01, ANSI C63.26.1:2018
Frequency stability, temperature variation	ANSI C63.26:2015, §5.6, KDB 971168 D01 v03r01
Frequency stability, voltage variation	ANSI C63.26:2015, §5.6, KDB 971168 D01 v03r01

2 Administrative Data

2.1 Identification of the Testing Laboratory

Company name:	cetecom advanced GmbH
Address:	Untertuerkheimer Str. 6-10 66117 Saarbruecken Germany
Responsible for testing laboratory:	Dipl.-Ing. (FH) Andreas Luckenbill M.Sc.
Accreditation scope:	DAkkS Webpage: FCC ISED
IC Lab company No. / CAB ID:	3462D / DE0001
Test location 1:	Im Teelbruch 116; 45219 Essen
Test location 2:	--

2.2 General limits for environmental conditions

Temperature:	22±2 °C
Relative. humidity:	45±15% rH

2.3 Test Laboratories sub-contracted

Company name:	--
---------------	----

2.4 Organizational Items

Responsible test manager:	Timo Franke
Receipt of EUT:	2023-Jun-14
Date(s) of test:	2023-Jul-17 to 2023-Aug-19
Version of template:	23.0401

2.5 Applicant's details

Applicant's name:	Schmitz Cargobull AG
Address:	Bahnhofstrasse 22 48612 Horstmar Germany
Contact Person:	Dieter Honkomp
Contact Person's Email:	dieter.honkomp@cargobull.com

2.6 Manufacturer's details

Manufacturer's name:	Bosch Car Multimédia Portugal, S.A.
Address:	Rua Max Grundig, 35 4705-820 Lomar Braga Norte Portugal

2.7 Equipment under Test (EUT)

EUT No.*)	Sample No.	Product	Model	Type	SN	HW	SW
EUT 1	23-1-00355S04_C01	Telematic Device	CTU-Pro	7620000458	99003313	H01	CBT.TCU3_EVO.21.01.D.064
EUT 2	23-1-00355S05_C01	Telematic Device	CTU-Pro	7620000458	99003219	H01	CBT.TCU3_EVO.21.01.D.064

*) EUT short description is used to simplify the identification of the EUT in this test report.

2.8 Untested Variant (VAR)

VAR No.*)	Sample No.	Product	Model	Type	SN	HW	SW
VAR 1	23-1-00355S15_C01	Telematic Device	CTU-Pro	7620000456	99003222	H01	CBT.TCU3_EVO.21.01.D.064

*) The listed additional untested model variant(s) (VAR) is/are not object of evaluation of compliance. For further information please see Annex 5: Declaration of applicant of model differences.

If the table above does not show any other line than the headline, no untested variants are available.

2.9 Auxiliary Equipment (AE)

AE No.*)	Sample No.	Auxiliary Equipment	Model	SN	HW	SW
AE 1	23-1-00355S11_C01	Laptop	HP EliteBook 840	N/A	N/A	N/A
AE 2	23-1-00355S12_C01	Power supply	N/A	N/A	N/A	N/A

*) AE short description is used to simplify the identification of the auxiliary equipment in this test report. If the table above does not show any other line than the headline, no AE was used during testing nor was taken into account for evaluation

2.10 Connected cables (CAB)

CAB No.*)	Sample No.	Cable Type	Connectors / Details	Length
CAB 1	23-1-00355S07_C01	Cable harness	--	< 300 cm
CAB 2	23-1-00355S08_C01	Cable harness	--	< 300 cm

*) CAB short description is used to simplify the identification of the connected cables in this test report. If the table above does not show any other line than the headline, no cable was used during testing nor was taken into account for evaluation

2.11 Software (SW)

SW No.*)	Sample No.	SW Name	Description	SW Status

*) SW short description is used to simplify the identification of the used software in this test report. If the table above does not show any other line than the headline, no SW was used during testing nor was taken into account for evaluation.

2.12 EUT set-ups

set-up no.*)	Combination of EUT and AE	Description
1	EUT 1 + AE 1 + AE 2 + CAB 1 + CAB 2	Used for radiated measurements. AE 1 + AE 2 used only for configuration.
2	EUT 2 + AE 1 + AE 2 + CAB 1 + CAB 2	Used for conducted measurements. AE 1 + AE 2 used only for configuration.

*) EUT set-up no. is used to simplify the identification of the EUT set-up in this test report.

2.13 EUT operation modes

EUT operating mode no.*)	Operating modes	Additional information
Operating mode 1	GSM 850 Traffic	Frequency / channel range: UL:824.20 to 848.80 MHz, DL: 869.20 to 993.80 MHz, Channel: UL: 128 to 251, DL: 128 to 251. A Communication link has been established between Radio Communication Tester CMU200 and EUT, GPRS modulation / 1 TX slot with max power of 33 dBm
Operating mode 2	GSM 1900 Traffic	Frequency / channel range: UL: 1850.20 to 1909.80 MHz, DL: 1930.20 to 1989.80 MHz, Channel: UL: 512 to 810, DL: 512 to 810. A Communication link has been established between Radio Communication Tester CMU200 and EUT, GPRS modulation / 1 TX slot with max power of 30 dBm

*) EUT operating mode no. is used to simplify the test report.

3 Equipment under test (EUT)

3.1 General Data of Main EUT as Declared by Applicant

Firmware	<input type="checkbox"/> for normal use	<input checked="" type="checkbox"/> Special version for test execution
Power supply	<input type="checkbox"/> AC Mains	-
	<input checked="" type="checkbox"/> DC Mains	12 V DC
	<input type="checkbox"/> Battery	-
EUT sample type	Pre-Production	
Weight	1.350 kg	
Size [LxWxH]	24.5 cm x 16.0 cm x 6.0 cm	
Interfaces/Ports	--	
For further details refer Applicants Declaration & following technical documents TECHNICAL_PASSPORT_CU-PRO_7620000456_458_Delta_V1.8.pdf		

3.2 Detailed Technical data of Main EUT as Declared by Applicant

TX Frequency range	<input checked="" type="checkbox"/> GSM850 824 - 849 MHz (Uplink), 869-894 MHz (Downlink) <input checked="" type="checkbox"/> GSM1900 1850 - 1910 MHz (Uplink), 1930-1990 MHz (Downlink)	
Number of channels	<input checked="" type="checkbox"/> GSM850 TCH range 128 - 251 <input checked="" type="checkbox"/> GSM1900 TCH range 512 - 810	
Type of modulation	GMSK 8-PSK	
Antenna Type	<input checked="" type="checkbox"/> Integrated <input type="checkbox"/> External, no RF-connector <input type="checkbox"/> External, separate RF-connector	
Antenna gain	GSM850: max 1 dBi GSM1900: max 3.50 dBi	
FCC label attached	No	
Test firmware / software and storage location	EUT 1	
For further details refer Applicants Declaration & following technical documents TECHNICAL_PASSPORT_CU-PRO_7620000456_458_V3-1		
Description of Reference Document (supplied by applicant)	Version	Total Pages
TECHNICAL_PASSPORT_CU-PRO_7620000456_458_V3-1	3.1	32

3.3 Modifications on Test sample

Additions/deviations or exclusions	--
------------------------------------	----

4 Measurements


4.1 Conducted RF output power

4.1.1 Description of the general test setup and methodology, see below example:

Following modified test set-up apply for tests performed inside the climatic chamber (frequency stability) or conducted RF-carrier power-measurement. The EUT RF-Signal is directly connected over suitable RF-connector over low-loss cable and an attenuator (2) to the cellular radio communication test-unit. (5).

The measurements were performed with the integrated power measurement function of the communication test-unit. (5).

Schematic:



Testing method:

The measurement is made according to relevant reference clauses:

(See Tables *Summary of Test Results* and *Summary of Test Methods* on page 5)

EUT settings

The EUT was instructed to send with maximum power (if adjustable) according applicants instructions.

The measurements were made at the low, middle and high carrier frequencies of each of the supported operating band within the designated range within the allowed channel bandwidths. Choosing three TX-carrier frequencies of the mobile phone, should be sufficient to demonstrate compliance

4.1.2 Measurement Location

Test site	120910 - Radio Laboratory 1 (TS 8997)
-----------	---------------------------------------

4.1.3 Limit

Frequency Range [MHz]	Limit [W]	Limit [dBm]
824 – 849	7 ERP	38.5
1850 – 1910	2 EiRP	33

4.1.4 Result

GPRS-Modulation 850MHz Band											
	ARFCN-Frequency (MHz)	Average power at Antenna Port (dBm)	Maximum declared Antenna Gain(dBi)	EIRP in dBm	EIRP in Watt	ERP in dBm	ERP in Watt	FCC Limit(W), ERP	FCC Limit (dBm), ERP	Verdict	
Channel 128		824.2	31.40	1.00	32.40	1.73780	30.25	1.05925	7.00	38.45	Passed
Channel 189		836.6	31.30	1.00	32.30	1.69824	30.15	1.03514	7.00	38.45	Passed
Channel 251		848.8	31.30	1.00	32.30	1.69824	30.15	1.03514	7.00	38.45	Passed
E-GPRS/EDGE Mode 850MHz Band											
Channel 128		824.2	25.99	1.00	26.99	0.50003	24.84	0.30479	7.00	38.45	Passed
Channel 189		836.6	25.93	1.00	26.93	0.49317	24.78	0.30061	7.00	38.45	Passed
Channel 251		848.8	25.78	1.00	26.78	0.47643	24.63	0.29040	7.00	38.45	Passed
GPRS-Modulation 1900MHz Band											
	ARFCN-Frequency (MHz)	Average power at Antenna Port (dBm)	Maximum declared Antenna Gain(dBi)	EIRP in dBm	EIRP in Watt				FCC Limit(W), ERP	FCC Limit (dBm); ERP	Verdict
Channel 512		1850.2	28.10	3.50	31.60	1.44544	x	x	2.00	33.01	Passed
Channel 661		1880.2	28.20	3.50	31.70	1.47911	x	x	2.00	33.01	Passed
Channel 810		1909.8	28.30	3.50	31.80	1.51356	x	x	2.00	33.01	Passed
E-GPRS/EDGE Mode 1900MHz Band											
Channel 512		1850.2	24.71	3.50	28.21	0.66222	x	x	2.00	33.01	Passed
Channel 661		1880.2	24.95	3.50	28.45	0.69984	x	x	2.00	33.01	Passed
Channel 810		1909.8	24.64	3.50	28.14	0.65163	x	x	2.00	33.01	Passed
EIRP= Average Power at Antenna Port + Maximum declared Antenna Gain - Path loss to Antenna Connector - Path loss in Antenna Cable ERP = EIRP - 2.15 Measured by cetecom advanced GmbH											


4.2 Radiated field strength emissions below 30 MHz

4.2.1 Description of the general test setup and methodology, see below example:

Evaluating the radiated field emissions are done first by an exploratory emission measurement and a final measurement for most critical frequencies determined.

The loop antenna was placed at 1 m height above ground plane and 3 m measurement distance from set-up for investigations. Because of reduced measurement distance, correction data were applied, as stated in chapter "General Limit - Radiated field strength emissions below 30 MHz". The tests are performed in the semi anechoic room recognized by the regulatory commission.

Schematic:



Testing method:

The measurement is made according to relevant reference clauses:

(See Tables *Summary of Test Results* and *Summary of Test Methods* on page 5)

Exploratory, preliminary measurements

The EUT and its associated accessories are placed on a non-conductive position manipulator (tipping device) of 0.8 m height which is placed on the turntable. By rotating the turntable (step 90°, range 0° to 360°) and the EUT itself either on 3-orthogonal axis (portable equipment) or 2-orthogonal axis (defined operational position of EUT), the emission spectrum was recorded.

The loop antenna was moved at least to 2-perpendicular axes (antenna vector in direction of EUT and parallel to EUT) in order to maximize the emissions. The results are documented in a diagram. Critical frequencies (low margin to limit) are saved within a data reduction table for further investigations. If various operating modes are supported, further investigations are made to find the worst-case. Also the interconnection cables and equipment position were varied in order to maximize the emissions.

Final measurement on critical frequencies

Based on the exploratory measurements, the most critical frequencies are re-measured by maintaining the EUT's worst-case operation mode, cable position, etc.

First a frequency zoom around the critical frequency is done to locate the frequency more precisely. After this step, for all identified critical frequencies, the maximum peak was determined.

Following parameters were varied: the turntable angle continuously in the range 0 to 360 degree, the EUT itself either over 3-orthogonal axis (not defined usage position) or 2-orthogonal axis (defined usage position).

On the determined worst-case position, a final measurement with necessary bandwidth and detector according standard has been carried out.

Formula:

$$E_C = E_R + AF + C_L + D_F - G_A$$

AF = Antenna factor

$$M = L_T - E_C$$

C_L = Cable loss

D_F = Distance correction factor (if used)

E_C = Electrical field – corrected value

E_R = Receiver reading

G_A = Gain of pre-amplifier (if used)

L_T = Limit

M = Margin

All units are dB-units, positive margin means value is below limit.

4.2.2 Sample calculation

Raw-Value [dBuV/m]	Antenna factor	Distance Correction [dB]	Cable Loss	Preamplifier	Resulting correction value [dB]	Final result [dBuV/m]	Remarks
19.83	18.9	-70.75	0.18	--	-51.67	-31.83	30 to 3 m correction used according ANSI C63.10-2013

Remark: This calculation is based on an example value at 458 kHz

4.2.3 Correction factors due to reduced meas. distance (f < 30 MHz):

The used correction factors when the measurement distance is reduced compared to regulatory measurement distance, are calculated according Extrapolation formulas valid for EUT's with maximum dimension of 0.625xLambda. Formula 2+3+4 as presented in ANSI C63.10, Chapter 6.4.4 are used for the calculations of proper extrapolation factors

Frequency Range	f [kHz/MHz]	Lambda [m]	Far-Field Point [m]	Distance Limit accord. 15.209 [m]	1st Condition (dmeas < Dnear-field)	2nd Condition (Limit distance bigger dnear-field)	Distance Correction accord. Formula
kHz	9	33333.33	5305.17	300	fullfilled	not fulfilled	-80.00
	10	30000.00	4774.65		fullfilled	not fulfilled	-80.00
	20	15000.00	2387.33		fullfilled	not fulfilled	-80.00
	30	10000.00	1591.55		fullfilled	not fulfilled	-80.00
	40	7500.00	1193.66		fullfilled	not fulfilled	-80.00
	50	6000.00	954.93		fullfilled	not fulfilled	-80.00
	60	5000.00	795.78		fullfilled	not fulfilled	-80.00
	70	4285.71	682.09		fullfilled	not fulfilled	-80.00
	80	3750.00	596.83		fullfilled	not fulfilled	-80.00
	90	3333.33	530.52		fullfilled	not fulfilled	-80.00
	100	3000.00	477.47		fullfilled	not fulfilled	-80.00
	125	2400.00	381.97		fullfilled	not fulfilled	-80.00
	200	1500.00	238.73		fullfilled	fullfilled	-78.02
	300	1000.00	159.16		fullfilled	fullfilled	-74.49
	400	750.00	119.37		fullfilled	fullfilled	-72.00
	490	612.24	97.44		fullfilled	fullfilled	-70.23
	500	600.00	95.49	30	fullfilled	not fulfilled	-40.00
	600	500.00	79.58		fullfilled	not fulfilled	-40.00
	700	428.57	68.21		fullfilled	not fulfilled	-40.00
	800	375.00	59.68		fullfilled	not fulfilled	-40.00
	900	333.33	53.05		fullfilled	not fulfilled	-40.00
MHz	1.00	300.00	47.75	30	fullfilled	not fulfilled	-40.00
	1.59	188.50	30.00		fullfilled	not fulfilled	-40.00
	2.00	150.00	23.87		fullfilled	fullfilled	-38.02
	3.00	100.00	15.92		fullfilled	fullfilled	-34.49
	4.00	75.00	11.94		fullfilled	fullfilled	-32.00
	5.00	60.00	9.55		fullfilled	fullfilled	-30.06
	6.00	50.00	7.96		fullfilled	fullfilled	-28.47
	7.00	42.86	6.82		fullfilled	fullfilled	-27.13
	8.00	37.50	5.97		fullfilled	fullfilled	-25.97
	9.00	33.33	5.31		fullfilled	fullfilled	-24.95
	10.00	30.00	4.77		fullfilled	fullfilled	-24.04
	10.60	28.30	4.50		fullfilled	fullfilled	-23.53
	11.00	27.27	4.34		fullfilled	fullfilled	-23.21
	12.00	25.00	3.98		fullfilled	fullfilled	-22.45
	13.56	22.12	3.52		fullfilled	fullfilled	-21.39
	15.00	20.00	3.18		fullfilled	fullfilled	-20.51
	15.92	18.85	3.00		fullfilled	fullfilled	-20.00
	17.00	17.65	2.81		not fulfilled	fullfilled	-20.00
	18.00	16.67	2.65		not fulfilled	fullfilled	-20.00
	20.00	15.00	2.39		not fulfilled	fullfilled	-20.00
	21.00	14.29	2.27		not fulfilled	fullfilled	-20.00
	23.00	13.04	2.08		not fulfilled	fullfilled	-20.00
	25.00	12.00	1.91		not fulfilled	fullfilled	-20.00
	27.00	11.11	1.77		not fulfilled	fullfilled	-20.00
	29.00	10.34	1.65		not fulfilled	fullfilled	-20.00
	30.00	10.00	1.59		not fulfilled	fullfilled	-20.00

4.2.4 Measurement Location

Test site	120901 - SAC3 - Radiated Emission <1GHz
-----------	---

4.2.5 Limit

Radiated emissions limits, 3 meters					
Frequency Range [MHz]	Limit [μ V/m]	Limit [$\text{dB}\mu\text{V}/\text{m}$]	Distance [m]	Detector	RBW [kHz]
0.009 – 0.09	2400 / f [kHz]	67.6 – 20Log(f) (kHz)	300	Pk & Avg	0.2
0.09 – 0.11	2400 / f [kHz]	67.6 – 20Log(f) (kHz)	300	Quasi peak	0.2
0.11 – 0.15	2400 / f [kHz]	67.6 – 20Log(f) (kHz)	300	Pk & Avg	0.2
0.15 – 0.49	2400 / f [kHz]	67.6 – 20Log(f) (kHz)	300	Pk & Avg	9
0.49 – 1.705	24000 / f [kHz]	87.6 – 20Log(f) (kHz)	30	Quasi peak	9
1.705 – 30	30	29.5	30	Quasi peak	9

*Remark: In Canada same limits apply, just unit reference is different

4.2.6 Result

Diagram	Band	Mode	Maximum Level [$\text{dB}\mu\text{V}/\text{m}$] Frequency Range 0.009 MHz – 30 MHz	Result
2.850	GSM850	1 Laying	No peaks < 6 dB margin found	Passed
2.851	GSM850	1 Standin	No peaks < 6 dB margin found	Passed
2.1901	GSM1900	2 Laying	No peaks < 6 dB margin found	Passed
2.1902	GSM1900	2 Standin	No peaks < 6 dB margin found	Passed


Remark: for more information and graphical plot see annex A1 **TR23-1-0035501T003a-A1-C01**

4.3 Radiated spurious emissions

4.3.1 Description of the general test setup and methodology, see below example:

Evaluating the emissions have to be done first by an exploratory emissions measurement and a final measurement for most critical frequencies. The tests are performed in a CISPR 16-1-4:2010 compliant fully anechoic room (FAR) recognized by the regulatory commission. The measurement distance was set to 3 meter for frequencies up to 18 GHz and 2 meter above 18 GHz. A logarithmic periodic antenna is used for the frequency range 30 MHz to 1 GHz. Horn antennas are used for frequency range 1 GHz to 40 GHz. The EUT is aligned within 3 dB beam width of the measurement antenna with three orthogonal axis measurements on the EUT.

Schematic:



Testing method:

The measurement is made according to relevant reference clauses:

(See Tables *Summary of Test Results* and *Summary of Test Methods* on page 5)

Exploratory, preliminary measurements

The EUT and its associated accessories are placed on a non-conductive position manipulator (tipping device) of 1.50 m height which is placed on the turntable. By rotating the turntable (range 0° to 360°, step 45°) and the EUT itself on 3-orthogonal axis (the emission spectrum and its characteristics was recorded with an EMI-receiver, broadband antenna and software).

The measurements are performed in horizontal and vertical polarization of the measurement antennas. The results are documented in a diagram. Critical frequencies (low margin to limit) are saved within a table for further investigations. If various operating modes are supported, further investigations are made to find the worst-case of them. Also the interconnection cables and equipment position were varied in order to maximize the emissions.

Final measurement on critical frequencies

Based on the exploratory measurements, the most critical frequencies are re-measured by maintaining the EUT's worst-case operation mode, cable position, etc.

First a frequency zoom around the critical frequency is done to locate the frequency more precisely. After this step, for all identified critical frequencies, the maximum peak was determined.

Following parameters were varied: the turntable angle continuously in the range 0 to 360 degree, the EUT itself over 3-orthogonal axis and the height for EUT with large dimensions.

On the determined worst-case position, a final measurement with necessary bandwidth and detector according standard has been carried out.

The readings on the spectrum analyzer are corrected with conversion value between field strength and E(I)RP, so the readings shown are equivalent to ERP/EIRP values. Critical measurements near the limit are re-measured with a substitution method accord. ANSI/TIA/EIA 603 C/D

Formula:

$$P_{EIRP} = P_{MEAS} + C_L + FSL - G_{PreA} - G_{ANT} \quad (1)$$

P_{MEAS} = measured power at instrument

M = Margin

L_T = Limit

FSL = Free Space loss = Function(frequency, measurement distance)

$M = L_T - P_{EIRP}$

C_L = cable loss

G_{PreA} = Gain of pre-amplifier (if used)

G_{ANT} = Gain of antenna in [dBi]

All units are dB-units, positive margin means value is below limit.

4.3.2 Measurement Location

Test site	120904 - FAC1 - Radiated Emissions
	120907 - FAC2 - Radiated Emissions

4.3.3 Limit

Frequency Range [MHz]	Limit [dBm]	Detector [MaxHold]	RBW / VBW [MHz]
30 - 8500	-13	Peak	1 / 3
30 - 19100	-13	Peak	1 / 3

4.3.4 Result

Diagram	Band	Mode	30 MHz to 9000 MHz	Result
8.01	GSM850	1	No peaks found	Passed

Diagram	Band	Mode	30 MHz to 18 GHz	18 GHz to 19.5 GHz	Result
8.02	GSM1900	2	No peaks < 6 dB margin found	--	Passed
8.03a	GSM1900	2 Laying	--	-21.91dBm (PK) @ 19.01 GHz	Passed
8.03b	GSM1900	2 Standing	--	No peaks < 6 dB margin found	Passed
8.03c	GSM1900	2 retest crit. freq.	--	No peaks < 6 dB margin found	Info

Remark: for more information and graphical plot see annex A1 **TR23-1-0035501T003a-A1-C01**


Remark: 8.03c is just a manual retest of test 8.03a

4.4 Radiated Band Edge

4.4.1 Description of the general test setup and methodology, see below example:

Evaluating the emissions have to be done first by an exploratory emissions measurement and a final measurement for most critical frequencies. The tests are performed in a CISPR 16-1-4:2010 compliant fully anechoic room (FAR) recognized by the regulatory commission. The measurement distance was set to 3 meter for frequencies up to 18 GHz and 2 meter above 18 GHz. A logarithmic periodic antenna is used for the frequency range 30 MHz to 1 GHz. Horn antennas are used for frequency range 1 GHz to 40 GHz. The EUT is aligned within 3 dB beam width of the measurement antenna with three orthogonal axis measurements on the EUT

Schematic:



Testing method:

The measurement is made according to relevant reference clauses:

(See Tables *Summary of Test Results* and *Summary of Test Methods* on page 5)

See chapter Radiated Spurious Emission for Test method.

4.4.2 Measurement Location

Test site	120904 - FAC1 - Radiated Emissions
-----------	------------------------------------

4.4.3 Limit

Frequency Range [MHz]	Limit [dBm]	Detector [MaxHold]	RBW / VBW [kHz]
Below 824 and above 849	-13	Peak	3 / 3
Below 1850 and above 1910	-13	Peak	3 / 3

4.4.4 Result

Diagram	Band	Mode	Edge [Low / High]	Value [dBm]	Result
9.01	850	Bandedge_low_Channel_128	Low	-16.91	Passed
9.02	850	Bandedge_high_Channel_251	High	-16.90	Passed
9.03	1900	Bandedge_low_Channel_512	Low	-15.73	Passed
9.04	1900	Bandedge_high_Channel_810	High	-18.23	Passed

Remark: for more information and graphical plot see annex A1 TR23-1-0035501T003a-A1-C01

4.5 Equipment lists

ID	Description	Manufacturer	SerNo	CheckType	Last Check	Interval	Next Check
	120901 - SAC3 - Radiated Emission <1GHz			calchk	cal: 2015-Jul-21	cal: 10Y	cal: 2025-Jul-21
20442	Semi Anechoic Chamber	ETS-Lindgren GmbH / Taufkirchen	-	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -
20482	filter matrix Filter matrix SAR 1	CETECOM GmbH	-	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -
20574	Biconilog Hybrid Antenna BTA-L	Frankonia GmbH / Heideck	980026L	cal	cal: 2022-Jun-15	cal: 36M	cal: 2025-Jun-15
20620	Test Receiver ESU26	Rohde & Schwarz Messgerätebau GmbH / Memmingen	100362	cal	cal: 2023-May-24	cal: 12M	cal: 2024-May-24
20885	Power Supply EA3632A	Agilent Technologies Deutschland GmbH	75305850	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -
25038	Loop Antenna HFH2-Z2	Rohde & Schwarz Messgerätebau GmbH / Memmingen	879824/13	cal	cal: 2022-Jul-04	cal: 24M	cal: 2024-Jul-04
	120904 - FAC1 - Radiated Emissions			chk	chk: 2023-Aug-22	chk: 12M	chk: 2024-Aug-22
20020	Horn Antenna 3115 (Subst 1)	EMCO Elektronik GmbH	9107-3699	calchk	cal: 2021-Aug-17 chk: 2013-Apr-20	cal: 36M chk: 12M	cal: 2024-Aug-17
20066	Notch Filter WRCT 1900/2200-5/40-10EEK	Wainwright Instruments GmbH	5	chk	chk: 2023-Aug-22	chk: 12M	chk: 2024-Aug-22
20121	Notch Filter WRCB 1879,5/1880,5EE	Wainwright Instruments GmbH	15	chk	chk: 2023-Aug-22	chk: 12M	chk: 2024-Aug-22
20122	Notch Filter WRCB 1747/1748	Wainwright Instruments GmbH	12	chk	chk: 2023-Aug-22	chk: 12M	chk: 2024-Aug-22
20254	High Pass Filter 5HC 2600/12750-1.5KK	Trilithic	23042	chk	chk: 2023-Aug-22	chk: 12M	chk: 2024-Aug-22
20287	Pre-Amplifier 25MHz - 4GHz AMF-2D-100M4G-35-10P	Miteq Inc.	379418	chk	chk: 2023-Aug-22	chk: 12M	chk: 2024-Aug-22
20290	Notch Filter WRCA 901,9/903,1SS	Wainwright Instruments GmbH	3RR	chk	chk: 2023-Aug-22	chk: 12M	chk: 2024-Aug-22
20291	High Pass Filter WHJ 2200-4EE	Wainwright Instruments GmbH	14	chk	chk: 2023-Aug-22	chk: 12M	chk: 2024-Aug-22
20338	Pre-Amplifier 100MHz - 26GHz JS4-00102600-38-5P	Miteq Inc.	838697	chk	chk: 2023-Aug-22	chk: 12M	chk: 2024-Aug-22
20341	Digital Multimeter Fluke 112	Fluke Deutschland GmbH / Glottental	81650455	cal	cal: 2022-May-18	cal: 24M	cal: 2024-May-18
20448	Notch Filter WRCT 1850,0/2170,0-5/40-10SSK	Wainwright Instruments GmbH	5	chk	chk: 2023-Aug-22	chk: 12M	chk: 2024-Aug-22
20449	Notch Filter WRCT 824,0/894,0-5/40-8SSK	Wainwright Instruments GmbH	1	chk	chk: 2023-Aug-22	chk: 12M	chk: 2024-Aug-22
20484	Pre-Amplifier 2,5GHz - 18GHz AMF-5D-02501800-25-10P	Miteq Inc.	1244554	chk	chk: 2023-Aug-22	chk: 12M	chk: 2024-Aug-22
20489	Test Receiver ESU40	Rohde & Schwarz Messgerätebau GmbH / Memmingen	100030	cal	cal: 2023-May-24	cal: 12M	cal: 2024-May-24
20512	Notch Filter WRCA 800/960-02/40-6EEK (GSM 850)	Wainwright Instruments GmbH	24	chk	chk: 2023-Aug-22	chk: 12M	chk: 2024-Aug-22
20549	Log. Per. Antenna HL025	Rohde & Schwarz Messgerätebau GmbH	1000060	calchk	cal: 2021-Aug-18	cal: 36M chk: 12M	cal: 2024-Aug-18
20558	Fully Anechoic Chamber 1	ETS-Lindgren GmbH / Taufkirchen	-	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -
20608	Ultrabroadband-Antenna HL562	Rohde & Schwarz Messgerätebau GmbH / Memmingen	830547/009	cal	cal: 2023-Jul-04	cal: 36M	cal: 2026-Jul-04
20611	Power Supply E3632A	Agilent Technologies Deutschland GmbH	KR 75305854	cpu			
20690	Spectrum Analyzer FSU	Rohde & Schwarz Messgerätebau GmbH / Memmingen	100302/026	cal	cal: 2023-May-25	cal: 24M	cal: 2025-May-25
20720	Measurement Software EMC32 [FAC]	Rohde & Schwarz Messgerätebau GmbH	V10.xx	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -
20868	High Pass Filter AFH-07000	AtlanTecRF	16071300004	chk	chk: 2023-Aug-22	chk: 12M	chk: 2024-Aug-22
20883	Open Switch and control Platform OSP-B200S2 Satellite	Rohde & Schwarz Messgerätebau GmbH / Memmingen	101432	chk	chk: 2023-Aug-22	chk: 12M	chk: 2024-Aug-22
20884	Open Switch and control Platform OSP320	Rohde & Schwarz Messgerätebau GmbH / Memmingen	101391	chk	chk: 2023-Aug-22	chk: 12M	chk: 2024-Aug-22
	120907 - FAC2 - Radiated Emissions			chk	chk: 2023-Feb-21	chk: 12M	chk: 2024-Feb-21
20005	AC - LISN 50 Ohm/50µH ESH2-Z5	Rohde & Schwarz Messgerätebau GmbH / Memmingen	861741/005	cal	cal: 2023-May-25	cal: 12M	cal: 2024-May-25
20133	Horn Antenna 3115 (Meas 1)	EMCO Elektronik GmbH / Gilching	9012-3629	cal	cal: 2023-May-22	cal: 36M	cal: 2026-May-22
20302	Horn Antenna BBHA9170 (Meas 1)	Schwarzbeck Mess-Elektronik OHG / Schönau	155	cpu	chk: 2020-Apr-15	chk: 12M	
20412	Fully Anechoic Chamber 2	ETS-Lindgren GmbH / Taufkirchen	without	chk	chk: 2023-Apr-14	chk: 6M	chk: 2023-Oct-14
20729	FS-Z140	Rohde & Schwarz Messgerätebau GmbH / Memmingen	101004	cal	cal: 2023-Jun-16	cal: 36M	cal: 2026-Jun-16
20730	FS-Z110	Rohde & Schwarz Messgerätebau GmbH / Memmingen	101468	cal	cal: 2023-Jun-02	cal: 36M	cal: 2026-Jun-02
20731	FS-Z75	Rohde & Schwarz Messgerätebau GmbH / Memmingen	101022	cal	cal: 2022-May-18	cal: 36M	cal: 2025-May-18
20732	Signal- and Spectrum Analyzer FSW67	Rohde & Schwarz Messgerätebau GmbH / Memmingen	104023	cal	cal: 2023-May-25	cal: 12M	cal: 2024-May-25
20767	Pickett-Potter Horn Antenna FH-PP 140-220	PGP-Radiometer Physics GmbH / Meckenheim	010011	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -
20811	Horn Antenna ASY-SGH-124-SMA	Antenna Systems Solutions S.L.	29F14182337	cal	cal: 2021-Oct-20	cal: 36M	cal: 2024-Oct-20
20814	Pickett-Potter Horn Antenna FH-PP 140	PGP-Radiometer Physics GmbH	10008	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -
20816	SGH Antenna SGH-26-WR10	Anteral S.L.	1144	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -
20836	1-18 GHz Amplifier	Wright Technologies, Inc., Inc. / Roseville	0001	chk		chk: 36M	
20907	Waveguide WR-15 attenuator STA-30-15-M2	SAGE Millimeter Inc.	13256-01	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -

ID	Description	Manufacturer	SerNo	CheckType	Last Check	Interval	Next Check
20908	Waveguide WR 10 attenuator STA-30-10-M2	SAGE Millimeter Inc.	13256-01	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -
20909	Waveguide Horn Antenna PE9881-24	Pasternack Enterprises, Inc.	37/2016	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -
20913	Phase Amplitude Stable Cable Assembly DC-40GHz	RF-Lambda Europe GmbH	AC19040001	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -
25457	DRG Horn Antenna SAS-574	A.H. Systems, Inc. / Chatsworth	383	cal	cal: 2022-Mar-28	cal: 36M	cal: 2025-Mar-28
20460	Radio Communication Tester CMU200	Rohde & Schwarz Messgerätebau GmbH / Memmingen	108901	cal	cal: 2023-Jun-24	cal: 12M	cal: 2024-Jun-02

Tools used in 'P1M1':

4.5.1 Legend

Note / remarks	Interval of calibration & Verification
12M	12 months
24M	24 months
36M	36 months
10Y	10 Years

Abbreviation Check Type	Description
cnn	Calibration and verification not necessary
cal	Calibration
calchk	Calibration plus intermediate Verification
chk	Verification
cpu	Verification before usage

5 Results from external laboratory

None

-

6 Opinions and interpretations

None

-

7 List of abbreviations

None

-

8 Measurement Uncertainty valid for conducted/radiated measurements

The reported uncertainties are calculated based on the standard uncertainty multiplied with the appropriate coverage factor **k**, such that a confidence level of approximately 95% is achieved. For uncertainty determination, each component used in the concrete measurement set-up was taken in account and its contribution to the overall uncertainty according its statistical distribution calculated.

Issue No.	Measurement type	Reference	Frequency range of measurement		Calculated Uncertainty based on confidence level of 95.54%	Remarks	
			Start [MHz]	Stop [MHz]			
1	Magnetic field strength	EN,FCC,JP,IC	0.009	30	4.86	Magnetic loop antenna, Pre-amp on	
2	RF-Output power (eirp) Unwanted emissions (eirp) [dB]	EN,FCC,JP,IC	30	100	4.57	without Pre-Amp	
			30	100	4.91	with PreAmp	
			100	1000	4.02	without Pre-Amp	
			100	1000	4.26	with PreAmp	
			1000	18000	4.36	without Pre-Amp	
			1000	18000	5.23	with PreAmp	
			18000	33000	4.92	Schwarzbeck BBHA9170 (#20302) Antenna set-up non-waveguide antenna	
			33000	50000	4.17	Set-up for Q-Band (WR-22), non-wave guide antenna	
			40000	60000	4.69	Set-up U-Band (WR-19), non-waveguide antenna	
			50000	75000	4.06	External Mixer set-up V-Band (WR-15)	
			75000	110000	4.17	External Mixer set-up W-Band (WR-6)	
			90000	140000	5.49	External Mixer set-up F-Band (WR-8)	
			140000	225000	6.22	External Mixer set-up G-Band (WR-5)	
			225000	325000	7.04	External Mixer set-up (WR-3)	
			325000	500000	8.84	External Mixer set-up (WR-2.2)	
3	Radiated Blocking [dB]	EN	1000	18000	2.85	Typical set-up with microwave generator and antenna, value for 7GHz calculated	
			18000	33000	4.66	Typical set-up with microwave generator and antenna	
			33000	50000	3.48	WR-22 set-up	
			50000	75000	3.73	WR-15 set-up	
			75000	110000	4.26	WR-6 set-up	
4	Frequency Error / UWB+FMCW [kHz]	EN, FCC,JP, ISED	40000	77000	276.19	calculated for 77 GHz (FMCW) carrier	
	Frequency Error / NFC [Hz]		6000	7000	33.92	calculated for 6.5GHz UWB Ch.5	
			11.00	14.00	20.76	calculated for 13.56MHz NFC carrier	
5	TS 8997 conducted Parameters	FCC15/18 / ISED	30	6000	1.11	1. Power measurement with Fast-sampling-detector	
			30	6000	1.20	2. Power measurement with Spectrum-Analyzer	
			30	6000	1.20	3. Power Spectrum-Density measurement	
			30	7500	1.20	4. Conducted Spurious emissions:	
			0.009	30	2.56	5. Conducted Spurious emissions:	
			2.4	2.48	1.95 ppm	6a. Bandwidth / 2-Marker Method for 2.4GHz ISM	
			5.18	5.825	7.180 ppm	6b. Bandwidth / 2-Marker Method for 5GHz WLAN	
			5.18	5.825	1.099 ppm	7 Frequency (Marker method) for 5GHz WLAN	
			30	6000	0.11561μs	8 Medium-Utilization factor / Timing	
			30	6000	1.85	9 Blocking-Level of companion device	
			30	6000	1.62	9 Blocking Generator level	
6	Conducted emissions	EN, FCC	0.009	30	3.57	general EMI-measurements on AC/DC ports	

9 Versions of test reports (change history)

Version	Applied changes	Date of release
--	Initial release	2024-Jul-19
C01	Change of antenna gain information Updated Conducted RF output power in chapter 4.1 Minor organizatoric changes	2024-Sep-03

End of Test Report