

Analysis Report

Report No.: 23060203HKG-001

The Equipment Under Test (EUT), is a portable 49.86MHz Transceiver for a Walkie Talkie. The sample supplied operated on a single channel, 49.86MHz.

The EUT is powered by 4 x 1.5V Button Cells. After switching on and pressing the button on the EUT, sound received by the Walkie Talkie will be transmitted to another Walkie Talkie.

Antenna Type: External Whip antenna

Antenna Gain: 0dBi

Nominal rated field strength: 65.1dBμV/m at 3m

Maximum allowed field strength of production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 68.1dBμV/m at 3m in frequency 49.860MHz, thus;

The EIRP = $[(FS \cdot D)^2 \cdot 1000 / 30] = 0.0029\text{mW}$

Thus;

Conducted power = Radiated Power (EIRP) – Antenna Gain

So;

Conducted Power = 0.0029mW.

The SAR Exclusion Threshold Level for 49.860MHz when the minimum test separation distance is < 50mm:

= $[474 \cdot (1 + \log_{10}(f(\text{MHz}))) / 2]$

= 308.6mW

Since the above conducted output power is well below the SAR Exclusion Threshold level, so the EUT is considered to comply with SAR requirement without testing.