



DC Fast Charging Station



CONFIRMS TO UL STD.2202
CERTIFIED TO CSA STD.C22.2#346



CAN ICES-3(A)/NMB-3(A)
IC: 31465-S12023
FCC ID: 2BC5D- S12023
4G module
Contains FCC ID:XMR201909EC25AFX
Contains IC:10224A-2019EC25AFX

- FOR USE WITH ELECTRIC VEHICLES. - POUR UTILISATION AVEC DES VÉHICULES ÉLECTRIQUES.

Model No. IDC1204

AC Input 480V / 3P+N+GND Rated 152A/120kW@50Hz/60Hz
DC Output A#(CCS1) 150~1000VDC Max. 250A (@50°C)
DC Output B#(CCS1) 150~1000VDC Max. 250A (@50°C)
Electrical Enclosure Type 3R (Rainproof)
Temperature Rating -30 ~ 50°C
Net Weight 416kg
S/N 2305WYKF22-00010001
Manufactured XX/XX/XXXX

Soneil International Ltd.



CONFIRMS TO UL STD.2202
CERTIFIED TO CSA STD.C22.2#346



CAN ICES-3(A)/NMB-3(A)
IC: 31465-S12023
FCC ID: 2BC5D- S12023
4G module
Contains FCC ID:XMR201909EC25AFX
Contains IC:10224A-2019EC25AFX

- FOR USE WITH ELECTRIC VEHICLES. - POUR UTILISATION AVEC DES VÉHICULES ÉLECTRIQUES.

Model No. IDC1505

AC Input 480V / 3P+N+GND Rated 190A/150kW@50Hz/60Hz
DC Output A#(CCS1) 150~1000VDC Max. 250A (@50°C)
DC Output B#(CCS1) 150~1000VDC Max. 250A (@50°C)
Electrical Enclosure Type 3R (Rainproof)
Temperature Rating -30 ~ 50°C
Net Weight 432kg
S/N 2305WYKF22-00010001
Manufactured XX/XX/XXXX

Soneil International Ltd.



DC Fast Charging Station

- FOR USE WITH ELECTRIC VEHICLES. - POUR UTILISATION AVEC DES VÉHICULES ÉLECTRIQUES.

Model No. IDC1806

AC Input 480V / 3P+N+GND Rated 228A/180kW@50Hz/60Hz

DC Output A#(CCS1) 150~1000VDC Max. 250A (@50°C)

DC Output B#(CCS1) 150~1000VDC Max. 250A (@50°C)

Electrical Enclosure Type 3R (Rainproof)

Temperature Rating -30 ~ 50°C

Net Weight 448kg

S/N 2305WYKF22-00010001

Manufactured XX/XX/XXXX



CONFIRMS TO UL STD.2202
CERTIFIED TO CSA STD.C22.2#346



CAN ICES-3(A)/NMB-3(A)
IC: 31465-S12023
FCC ID: 2BC5D- S12023
4G module
Contains FCC ID:XMR201909EC25AFX
Contains IC:10224A-2019EC25AFX

Soneil International Ltd.



DC Fast Charging Station

- FOR USE WITH ELECTRIC VEHICLES. - POUR UTILISATION AVEC DES VÉHICULES ÉLECTRIQUES.

Model No. IDC2408

AC Input 480V / 3P+N+GND Rated 304A/240kW@50Hz/60Hz

DC Output A#(CCS1) 150~1000VDC Max. 250A (@50°C)

DC Output B#(CCS1) 150~1000VDC Max. 250A (@50°C)

Electrical Enclosure Type 3R (Rainproof)

Temperature Rating -30 ~ 50°C

Net Weight 480kg

S/N 2305WYKF22-00010001

Manufactured XX/XX/XXXX



CONFIRMS TO UL STD.2202
CERTIFIED TO CSA STD.C22.2#346



CAN ICES-3(A)/NMB-3(A)
IC: 31465-S12023
FCC ID: 2BC5D- S12023
4G module
Contains FCC ID:XMR201909EC25AFX
Contains IC:10224A-2019EC25AFX

Soneil International Ltd.



Label Location