

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-04-15

Tested By:

Nan Zhong

EUT:

Wine Cooler

Model Number:

ROCCO2023

Test Mode:

TX AC20 5720MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.8°C;Humi:47.2%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G KUAYUE\24

Memo:

Sample Numbler:S25030626-001 Power Setting:16



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 5452.925    | 43.25            | 33.00               | 5.48            | -29.60   | 52.13          | 74.00          | 21.87       | PK       | Vertical |
| 2                   | 5470.000    | 40.63            | 33.00               | 5.49            | -29.60   | 49.52          | 68.20          | 18.68       | PK       | Vertical |
| 3                   | 5850.000    | 40.47            | 34.00               | 5.74            | -29.60   | 50.61          | 68.20          | 17.59       | PK       | Vertical |
| 4                   | 5884.970    | 43.09            | 34.07               | 5.76            | -29.60   | 53.32          | 68.20          | 14.88       | PK       | Vertical |

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX AX20 5720MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G KUAYUE\25  
**Memo:** Sample Numbler:S25030626-001 Power Setting:16



### Suspected Data List

| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| 1  | 5454.770    | 42.57            | 33.00               | 5.48            | -29.60   | 51.45          | 74.00          | 22.55       | PK       | Horizontal |
| 2  | 5470.000    | 41.76            | 33.00               | 5.49            | -29.60   | 50.65          | 68.20          | 17.55       | PK       | Horizontal |
| 3  | 5850.000    | 40.09            | 34.00               | 5.74            | -29.60   | 50.23          | 68.20          | 17.97       | PK       | Horizontal |
| 4  | 5884.205    | 43.18            | 34.07               | 5.76            | -29.60   | 53.41          | 68.20          | 14.79       | PK       | Horizontal |

#### Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-04-15

Tested By:

Nan Zhong

EUT:

Wine Cooler

Model Number:

ROCCO2023

Test Mode:

TX AX20 5720MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.8°C;Humi:47.2%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G KUAYUE\26

Memo:

Sample Numbler:S25030626-001 Power Setting:16




| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 5464.940    | 43.35            | 33.00               | 5.49            | -29.60   | 52.24          | 68.20          | 15.96       | PK       | Vertical |
| 2                   | 5470.000    | 41.86            | 33.00               | 5.49            | -29.60   | 50.75          | 68.20          | 17.45       | PK       | Vertical |
| 3                   | 5850.000    | 39.32            | 34.00               | 5.74            | -29.60   | 49.46          | 68.20          | 18.74       | PK       | Vertical |
| 4                   | 5864.315    | 42.17            | 34.03               | 5.75            | -29.60   | 52.35          | 68.20          | 15.85       | PK       | Vertical |

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-04-15 Tested By: Nan Zhong  
EUT: Wine Cooler Model Number: ROCCO2023  
Test Mode: TX N40 5710MHz Mode Power Supply: AC 120V/60Hz  
Condition: Temp:24.8°C;Humi:47.2% Test Site: DDT 3# Chamber  
File Path: d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G KUAYUE\35  
Memo: Sample Numbler:S25030626-001 Power Setting:16




| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 5452.925    | 42.63            | 33.00               | 5.48            | -29.60   | 51.51          | 74.00          | 22.49       | PK       | Horizontal |
| 2                   | 5470.000    | 39.52            | 33.00               | 5.49            | -29.60   | 48.41          | 68.20          | 19.79       | PK       | Horizontal |
| 3                   | 5850.000    | 39.75            | 34.00               | 5.74            | -29.60   | 49.89          | 68.20          | 18.31       | PK       | Horizontal |
| 4                   | 5864.405    | 42.34            | 34.03               | 5.75            | -29.60   | 52.52          | 68.20          | 15.68       | PK       | Horizontal |

Note:  
1. Level = Reading + Cable loss + Antenna Factor + AMP  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-04-15 Tested By: Nan Zhong  
EUT: Wine Cooler Model Number: ROCCO2023  
Test Mode: TX N40 5710MHz Mode Power Supply: AC 120V/60Hz  
Condition: Temp:24.8°C;Humi:47.2% Test Site: DDT 3# Chamber  
File Path: d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G KUAYUE\36  
Memo: Sample Numbler:S25030626-001 Power Setting:16



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 5468.405    | 41.77            | 33.00               | 5.49            | -29.60   | 50.66          | 68.20          | 17.54       | PK       | Vertical |
| 2                   | 5470.000    | 39.88            | 33.00               | 5.49            | -29.60   | 48.77          | 68.20          | 19.43       | PK       | Vertical |
| 3                   | 5850.000    | 39.08            | 34.00               | 5.74            | -29.60   | 49.22          | 68.20          | 18.98       | PK       | Vertical |
| 4                   | 5890.955    | 40.91            | 34.08               | 5.77            | -29.60   | 51.16          | 68.20          | 17.04       | PK       | Vertical |

Note:  
1. Level = Reading + Cable loss + Antenna Factor + AMP  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-04-15

Tested By:

Nan Zhong

EUT:

Wine Cooler

Model Number:

ROCCO2023

Test Mode:

TX AC40 5710MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.8°C;Humi:47.2%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G KUAYUE\33

Memo:

Sample Numbler:S25030626-001 Power Setting:16




| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 5453.735    | 42.62            | 33.00               | 5.48            | -29.60   | 51.50          | 74.00          | 22.50       | PK       | Horizontal |
| 2                   | 5470.000    | 39.52            | 33.00               | 5.49            | -29.60   | 48.41          | 68.20          | 19.79       | PK       | Horizontal |
| 3                   | 5850.000    | 39.75            | 34.00               | 5.74            | -29.60   | 49.89          | 68.20          | 18.31       | PK       | Horizontal |
| 4                   | 5870.030    | 42.95            | 34.04               | 5.75            | -29.60   | 53.14          | 68.20          | 15.06       | PK       | Horizontal |

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX AC40 5710MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G KUAYUE\34  
**Memo:** Sample Numbler:S25030626-001 Power Setting:16



### Suspected Data List


| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| 1  | 5466.830    | 42.87            | 33.00               | 5.49            | -29.60   | 51.76          | 68.20          | 16.44       | PK       | Vertical |
| 2  | 5470.000    | 39.88            | 33.00               | 5.49            | -29.60   | 48.77          | 68.20          | 19.43       | PK       | Vertical |
| 3  | 5850.000    | 39.58            | 34.00               | 5.74            | -29.60   | 49.72          | 68.20          | 18.48       | PK       | Vertical |
| 4  | 5871.470    | 42.64            | 34.04               | 5.76            | -29.60   | 52.84          | 68.20          | 15.36       | PK       | Vertical |

#### Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX AX40 5710MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G KUAYUE\27  
**Memo:** Sample Numbler:S25030626-001 Power Setting:16



### Suspected Data List


| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| 1  | 5466.920    | 42.94            | 33.00               | 5.49            | -29.60   | 51.83          | 68.20          | 16.37       | PK       | Horizontal |
| 2  | 5470.000    | 42.60            | 33.00               | 5.49            | -29.60   | 51.49          | 68.20          | 16.71       | PK       | Horizontal |
| 3  | 5850.000    | 41.20            | 34.00               | 5.74            | -29.60   | 51.34          | 68.20          | 16.86       | PK       | Horizontal |
| 4  | 5880.605    | 43.10            | 34.06               | 5.76            | -29.60   | 53.32          | 68.20          | 14.88       | PK       | Horizontal |

#### Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-04-15 Tested By: Nan Zhong  
EUT: Wine Cooler Model Number: ROCCO2023  
Test Mode: TX AX40 5710MHz Mode Power Supply: AC 120V/60Hz  
Condition: Temp:24.8°C;Humi:47.2% Test Site: DDT 3# Chamber  
File Path: d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G KUAYUE\28  
Memo: Sample Numbler:S25030626-001 Power Setting:16




| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 5468.990    | 43.48            | 33.00               | 5.49            | -29.60   | 52.37          | 68.20          | 15.83       | PK       | Vertical |
| 2                   | 5470.000    | 40.41            | 33.00               | 5.49            | -29.60   | 49.30          | 68.20          | 18.90       | PK       | Vertical |
| 3                   | 5850.000    | 40.34            | 34.00               | 5.74            | -29.60   | 50.48          | 68.20          | 17.72       | PK       | Vertical |
| 4                   | 5868.410    | 42.90            | 34.04               | 5.75            | -29.60   | 53.09          | 68.20          | 15.11       | PK       | Vertical |

Note:  
1. Level = Reading + Cable loss + Antenna Factor + AMP  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-04-15 Tested By: Nan Zhong  
EUT: Wine Cooler Model Number: ROCCO2023  
Test Mode: TX AC80 5690MHz Mode Power Supply: AC 120V/60Hz  
Condition: Temp:24.8°C;Humi:47.2% Test Site: DDT 3# Chamber  
File Path: d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G KUAYUE\31  
Memo: Sample Numbler:S25030626-001 Power Setting:16



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 5461.115    | 43.44            | 33.00               | 5.48            | -29.60   | 52.32          | 68.20          | 15.88       | PK       | Horizontal |
| 2                   | 5470.000    | 40.96            | 33.00               | 5.49            | -29.60   | 49.85          | 68.20          | 18.35       | PK       | Horizontal |
| 3                   | 5850.000    | 40.73            | 34.00               | 5.74            | -29.60   | 50.87          | 68.20          | 17.33       | PK       | Horizontal |
| 4                   | 5875.880    | 43.40            | 34.05               | 5.76            | -29.60   | 53.61          | 68.20          | 14.59       | PK       | Horizontal |

Note:  
1. Level = Reading + Cable loss + Antenna Factor + AMP  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-04-15

Tested By:

Nan Zhong

EUT:

Wine Cooler

Model Number:

ROCCO2023

Test Mode:

TX AC80 5690MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.8°C;Humi:47.2%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G KUAYUE\32

Memo:

Sample Numbler:S25030626-001 Power Setting:16



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 5455.490    | 43.22            | 33.00               | 5.48            | -29.60   | 52.10          | 74.00          | 21.90       | PK       | Vertical |
| 2                   | 5470.000    | 41.18            | 33.00               | 5.49            | -29.60   | 50.07          | 68.20          | 18.13       | PK       | Vertical |
| 3                   | 5850.000    | 39.77            | 34.00               | 5.74            | -29.60   | 49.91          | 68.20          | 18.29       | PK       | Vertical |
| 4                   | 5881.190    | 41.91            | 34.06               | 5.76            | -29.60   | 52.13          | 68.20          | 16.07       | PK       | Vertical |

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-04-15      Tested By: Nan Zhong  
EUT: Wine Cooler      Model Number: ROCCO2023  
Test Mode: TX AX80 5690MHz Mode      Power Supply: AC 120V/60Hz  
Condition: Temp:24.8°C;Humi:47.2%      Test Site: DDT 3# Chamber  
File Path: d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G KUAYUE\29  
Memo: Sample Numbler:S25030626-001 Power Setting:16




| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 5456.075    | 43.39            | 33.00               | 5.48            | -29.60   | 52.27          | 74.00          | 21.73       | PK       | Horizontal |
| 2                   | 5470.000    | 41.79            | 33.00               | 5.49            | -29.60   | 50.68          | 68.20          | 17.52       | PK       | Horizontal |
| 3                   | 5850.000    | 40.40            | 34.00               | 5.74            | -29.60   | 50.54          | 68.20          | 17.66       | PK       | Horizontal |
| 4                   | 5885.105    | 42.92            | 34.07               | 5.76            | -29.60   | 53.15          | 68.20          | 15.05       | PK       | Horizontal |

Note:  
1. Level = Reading + Cable loss + Antenna Factor + AMP  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-04-15 Tested By: Nan Zhong  
EUT: Wine Cooler Model Number: ROCCO2023  
Test Mode: TX AX80 5690MHz Mode Power Supply: AC 120V/60Hz  
Condition: Temp:24.8°C;Humi:47.2% Test Site: DDT 3# Chamber  
File Path: d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G KUAYUE\30  
Memo: Sample Numbler:S25030626-001 Power Setting:16



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 5457.290    | 42.98            | 33.00               | 5.48            | -29.60   | 51.86          | 74.00          | 22.14       | PK       | Vertical |
| 2                   | 5470.000    | 41.96            | 33.00               | 5.49            | -29.60   | 50.85          | 68.20          | 17.35       | PK       | Vertical |
| 3                   | 5850.000    | 40.02            | 34.00               | 5.74            | -29.60   | 50.16          | 68.20          | 18.04       | PK       | Vertical |
| 4                   | 5866.295    | 43.03            | 34.03               | 5.75            | -29.60   | 53.21          | 68.20          | 14.99       | PK       | Vertical |

Note:  
1. Level = Reading + Cable loss + Antenna Factor + AMP  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-04-15

Tested By:

Nan Zhong

EUT:

Wine Cooler

Model Number:

ROCCO2023

Test Mode:

TX 11A 5745MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.8°C;Humi:47.2%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\1

Memo:

Sample Numbler:S25030626-001 Power Setting:16



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 5665.282    | 43.65            | 33.46               | 5.62            | -29.60   | 53.13          | 79.54          | 26.41       | PK       | Horizontal |
| 2                   | 5725.000    | 40.00            | 33.75               | 5.66            | -29.60   | 49.81          | 125.30         | 75.49       | PK       | Horizontal |
| 3                   | 5747.262    | 78.56            | 33.88               | 5.67            | -29.60   | 88.51          | 125.30         | 36.79       | PK       | Horizontal |
| 4                   | 5850.000    | 40.84            | 34.00               | 5.74            | -29.60   | 50.98          | 125.30         | 74.32       | PK       | Horizontal |
| 5                   | 5888.744    | 44.03            | 34.08               | 5.77            | -29.60   | 54.28          | 95.10          | 40.82       | PK       | Horizontal |

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX 11A 5745MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\2  
**Memo:** Sample Numble:S25030626-001 Power Setting:16

**Suspected Data List**

| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| 1  | 5672.126    | 44.40            | 33.49               | 5.62            | -29.60   | 53.91          | 84.62          | 30.71       | PK       | Vertical |
| 2  | 5725.000    | 40.65            | 33.75               | 5.66            | -29.60   | 50.46          | 125.30         | 74.84       | PK       | Vertical |
| 3  | 5747.911    | 69.87            | 33.89               | 5.67            | -29.60   | 79.83          | 125.30         | 45.47       | PK       | Vertical |
| 4  | 5850.000    | 39.87            | 34.00               | 5.74            | -29.60   | 50.01          | 125.30         | 75.29       | PK       | Vertical |
| 5  | 5876.118    | 43.41            | 34.05               | 5.76            | -29.60   | 53.62          | 104.47         | 50.85       | PK       | Vertical |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:2025-04-15

Tested By:Nan Zhong

EUT:Wine Cooler

Model Number:ROCCO2023

Test Mode:TX 11A 5785MHz Mode


Power Supply:AC 120V/60Hz

Condition:Temp:24.8°C;Humi:47.2%

Test Site:DDT 3# Chamber

File Path:d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\3

Memo:Sample Numbler:S25030626-001 Power Setting:16



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 5700.121    | 43.72            | 33.60               | 5.64            | -29.60   | 53.36          | 105.33         | 51.97       | PK       | Horizontal |
| 2                   | 5725.000    | 40.66            | 33.75               | 5.66            | -29.60   | 50.47          | 125.30         | 74.83       | PK       | Horizontal |
| 3                   | 5792.515    | 79.47            | 34.16               | 5.70            | -29.60   | 89.73          | 125.30         | 35.57       | PK       | Horizontal |
| 4                   | 5850.000    | 41.64            | 34.00               | 5.74            | -29.60   | 51.78          | 125.30         | 73.52       | PK       | Horizontal |
| 5                   | 5877.534    | 43.26            | 34.06               | 5.76            | -29.60   | 53.48          | 103.42         | 49.94       | PK       | Horizontal |

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX 11A 5785MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\4  
**Memo:** Sample Numbler:S25030626-001 Power Setting:16

**Suspected Data List**


| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| 1  | 5676.285    | 43.47            | 33.51               | 5.63            | -29.60   | 53.01          | 87.70          | 34.69       | PK       | Vertical |
| 2  | 5725.000    | 41.01            | 33.75               | 5.66            | -29.60   | 50.82          | 125.30         | 74.48       | PK       | Vertical |
| 3  | 5790.716    | 72.78            | 34.14               | 5.70            | -29.60   | 83.02          | 125.30         | 42.28       | PK       | Vertical |
| 4  | 5850.000    | 41.12            | 34.00               | 5.74            | -29.60   | 51.26          | 125.30         | 74.04       | PK       | Vertical |
| 5  | 5880.809    | 43.26            | 34.06               | 5.76            | -29.60   | 53.48          | 100.99         | 47.51       | PK       | Vertical |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX 11A 5825MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\5  
**Memo:** Sample Numble:S25030626-001 Power Setting:16

**Suspected Data List**

| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| 1  | 5713.219    | 43.51            | 33.68               | 5.65            | -29.60   | 53.24          | 109.00         | 55.76       | PK       | Horizontal |
| 2  | 5725.000    | 41.89            | 33.75               | 5.66            | -29.60   | 51.70          | 125.30         | 73.60       | PK       | Horizontal |
| 3  | 5823.490    | 79.68            | 34.11               | 5.72            | -29.60   | 89.91          | 125.30         | 35.39       | PK       | Horizontal |
| 4  | 5850.000    | 40.29            | 34.00               | 5.74            | -29.60   | 50.43          | 125.30         | 74.87       | PK       | Horizontal |
| 5  | 5906.149    | 43.29            | 34.11               | 5.78            | -29.60   | 53.58          | 82.19          | 28.61       | PK       | Horizontal |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:2025-04-15

Tested By:Nan Zhong

EUT:Wine Cooler

Model Number:ROCCO2023

Test Mode:TX 11A 5825MHz Mode


Power Supply:AC 120V/60Hz

Condition:Temp:24.8°C;Humi:47.2%

Test Site:DDT 3# Chamber

File Path:d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\6

Memo:Sample Numbler:S25030626-001 Power Setting:16



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 5653.069    | 44.91            | 33.41               | 5.61            | -29.60   | 54.33          | 70.48          | 16.15       | PK       | Vertical |
| 2                   | 5725.000    | 40.93            | 33.75               | 5.66            | -29.60   | 50.74          | 125.30         | 74.56       | PK       | Vertical |
| 3                   | 5821.573    | 68.79            | 34.11               | 5.72            | -29.60   | 79.02          | 125.30         | 46.28       | PK       | Vertical |
| 4                   | 5850.000    | 41.46            | 34.00               | 5.74            | -29.60   | 51.60          | 125.30         | 73.70       | PK       | Vertical |
| 5                   | 5912.639    | 43.37            | 34.13               | 5.78            | -29.60   | 53.68          | 77.37          | 23.69       | PK       | Vertical |

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX N20 5745MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\7  
**Memo:** Sample Numble:S25030626-001 Power Setting:16

**Suspected Data List**

| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| 1  | 5647.287    | 44.43            | 33.39               | 5.61            | -29.60   | 53.83          | 68.20          | 14.37       | PK       | Horizontal |
| 2  | 5725.000    | 41.75            | 33.75               | 5.66            | -29.60   | 51.56          | 125.30         | 73.74       | PK       | Horizontal |
| 3  | 5743.722    | 79.99            | 33.86               | 5.67            | -29.60   | 89.92          | 125.30         | 35.38       | PK       | Horizontal |
| 4  | 5850.000    | 41.87            | 34.00               | 5.74            | -29.60   | 52.01          | 125.30         | 73.29       | PK       | Horizontal |
| 5  | 5907.152    | 43.30            | 34.11               | 5.78            | -29.60   | 53.59          | 81.44          | 27.85       | PK       | Horizontal |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-04-15

Tested By:

Nan Zhong

EUT:

Wine Cooler

Model Number:

ROCCO2023

Test Mode:

TX N20 5745MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.8°C;Humi:47.2%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\8

Memo:

Sample Numble:S25030626-001 Power Setting:16



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 5682.628    | 44.53            | 33.53               | 5.63            | -29.60   | 54.09          | 92.41          | 38.32       | PK       | Vertical |
| 2                   | 5725.000    | 40.06            | 33.75               | 5.66            | -29.60   | 49.87          | 125.30         | 75.43       | PK       | Vertical |
| 3                   | 5738.412    | 71.88            | 33.83               | 5.67            | -29.60   | 81.78          | 125.30         | 43.52       | PK       | Vertical |
| 4                   | 5850.000    | 40.86            | 34.00               | 5.74            | -29.60   | 51.00          | 125.30         | 74.30       | PK       | Vertical |
| 5                   | 5876.089    | 43.30            | 34.05               | 5.76            | -29.60   | 53.51          | 104.49         | 50.98       | PK       | Vertical |

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX N20 5785MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\9  
**Memo:** Sample Numbler:S25030626-001 Power Setting:16



### Suspected Data List


| NO. | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|-----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| 1   | 5699.472    | 43.65            | 33.60               | 5.64            | -29.60   | 53.29          | 104.91         | 51.62       | PK       | Horizontal |
| 2   | 5725.000    | 41.28            | 33.75               | 5.66            | -29.60   | 51.09          | 125.30         | 74.21       | PK       | Horizontal |
| 3   | 5786.497    | 80.70            | 34.12               | 5.70            | -29.60   | 90.92          | 125.30         | 34.38       | PK       | Horizontal |
| 4   | 5850.000    | 40.79            | 34.00               | 5.74            | -29.60   | 50.93          | 125.30         | 74.37       | PK       | Horizontal |
| 5   | 5879.894    | 43.91            | 34.06               | 5.76            | -29.60   | 54.13          | 101.67         | 47.54       | PK       | Horizontal |

#### Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-04-15 Tested By: Nan Zhong  
EUT: Wine Cooler Model Number: ROCCO2023  
Test Mode: TX N20 5785MHz Mode Power Supply: AC 120V/60Hz  
Condition: Temp:24.8°C;Humi:47.2% Test Site: DDT 3# Chamber  
File Path: d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\10  
Memo: Sample Numble:S25030626-001 Power Setting:16




| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 5661.683    | 44.21            | 33.45               | 5.62            | -29.60   | 53.68          | 76.87          | 23.19       | PK       | Vertical |
| 2                   | 5725.000    | 40.48            | 33.75               | 5.66            | -29.60   | 50.29          | 125.30         | 75.01       | PK       | Vertical |
| 3                   | 5789.064    | 74.23            | 34.13               | 5.70            | -29.60   | 84.46          | 125.30         | 40.84       | PK       | Vertical |
| 4                   | 5850.000    | 40.40            | 34.00               | 5.74            | -29.60   | 50.54          | 125.30         | 74.76       | PK       | Vertical |
| 5                   | 5867.711    | 43.68            | 34.04               | 5.75            | -29.60   | 53.87          | 107.34         | 53.47       | PK       | Vertical |

Note:  
1. Level = Reading + Cable loss + Antenna Factor + AMP  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX N20 5825MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\11  
**Memo:** Sample Numble:S25030626-001 Power Setting:16

**Suspected Data List**

| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| 1  | 5683.778    | 44.24            | 33.54               | 5.63            | -29.60   | 53.81          | 93.26          | 39.45       | PK       | Horizontal |
| 2  | 5725.000    | 41.18            | 33.75               | 5.66            | -29.60   | 50.99          | 125.30         | 74.31       | PK       | Horizontal |
| 3  | 5822.900    | 80.23            | 34.11               | 5.72            | -29.60   | 90.46          | 125.30         | 34.84       | PK       | Horizontal |
| 4  | 5850.000    | 40.29            | 34.00               | 5.74            | -29.60   | 50.43          | 125.30         | 74.87       | PK       | Horizontal |
| 5  | 5894.408    | 43.53            | 34.09               | 5.77            | -29.60   | 53.79          | 90.90          | 37.11       | PK       | Horizontal |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-04-15

Tested By:

Nan Zhong

EUT:

Wine Cooler

Model Number:

ROCCO2023

Test Mode:

TX N20 5825MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.8°C;Humi:47.2%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\12

Memo:

Sample Numble:S25030626-001 Power Setting:16



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 5690.858    | 43.96            | 33.56               | 5.64            | -29.60   | 53.56          | 98.52          | 44.96       | PK       | Vertical |
| 2                   | 5725.000    | 40.89            | 33.75               | 5.66            | -29.60   | 50.70          | 125.30         | 74.60       | PK       | Vertical |
| 3                   | 5826.912    | 74.33            | 34.09               | 5.73            | -29.60   | 84.55          | 125.30         | 40.75       | PK       | Vertical |
| 4                   | 5850.000    | 41.80            | 34.00               | 5.74            | -29.60   | 51.94          | 125.30         | 73.36       | PK       | Vertical |
| 5                   | 5892.019    | 43.63            | 34.08               | 5.77            | -29.60   | 53.88          | 92.67          | 38.79       | PK       | Vertical |

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX AC20 5745MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\13  
**Memo:** Sample Numble:S25030626-001 Power Setting:16

**Suspected Data List**

| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| 1  | 5679.412    | 44.44            | 33.52               | 5.63            | -29.60   | 53.99          | 90.02          | 36.03       | PK       | Horizontal |
| 2  | 5725.000    | 40.75            | 33.75               | 5.66            | -29.60   | 50.56          | 125.30         | 74.74       | PK       | Horizontal |
| 3  | 5743.280    | 80.15            | 33.86               | 5.67            | -29.60   | 90.08          | 125.30         | 35.22       | PK       | Horizontal |
| 4  | 5850.000    | 41.53            | 34.00               | 5.74            | -29.60   | 51.67          | 125.30         | 73.63       | PK       | Horizontal |
| 5  | 5895.706    | 42.76            | 34.09               | 5.77            | -29.60   | 53.02          | 89.94          | 36.92       | PK       | Horizontal |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-04-15

Tested By:

Nan Zhong

EUT:

Wine Cooler

Model Number:

ROCCO2023

Test Mode:

TX AC20 5745MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.8°C;Humi:47.2%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\14

Memo:

Sample Numbler:S25030626-001 Power Setting:16



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 5646.697    | 44.21            | 33.39               | 5.61            | -29.60   | 53.61          | 68.20          | 14.59       | PK       | Vertical |
| 2                   | 5725.000    | 40.30            | 33.75               | 5.66            | -29.60   | 50.11          | 125.30         | 75.19       | PK       | Vertical |
| 3                   | 5740.831    | 71.50            | 33.84               | 5.67            | -29.60   | 81.41          | 125.30         | 43.89       | PK       | Vertical |
| 4                   | 5850.000    | 43.02            | 34.00               | 5.74            | -29.60   | 53.16          | 125.30         | 72.14       | PK       | Vertical |
| 5                   | 5893.199    | 43.59            | 34.09               | 5.77            | -29.60   | 53.85          | 91.80          | 37.95       | PK       | Vertical |

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX AC20 5785MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\15  
**Memo:** Sample Numbler:S25030626-001 Power Setting:16

**Suspected Data List**

| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| 1  | 5672.332    | 44.59            | 33.49               | 5.62            | -29.60   | 54.10          | 84.77          | 30.67       | PK       | Horizontal |
| 2  | 5725.000    | 41.35            | 33.75               | 5.66            | -29.60   | 51.16          | 125.30         | 74.14       | PK       | Horizontal |
| 3  | 5788.828    | 80.78            | 34.13               | 5.70            | -29.60   | 91.01          | 125.30         | 34.29       | PK       | Horizontal |
| 4  | 5850.000    | 40.46            | 34.00               | 5.74            | -29.60   | 50.60          | 125.30         | 74.70       | PK       | Horizontal |
| 5  | 5897.712    | 43.58            | 34.10               | 5.77            | -29.60   | 53.85          | 88.45          | 34.60       | PK       | Horizontal |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-04-15

Tested By:

Nan Zhong

EUT:

Wine Cooler

Model Number:

ROCCO2023

Test Mode:

TX AC20 5785MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.8°C;Humi:47.2%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\16

Memo:

Sample Numbler:S25030626-001 Power Setting:16



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 5692.009    | 43.78            | 33.57               | 5.64            | -29.60   | 53.39          | 99.37          | 45.98       | PK       | Vertical |
| 2                   | 5725.000    | 39.77            | 33.75               | 5.66            | -29.60   | 49.58          | 125.30         | 75.72       | PK       | Vertical |
| 3                   | 5778.060    | 70.19            | 34.07               | 5.69            | -29.60   | 80.35          | 125.30         | 44.95       | PK       | Vertical |
| 4                   | 5850.000    | 42.76            | 34.00               | 5.74            | -29.60   | 52.90          | 125.30         | 72.40       | PK       | Vertical |
| 5                   | 5866.354    | 44.16            | 34.03               | 5.75            | -29.60   | 54.34          | 107.72         | 53.38       | PK       | Vertical |

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX AC20 5825MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\17  
**Memo:** Sample Numble:S25030626-001 Power Setting:16

**Suspected Data List**


| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| 1  | 5679.943    | 43.87            | 33.52               | 5.63            | -29.60   | 53.42          | 90.42          | 37.00       | PK       | Horizontal |
| 2  | 5725.000    | 42.63            | 33.75               | 5.66            | -29.60   | 52.44          | 125.30         | 72.86       | PK       | Horizontal |
| 3  | 5817.531    | 80.71            | 34.13               | 5.72            | -29.60   | 90.96          | 125.30         | 34.34       | PK       | Horizontal |
| 4  | 5850.000    | 40.96            | 34.00               | 5.74            | -29.60   | 51.10          | 125.30         | 74.20       | PK       | Horizontal |
| 5  | 5897.565    | 43.73            | 34.10               | 5.77            | -29.60   | 54.00          | 88.56          | 34.56       | PK       | Horizontal |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX AC20 5825MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\18  
**Memo:** Sample Numbler:S25030626-001 Power Setting:16

**Suspected Data List**


| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| 1  | 5681.330    | 44.04            | 33.53               | 5.63            | -29.60   | 53.60          | 91.45          | 37.85       | PK       | Vertical |
| 2  | 5725.000    | 39.40            | 33.75               | 5.66            | -29.60   | 49.21          | 125.30         | 76.09       | PK       | Vertical |
| 3  | 5830.187    | 74.61            | 34.08               | 5.73            | -29.60   | 84.82          | 125.30         | 40.48       | PK       | Vertical |
| 4  | 5850.000    | 40.83            | 34.00               | 5.74            | -29.60   | 50.97          | 125.30         | 74.33       | PK       | Vertical |
| 5  | 5908.775    | 43.32            | 34.12               | 5.78            | -29.60   | 53.62          | 80.24          | 26.62       | PK       | Vertical |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX AX20 5745MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\19  
**Memo:** Sample Numbler:S25030626-001 Power Setting:16

**Suspected Data List**

| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| 1  | 5684.132    | 44.11            | 33.54               | 5.63            | -29.60   | 53.68          | 93.53          | 39.85       | PK       | Horizontal |
| 2  | 5725.000    | 40.80            | 33.75               | 5.66            | -29.60   | 50.61          | 125.30         | 74.69       | PK       | Horizontal |
| 3  | 5750.596    | 81.70            | 33.90               | 5.68            | -29.60   | 91.68          | 125.30         | 33.62       | PK       | Horizontal |
| 4  | 5850.000    | 41.40            | 34.00               | 5.74            | -29.60   | 51.54          | 125.30         | 73.76       | PK       | Horizontal |
| 5  | 5874.378    | 44.22            | 34.05               | 5.76            | -29.60   | 54.43          | 105.47         | 51.04       | PK       | Horizontal |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-04-15

Tested By:

Nan Zhong

EUT:

Wine Cooler

Model Number:

ROCCO2023

Test Mode:

TX AX20 5745MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.8°C;Humi:47.2%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\20

Memo:

Sample Numble:S25030626-001 Power Setting:16



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 5699.354    | 44.59            | 33.60               | 5.64            | -29.60   | 54.23          | 104.82         | 50.59       | PK       | Vertical |
| 2                   | 5725.000    | 39.94            | 33.75               | 5.66            | -29.60   | 49.75          | 125.30         | 75.55       | PK       | Vertical |
| 3                   | 5748.000    | 72.01            | 33.89               | 5.67            | -29.60   | 81.97          | 125.30         | 43.33       | PK       | Vertical |
| 4                   | 5850.000    | 40.37            | 34.00               | 5.74            | -29.60   | 50.51          | 125.30         | 74.79       | PK       | Vertical |
| 5                   | 5882.490    | 42.79            | 34.06               | 5.76            | -29.60   | 53.01          | 99.74          | 46.73       | PK       | Vertical |

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX AX20 5785MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\21  
**Memo:** Sample Numbler:S25030626-001 Power Setting:16

**Suspected Data List**


| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| 1  | 5681.949    | 43.99            | 33.53               | 5.63            | -29.60   | 53.55          | 91.91          | 38.36       | PK       | Horizontal |
| 2  | 5725.000    | 42.29            | 33.75               | 5.66            | -29.60   | 52.10          | 125.30         | 73.20       | PK       | Horizontal |
| 3  | 5787.058    | 81.49            | 34.12               | 5.70            | -29.60   | 91.71          | 125.30         | 33.59       | PK       | Horizontal |
| 4  | 5850.000    | 39.71            | 34.00               | 5.74            | -29.60   | 49.85          | 125.30         | 75.45       | PK       | Horizontal |
| 5  | 5901.636    | 44.19            | 34.10               | 5.78            | -29.60   | 54.47          | 85.54          | 31.07       | PK       | Horizontal |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX AX20 5785MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\22  
**Memo:** Sample Numble:S25030626-001 Power Setting:16

**Suspected Data List**

| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| 1  | 5669.530    | 44.44            | 33.48               | 5.62            | -29.60   | 53.94          | 82.69          | 28.75       | PK       | Vertical |
| 2  | 5725.000    | 41.13            | 33.75               | 5.66            | -29.60   | 50.94          | 125.30         | 74.36       | PK       | Vertical |
| 3  | 5793.017    | 71.96            | 34.16               | 5.70            | -29.60   | 82.22          | 125.30         | 43.08       | PK       | Vertical |
| 4  | 5850.000    | 40.85            | 34.00               | 5.74            | -29.60   | 50.99          | 125.30         | 74.31       | PK       | Vertical |
| 5  | 5869.510    | 43.32            | 34.04               | 5.75            | -29.60   | 53.51          | 106.84         | 53.33       | PK       | Vertical |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-04-15

Tested By:

Nan Zhong

EUT:

Wine Cooler

Model Number:

ROCCO2023

Test Mode:

TX AX20 5825MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.8°C;Humi:47.2%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\23

Memo:

Sample Numbler:S25030626-001 Power Setting:16



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 5698.912    | 43.91            | 33.60               | 5.64            | -29.60   | 53.55          | 104.49         | 50.94       | PK       | Horizontal |
| 2                   | 5725.000    | 41.14            | 33.75               | 5.66            | -29.60   | 50.95          | 125.30         | 74.35       | PK       | Horizontal |
| 3                   | 5832.193    | 81.36            | 34.07               | 5.73            | -29.60   | 91.56          | 125.30         | 33.74       | PK       | Horizontal |
| 4                   | 5850.000    | 41.90            | 34.00               | 5.74            | -29.60   | 52.04          | 125.30         | 73.26       | PK       | Horizontal |
| 5                   | 5883.405    | 43.72            | 34.07               | 5.76            | -29.60   | 53.95          | 99.06          | 45.11       | PK       | Horizontal |

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX AX20 5825MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\24  
**Memo:** Sample Numbler:S25030626-001 Power Setting:16

**Suspected Data List**


| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| 1  | 5684.132    | 43.45            | 33.54               | 5.63            | -29.60   | 53.02          | 93.53          | 40.51       | PK       | Vertical |
| 2  | 5725.000    | 41.88            | 33.75               | 5.66            | -29.60   | 51.69          | 125.30         | 73.61       | PK       | Vertical |
| 3  | 5821.248    | 73.80            | 34.12               | 5.72            | -29.60   | 84.04          | 125.30         | 41.26       | PK       | Vertical |
| 4  | 5850.000    | 41.44            | 34.00               | 5.74            | -29.60   | 51.58          | 125.30         | 73.72       | PK       | Vertical |
| 5  | 5859.893    | 43.17            | 34.02               | 5.75            | -29.60   | 53.34          | 109.53         | 56.19       | PK       | Vertical |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX N40 5755MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\33  
**Memo:** Sample Numble:S25030626-001 Power Setting:16

**Suspected Data List**


| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| 1  | 5673.276    | 43.75            | 33.49               | 5.62            | -29.60   | 53.26          | 85.47          | 32.21       | PK       | Horizontal |
| 2  | 5725.000    | 41.56            | 33.75               | 5.66            | -29.60   | 51.37          | 125.30         | 73.93       | PK       | Horizontal |
| 3  | 5765.434    | 77.24            | 33.99               | 5.69            | -29.60   | 87.32          | 125.30         | 37.98       | PK       | Horizontal |
| 4  | 5850.000    | 41.24            | 34.00               | 5.74            | -29.60   | 51.38          | 125.30         | 73.92       | PK       | Horizontal |
| 5  | 5888.862    | 43.45            | 34.08               | 5.77            | -29.60   | 53.70          | 95.01          | 41.31       | PK       | Horizontal |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX N40 5755MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\34  
**Memo:** Sample Numbler:S25030626-001 Power Setting:16

**Suspected Data List**

| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| 1  | 5701.390    | 44.37            | 33.61               | 5.64            | -29.60   | 54.02          | 105.69         | 51.67       | PK       | Vertical |
| 2  | 5725.000    | 40.00            | 33.75               | 5.66            | -29.60   | 49.81          | 125.30         | 75.49       | PK       | Vertical |
| 3  | 5770.449    | 68.05            | 34.02               | 5.69            | -29.60   | 78.16          | 125.30         | 47.14       | PK       | Vertical |
| 4  | 5850.000    | 42.48            | 34.00               | 5.74            | -29.60   | 52.62          | 125.30         | 72.68       | PK       | Vertical |
| 5  | 5870.454    | 43.40            | 34.04               | 5.75            | -29.60   | 53.59          | 106.57         | 52.98       | PK       | Vertical |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-04-15

Tested By:

Nan Zhong

EUT:

Wine Cooler

Model Number:

ROCCO2023

Test Mode:

TX N40 5795MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.8°C;Humi:47.2%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\35

Memo:

Sample Numbler:S25030626-001 Power Setting:16



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 5686.109    | 44.31            | 33.54               | 5.63            | -29.60   | 53.88          | 94.99          | 41.11       | PK       | Horizontal |
| 2                   | 5725.000    | 40.34            | 33.75               | 5.66            | -29.60   | 50.15          | 125.30         | 75.15       | PK       | Horizontal |
| 3                   | 5803.666    | 78.63            | 34.19               | 5.71            | -29.60   | 88.93          | 125.30         | 36.37       | PK       | Horizontal |
| 4                   | 5850.000    | 42.27            | 34.00               | 5.74            | -29.60   | 52.41          | 125.30         | 72.89       | PK       | Horizontal |
| 5                   | 5875.882    | 43.23            | 34.05               | 5.76            | -29.60   | 53.44          | 104.65         | 51.21       | PK       | Horizontal |

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-04-15      Tested By: Nan Zhong  
EUT: Wine Cooler      Model Number: ROCCO2023  
Test Mode: TX N40 5795MHz Mode      Power Supply: AC 120V/60Hz  
Condition: Temp:24.8°C;Humi:47.2%      Test Site: DDT 3# Chamber  
File Path: d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\36  
Memo: Sample Numble:S25030626-001 Power Setting:16




| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 5676.315    | 44.29            | 33.51               | 5.63            | -29.60   | 53.83          | 87.73          | 33.90       | PK       | Vertical |
| 2                   | 5725.000    | 41.11            | 33.75               | 5.66            | -29.60   | 50.92          | 125.30         | 74.38       | PK       | Vertical |
| 3                   | 5781.512    | 68.57            | 34.09               | 5.70            | -29.60   | 78.76          | 125.30         | 46.54       | PK       | Vertical |
| 4                   | 5850.000    | 41.20            | 34.00               | 5.74            | -29.60   | 51.34          | 125.30         | 73.96       | PK       | Vertical |
| 5                   | 5870.956    | 44.49            | 34.04               | 5.75            | -29.60   | 54.68          | 106.43         | 51.75       | PK       | Vertical |

Note:  
1. Level = Reading + Cable loss + Antenna Factor + AMP  
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX AC40 5755MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\29  
**Memo:** Sample Numbler:S25030626-001 Power Setting:16

**Suspected Data List**


| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| 1  | 5691.979    | 43.43            | 33.57               | 5.64            | -29.60   | 53.04          | 99.35          | 46.31       | PK       | Horizontal |
| 2  | 5725.000    | 40.68            | 33.75               | 5.66            | -29.60   | 50.49          | 125.30         | 74.81       | PK       | Horizontal |
| 3  | 5742.159    | 76.22            | 33.85               | 5.67            | -29.60   | 86.14          | 125.30         | 39.16       | PK       | Horizontal |
| 4  | 5850.000    | 41.68            | 34.00               | 5.74            | -29.60   | 51.82          | 125.30         | 73.48       | PK       | Horizontal |
| 5  | 5870.897    | 43.61            | 34.04               | 5.75            | -29.60   | 53.80          | 106.45         | 52.65       | PK       | Horizontal |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX AC40 5755MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\30  
**Memo:** Sample Numble:S25030626-001 Power Setting:16

**Suspected Data List**


| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| 1  | 5683.011    | 44.27            | 33.53               | 5.63            | -29.60   | 53.83          | 92.69          | 38.86       | PK       | Vertical |
| 2  | 5725.000    | 41.41            | 33.75               | 5.66            | -29.60   | 51.22          | 125.30         | 74.08       | PK       | Vertical |
| 3  | 5767.470    | 68.01            | 34.00               | 5.69            | -29.60   | 78.10          | 125.30         | 47.20       | PK       | Vertical |
| 4  | 5850.000    | 42.08            | 34.00               | 5.74            | -29.60   | 52.22          | 125.30         | 73.08       | PK       | Vertical |
| 5  | 5862.224    | 43.30            | 34.02               | 5.75            | -29.60   | 53.47          | 108.88         | 55.41       | PK       | Vertical |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX AC40 5795MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\31  
**Memo:** Sample Numble:S25030626-001 Power Setting:16

**Suspected Data List**

| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| 1  | 5717.408    | 44.37            | 33.70               | 5.65            | -29.60   | 54.12          | 110.17         | 56.05       | PK       | Horizontal |
| 2  | 5725.000    | 41.30            | 33.75               | 5.66            | -29.60   | 51.11          | 125.30         | 74.19       | PK       | Horizontal |
| 3  | 5808.534    | 77.47            | 34.17               | 5.71            | -29.60   | 87.75          | 125.30         | 37.55       | PK       | Horizontal |
| 4  | 5850.000    | 40.38            | 34.00               | 5.74            | -29.60   | 50.52          | 125.30         | 74.78       | PK       | Horizontal |
| 5  | 5883.080    | 43.11            | 34.07               | 5.76            | -29.60   | 53.34          | 99.30          | 45.96       | PK       | Horizontal |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-04-15

Tested By:

Nan Zhong

EUT:

Wine Cooler

Model Number:

ROCCO2023

Test Mode:

TX AC40 5795MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.8°C;Humi:47.2%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\32

Memo:

Sample Numble:S25030626-001 Power Setting:16




| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 5702.688    | 44.65            | 33.62               | 5.64            | -29.60   | 54.31          | 106.05         | 51.74       | PK       | Vertical |
| 2                   | 5725.000    | 42.51            | 33.75               | 5.66            | -29.60   | 52.32          | 125.30         | 72.98       | PK       | Vertical |
| 3                   | 5798.533    | 69.38            | 34.19               | 5.71            | -29.60   | 79.68          | 125.30         | 45.62       | PK       | Vertical |
| 4                   | 5850.000    | 41.36            | 34.00               | 5.74            | -29.60   | 51.50          | 125.30         | 73.80       | PK       | Vertical |
| 5                   | 5882.018    | 42.98            | 34.06               | 5.76            | -29.60   | 53.20          | 100.09         | 46.89       | PK       | Vertical |

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX AX40 5755MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\25  
**Memo:** Sample Numble:S25030626-001 Power Setting:16

**Suspected Data List**

| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| 1  | 5658.290    | 44.06            | 33.43               | 5.61            | -29.60   | 53.50          | 74.35          | 20.85       | PK       | Horizontal |
| 2  | 5725.000    | 41.08            | 33.75               | 5.66            | -29.60   | 50.89          | 125.30         | 74.41       | PK       | Horizontal |
| 3  | 5773.458    | 77.19            | 34.04               | 5.69            | -29.60   | 87.32          | 125.30         | 37.98       | PK       | Horizontal |
| 4  | 5850.000    | 39.91            | 34.00               | 5.74            | -29.60   | 50.05          | 125.30         | 75.25       | PK       | Horizontal |
| 5  | 5877.328    | 44.24            | 34.05               | 5.76            | -29.60   | 54.45          | 103.57         | 49.12       | PK       | Horizontal |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-04-15

Tested By:

Nan Zhong

EUT:

Wine Cooler

Model Number:

ROCCO2023

Test Mode:

TX AX40 5755MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.8°C;Humi:47.2%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\26

Memo:

Sample Numble:S25030626-001 Power Setting:16



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 5698.204    | 43.72            | 33.59               | 5.64            | -29.60   | 53.35          | 103.97         | 50.62       | PK       | Vertical |
| 2                   | 5725.000    | 39.29            | 33.75               | 5.66            | -29.60   | 49.10          | 125.30         | 76.20       | PK       | Vertical |
| 3                   | 5765.818    | 68.62            | 33.99               | 5.69            | -29.60   | 78.70          | 125.30         | 46.60       | PK       | Vertical |
| 4                   | 5850.000    | 41.16            | 34.00               | 5.74            | -29.60   | 51.30          | 125.30         | 74.00       | PK       | Vertical |
| 5                   | 5898.656    | 43.14            | 34.10               | 5.77            | -29.60   | 53.41          | 87.75          | 34.34       | PK       | Vertical |

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX AX40 5795MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\27  
**Memo:** Sample Numble:S25030626-001 Power Setting:16



### Suspected Data List


| NO. | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|-----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| 1   | 5682.687    | 43.95            | 33.53               | 5.63            | -29.60   | 53.51          | 92.45          | 38.94       | PK       | Horizontal |
| 2   | 5725.000    | 40.08            | 33.75               | 5.66            | -29.60   | 49.89          | 125.30         | 75.41       | PK       | Horizontal |
| 3   | 5810.274    | 79.32            | 34.16               | 5.71            | -29.60   | 89.59          | 125.30         | 35.71       | PK       | Horizontal |
| 4   | 5850.000    | 39.98            | 34.00               | 5.74            | -29.60   | 50.12          | 125.30         | 75.18       | PK       | Horizontal |
| 5   | 5861.929    | 43.21            | 34.02               | 5.75            | -29.60   | 53.38          | 108.96         | 55.58       | PK       | Horizontal |

#### Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX AX40 5795MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\28  
**Memo:** Sample Numbler:S25030626-001 Power Setting:16



### Suspected Data List

| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| 1  | 5683.867    | 44.28            | 33.54               | 5.63            | -29.60   | 53.85          | 93.33          | 39.48       | PK       | Vertical |
| 2  | 5725.000    | 40.94            | 33.75               | 5.66            | -29.60   | 50.75          | 125.30         | 74.55       | PK       | Vertical |
| 3  | 5804.404    | 73.61            | 34.18               | 5.71            | -29.60   | 83.90          | 125.30         | 41.40       | PK       | Vertical |
| 4  | 5850.000    | 41.04            | 34.00               | 5.74            | -29.60   | 51.18          | 125.30         | 74.12       | PK       | Vertical |
| 5  | 5899.217    | 44.62            | 34.10               | 5.77            | -29.60   | 54.89          | 87.33          | 32.44       | PK       | Vertical |

### Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-04-15

Tested By:

Nan Zhong

EUT:

Wine Cooler

Model Number:

ROCCO2023

Test Mode:

TX AC80 5775MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.8°C;Humi:47.2%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\37

Memo:

Sample Numble:S25030626-001 Power Setting:16



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 5671.447    | 43.98            | 33.49               | 5.62            | -29.60   | 53.49          | 84.11          | 30.62       | PK       | Horizontal |
| 2                   | 5725.000    | 40.79            | 33.75               | 5.66            | -29.60   | 50.60          | 125.30         | 74.70       | PK       | Horizontal |
| 3                   | 5797.914    | 73.47            | 34.19               | 5.71            | -29.60   | 83.77          | 125.30         | 41.53       | PK       | Horizontal |
| 4                   | 5850.000    | 40.88            | 34.00               | 5.74            | -29.60   | 51.02          | 125.30         | 74.28       | PK       | Horizontal |
| 5                   | 5877.859    | 43.27            | 34.06               | 5.76            | -29.60   | 53.49          | 103.18         | 49.69       | PK       | Horizontal |

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-04-15

Tested By:

Nan Zhong

EUT:

Wine Cooler

Model Number:

ROCCO2023

Test Mode:

TX AC80 5775MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.8°C;Humi:47.2%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\38

Memo:

Sample Numbler:S25030626-001 Power Setting:16



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 5696.168    | 43.94            | 33.58               | 5.64            | -29.60   | 53.56          | 102.46         | 48.90       | PK       | Vertical |
| 2                   | 5725.000    | 40.84            | 33.75               | 5.66            | -29.60   | 50.65          | 125.30         | 74.65       | PK       | Vertical |
| 3                   | 5805.377    | 64.19            | 34.18               | 5.71            | -29.60   | 74.48          | 125.30         | 50.82       | PK       | Vertical |
| 4                   | 5850.000    | 41.81            | 34.00               | 5.74            | -29.60   | 51.95          | 125.30         | 73.35       | PK       | Vertical |
| 5                   | 5876.354    | 43.41            | 34.05               | 5.76            | -29.60   | 53.62          | 104.30         | 50.68       | PK       | Vertical |

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2025-04-15 **Tested By:** Nan Zhong  
**EUT:** Wine Cooler **Model Number:** ROCCO2023  
**Test Mode:** TX AX80 5775MHz Mode **Power Supply:** AC 120V/60Hz  
**Condition:** Temp:24.8°C;Humi:47.2% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\39  
**Memo:** Sample Numble:S25030626-001 Power Setting:16

**Suspected Data List**

| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| 1  | 5679.353    | 43.86            | 33.52               | 5.63            | -29.60   | 53.41          | 89.98          | 36.57       | PK       | Horizontal |
| 2  | 5725.000    | 42.26            | 33.75               | 5.66            | -29.60   | 52.07          | 125.30         | 73.23       | PK       | Horizontal |
| 3  | 5783.046    | 75.15            | 34.10               | 5.70            | -29.60   | 85.35          | 125.30         | 39.95       | PK       | Horizontal |
| 4  | 5850.000    | 40.78            | 34.00               | 5.74            | -29.60   | 50.92          | 125.30         | 74.38       | PK       | Horizontal |
| 5  | 5915.324    | 43.01            | 34.13               | 5.78            | -29.60   | 53.32          | 75.38          | 22.06       | PK       | Horizontal |

**Note:**

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-04-15

Tested By:

Nan Zhong

EUT:

Wine Cooler

Model Number:

ROCCO2023

Test Mode:

TX AX80 5775MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:24.8°C;Humi:47.2%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25030626-1E\FCC ABOVE1G MASK\40

Memo:

Sample Numbler:S25030626-001 Power Setting:16



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 5671.329    | 44.42            | 33.49               | 5.62            | -29.60   | 53.93          | 84.03          | 30.10       | PK       | Vertical |
| 2                   | 5725.000    | 39.77            | 33.75               | 5.66            | -29.60   | 49.58          | 125.30         | 75.72       | PK       | Vertical |
| 3                   | 5808.976    | 68.62            | 34.16               | 5.71            | -29.60   | 78.89          | 125.30         | 46.41       | PK       | Vertical |
| 4                   | 5850.000    | 40.23            | 34.00               | 5.74            | -29.60   | 50.37          | 125.30         | 74.93       | PK       | Vertical |
| 5                   | 5902.196    | 43.00            | 34.10               | 5.78            | -29.60   | 53.28          | 85.12          | 31.84       | PK       | Vertical |

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## 15. Power Line Conducted Emissions

### 15.1. Test equipment

| Equipment          | Manufacturer    | Model No. | Serial No.  | Cal Due To |
|--------------------|-----------------|-----------|-------------|------------|
| Artificial mains   | R&S             | ESH2-Z5   | DDT-ZC00538 | 2025/07/08 |
| EMI Test Software  | Audix/TW        | e3        | DDT-ZC01252 | /          |
| Two Line V-Network | R&S             | ENV216    | DDT-ZC00535 | 2025/07/08 |
| EMI Test Receiver  | R&S             | ESCI      | DDT-ZC00235 | 2025/07/08 |
| Pulse Limiter      | SCHWARZBEC<br>K | ESH3-Z2   | DDT-ZC00539 | 2025/07/08 |
| CE Cable 1         | R&S             | ESU8/RF2  | DDT-ZC00566 | 2025/07/08 |

### 15.2. Block diagram of test setup



### 15.3. Limits

| Frequency       | Quasi-Peak Level<br>dB(uV) | Average Level<br>dB(uV) |
|-----------------|----------------------------|-------------------------|
| 150 kHz~500 kHz | 66 ~ 56*                   | 56 ~ 46*                |
| 500 kHz~5 MHz   | 56                         | 46                      |
| 5 MHz~30 MHz    | 60                         | 50                      |

Note 1: \* Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

### 15.4. Assistant equipment used for test

| Assistant equipment | Manufacturer | Model number | Description | other |
|---------------------|--------------|--------------|-------------|-------|
| /                   | /            | /            | /           | /     |

### 15.5. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

## 15.6. Test result

### **PASS. (See below detailed test result)**

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “----” means Peak detection; “-----” means Average detection.

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded the worst case.

15.7. Test data

TR-4-E-010 Conducted Emission Test Result

Test Site

: DDT 1# Shield Room

Test Date

: 2025-04-18

EUT

: Wine Cooler

Power Supply

: AC 120V/60Hz

Condition

: TEMP:22.6°C, RH:56.6%

Memo

:

D:\2025 CE report data\Q25030626-1E\CE.EM6

Tested By

: Nan Zhong

Model Number


: ROCCO2023

Test Mode

: 5G mode

LISN

: 2024 1# ENV216/LINE




| Item   | Freq. | Read Level | LISN  | Cable | Pulse               | Result | Limit  | Over   | Detector | Phase |
|--------|-------|------------|-------|-------|---------------------|--------|--------|--------|----------|-------|
| (Mark) | (MHz) | (dBμV)     | (dB)  | (dB)  | Limiter Factor (dB) | (dBμV) | (dBμV) | (dB)   |          |       |
| 1      | 0.19  | 35.07      | 9.77  | 0.12  | 9.86                | 54.82  | 64.11  | -9.29  | QP       | LINE  |
| 2      | 0.19  | 28.91      | 9.77  | 0.12  | 9.86                | 48.66  | 54.11  | -5.45  | Average  | LINE  |
| 3      | 0.82  | 14.27      | 9.82  | 0.08  | 9.87                | 34.04  | 56.00  | -21.96 | QP       | LINE  |
| 4      | 0.82  | 9.26       | 9.82  | 0.08  | 9.87                | 29.03  | 46.00  | -16.97 | Average  | LINE  |
| 5      | 1.72  | 9.54       | 9.76  | 0.04  | 9.87                | 29.21  | 56.00  | -26.79 | QP       | LINE  |
| 6      | 1.72  | 3.95       | 9.76  | 0.04  | 9.87                | 23.62  | 46.00  | -22.38 | Average  | LINE  |
| 7      | 8.64  | 12.23      | 9.79  | 0.11  | 9.95                | 32.08  | 60.00  | -27.92 | QP       | LINE  |
| 8      | 8.64  | 6.96       | 9.79  | 0.11  | 9.95                | 26.81  | 50.00  | -23.19 | Average  | LINE  |
| 9      | 15.47 | 12.84      | 9.96  | 0.14  | 9.93                | 32.87  | 60.00  | -27.13 | QP       | LINE  |
| 10     | 15.47 | 6.80       | 9.96  | 0.14  | 9.93                | 26.83  | 50.00  | -23.17 | Average  | LINE  |
| 11     | 24.14 | 11.53      | 10.14 | 0.18  | 9.99                | 31.84  | 60.00  | -28.16 | QP       | LINE  |
| 12     | 24.14 | 0.84       | 10.14 | 0.18  | 9.99                | 21.15  | 50.00  | -28.85 | Average  | LINE  |

Note:

1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

## TR-4-E-010 Conducted Emission Test Result

**Test Site** : DDT 1# Shield Room **D:\2025 CE report data\Q25030626-1E\CE.EM6**  
**Test Date** : 2025-04-18 **Tested By** : Nan Zhong  
**EUT** : Wine Cooler **Model Number** : ROCCO2023  
**Power Supply** : AC 120V/60Hz **Test Mode** : 5G mode  
**Condition** : TEMP:22.6°C, RH:56.6% **LISN** : 2024 1# ENV216/NEUTRAL  
**Memo** :



| Item   | Freq. | Read Level | LISN Factor | Cable Loss | Pulse Limiter Factor | Result Level | Limit Line | Over Limit | Detector | Phase   |
|--------|-------|------------|-------------|------------|----------------------|--------------|------------|------------|----------|---------|
| (Mark) | (MHz) | (dBμV)     | (dB)        | (dB)       | (dB)                 | (dBμV)       | (dBμV)     | (dB)       |          |         |
| 1      | 0.19  | 35.33      | 9.68        | 0.12       | 9.86                 | 54.99        | 64.15      | -9.16      | QP       | NEUTRAL |
| 2      | 0.19  | 28.04      | 9.68        | 0.12       | 9.86                 | 47.70        | 54.15      | -6.45      | Average  | NEUTRAL |
| 3      | 0.64  | 14.00      | 9.76        | 0.08       | 9.87                 | 33.71        | 56.00      | -22.29     | QP       | NEUTRAL |
| 4      | 0.64  | 10.29      | 9.76        | 0.08       | 9.87                 | 30.00        | 46.00      | -16.00     | Average  | NEUTRAL |
| 5      | 1.59  | 11.10      | 9.69        | 0.04       | 9.87                 | 30.70        | 56.00      | -25.30     | QP       | NEUTRAL |
| 6      | 1.59  | 5.37       | 9.69        | 0.04       | 9.87                 | 24.97        | 46.00      | -21.03     | Average  | NEUTRAL |
| 7      | 6.12  | 8.22       | 9.69        | 0.07       | 9.89                 | 27.87        | 60.00      | -32.13     | QP       | NEUTRAL |
| 8      | 6.12  | 2.59       | 9.69        | 0.07       | 9.89                 | 22.24        | 50.00      | -27.76     | Average  | NEUTRAL |
| 9      | 8.82  | 12.92      | 9.73        | 0.12       | 9.96                 | 32.73        | 60.00      | -27.27     | QP       | NEUTRAL |
| 10     | 8.82  | 7.36       | 9.73        | 0.12       | 9.96                 | 27.17        | 50.00      | -22.83     | Average  | NEUTRAL |
| 11     | 15.64 | 13.05      | 9.86        | 0.14       | 9.93                 | 32.98        | 60.00      | -27.02     | QP       | NEUTRAL |
| 12     | 15.64 | 7.30       | 9.86        | 0.14       | 9.93                 | 27.23        | 50.00      | -22.77     | Average  | NEUTRAL |

Note:

1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

## 17. Photos of the EUT

Please refer to DDT-Q25030626-1E appendix I

-----End Report-----