

Declaration Letter

FCC ID: 2BC6R-FW

Pursuant to KDB 680106 of the YCHANG TRADING LIMITED Hereby declare our product which is an inductive wireless power transfer applications that meet all of the following requirements are not required to submit a KDB inquiry for devices approved using a PAG for equipment approved using certification to address RF exposure compliance.

The EUT does comply with item 5.2 of KDB 680106 D01v03r01 as follows table:

Requirements of KDB 680106 section 5.2	Yes or No	Description
Wireless power transfer frequency is below 1MHz	Yes	The device operate in the frequency range 110.5kHz-250kHz.
Output power from each primary coil is less than 15 watts	Yes	The maximum output power of the primary coil is 15W.
The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.	Yes	The transfer system includes single coil that is able to detect receiver device.
Client device is placed directly in contact with the transmitter.	Yes	Client device is placed directly in contact with the transmitter.
Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	No	Device can be used in portable and mobile conditions.
The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.	Yes	The EUT H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

Yours sincerely,



Name: Zhong Pei Yong

Title: General Manager