

FCC Test Report

Report No.: AGC02762231004FR01

FCC ID : 2BC6R-FW

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: Magnetic Power Bank

BRAND NAME : LL TRADER

MODEL NAME : FW32, P02B1W, P02W1W, P02P1W, FW33, FW34, FW35,

FW36, FW37, FW38, FW39

APPLICANT: YCHANG TRADING LIMITED

DATE OF ISSUE : Oct. 20, 2023

STANDARD(S) : FCC Part 15 Subpart C

REPORT VERSION: V 1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



Page 2 of 29


Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Oct. 20, 2023	Valid	Initial Release



Table of Contents

1. General Information	4
2. Product Information	5
2.1 Product Technical Description	5
2.2 Test frequency list	5
2.3 Test Methodology	6
2.4 Special Accessories	6
2.5 Equipment Modifications	6
2.6 Antenna Requirement	6
3. Test Environment	7
3.1 Address of The Test Laboratory	7
3.2 Test Facility	7
3.3 Environmental Conditions	8
3.4 measurement uncertainty	8
3.5 List of Equipment Used	g
4.System Test Configuration	10
4.1 EUT Configuration	10
4.2 EUT Exercise	10
4.3 Configuration of Tested System	
4.4 Equipment Used in Tested System	
4.5 Summary of Test Results	11
5. Description of Test Modes	12
6. Field Strength of Fundamental	
6.1 Provisions Applicable	13
6.3 Field Strength Calculation	
6.4 Measurement Setup (Block Diagram of Configuration)	16
6.5 Measurement Results	
7. 20 DB Bandwidth	
7.1 Provisions Applicable	23
7.2 Measurement Procedure	23
7.3 Measurement Setup (Block Diagram of Configuration)	
7.4 Measurement Results	
8. AC Power Line Conducted Emission Test	
8.1 Limits of Line Conducted Emission Test	
8.2 Measurement Setup (Block Diagram of Configuration)	
8.3 Preliminary Procedure of Line Conducted Emission Test	
8.4 Final Procedure of Line Conducted Emission Test	
8.5 Measurement Results	
Appendix I: Photographs of Test Setup	
Annendix II: Photographs of Test FLIT	20





1. General Information

Applicant	YCHANG TRADING LIMITED
Address	RM 202, 2/F CORN YAN CTR 3, JUPITER ST NORTH POINT, HONG KONG, 999077,China
Manufacturer	YCHANG TRADING LIMITED
Address	RM 202, 2/F CORN YAN CTR 3, JUPITER ST NORTH POINT, HONG KONG, 999077, China
Factory	YCHANG TRADING LIMITED
Address	RM 202, 2/F CORN YAN CTR 3, JUPITER ST NORTH POINT, HONG KONG, 999077,China
Product Designation	Magnetic Power Bank
Brand Name	LL TRADER
Test Model	FW32
Series Model(s)	P02B1W, P02W1W, P02P1W, FW33, FW34, FW35, FW36, FW37, FW38, FW39
Difference Description	All the series models are the same as the test model except for the model names.
Date of receipt of test item	Oct. 12, 2023
Date of Test	Oct. 12, 2023 - Oct. 20, 2023
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER -FCC-WPT-V1

The test results of this report relate only to the tested sample identified in this report.

Prepared By

Jack Gui
(Project Engineer)

Calvin Liu
(Reviewer)

Approved By

Max Zhang
(Authorized Officer)

Oct. 20, 2023

Oct. 20, 2023



Page 5 of 29

2. Product Information

2.1 Product Technical Description

Hardware Version	FD-FW32-SW6201-CR5791G-V1.1	
Software Version	V1.0	
Frequency Band	110.5KHz-205KHz	
Operation Frequency	113KHz	
Modulation Type	ASK	
Number of channels	1	
Field Strength of Fundamental	73.35dBuV/m (Max)	
Antenna Designation	Coil Antenna	
Antenna Gain	0dBi	
Power Supply	Input: USB-C:5.0V/3.0A, 9.0A/2.0A Lighting: 5V/2A Output: USB-A:QC22.5W Max(5V/4.5A, 9V/2A) USB-C:PO20W Max(5V/3A, 5V/2.22A,12V/1.67A) Wireless:15W/7.5W/5W	

2.2 TEST FREQUENCY LIST

Frequency Band	Channel Number	Frequency
110.5~205KHz	01	113KHz



Page 6 of 29

2.3 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title		
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations		
2	FCC 47 CFR Part 15	Radio Frequency Devices		
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices		

2.4 Special Accessories

Not available for this EUT intended for grant.

2.5 Equipment Modifications

Not available for this EUT intended for grant.

2.6 Antenna Requirement

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 0dBi.



Page 7 of 29

3. Test Environment

3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories.)

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



Page 8 of 29


3.3 Environmental Conditions

	Normal Conditions
Temperature range (℃)	15 - 35
Relative humidity range	20% - 75%
Pressure range (kPa)	86 - 106

3.4 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 150kHz	$U_c = \pm 4.2 \text{ dB}$
Uncertainty of Radiated Emission below 30MHz	$U_c = \pm 3.8 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Occupied Channel Bandwidth	U _c = ±2 %





3.5 List of Equipment Used

• Ra	Radiated Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2023/02/18	2024/02/17	
\boxtimes	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2023/06/03	2024/06/02	
\boxtimes	AGC-EM-E086	Active Loop Antenna (9K-30Mhz)	ZHINAN	ZN30900C	18051	2022/03/12	2024/03/11	
\boxtimes	AGC-ER-E061	Signal Analyzer	Aglient	N9020A	MY52090123	2023/06/03	2024/06/02	
	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023/05/11	2025/05/10	
	AGC-ER-E005	Wideband Antenna	SCHWARZBECK	VULB9168	VULB9168-494	2023/01/05	2024/04/04	
	AGC-EM-E029	Horn Antenna	ETS	3117	00034609	2023/03/23	2024/03/22	
	AGC-EM-E096	Pre-amplifier	ETS	3117-PA	00246148	2022/08/04	2024/08/03	
	AGC-EM-S003	Test Software	FARA	V.RA-03A	N/A	N/A	N/A	
	AGC-EM-S004	Test Software	Tonscend	4.0.0.0	N/A	N/A	N/A	

• Co	Conducted Emission						
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
\boxtimes	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2023/06/03	2024/06/02
\boxtimes	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2023/06/03	2024/06/02
	AGC-EM-S001	Test Software	R&S	ES-K1 (Ver.V1.71)	N/A	N/A	N/A



Page 10 of 29

4. System Test Configuration

4.1 EUT Configuration


The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise


The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System

Radiated Emission Configure:



Conducted Emission Configure:



4.4 Equipment Used in Tested System

the following peripheral devices and interface cables were connected during the measurement:

☐ Test Accessories Come From The Laboratory

Item	Equipment	Model No.	Identifier	Note
1	wireless charging load N/A N/A		N/A	Accessories
2	Adapter	HW-200440C00	DC: 5V/2A;9V/2A;12V/2A ;15V/3A;20V/3.25A	Accessories
3	Lightning Cable	N/A	0.8m, Unshielded	Accessories

☐ Test Accessories Come From The Manufacturer

Item	Equipment	Model No.	Identifier	Note
1	Magnetic Power Bank	FW32	2BC6R-FW	EUT
2	USB Cable	N/A	0.3m, Unshielded	Accessories



Page 11 of 29

4.5 Summary of Test Results

Item	FCC Rules	Description Of Test	Result
1	§15.203	Antenna Equipment	Pass
2	§15.209(a)(f)	Radiated Spurious Emission	Pass
3	§15.215(c)	20dB Bandwidth	Pass
4	§15.205(a)	Restricted Bands of Operation	Pass
5	§15.207	AC Power Line Conducted Emission	Pass



Page 12 of 29

5. Description of Test Modes

Summary table of Test Cases					
	Equipment type / Modulation				
Test Item	WPT_ASK				
Radiated &Conducted Test Cases	Mode 1: AC/DC Adapter (By USB-C port) + EUT (Battery Status: <1%) +Wireless load (Full load:5W) Mode 2: AC/DC Adapter (By USB-C port) + EUT (Battery Status: <1%) +Wireless load (Half load:2.5W) Mode 3: AC/DC Adapter (By USB-C port) + EUT (Battery Status: <1%) +Wireless load (Null load:0W) Mode 4: AC/DC Adapter (By Lightning port) + EUT (Battery Status: <1%) +Wireless load (Full load:5W) Mode 5: AC/DC Adapter (By Lightning port) + EUT (Battery Status: <1%) +Wireless load (Half load:2.5W) Mode 6: AC/DC Adapter (By Lightning port) + EUT (Battery Status: <1%) +Wireless load (Null load:0W) Mode 7: EUT(Battery Status: 100%) +Wireless load (Full load:15W) Mode 9: EUT(Battery Status: 100%) +Wireless load (Null load:0W)				
AC Conducted Emission	Mode 1: AC/DC Adapter (By USB-C port) + EUT (Battery Status: <1%)				

Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. The maximum wireless load is 5W during EUT charging.



Page 13 of 29

6. Field Strength of Fundamental

6.1 Provisions Applicable

Test Requirement:	FCC Part15 C Secti	FCC Part15 C Section 15.209						
Test Method:	ANSI C63.10:2013	ANSI C63.10:2013						
Test Frequency Range:	9kHz to 1GHz	9kHz to 1GHz						
Test site:	Measurement Dista	Measurement Distance: 3m						
	Frequency	Detector	RBW	VBW	Value			
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak			
Receiver setup:	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak			
ixeceivei selup.	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak			
	Above 1GHz	Peak	1MHz	3MHz	Peak			
	Above 1GHZ	Peak	1MHz	10Hz	Average			

Limits for frequency below 30MHz

Frequency	Limit (uV/m)	Measurement Distance(m)	Remark
0.009-0.490	2400/F(kHz)	300	Quasi-peak Value
0.490-1.705	24000/F(kHz)	30	Quasi-peak Value
1.705-30	30	30	Quasi-peak Value

Limits for frequency Above 30MHz

Frequency	Limit (dBuV/m @3m)	Remark	
30MHz-88MHz	40.00	Quasi-peak Value	
88MHz-216MHz	43.50	Quasi-peak Value	
216MHz-960MHz	46.00	Quasi-peak Value	
960MHz-1GHz	54.00	Quasi-peak Value	
Above 1CH7	54.00	Average Value	
Above 1GHz	74.00	Peak Value	

Remark: (1) Emission level dB μ V = 20 log Emission level μ V/m

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance Is The Distance In Meters Between The Measuring Instrument, Antenna And The Closest Point Of Any Part Of The Device Or System.



Page 14 of 29

6.2 Measurement Procedure

- The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



Report No.: AGC02762231004FR01 Page 15 of 29

6.3 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CF - AG - AV

where $FS = Field Strength in dB\mu V/m$

RA = Receiver Amplitude (including preamplifier) in dBµV

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB/m AG = Amplifier Gain in dB AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

FS = RR + LF where FS = Field Strength in $dB\mu V/m$ RR = RA - AG - AV in $dB\mu V$ LF = CF + AF in dB

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB/m and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB μ V/m.

This value in dBµV/m was converted to its corresponding level in µV/m.

 $RA = 52.0 dB\mu V/m$

AF = 7.4 dB/m $RR = 18.0 \text{ dB}\mu\text{V}$ CF = 1.6 dB LF = 9.0 dB

AG = 29.0 dB

AV = 5.0 dB

FS = RR + LF

 $FS = 18 + 9 = 27 dB\mu V/m$

Level in μ V/m = Common Antilogarithm [(27 dB μ V/m)/20] = 22.4 μ V/m

Magnetic field strength calculation (9 kHz – 30 MHz)

When the limit is in terms of magnetic field, the following equation applies:

 $H[dB(\mu A/m)] = V[dB(\mu V)] + LC[dB] - GPA[dB] + AFH[dB(S/m)]$

Where,

H is the magnetic field strength (to be compared with the limit),

V is the voltage level measured by the receiver or spectrum analyzer,

LC is the cable loss,

GPA is the gain of the preamplifier (if used), and

AFH is the magnetic antenna factor.

If the "electrical" antenna factor is used instead, the above equation becomes:

 $H[dB(\mu A/m)] = V[dB(\mu V)] + LC[dB] - GPA[dB] + AFE[dB(m-1)] - 51.5[dB\Omega]$

where AFE is the "electric" antenna factor, as provided by the antenna calibration laboratory.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd


Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/




6.4 Measurement Setup (Block Diagram of Configuration)

Radiated Emission Test Setup 9KHz-30MHz



Radiated Emission Test Setup 30MHz-1000MHz




The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.205 limits.



6.5 Measurement Results

Electric Field Test in The Frequency Range 9KHz-150KHz

EUT	Magnetic Power Bank	Model Name	FW32				
Temperature	22.5° C	Relative Humidity	54.6%				
Pressure	960hPa	Test Voltage	Normal Voltage				
Test Mode	Mode 1	Antenna	Face				




No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
	MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	0.0106	10.45	28.30	38.75	126.8	-88.14	peak
2	0.0160	9.32	27.89	37.21	123.3	-86.13	peak
3	0.0258	8.96	27.16	36.12	119.2	-83.09	peak
4	0.0432	8.46	25.86	34.32	114.7	-80.44	peak
5	0.0850	9.29	22.74	32.03	108.9	-76.89	peak
6 *	0.1280	51.78	21.57	73.35	105.9	-32.04	peak

Result: Pass




Electric Field Test In The Frequency Range 9KHz-150KHz

EUT	Magnetic Power Bank	Model Name	FW32
Temperature	22.5° C	Relative Humidity	54.6%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Side



No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
	MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	0.0091	15.63	28.41	44.04	128.2	-84.17	peak
2	0.0240	12.43	27.29	39.72	119.8	-80.12	peak
3	0.0313	10.18	26.75	36.93	117.5	-80.62	peak
4	0.0422	8.73	25.94	34.67	114.9	-80.30	peak
5	0.0623	10.11	24.44	34.55	111.6	-77.05	peak
6 *	0.1280	45.23	21.57	66.80	105.9	-38.59	peak


Result: Pass






Electric Field Test In The Frequency Range 150KHz-30MHz

EUT	Magnetic Power Bank	Model Name	FW32
Temperature	22.5° C	Relative Humidity	54.6%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Face



No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
	MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	0.2268	20.20	21.39	41.59	100.4	-58.88	peak
2	0.3596	22.15	21.14	43.29	96.48	-53.19	peak
3	0.6043	20.17	20.97	41.14	71.98	-30.84	peak
4	2.5400	17.72	22.27	39.99	69.54	-29.55	peak
5	4.6469	16.98	22.91	39.89	69.54	-29.65	peak
6 *	20.1625	15.81	25.09	40.90	69.54	-28.64	peak


Result: Pass





Electric Field Test in The Frequency Range 150KHz-30MHz

EUT	Magnetic Power Bank	Model Name	FW32
Temperature	22.5° C	Relative Humidity	54.6%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Side



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		0.1758	19.20	21.48	40.68	102.6	-61.99	peak
2		0.3615	20.44	21.14	41.58	96.43	-54.85	peak
3		0.5979	19.19	20.96	40.15	72.07	-31.92	peak
4	*	1.6363	16.21	21.81	38.02	63.33	-25.31	peak
5		7.9353	17.72	23.82	41.54	69.54	-28.00	peak
6		16.7497	16.02	24.87	40.89	69.54	-28.65	peak

Result: Pass


Notes:

- 1. Negative value in the margin column shows emission below limit.
- 2. All measurements were made with 0.6m loop antenna at 3m distance. All emissions are below the QP limit.
- 3. Corr. Factor= Antenna Factor (dB/m) + Cable Loss (dB)
- 4. Loop antenna is used for the emission under 30MHz.




Radiated Emission Below 1GHz

	radiated Eilieeleli B	0.01.	
EUT	Magnetic Power Bank	Model Name	FW32
Temperature	22.5° C	Relative Humidity	54.6%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		43.3534	7.90	13.67	21.57	40.00	-18.43	peak
2		121.9755	7.08	16.28	23.36	43.50	-20.14	peak
3		191.7450	11.94	13.55	25.49	43.50	-18.01	peak
4		443.2943	6.81	24.98	31.79	46.00	-14.21	peak
5		601.4265	6.54	25.11	31.65	46.00	-14.35	peak
6	*	900.1474	5.02	31.78	36.80	46.00	-9.20	peak


Result: Pass





Radiated Emission Below 1GHz

	Tradiated Elillocion B		
EUT	Magnetic Power Bank	Model Name	FW32
Temperature	22.5° C	Relative Humidity	54.6%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		30.3172	14.93	13.70	28.63	40.00	-11.37	peak
2	*	43.3534	18.70	16.93	35.63	40.00	-4.37	peak
3		46.5030	16.53	16.96	33.49	40.00	-6.51	peak
4		52.0251	12.04	17.02	29.06	40.00	-10.94	peak
5	,	143.8294	14.02	18.20	32.22	43.50	-11.28	peak
6	(962.1622	6.58	30.10	36.68	54.00	-17.32	peak

Result: Pass

Note: 1. Factor=Antenna Factor + Cable loss, Over=Measurement-Limit.

- 2. All test modes had been pre-tested. The mode 1 is the worst case and recorded in the report.
- 3. The "Factor" value can be calculated automatically by software of measurement system.



Page 23 of 29

7. 20 DB Bandwidth

7.1 Provisions Applicable


N/A

7.2 Measurement Procedure

Set the parameters of SPA as below:


- 1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
- 2. Centre frequency = Operation Frequency
- 3. The resolution bandwidth of 300 Hz and the video bandwidth of 1 kHz were used.
- 4. Span: 3kHz, Sweep time: Auto
- 5. Set the EUT to continue transmitting mode. Allow the trace to stabilize. Use the "N dB down" function of SPA to define the bandwidth.
- 6. Measured the spectrum width with power higher than 20dB below carrier.
- 7. Measured the 99% OBW.
- 8. Record the plots and Reported.

7.3 Measurement Setup (Block Diagram of Configuration)



7.4 Measurement Results

	Tes	st Data of Occupied Bandwi	dth and -20dB Bandwid	dth	
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (kHz)	-20dB Bandwidth (kHz)	Limits (MHz)	Pass or Fail
ASK	0.113	0.808	0.970	N/A	Pass





Test Graphs of Occupied Bandwidth-1





8. AC Power Line Conducted Emission Test


8.1 Limits of Line Conducted Emission Test

Francis	Maximum RF Line Voltage					
Frequency	Q.P. (dBμV)	Average (dBμV)				
150kHz~500kHz	66-56	56-46				
500kHz~5MHz	56	46				
5MHz~30MHz	60	50				

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

8.2 Measurement Setup (Block Diagram of Configuration)





Page 26 of 29

8.3 Preliminary Procedure of Line Conducted Emission Test

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 12V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

8.4 Final Procedure of Line Conducted Emission Test

- EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.



8.5 Measurement Results

		AC Powe	r Line Cond	lucted Em	nission Test		
est Mode	Mode 1			LIS	SN Line	Hot S	Side
Lei	vel [dBµV]						
80 -	vei [ubµv] ·						
70			 			, , , , , , , , , , , , , , , , , , , ,	
60		i i i i	i 				
50	A-j-6					<u> </u>	-
40	4\1\1\1\1\1\1\1\1\1\1\1\1\1\1\1\1\1\1\1	15 14 17 15 5 5 5					
30	++-+-+-	######################################					
20	~- <u>~</u> ~\\\M\M	MMMMMMM	/-		A William Saffer A No.	ttyri-highlihitphipo _d os _{old}	Mhfhlpygr
10			-L		1000 1000 1000 1000 1000 1000 1000 100		A Control of the Cont
-10						,,	
10 1	50k 300k 400k	600k 800k		2M 3M	4M 5M 6M	8M 10M	20M 30M
			Fred	uency [Hz]			
	EASUREMENT 023/10/16 17		: "agc_	fin"			
20	Frequency	Level	Transd	Limit	Margin	Detector	Line
	MHz	dΒμV	dB	dΒμV	dB		
	0.170000	50.10	6.1	65	14.9	QP	L1
	0.230000 0.458000	46.10 40.80	6.1 6.1	62 57	16.3 15.9	QP QP	L1 L1
	1.566000	38.30	6.2	56	17.7	QP	L1
	1.678000	37.40	6.2	56	18.6	QP	L1
	2.758000	36.70	6.3	56	19.3	QP	L1
M	EASUREMENT	RESULT	: "agc	fin2"			
	EASUREMENT 023/10/16 17		: "agc_	fin2"			

Result: Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. $Further\ enquiry\ of\ validity\ or\ verification\ of\ the\ test\ report\ should\ be\ addressed\ to\ AGC\ by\ agc 01@agccert.com.$

dB

6.2

39.90 6.1 55 35.20 6.1 52 33.70 6.2 46 32.50 6.2 46 33.20 6.2 46

Level Transd Limit Margin Detector Line

dΒ

15.1 AV

17.2 AV

12.3 AV

13.5 AV

12.8 AV

13.7 AV

L1

L1

L1

L1

L1

L1

dΒμV

46

Frequency

0.170000

0.230000

0.514000

1.082000

1.366000

1.310000


MHz

dΒμV

32.30

Web: http://www.agccert.com/





Result: Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Transd Limit Margin

dΒμV

46

46

46

46

46

46

dΒ

6.2

6.2

6.2

6.2

6.2

6.2

Detector

dΒ

11.1 AV

11.4 AV

13.4 AV

13.4 AV

13.0 AV

13.8 AV

Line

Ν

Ν

Ν

Ν

Ν

Frequency

0.514000

0.630000

0.858000

1.030000

1.202000

1.374000

MHz

Level

dΒμV

34.90

34.60

32.60

32.60

33.00

32.20

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Page 29 of 29

Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC02762231004AP01

Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC02762231004AP02

----End of Report----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.