

FCC TEST REPORT

For

The Wheel Group

Sensor

Test Model: GEN5A

Additional Model No.: GEN2, GEN6

Prepared for

: The Wheel Group

Address

: 1050 Vineyard Ave, Ontario California, 91764 United States

Prepared by

: Guangzhou LCS Compliance Testing Laboratory Ltd.

Address

: No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China

Tel

: (+86) 020-39166689

Fax

: (+86) 020-39166619

Web

: www.LCS-cert.com

Mail

: webmaster@LCS-cert.com

Date of receipt of test sample : August 22, 2025

Number of tested samples : 2

Sample No. : C250822005-1, C250822005-2

Serial number : Prototype

Date of Test : August 22, 2025 ~ August 26, 2025

Date of Report : August 27, 2025

FCC TEST REPORT
FCC CFR 47 PART 15 C(15.231(e))

Report Reference No. : **LCSC04305006EA**

Date of Issue..... : August 27, 2025

Testing Laboratory Name..... : **Guangzhou LCS Compliance Testing Laboratory Ltd.**

Address..... : No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China

Testing Location/ Procedure..... : Full application of Harmonised standards Partial application of Harmonised standards Other standard testing method

Applicant's Name..... : **The Wheel Group**

Address..... : 1050 Vineyard Ave, Ontario California, 91764 United States

Test Specification

Standard..... : FCC Part 15.231(e), ANSI C63.10-2013

Test Report Form No...... : LCSEMC-1.0

TRF Originator..... : Guangzhou LCS Compliance Testing Laboratory Ltd.

Master TRF..... : Dated 2011-03

Guangzhou LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Guangzhou LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Guangzhou LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description..... : **Sensor**

Trade Mark..... : N/A

Test Model..... : GEN5A

Ratings..... : DC 3.0V By CR2050B2 Battery


Result : **PASS**

Compiled by:




Lifeng Le/ Administrator

Supervised by:



Justin Zhu/ Technique principal

Approved by:



Gavin Liang/ Manager

FCC -- TEST REPORT

Test Report No. : LCSC04305006EA	<u>August 27, 2025</u> Date of issue
EUT..... : Sensor	
Test Model..... : GEN5A	
Applicant..... : The Wheel Group	
Address..... : 1050 Vineyard Ave, Ontario California, 91764 United States	
Telephone..... : /	
Fax..... : /	
Manufacturer..... : Shanghai Representative Office of wheel group	
Address..... : Room 1502 Bilding A NO1055 Zhongshan Rd West Shanghai China	
Telephone..... : /	
Fax..... : /	
Factory..... : Shanghai Representative Office of wheel group	
Address..... : Room 1502 Bilding A NO1055 Zhongshan Rd West Shanghai China	
Telephone..... : /	
Fax..... : /	

Test Result	PASS
--------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Report Version	Issue Date	Revision Content	Revised By
000	August 27, 2025	Initial Issue	--

TABLE OF CONTENTS

1. GENERAL INFORMATION	6
1.1. DESCRIPTION OF DEVICE (EUT)	6
1.2. OBJECTIVE	7
1.3. ENVIRONMENTAL CONDITIONS	7
1.4. SUPPORT EQUIPMENT LIST	7
1.5. EXTERNAL I/O PORT	7
1.6. EUT OPERATION	8
1.7. ANTENNA SYSTEM	8
1.8. DESCRIPTION OF TEST FACILITY	8
1.9. STATEMENT OF THE MEASUREMENT UNCERTAINTY	8
2. TEST METHODOLOGY	9
2.1. EUT CONFIGURATION	9
2.2. EUT EXERCISE	9
2.3. GENERAL TEST PROCEDURES	9
2.4. INSTRUMENT CALIBRATION	9
2.5. TEST MODE	9
3. SYSTEM TEST CONFIGURATION	10
3.1. JUSTIFICATION	10
3.2. EUT EXERCISE SOFTWARE	10
3.3. SPECIAL ACCESSORIES	10
3.4. BLOCK DIAGRAM/SCHEMATICS	10
3.5. EQUIPMENT MODIFICATIONS	10
3.6. TEST SETUP	10
4. SUMMARY OF TEST RESULTS	11
5. TEST ITEMS AND RESULTS	12
5.1. TRANSMITTER DEACTIVATION TIME	12
5.2. TRANSMITTER FIELD STRENGTH OF EMISSIONS AND SPURIOUS EMISSION	13
5.3. 20DB BANDWIDTH EMISSIONS	23
5.4. POWER LINE CONDUCTED EMISSIONS	25
5.5. ANTENNA REQUIREMENT	26
6. LIST OF MEASURING EQUIPMENTS	27
7. TEST SETUP PHOTOGRAPHS	28
8. EXTERIOR PHOTOGRAPHS OF THE EUT	28
9. INTERIOR PHOTOGRAPHS OF THE EUT	28

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	: Sensor
Test Model	: GEN5A
Additional Model No.	: GEN2, GEN6
Model Declaration	: PCB board, structure and internal of these model(s) are the same, So no additional models were tested
Hardware version	: /
Software version	: /
Ratings	: DC 3.0V By CR2050B2 Battery
433MHz Operation frequency	: 433.92MHz
Modulation Type	: ASK, FSK
Channel Number	: 1
Antenna Type	: Internal antenna
Antenna Gain	: 0dBi (Max)
315MHz Operation frequency	: 315MHz
Modulation Type	: ASK, FSK
Channel Number	: 1
Antenna Type	: Internal antenna
Antenna Gain	: 0dBi (Max)

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.

1.2. Objective

The primary objective of the manufacturer is compliance with Subpart C of Part 15 of FCC Rules for the radiated and conducted emissions of intentional radiator. Certification of these devices is required as a prerequisite to marketing as defined in Part 2 of the FCC Rules. Certification is a procedure where the manufacturer or a contracted laboratory makes measurements and submits the test data and technical information to the FCC. The FCC issues a grant of equipment authorization upon successful completion of their review of the submitted documents. Once the equipment authorization has been obtained, the label indicating compliance must be attached to all identical units, which are subsequently manufactured. Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product which may result in increased emissions should be checked to ensure compliance has been maintained (i.e., printed circuit board layout changes, different line filter, different power supply, harnessing or I/O cable changes, etc.).

1.3. Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

- Temperature: 15-35°C
- Humidity: 30-60 %
- Atmospheric pressure: 86-106 kPa

1.4. Support Equipment List

Manufacturer	Description	Model	Serial Number	Certificate
---	---	---	---	---

1.5. External I/O Port

I/O Port Description	Quantity	Cable
---	---	---

1.6. EUT Operation

The EUT was placed in a RF test mode for testing of the transmitter and in normal mode of operation for testing the digital circuitry and receiver.

1.7. Antenna System

The directional gains of antenna used for transmitting is 0dBi , and EUT uses an Internal antenna which is permanently attached.

1.8. Description of Test Facility

Site Description

EMC Lab.

: CNAS Registration Number is L11555
 A2LA Certificate Number: 5099.01
 FCC Designation Number is CN1379
 Test Firm Registration Number: 729882

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

1.9. Statement of The Measurement Uncertainty

ISO Guide 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level and were calculated in accordance with NAMAS document NIS 81.

Test Item	Frequency Range	Uncertainty	Note
Radiation Uncertainty	9KHz~30MHz	±3.10dB	(1)
	30MHz~200MHz	±2.96dB	(1)
	200MHz~1000MHz	±3.10dB	(1)
	1GHz~26.5GH	±4.20dB	(1)
Conduction Uncertainty	150kHz~30MHz	±1.63dB	(1)
Power disturbance	30MHz~300MHz	±1.60dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Guangzhou LCS Compliance Testing Laboratory Ltd.

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the normal operating mode. The TX frequency that was fixed which was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.209 and 15.231(e) under the FCC Rules Part 15 Subpart C.

2.3. General Test Procedures

2.3.1 Conducted Emissions(N/A)

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.10 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane and for below 1GHz and 1.5m for above 1GHz. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.10

2.4. Instrument Calibration

All test equipment is regularly checked to ensure that performance is maintained in accordance with the manufacturer's specifications. All antennas are calibrated at regular intervals with respect to tuned half-wave dipoles. An exhibit of this report contains the list of test equipment used and calibration information.

2.5. Test Mode

The EUT has been tested under engineering mode. The field strength of radiation emission was measured in the following position: EUT stand-up position (Y axis), lie-down position (X, Z axis). The worst case of X axis was reported.

A new battery supplied DC 3.0V power to the EUT for testing.

***Note: Using a temporary antenna connector for the EUT when conducted measurements are performed.

3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in a continuous transmits condition.

3.2. EUT Exercise Software

N/A

3.3. Special Accessories

N/A

3.4. Block Diagram/Schematics

Please refer to the related document

3.5. Equipment Modifications

Guangzhou LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6. Test Setup

Please refer to the test setup photo.

4. SUMMARY OF TEST RESULTS

FCC Rules	Description of test	Result
§15.203	Antenna Requirement	Compliant
§15.231 (e) & §15.209	Transmitter Field Strength of Emissions and Spurious Emission	Compliant
§15.231 (c)	20dB Bandwidth Testing	Compliant
§15.231 (e)	Deactivation Testing	Compliant
§15.207	Conducted Emissions	N/A

Note: All test modes were taken into consideration, but we only recorded the worst case in this report.

5. TEST ITEMS AND RESULTS

5.1. Transmitter Deactivation Time

FCC 15.231 (e)

5.1.1. Limit

devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

5.1.2. Test Procedure


Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

5.1.3. Test Results

Test Result: PASS

Temperature	23.8°C	Humidity	52.2%
Test Engineer	Yongzhou Huang	Configurations	TX Mode

mode	Frequency (MHz)	the duration of each transmission (s)	Limit: the duration of each transmission shall not be greater than one second(s)	the silent period (s)	Limit: shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.	Conclusion
ASK	433.92	0.80	1	60.60		
FSK	433.92	0.90	1	60.70		PASS



5.2. Transmitter Field Strength of Emissions and Spurious Emission

5.2.1. Limit

FCC §15.231 (e) & FCC §15.209

In addition to the provisions of § 15.205, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental frequency (MHz)	Field Strength of Fundamental (microvolt/meter)	Field Strength of spurious emissions (microvolt/meter)
40.66-40.70	1000	100
70-130	500	50
130-174	500 to 1500	50 to 150
174-260	1500	150
260-470	1500 to 5000	150 to 500
Above 470	5000	500

[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 260-470 MHz, $\mu\text{V/m}$ at 3 meters = $16.6667(F) - 2833.3333$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]

§15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	608-614	4.5-5.15
10.495-0.505	16.69475-16.68525	960-1240	5.35-5.46
2.1735-2.1905	16.80425-16.80475	1300-1427	7.25-7.75
4.125-4.128	25.525.67	1435-1626.5	8.025-8.5
4.17725-4.17775	37.5-38.25	1645.5-1646.5	9.0-9.2
4.20725-4.20775	73-74.6	1660-1710	9.3-9.5
6.215-6.218	74.8-75.2	1718.8-1722.2	10.6-12.7
6.26775-6.26825	108-121.94	2200-2300	13.25-13.4
6.31175-6.31225	123-138	2310-2390	14.47-14.5
8.291-8.294	149.9-150.05	2483.5-2500	15.35-16.2
8.362-8.366	156.52475-156.52525	2655-2900	17.7-21.4
5			
8.37625-8.38675	156.7-156.9	3260-3267	22.01-23.12
8.41425-8.41475	162.0125167.17	3332-3339	23.6-24.0
12.29-12.293	167.72-173.2	3345.8-3358	31.2-31.8
12.51975-12.52025	240-285	3600-4400	36.43-36.5
12.57675-12.57725	322-335.4		(2)
13.36-13.41	399.9-410		

1. Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

2. Above 38.6

§15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F (KHz)	300
0.490-1.705	24000 (KHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 72 MHz, 76 88 MHz, 174 216 MHz or 470 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

5.2.2. Measuring Instruments and Setting

Please refer to section 6 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average

Spectrum Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

5.2.3. Test Procedures

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.5 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

3) Sequence of testing 1 GHz to 5 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.




Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height is 1.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum found antenna polarisation and turntable position of the premeasurement the software maximizes the peaks by rotating the turntable position (0° to 360°). This measurement is repeated for different EUT-table positions (0° to 150° in 30°-steps). This procedure is repeated for both antenna polarisations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and RMS detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

5.2.4 Block Diagram of Test Setup



5.2.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.2.6. Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$\text{FS (dBuV/m)} = \text{RA (dBuV)} + \text{AF (dB/m)} + \text{CL (dB)} - \text{AG (dB)}$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

5.2.7. Results of Radiated Emissions (9 kHz~30MHz)

Temperature	23.8°C	Humidity	52.2%
Test Engineer	Yongzhou Huang	Configurations	TX Mode

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Over Limit (dBuV)	Remark
-	-	-	-	See Note

Note:


The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = 40 log (specific distance / test distance) (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

5.2.7. Results of Radiated Emissions (30MHz~1GHz)

Temperature	23.8°C	Humidity	52.1%
Test Engineer	Yongzhou Huang	Configurations	TX Mode




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	53.5052	39.38	-16.18	23.20	40.00	-16.80	QP
2	78.4133	49.55	-19.83	29.72	40.00	-10.28	QP
3	84.9993	44.31	-19.78	24.53	40.00	-15.47	QP
4	291.0358	36.57	-15.89	20.68	46.00	-25.32	QP
5	434.0649	74.80	-13.18	61.62	46.00	15.62	peak
6	866.0878	43.69	-8.24	35.45	46.00	-10.55	QP

Fundamental and Harmonics Result				
Frequency (MHz)	Peak Level (dB μ V/m)	Limit(dB μ V/m) (average)	Limit(dB μ V/m) (Peak)	Conclusion
434.0649	61.62	72.87	92.87	PASS
869.1300	35.45	60.8		PASS

Vertical

Fundamental Frequency Point



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	37.0248	39.85	-17.69	22.16	40.00	-17.84	QP
2	70.8315	36.39	-19.50	16.89	40.00	-23.11	QP
3	98.1418	30.61	-18.31	12.30	43.50	-31.20	QP
4	210.0481	27.81	-17.13	10.68	43.50	-32.82	QP
5	434.0649	75.56	-14.44	61.12	46.00	15.12	peak
6	869.1300	44.27	-8.75	35.52	46.00	-10.48	QP

Fundamental and Harmonics Result

Frequency (MHz)	Peak Level (dB μ V/m)	Limit(dB μ V/m) (average)	Limit(dB μ V/m) (Peak)	Conclusion
434.0649	61.12	72.87	92.87	PASS
869.1300	50.52	60.8		PASS

Note:

1. All reading are Quasi-peak values.
2. Measured = Reading + Antenna Factor + Cable Loss
3. The emission that are 20dB below the official limit are not reported
4. * - means fundamental frequency
5. ** - means harmonic frequency
6. Pre-scan all modes and recorded the worst case results in this report ASK mode.

Due to the measure PK emission level less than the AV limit value. No necessary to take down the AV emission level.

5.2.8. Results of Radiated Emissions (Above 1GHz)

Temperature	23.8°C	Humidity	52.2%
Test Engineer	Yongzhou Huang	Configurations	TX Mode

Peak Value:					
Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Over limit (dB)	Polarization	
1300.54	45.54	74.00	-28.46	Horizontal	
1738.20	38.10	74.00	-35.90	Horizontal	
2168.37	41.00	74.00	-33.00	Vertical	
1301.69	45.34	74.00	-28.66	Vertical	

Average Value:						
Frequency (MHz)	Peak Level (dBuV/m)	average factor	Average value (dBuV/m)	Limit Line (dBuV/m)	Over limit (dB)	Polarization
1300.54	45.54	-14.35	31.19	54.00	-22.81	Horizontal
1738.20	38.10	-14.35	23.75	54.00	-30.25	Horizontal
2168.37	41.00	-14.35	26.65	54.00	-27.35	Vertical
1301.69	45.34	-14.35	30.99	54.00	-23.01	Vertical

1. Measuring frequencies from 9k~10th harmonic (ex. 5GHz), No emission found between lowest internal used/generated frequency to 30MHz.
2. Radiated emissions measured in frequency range from 9k~10th harmonic (ex. 5GHz) were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown “---” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Pre-scan all modes and recorded the worst case results in this report ASK mode.

5.3. 20dB Bandwidth Emissions

FCC 15.231 (c)

5.3.1. Limit

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.


5.3.2. Test Procedure


With the EUT's antenna attached, the EUT's 20dB Bandwidth power was received by the test antenna which was connected to the spectrum analyzer with the START and STOP frequencies set to the EUT's operation band.

5.3.3. Test Data

Temperature	23.8°C	Humidity	52.2%
Test Engineer	Yongzhou Huang	Configurations	TX Mode

mode	Center Frequency of operation MHz	Maximum allowed bandwidth kHz	Measured 20dB bandwidth kHz	Result
ASK	433.92	1084.8	28.31	PASS
FSK	433.92	1084.8	106.0	PASS
Maximum allowed bandwidth:		<input checked="" type="checkbox"/> 0.25% of the centre operating frequency <input type="checkbox"/> 0.5% of the centre operating frequency		
RBW:		<input type="checkbox"/> 10kHz <input type="checkbox"/> 100kHz <input checked="" type="checkbox"/> other kHz		
VBW:		<input type="checkbox"/> 30kHz <input type="checkbox"/> 300kHz <input checked="" type="checkbox"/> other kHz		






5.4. Power line conducted emissions

5.4.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

5.4.2 Block Diagram of Test Setup



5.4.3 Test Results

Not applicable.

5.5. Antenna Requirement

FCC 15.203

5.5.1. Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

This EUT uses an integral antenna which is permanently attached.

5.5.2. Result

Compliant.

The antenna used for transmitting is permanently attached and no consideration of replacement. Please see EUT photo for details.

6. LIST OF MEASURING EQUIPMENTS

Item	Equipment	Manufacturer	Model No.	Equipment No.	Cal Date	Due Date
1	Power Meter	Keysight	E4417A	GLCS-E-279	2025-04-10	2026-04-09
2	Power Sensor	Keysight	E9304A	GLCS-E-280	2025-04-10	2026-04-09
3	Power Sensor	Keysight	E9304A	GLCS-E-281	2025-04-10	2026-04-09
4	Test Software	MWRFtest	TS 8310	N/A	N/A	N/A
5	MXA Signal Analyzer	Agilent	N9020A	GLCS-E-346	2025-07-15	2026-07-14
6	DC Power Supply	Manson	HCS-3604	GLCS-E-126	2025-04-10	2026-04-09
7	EMI Test Software	Farad	EZ-EMC(Ver.F A-03A2 RE+)	GLCS-E-012	N/A	N/A
8	Semi Anechoic Chamber#1	Maorui	966	GLCS-E-001	2024-04-21	2027-04-20
9	Positioning Controller	Max-Full	MF-7802	GLCS-E-015	N/A	N/A
10	Active Loop Antenna	TESEQ	HLA 6121	GLCS-E-155	2025-07-27	2026-07-26
11	By-log Antenna	SCHWARZBECK	VULB9163	GLCS-E-352	2025-07-15	2026-07-14
12	Horn Antenna	SCHWARZBECK	BBHA 9120D	GLCS-E-060	2025-07-19	2026-07-18
13	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	GLCS-E-347	2025-07-15	2026-07-14
14	Broadband Preamplifier	SCHWARZBECK	BBV9719	GLCS-E-348	2025-07-15	2026-07-14
15	EMI Test Receiver	R&S	ESR 7	GLCS-E-192	2025-04-10	2026-04-09
16	RS SPECTRUM ANALYZER	R&S	FSP40	GLCS-E-349	2025-07-15	2026-07-14
17	Low-frequency amplifier	Sonoma	310N	GLCS-E-036	2025-04-10	2026-04-09
18	High-frequency amplifier	SKET	LNPA_30M06 G-40	GLCS-E-286	2025-04-11	2026-04-10
19	6dB Attenuator	/	100W/6dB	GLCS-E-350	2025-07-15	2026-07-14
20	3dB Attenuator	/	2N-3dB	GLCS-E-351	2025-07-15	2026-07-14
21	EMI Test Receiver	ROHDE & SCHWARZ	ESR7	GLCS-E-158	2025-04-10	2026-04-09
22	Artificial Mains Network	ROHDE & SCHWARZ	ESH2-Z5	GLCS-E-011	2025-04-10	2026-04-09
23	EMI Test Software	Farad	EZ-EMC(Ver.F A-03A2 RE+)	GLCS-E-017	N/A	N/A
24	Antenna Mast	Maorui	BK-4AT-BS	GLCS-E-249	N/A	N/A
25	Pulse Limiter	SCHWARZBECK	VTSD 9561-F	GLCS-E-052	2025-04-10	2026-04-09

7. TEST SETUP PHOTOGRAPHS

Please refer to separated files for External Photos of the EUT.

8. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

9. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF TEST REPORT-----