

FCC RADIO TEST REPORT

Applicant..... : Shenzhen DXC Technology Co., LTD
Address..... : 301-D6, Wisdom Valley Innovation PLZ, 542 Minzhi Ave, Xinniu Community,
Minzhi St, Longhua Dist, Shenzhen City, Guangdong, China
Manufacturer..... : Shenzhen DXC Technology Co., LTD
Address..... : 301-D6, Wisdom Valley Innovation PLZ, 542 Minzhi Ave, Xinniu Community,
Minzhi St, Longhua Dist, Shenzhen City, Guangdong, China
Factory..... : HUI ZHOU SHUANG HAO ELECTRONICS TECHNOLOGY CO.,LTD
Address..... : 3F, Bldg A3, Yidong Industrial Park, Yuanhui Road, Chenjiang Town, Huicheng
district, Huizhou city, Guangdong Province, China
Product Name..... : REMOTE BULB
Brand Name..... : 
Model No. : B01A, B01B, B01C, B01D, B01E, B01F
(For model difference refer to section 2)
FCC ID..... : 2BC7D-B01A
Measurement Standard..... : 47 CFR FCC Part 15, Subpart C (Section 15.249)
Receipt Date of Samples.... : October 13, 2023
Date of Tested..... : October 13, 2023 to October 26, 2023
Date of Report..... : November 03, 2023

This report shows that above equipment is technically compliant with the requirements of the standards above. All test results in this report apply only to the tested sample(s). Without prior written approval of Dongguan Nore Testing Center Co., Ltd, this report shall not be reproduced except in full.



Prepared by

Rose Hu / Project Engineer


Iori Fan / Authorized Signatory

Table of Contents

1. Summary of Test Result.....	4
2. General Description of EUT	5
3. Test Channels and Modes Detail	7
4. Configuration of EUT	7
5. Modification of EUT	7
6. Description of Support Device.....	7
7. Test Facility and Location	8
8. Applicable Standards and References.....	8
9. Deviations and Abnormalities from Standard Conditions	9
10. Test Conditions	9
11. Measurement Uncertainty	10
12. Sample Calculations	11
13. Test Items and Results	12
13.1 Conducted Emissions Measurement	12
13.2 Radiated Spurious Emissions and Restricted Bands Measurement.....	20
13.3 20dB Bandwidth Measurement.....	31
13.4 Antenna Requirement	33
14. Test Equipment List.....	34

Revision History

[illegible]

1. Summary of Test Result

FCC Rules	Description of Test	Result	Remarks
§15.207 (a)	AC Power Conducted Emission	PASS	---
§15.249(a)/ 15.209	Radiated Emissions	PASS	---
§15.249(d)/ 15.205	Band Edge	PASS	---
§15.215(c)	20dB Bandwidth	PASS	---
§15.203	Antenna Requirement	PASS	---

2. General Description of EUT

Product Information	
Product name:	REMOTE BULB
Main Model Name:	B01A
Additional Model Name:	B01B, B01C, B01D, B01E, B01F
Model Difference:	These models have the same circuit schematic, construction, PCB Layout and critical components. The differences are model number, parameters of current sense resistor (R8, R9) and voltage adjusting resistor (R5), LED type, and power due to trading purpose.
S/N:	2310-4813
Brand Name:	
Hardware version:	Not stated
Software version:	Not stated
Rating:	AC 100-245V, 50/60Hz 12W for model B01A, B01D; 9W for model B01B, B01E; 7W for model B01C, B01F
Typical arrangement:	Table-top
I/O Port:	Refer to user manual
Accessories Information	
Adapter:	N/A
Cable:	N/A
Other:	N/A

Additional Information

Note:	According to these model differences, all tests were performed on model B01A; and for model B01B & B01C we have re-test items Conducted emission and Radiated emission(Below 1GHz) according to the manufacturer requirement.
Remark:	All the information above are provided by the manufacturer. More detailed feature of the EUT please refers to the user manual.

Technical Specification (2.4G Function)


Frequency Range:	2426MHz
Modulation Type:	GFSK
Number of Channel:	1
Antenna Type:	Wire Antenna
Antenna Gain:	2.51 dBi (Declared by manufacturer)

3. Test Channels and Modes Detail

Mode		Channel	Frequency (MHz)	Modulation
1	TX	1	2426	GFSK
2.	Normal Mode	---	---	---

Note: TX mode means that the EUT was programmed to be in continuously transmitting mode.

4. Configuration of EUT



5. Modification of EUT

No modifications are made to the EUT during all test items.

6. Description of Support Device

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Brand	M/N	S/N	Cable Specification	Remarks
---	---	---	---	---	---	---

No.	Test Software	Modulation	Power Setting
--	---	---	---

7. Test Facility and Location

Test Site	:	Dongguan Nore Testing Center Co., Ltd. (Dongguan NTC Co., Ltd.)
Accreditations and Authorizations	:	The Laboratory has been assessed and proved to be in compliance with CNAS/CL01 Listed by CNAS, August 13, 2018 The Certificate Registration Number is L5795. The Certificate is valid until August 13, 2024 The Laboratory has been assessed and proved to be in compliance with ISO17025 Listed by A2LA, November 01, 2017 The Certificate Registration Number is 4429.01 Listed by FCC, November 06, 2017 Test Firm Registration Number: 907417 Listed by Industry Canada, June 08, 2017 The Certificate Registration Number. Is 46405-9743A
Test Site Location	:	Building D, Gaosheng Science and Technology Park, Hongtu Road, Nancheng District, Dongguan City, Guangdong Province, China

8. Applicable Standards and References

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

Test Standards:

47 CFR Part 15, Subpart C, 15.249

ANSI C63.10-2013

References Test Guidance:

N/A

9. Deviations and Abnormalities from Standard Conditions

No additions, deviations and exclusions from the standard.

10. Test Conditions

No.	Test Item	Test Mode	Test Voltage	Tested by	Remarks
1.	AC Power Conducted Emission	2	AC 120V 60Hz AC 240V 50Hz	Sean	See note 1
2.	Radiated Emissions	1-2	AC 120V 60Hz AC 240V 50Hz	Sean	See note 1
3.	Band Edge	1	AC 120V 60Hz AC 240V 50Hz	Sean	See note 1
4.	20dB Bandwidth	1	AC 120V 60Hz AC 240V 50Hz	Sean	See note 1
5.	Antenna Requirement	---	---	---	---

Note:

1. The testing climatic conditions for temperature, humidity, and atmospheric pressure are within: 15~35℃, 30~70%, 86~106kPa
2. Only the worst case was recorded in the report.

11. Measurement Uncertainty

No.	Test Item	Frequency	Uncertainty	Remarks
1.	Conducted Emission	150KHz ~ 30MHz	±2.52 dB	---
2.	Radiated Emission Test	9kHz ~ 30MHz	±5.66 dB	---
		30MHz ~ 1GHz	±5.66 dB	---
		1GHz ~ 18GHz	±5.19 dB	---
		18GHz ~ 40GHz	±5.19 dB	---
3.	RF Conducted Test	10Hz ~ 40GHz	±1.18 dB	---
4.	Occupied Channel Bandwidth	---	±0.72%	---

Note:

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.
2. The measurement uncertainty levels above are estimated and calculated according to CISPR 16-4-2.
3. The conformity assessment statement in this report is based solely on the test results, measurement uncertainty is excluded.

12. Sample Calculations

Conducted Emission						
Freq. (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
0.1740	38.70	20.60	59.30	64.77	-5.47	QP
Where, Freq. = Emission frequency in MHz Reading Level = Spectrum Analyzer/Receiver Reading Corrector Factor = Insertion loss of LISN + Cable Loss + RF Switching Unit attenuation Measurement = Reading + Corrector Factor Limit = Limit stated in standard Margin = Measurement - Limit Detector = Reading for Quasi-Peak / Average / Peak						

Radiated Spurious Emissions and Restricted Bands						
Freq. (MHz)	Reading Level (dBuV)	Correct Factor (dB/m)	Measurement (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector
196.8400	34.03	-7.83	26.20	43.50	-17.30	QP
Where, Freq. = Emission frequency in MHz Reading Level = Spectrum Analyzer/Receiver Reading Corrector Factor = Antenna Factor + Cable Loss - Pre-amplifier Measurement = Reading + Corrector Factor Limit = Limit stated in standard Over = Margin, which calculated by Measurement - Limit Detector = Reading for Quasi-Peak / Average / Peak						

Note: For all conducted test items, the spectrum analyzer offset or transducer is derived from RF cable loss and attenuator factor. The offset or transducer is equal to the RF cable loss plus attenuator factor.

13. Test Items and Results

13.1 Conducted Emissions Measurement


LIMITS

According to the requirements of FCC PART 15.207, the limits are as follows:

Frequency (MHz)	Quasi-peak	Average
0.15 to 0.5	66 to 56	56 to 46
0.5 to 5	56	46
5 to 30	60	50

- Note:
1. If the limits for the average detector are met when using the quasi-peak detector, then the limits for the measurements with the average detector are considered to be met.
 2. The lower limit shall apply at the transition frequencies.
 3. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5MHz.

BLOCK DIAGRAM OF TEST SETUP



TEST PROCEDURES

- a. The EUT was placed on a wooden table 0.8m height from the metal ground plan and 0.4m from the conducting wall of the shielding room and it was kept at 0.8m from any other grounded conducting surface.
- b. All I/O cables and support devices were positioned as per ANSI C63.10.
- c. Connect mains power port of the EUT to a line impedance stabilization network (LISN).
- d. Connect all support devices to the other LISN and AAN, if needed.
- e. Scan the frequency range from 150KHz to 30MHz at both sides of AC line for maximum conducted interference checking and record the test data.

TEST RESULTS

PASS

Please refer to the following pages.

M/N: B01A

Testing Voltage: AC 120V 60Hz

Phase: L1


Detector: QP,AVG

Test Mode: 1

Conducted Emission Measurement

Date: 2023/10/17

Time: 9:40:06




No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV	dBuV	dB		
1 *	0.1740	38.70	20.60	59.30	64.77	-5.47	QP	
2	0.1740	19.30	20.60	39.90	54.77	-14.87	AVG	
3	0.2128	35.99	20.61	56.60	63.10	-6.50	QP	
4	0.2128	11.29	20.61	31.90	53.10	-21.20	AVG	
5	0.2980	29.78	20.62	50.40	60.30	-9.90	QP	
6	0.2980	7.28	20.62	27.90	50.30	-22.40	AVG	
7	0.3740	23.29	20.61	43.90	58.41	-14.51	QP	
8	0.3740	0.59	20.61	21.20	48.41	-27.21	AVG	
9	0.4660	21.29	20.61	41.90	56.58	-14.68	QP	
10	0.4660	3.49	20.61	24.10	46.58	-22.48	AVG	
11	0.5540	18.70	20.60	39.30	56.00	-16.70	QP	
12	0.5540	1.20	20.60	21.80	46.00	-24.20	AVG	

M/N: B01A	Testing Voltage: AC 120V 60Hz
Phase: N	Detector: QP,AVG
Test Mode: 1	

Conducted Emission Measurement

Date: 2023/10/17

Time: 9:46:40



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1 *	0.1860	35.14	20.56	55.70	64.21	-8.51	QP	
2	0.1860	13.24	20.56	33.80	54.21	-20.41	AVG	
3	0.2300	31.43	20.57	52.00	62.45	-10.45	QP	
4	0.2300	12.23	20.57	32.80	52.45	-19.65	AVG	
5	0.2779	27.33	20.57	47.90	60.88	-12.98	QP	
6	0.2779	7.53	20.57	28.10	50.88	-22.78	AVG	
7	0.3260	23.82	20.58	44.40	59.55	-15.15	QP	
8	0.3260	3.32	20.58	23.90	49.55	-25.65	AVG	
9	0.3740	20.32	20.58	40.90	58.41	-17.51	QP	
10	0.3740	1.02	20.58	21.60	48.41	-26.81	AVG	
11	0.4180	18.03	20.57	38.60	57.49	-18.89	QP	
12	0.4180	2.23	20.57	22.80	47.49	-24.69	AVG	

M/N: B01B

Testing Voltage: AC 120V 60Hz

Phase: L1


Detector: QP,AVG

Test Mode: 1

Conducted Emission Measurement

Date: 2023/10/17

Time: 9:47:25




No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1 *	0.1780	39.30	20.60	59.90	64.58	-4.68	QP	
2	0.1780	23.10	20.60	43.70	54.58	-10.88	AVG	
3	0.2220	36.00	20.60	56.60	62.74	-6.14	QP	
4	0.2220	20.80	20.60	41.40	52.74	-11.34	AVG	
5	0.2660	32.19	20.61	52.80	61.24	-8.44	QP	
6	0.2660	14.59	20.61	35.20	51.24	-16.04	AVG	
7	0.3100	28.68	20.62	49.30	59.97	-10.67	QP	
8	0.3100	12.58	20.62	33.20	49.97	-16.77	AVG	
9	0.3580	25.98	20.62	46.60	58.77	-12.17	QP	
10	0.3580	8.48	20.62	29.10	48.77	-19.67	AVG	
11	0.3980	23.19	20.61	43.80	57.90	-14.10	QP	
12	0.3980	6.29	20.61	26.90	47.90	-21.00	AVG	

M/N: B01B	Testing Voltage: AC 120V 60Hz
Phase: N	Detector: QP,AVG
Test Mode: 1	

Conducted Emission Measurement

Date: 2023/10/17

Time: 9:53:30




No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1 *	0.1780	31.94	20.56	52.50	64.58	-12.08	QP	
2	0.1780	14.94	20.56	35.50	54.58	-19.08	AVG	
3	0.2180	29.23	20.57	49.80	62.89	-13.09	QP	
4	0.2180	14.93	20.57	35.50	52.89	-17.39	AVG	
5	0.2660	26.23	20.57	46.80	61.24	-14.44	QP	
6	0.2660	13.23	20.57	33.80	51.24	-17.44	AVG	
7	0.3100	22.92	20.58	43.50	59.97	-16.47	QP	
8	0.3100	8.62	20.58	29.20	49.97	-20.77	AVG	
9	0.3540	20.22	20.58	40.80	58.87	-18.07	QP	
10	0.3540	7.72	20.58	28.30	48.87	-20.57	AVG	
11	0.3980	17.22	20.58	37.80	57.90	-20.10	QP	
12	0.3980	-0.08	20.58	20.50	47.90	-27.40	AVG	

M/N: B01C	Testing Voltage: AC 120V 60Hz
Phase: L1	Detector: QP,AVG
Test Mode: 1	

Conducted Emission Measurement

Date: 2023/10/17

Time: 9:52:55




No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV	dBuV	dB		
1 *	0.1780	34.90	20.60	55.50	64.58	-9.08	QP	
2	0.1780	16.10	20.60	36.70	54.58	-17.88	AVG	
3	0.2220	33.00	20.60	53.60	62.74	-9.14	QP	
4	0.2220	17.90	20.60	38.50	52.74	-14.24	AVG	
5	0.2700	29.39	20.61	50.00	61.12	-11.12	QP	
6	0.2700	16.19	20.61	36.80	51.12	-14.32	AVG	
7	0.3100	26.48	20.62	47.10	59.97	-12.87	QP	
8	0.3100	8.98	20.62	29.60	49.97	-20.37	AVG	
9	0.3620	23.08	20.62	43.70	58.68	-14.98	QP	
10	0.3620	4.98	20.62	25.60	48.68	-23.08	AVG	
11	0.4020	21.49	20.61	42.10	57.81	-15.71	QP	
12	0.4020	7.49	20.61	28.10	47.81	-19.71	AVG	

M/N: B01C	Testing Voltage: AC 120V 60Hz
Phase: N	Detector: QP,AVG
Test Mode: 1	

Conducted Emission Measurement

Date: 2023/10/17

Time: 9:59:39



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV	dBuV	dB		
1 *	0.1860	31.94	20.56	52.50	64.21	-11.71	QP	
2	0.1860	16.54	20.56	37.10	54.21	-17.11	AVG	
3	0.2340	28.33	20.57	48.90	62.31	-13.41	QP	
4	0.2340	11.63	20.57	32.20	52.31	-20.11	AVG	
5	0.2779	25.63	20.57	46.20	60.88	-14.68	QP	
6	0.2779	9.33	20.57	29.90	50.88	-20.98	AVG	
7	0.3260	22.72	20.58	43.30	59.55	-16.25	QP	
8	0.3260	6.62	20.58	27.20	49.55	-22.35	AVG	
9	0.8059	18.33	20.57	38.90	56.00	-17.10	QP	
10	0.8059	5.53	20.57	26.10	46.00	-19.90	AVG	
11	1.3300	16.43	20.57	37.00	56.00	-19.00	QP	
12	1.3300	3.03	20.57	23.60	46.00	-22.40	AVG	

13.2 Radiated Spurious Emissions and Restricted Bands Measurement


LIMITS

Frequency range MHz	Distance Meters	Field Strengths Limit (15.209)	
		$\mu\text{V/m}$	
0.009 ~ 0.490	300	2400/F(kHz)	
0.490 ~ 1.705	30	24000/F(kHz)	
1.705 ~ 30	30	30	
30 ~ 88	3	100	
88 ~ 216	3	150	
216 ~ 960	3	200	
Above 960	3	500	
Frequency range MHz	Distance Meters	Field Strengths Limit (15.249)	
		mV/m (Field strength of fundamental)	$\mu\text{V/m}$ (Field strength of Harmonics)
902 ~ 928	3	50	500
2400 ~ 2483.5	3	50	500
5725 ~ 5875	3	50	500
24000 ~ 2425000	3	250	2500


- Remark: (1) Emission level (dB) μV = 20 log Emission level $\mu\text{V/m}$
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
- (4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.
- (5) §15.249(d) specifies that emissions which fall in the restricted bands, as defined in §15.205 comply with radiated emission limits specified in §15.209.

BLOCK DIAGRAM OF TEST SETUP


For Radiated Emission below 30MHz



For Radiated Emission 30-1000MHz



For Radiated Emission Above 1000MHz.



TEST PROCEDURES

- a. Below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room.
- b. For the radiated emission test above 1GHz:
The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.
- f. A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Frequency Band (MHz)	Detector	Resolution Bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	3 MHz
	Average	1 MHz	10 Hz

TEST RESULTS

PASS

Please refer to the following pages.


M/N: B01A	Testing Voltage: AC 120V 60Hz
Polarization: Horizontal	Detector: QP
Test Mode: 1	Distance: 3m

Radiated Emission Measurement

Date: 2023/10/24

Time: 9:02:12

00.0 dBuV/m



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		196.8400	34.03	-7.83	26.20	43.50	-17.30	QP	
2		209.4500	31.91	-7.61	24.30	43.50	-19.20	QP	
3		348.1600	31.99	-4.19	27.80	46.00	-18.20	QP	
4		830.2500	23.02	4.48	27.50	46.00	-18.50	QP	
5	*	915.6100	23.58	6.22	29.80	46.00	-16.20	QP	
6		953.4400	22.52	6.28	28.80	46.00	-17.20	QP	


Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

M/N: B01A	Testing Voltage: AC 120V 60Hz
Polarization: Vertical	Detector: QP
Test Mode: 1	Distance: 3m

Radiated Emission Measurement

Date: 2023/10/24

Time: 9:09:25



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	31.9400	33.90	-9.60	24.30	40.00	-15.70	QP	
2		180.3500	35.27	-9.37	25.90	43.50	-17.60	QP	
3		812.7900	23.40	4.20	27.60	46.00	-18.40	QP	
4		878.7500	23.77	4.93	28.70	46.00	-17.30	QP	
5		910.7600	23.33	4.97	28.30	46.00	-17.70	QP	
6		953.4400	22.51	5.09	27.60	46.00	-18.40	QP	


Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

M/N: B01B	Testing Voltage: AC 120V 60Hz
Polarization: Horizontal	Detector: QP
Test Mode: 1	Distance: 3m

Radiated Emission Measurement

Date: 2023/10/24

Time: 9:21:58



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		62.0100	32.69	-7.29	25.40	40.00	-14.60	QP	
2		203.6300	36.57	-7.67	28.90	43.50	-14.60	QP	
3		755.5600	24.37	3.13	27.50	46.00	-18.50	QP	
4		802.1200	23.91	3.99	27.90	46.00	-18.10	QP	
5		904.9400	23.50	6.20	29.70	46.00	-16.30	QP	
6	*	949.5600	25.33	6.27	31.60	46.00	-14.40	QP	


Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

M/N: B01B	Testing Voltage: AC 120V 60Hz
Polarization: Vertical	Detector: QP
Test Mode: 1	Distance: 3m

Radiated Emission Measurement

Date: 2023/10/24

Time: 9:15:45



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		31.9400	34.80	-9.60	25.20	40.00	-14.80	QP	
2		53.2800	36.37	-7.47	28.90	40.00	-11.10	QP	
3		162.8900	38.04	-10.74	27.30	43.50	-16.20	QP	
4		175.5000	42.19	-9.79	32.40	43.50	-11.10	QP	
5	*	191.0200	42.36	-9.06	33.30	43.50	-10.20	QP	
6		205.5700	40.37	-8.67	31.70	43.50	-11.80	QP	

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

M/N: B01C

Testing Voltage: AC 120V 60Hz

Polarization: Horizontal

Detector: QP

Test Mode: 1


Distance: 3m

Radiated Emission Measurement

Date: 2023/10/24

Time: 9:36:51

80.0 dBuV/m



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		84.3200	36.68	-10.88	25.80	40.00	-14.20	QP	
2		177.4400	39.35	-9.45	29.90	43.50	-13.60	QP	
3	*	205.5700	43.06	-7.66	35.40	43.50	-8.10	QP	
4		224.0000	37.33	-7.23	30.10	46.00	-15.90	QP	
5		786.6000	26.48	3.72	30.20	46.00	-15.80	QP	
6		950.5300	24.93	6.27	31.20	46.00	-14.80	QP	


Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

M/N: B01C	Testing Voltage: AC 120V 60Hz
Polarization: Vertical	Detector: QP
Test Mode: 1	Distance: 3m

Radiated Emission Measurement

Date: 2023/10/24

Time: 9:27:52



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		51.3400	36.23	-7.13	29.10	40.00	-10.90	QP	
2		73.6500	40.77	-11.27	29.50	40.00	-10.50	QP	
3		84.3200	40.37	-10.97	29.40	40.00	-10.60	QP	
4		95.9600	41.25	-9.05	32.20	43.50	-11.30	QP	
5		175.5000	43.19	-9.79	33.40	43.50	-10.10	QP	
6	*	201.6900	43.32	-8.72	34.60	43.50	-8.90	QP	

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.


Modulation: GFSK				Test Result: PASS			Test frequency range: 1-25GHz			
Freq. (MHz)	Ant. Pol. (H/V)	Reading Level(dBuV)		Factor (dB/m)	Emission Level (dBuV/m)		Limit 3m (dBuV/m)		Margin (dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
Operation Mode: TX Mode)										
2426	V	92.13	56.58	0.20	92.33	56.78	114.00	94.00	-21.67	-37.22
4852	V	56.62	40.09	6.48	63.10	46.57	74.00	54.00	-10.90	-7.43
7278	V	61.97	39.80	10.53	72.50	50.33	74.00	54.00	-1.50	-3.67

2426	H	89.43	54.75	0.20	89.63	54.95	114.00	94.00	-24.37	-39.05
4852	H	58.45	41.05	6.48	64.93	47.53	74.00	54.00	-9.07	-6.47
7278	H	57.01	40.77	10.53	67.54	51.30	74.00	54.00	-6.46	-2.70

Band edge										
2390.000	V	47.47	32.35	0.09	47.56	32.44	74.00	54.00	-26.44	-21.56
2399.990	V	52.11	34.43	0.13	52.24	34.56	74.00	54.00	-21.76	-19.44

2390.000	H	45.84	30.16	0.09	45.93	30.25	74.00	54.00	-28.07	-23.75
2399.990	H	50.60	32.33	0.13	50.73	32.46	74.00	54.00	-23.27	-21.54

Remark: 1. Data of measurement within this frequency range shown “---” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits.
2. Other band edge, the emissions are lower than 20dB below the allowable limit.




13.3 20dB Bandwidth Measurement

LIMITS

There is no limit.

BLOCK DIAGRAM OF TEST SETUP



TEST PROCEDURES

The 20dB bandwidth of the emission was contained within the frequency band designated which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered, FCC Rule 15.215(c):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was chosen so that the display was a result of the hopping channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. Use the spectrum 20dB down delta function to measure the bandwidth.

TEST RESULTS

PASS

Please refer to the following table.

GFSK			
Channel	Frequency (MHz)	20dB Bandwidth (MHz)	Result
1	2426	5.229	PASS



13.4 Antenna Requirement

STANDARD APPLICABLE

According to of FCC part 15C section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

ANTENNA CONNECTED CONSTRUCTION

The antenna is wire antenna that no antenna other than furnished by the responsible party shall be used with the device, and the best case gain of the antenna is 0.58 dBi, Therefore, the antenna is considered to meet the requirement.

14. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCI7	100837	Mar. 13, 2023	1 Year
2.	Antenna	Schwarzbeck	VULB9162	9162-010	Mar. 23, 2022	2 Year
3.	Spectrum Analyzer	Rohde & Schwarz	FSU26	200409/026	Mar. 13, 2023	1 Year
4.	Spectrum Analyzer	Keysight	N9020A	MY54200831	Mar. 13, 2023	1 Year
5.	Spectrum Analyzer	Rohde & Schwarz	FSV40	101094	Mar. 13, 2023	1 Year
6.	Horn Antenna	Schwarzbeck	BBHA9170	9170-172	Mar. 23, 2022	2 Year
7.	Power Sensor	DARE	RPR3006W	15I00041SNO 64	Mar. 13, 2023	1 Year
8.	Horn Antenna	COM-Power	AH-118	071078	Mar. 23, 2022	2 Year
9.	Pre-Amplifier	HP	HP 8449B	3008A00964	Mar. 13, 2023	1 Year
10.	Pre-Amplifier	HP	HP 8447D	1145A00203	Mar. 13, 2023	1 Year
11.	Loop Antenna	Schwarzbeck	FMZB 1513	1513-272	Mar. 23, 2022	2 Year
12.	Test Receiver	Rohde & Schwarz	ESCI	101152	Mar. 13, 2023	1 Year
13.	L.I.S.N	Rohde & Schwarz	ENV 216	101317	Mar. 13, 2023	1 Year
14.	RF Switching Unit	Compliance Direction Systems Inc.	RSU-M2	38311	Mar.13, 2023	1 Year
15.	Temporary antenna connector	TESCOM	SS402	N/A	N/A	N/A
16.	Test Software	EZ	EZ_EMC NTC-3A1.1	N/A	N/A	N/A

Note: For photographs of EUT and measurement, please refer to appendix in separate documents.

---End---