

# Test Report

<b>Applicant</b>	: Shenzhen ZTW Model Science & Technology Co.,Ltd
<b>Address</b>	: 2/F, Block1, GuanFeng Industrial Park, Jiuwei New Village, Xixiang, Baoan, Shenzhen, China, Zip Code: 518126
<b>Product Name</b>	: Bluetooth Module
<b>Brand Mark</b>	: N/A
<b>Model</b>	: BLUENRG1-ESC
<b>FCC ID</b>	: 2BC7H-BLUENRG1
<b>Report Number</b>	: BLA-EMC-202405-A8901
<b>Date of Receipt</b>	: 2024.05.24
<b>Date of Test</b>	: 2024.05.24 to 2024.06.11
<b>Test Standard</b>	: 47 CFR Part 15, Subpart C 15.247
<b>Test Result</b>	: Pass

Compiled by:

Hugh

Review by:

Sweet

Approved by:

Blue Zheng

Issued Date: 2024.06.11

**BlueAsia of Technical Services(Shenzhen) Co.,Ltd.**

Address: Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China



The test report is effective only with both signature and specialized stamp and The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full. The results described in this report do not represent the quality or characteristics of the sampled batch, nor do they represent any similar or identical products that are not explicitly stated.

## Table of Contents

<b>1</b>	<b>General information .....</b>	<b>4</b>
1.1	General information .....	4
1.2	General description of EUT .....	4
<b>2</b>	<b>Test summary .....</b>	<b>5</b>
<b>3</b>	<b>Test Configuration .....</b>	<b>6</b>
3.1	Test mode .....	6
3.2	Operation Frequency each of channel .....	7
3.3	Test channel .....	7
3.4	Configuration diagram of EUT .....	7
3.5	Auxiliary equipment .....	8
3.6	Test environment .....	8
<b>4</b>	<b>Laboratory information .....</b>	<b>9</b>
4.1	Laboratory and accreditations .....	9
4.2	Measurement uncertainty .....	9
<b>5</b>	<b>Test equipment .....</b>	<b>10</b>
<b>6</b>	<b>Test result .....</b>	<b>11</b>
6.1	Antenna requirement .....	11
6.2	Conducted emissions at AC power line (150 kHz-30 MHz) .....	12
6.3	Conducted peak output Power .....	16
6.4	Minimum 6dB bandwidth .....	17
6.5	Power spectrum density .....	18
6.6	Conducted Band Edges Measurement .....	19
6.7	Conducted spurious emissions .....	20
6.8	Radiated spurious emissions .....	21
6.9	Radiated emissions which fall in the restricted bands .....	32
<b>7</b>	<b>Appendix A .....</b>	<b>39</b>
<b>Appendix B: photographs of test setup .....</b>		<b>54</b>
<b>Appendix C: photographs of EUT .....</b>		<b>56</b>

## Revise Record

Version No.	Date	Description
01	2024.06.11	Original

BlueAsia

## 1 General information

### 1.1 General information

Applicant	Shenzhen ZTW Model Science & Technology Co.,Ltd
Address	2/F, Block1, GuanFeng Industrial Park, Jiuwei New Village, Xixiang, Baoan, Shenzhen, China, Zip Code: 518126
Manufacturer	Shenzhen ZTW Model Science & Technology Co.,Ltd
Address	2/F, Block1, GuanFeng Industrial Park, Jiuwei New Village, Xixiang, Baoan, Shenzhen, China, Zip Code: 518126
Factory	Shenzhen ZTW Model Science & Technology Co.,Ltd
Address	2/F, Block1, GuanFeng Industrial Park, Jiuwei New Village, Xixiang, Baoan, Shenzhen, China, Zip Code: 518126

### 1.2 General description of EUT

Product Name	Bluetooth Module
Model No.	BLUENRG1-ESC
Series model	N/A
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Rate data:	1Mbps
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	Chip antenna
Antenna Gain:	-10.5 dBi (Provided by customer)
Power supply or adapter information	DC3.3V
Hardware Version	N/A
Software Version	N/A

*Note: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.*

## 2 Test summary

No.	Test item	Result	Remark
1	Antenna Requirement	Pass	
2	Conducted Emissions at AC Power Line (150kHz-30MHz)	Pass	
3	Conducted Peak Output Power	Pass	
4	Minimum 6dB Bandwidth	Pass	
5	Power Spectrum Density	Pass	
6	Conducted Band Edges Measurement	Pass	
7	Conducted Spurious Emissions	Pass	
8	Radiated Spurious Emissions	Pass	
9	Radiated Emissions which fall in the restricted bands	Pass	

### 3 Test Configuration

#### 3.1 Test mode


Test Mode <sup>Note 1</sup>	Description
TX	Keep the EUT in continuously transmitting with modulation mode.
RX	Keep the EUT in receiving mode
TX Low channel	Keep the EUT in continuously transmitting mode in low channel
TX middle channel	Keep the EUT in continuously transmitting mode in middle channel
TX high channel	Keep the EUT in continuously transmitting mode in high channel

*Note 1: The EUT was configured to measure its highest possible emission and/or immunity level. The test modes were adapted according to the operation manual for use; the EUT was operated in the engineering mode <sup>Note 2</sup> to fix the TX or Rx frequency that was for the purpose of the measurements.*

*Note 2: Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.*

Power level setup in software			
Test Software Name	BlueNRG GUI V4.6.0		
Mode	Channel	Frequency (MHz)	Soft Set
GFSK	CH00	2402	TX level : 7
	CH20	2442	
	CH39	2480	

#### Run Software



### 3.2 Operation Frequency each of channel

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
...	...	...	...	...	...	...	...
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

### 3.3 Test channel

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2442MHz
The Highest channel	2480MHz

### 3.4 Configuration diagram of EUT



### Support equipment

Name	Device type	Brand	Mode	Series No	Remark
(1)	PC	Lenovo	E460C	N/A	N/A
(2)	Fixed frequency board	N/A	N/A	N/A	N/A

Note: See test photographs attached in APPENDIX A for the actual connections between Product and support equipment.

### 3.5 Auxiliary equipment

Device Type	Manufacturer	Model Name	Serial No.	Remark
PC	Lenovo	E460C	N/A	From lab (No.BLA-ZC-BS-2022005)

**Note:**  
"--" mean no any auxiliary device during testing.

### 3.6 Test environment

Environment	Temperature	Voltage
Normal	25°C	DC 3.3V

## 4 Laboratory information

### 4.1 Laboratory and accreditations

The test facility is recognized, certified, or accredited by the following organizations:

Company name:	BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Address:	Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
CNAS accredited No.:	L9788
A2LA Cert. No.:	5071.01
FCC Designation No.:	CN1252
ISED CAB identifier No.:	CN0028
Telephone:	+86-755-28682673
FAX:	+86-755-28682673

### 4.2 Measurement uncertainty

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=1.96$ .

Parameter	Expanded Uncertainty
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±1.5 dB
Power Spectral Density, conducted	±3.0 dB
Unwanted Emissions, conducted	±3.0 dB
Temperature	±3 °C
Supply voltages	±3 %
Time	±5 %

## 5 Test equipment

Equipment No.	Equipment Name	Model No.	Manufacture	S/N	Cal. Date	Next Cal. Date
BLA-EMC-008	Spectrum	FSP40	R&S	100817	2023/08/30	2024/08/29
BLA-EMC-009	EMI Receiver	ESR7	R&S	101199	2023/08/30	2024/08/29
BLA-EMC-012	broad band Antenna	VULB9168	Schwarz beck	00836 P:00227	2022/10/12	2025/10/11
BLA-EMC-013	Horn Antenna	BBHA9120D	Schwarz beck	01892	2022/09/13	2025/09/12
BLA-EMC-014	Amplifier	PA_000318G-45	SKET	PA2018043003	2023/08/30	2024/08/29
BLA-EMC-016	Signal Generator	N5182A	Agilent	MY52420567	2023/11/16	2024/11/15
BLA-EMC-028	Spectrum	N9020A	Agilent	MY53420839	2023/11/16	2024/11/15
BLA-EMC-038	Spectrum	N9020A	Agilent	MY49100060	2023/08/30	2024/08/29
BLA-EMC-042	Power sensor	RPR3006W	DARE	14I00889SN042	2023/09/01	2024/08/31
BLA-EMC-043	Loop antenna	FMZB1519B	SCHNARZBECK	00102	2022/09/14	2025/09/13
BLA-EMC-044	Wideband radio communication tester	CMW500	R&S	132429	2023/08/30	2024/08/29
BLA-EMC-046	Filter bank	2.4G/5G Filter bank	SKET	N/A	2023/07/07	2024/07/06
BLA-EMC-061	Receiver	ESPI7	R&S	101477	2023/07/07	2024/07/06
BLA-EMC-062	Signal Generator	N5181A	Agilent	MY46240904	2023/07/07	2024/07/06
BLA-EMC-064	Signal Generator	N5182B	KEYSIGHT	MY58108892	2023/07/07	2024/07/06
BLA-EMC-065	broadband Antenna	VULB9168	Schwarz beck	01065P	2022/12/12	2025/12/11
BLA-EMC-066	Amplifier	LNPA_30M01G-30	SKET	SK2021060801	2023/07/07	2024/07/06
BLA-EMC-079	Spectrum	N9020A	Agilent	MY54420161	2023/08/30	2024/08/29
BLA-EMC-080	Signal Generator	N5182A	Agilent	MY47420955	2023/08/30	2024/08/29
BLA-EMC-086	Amplifier	LNPA_18G40G-50dB	SKET	SK2022071301	2023/08/14	2024/08/13

## 6 Test result

### 6.1 Antenna requirement

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A

#### 6.1.1 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of a so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

#### EUT antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is -10.5 dBi.

## 6.2 Conducted emissions at AC power line (150 kHz-30 MHz)


<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.2
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX

### 6.2.1 Limit

Frequency of emission(MHz)	Conducted limit(dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

## 6.2.2 Test setup



### Description of test setup connection:

- a) Connect the control PC to the receiver through a USB to GPIB cable;
- b) The receiver is connected to the LISN through a coaxial line;
- c) Connect the power port of LISN to the EUT.

### 6.2.3 Procedure


- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

LISN=Read Level+ Cable Loss+ LISN Factor

### 6.2.4 Test data

[Test mode: TX]; [Line: Line];[Power:AC120V/60Hz]

#### Conducted Emission Measurement



Site	Phase:	<b>L1</b>	Temperature: (C)
Limit: FCC Class B Conduction(QP)	Power:		Humidity: %RH
EUT: Bluetooth Module	Distance:	RBW: 9 KHz	
M/N: BLUENRG1-ESC		VBW: 30 KHz	Sweep Time: 10 ms
Mode: BLE TX			
Note:			

No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Antenna Height	Table Degree	Comment
		dBuV	dB	dBuV	dB	Detector	cm	degree	
1	0.2180	29.63	10.43	40.06	62.89	-22.83	QP		
2	0.2180	20.08	10.43	30.51	52.89	-22.38	AVG		
3	0.2620	24.57	10.75	35.32	61.37	-26.05	QP		
4	0.2620	15.16	10.75	25.91	51.37	-25.46	AVG		
5	1.1580	11.17	9.86	21.03	56.00	-34.97	QP		
6	1.1580	8.49	9.86	18.35	46.00	-27.65	AVG		
7	3.4020	25.72	10.35	36.07	56.00	-19.93	QP		
8	3.4020	16.19	10.35	26.54	46.00	-19.46	AVG		
9	7.3060	22.21	10.16	32.37	60.00	-27.63	QP		
10	7.3060	19.91	10.16	30.07	50.00	-19.93	AVG		
11	14.0100	28.65	10.12	38.77	60.00	-21.23	QP		
12 *	14.0100	25.88	10.12	36.00	50.00	-14.00	AVG		

\*:Maximum data    x:Over limit    !:over margin

(Reference Only)

Receiver: **ESPI\_1**

Spectrum Analyzer: **ESPI**

**Test Result: Pass**

[**Test mode: TX**]; [**Line: Neutral**]; [**Power: AC120V/60Hz**]

**Conducted Emission Measurement**

Project No.: CE

Data #:1

2024/6/11



Site

Phase: **N**

Temperature: (C)

Limit: FCC Class B Conduction(QP)

Power:

Humidity: %RH

EUT: Bluetooth Module

Distance:

RBW: 9 KHz

M/N: BLUENRG1-ESC

VBW: 30 KHz

Sweep Time: 10 ms

Mode: BLE TX

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over		Antenna Height cm	Table Degree degree	Table Degree Comment
							Over dB	Detector			
1	0.1580	43.97	10.15	54.12	65.57	-11.45	QP				
2	0.1580	27.42	10.15	37.57	55.57	-18.00	AVG				
3	0.2900	30.08	9.98	40.06	60.52	-20.46	QP				
4	0.2900	22.17	9.98	32.15	50.52	-18.37	AVG				
5	2.0380	21.06	10.05	31.11	56.00	-24.89	QP				
6	2.0380	17.08	10.05	27.13	46.00	-18.87	AVG				
7	3.5940	24.08	10.24	34.32	56.00	-21.68	QP				
8	3.5940	18.89	10.24	29.13	46.00	-16.87	AVG				
9	7.2180	27.28	10.24	37.52	60.00	-22.48	QP				
10	7.2180	23.91	10.24	34.15	50.00	-15.85	AVG				
11	13.6420	34.96	10.08	45.04	60.00	-14.96	QP				
12 *	13.6420	29.67	10.08	39.75	50.00	-10.25	AVG				

\*:Maximum data x:Over limit !:over margin

(Reference Only)

Receiver: **ESPI\_1**

Spectrum Analyzer:

**ESPI**
**Test Result: Pass**


## 6.3 Conducted peak output Power

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.5
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX

### 6.3.1 Limit

<b>Frequency range(MHz)</b>	<b>Output power of the intentional radiator(watt)</b>
902-928	1 for $\geq 50$ hopping channels
	0.25 for $25 \leq$ hopping channels $< 50$
	1 for digital modulation
2400-2483.5	1 for $\geq 75$ non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

### 6.3.2 Test setup



### 6.3.3 Test data

Pass: Please refer to appendix A for details


## 6.4 Minimum 6dB bandwidth

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 11.8.1
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX

### 6.4.1 Limit

≥500 kHz

### 6.4.2 Test setup



### 6.4.3 Test data

Pass: Please refer to appendix A for details


## 6.5 Power spectrum density

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 11.10.2
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX

### 6.5.1 Limit

≤8dBm in any 3 kHz band during any time interval of continuous transmission

### 6.5.2 Test setup



### 6.5.3 Test data

Pass: Please refer to appendix A for details

## 6.6 Conducted Band Edges Measurement

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX

### 6.6.1 Limit


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20dB.

Attenuation below the general limits specified in §15.209(a) is not required.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 6.6.2 Test setup



### 6.6.3 Test data

Pass: Please refer to appendix A for details

## 6.7 Conducted spurious emissions

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX

### 6.7.1 Limit


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20dB.

Attenuation below the general limits specified in §15.209(a) is not required.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 6.7.2 Test setup



### 6.7.3 Test data

Pass: Please refer to appendix A for details

## 6.8 Radiated spurious emissions

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.4,6.5,6.6
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX


### 6.8.1 Limit

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


*Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.*

### 6.8.2 Test setup


Below 1GHz:



30MHz-1GHz:



Above 1GHz:



### 6.8.3 Procedure

- a) For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c) The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d) The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g) If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h) Test the EUT in the lowest channel, the middle channel, the highest channel.
- i) The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j) Repeat above procedures until all frequencies measured was complete.

*Note 1: Scan from 9 kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown.*

*Note 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.*


*Note 3: The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:*

$$\text{Level (dBuV)} = \text{Reading (dBuV)} + \text{Factor (dB/m)}$$

### 6.8.4 Test data

Below 1GHz


[Test mode: TX]; [Polarity: Horizontal]



\* Maximum data      \*\* Over limit      \*\*\* Lower margin

**Test Result: Pass**

[Test mode: TX]; [Polarity: Vertical]




\*Maximum data    \*\*Over limit    \*\*\*Over margin

Test Result: Pass

Above 1GHz:

[Test mode: TX low channel]; [Polarity: Horizontal]



\*:Maximum data x:Over limit !:over margin

⟨Reference Only

## Test Result: Pass

[Test mode: TX low channel]; [Polarity: Vertical]

## Radiated Emission Measurement

Project No.: RE

Data :#8

2024/6/3



---

## Site

Polarization: *Vertical*

Temperature: (C)

Limit: FCC Part15 (PK)

## Power:

Humidity: %RH

EUT: Bluetooth Module

M/N: BLUENRG1-ESC

Mode: BLE 1M TX 2402

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4804.000	40.12	5.64	45.76	74.00	-28.24	peak	
2		6005.500	41.08	5.61	46.69	74.00	-27.31	peak	
3		7206.000	37.86	9.24	47.10	74.00	-26.90	peak	
4		8849.000	38.69	11.77	50.46	74.00	-23.54	peak	
5		9608.000	35.91	12.31	48.22	74.00	-25.78	peak	
6	*	11340.00	38.61	12.67	51.28	74.00	-22.72	peak	

\*:Maximum data    x:Over limit    l:over margin

⟨Reference Only

Receiver: ESR 1

Spectrum Analyzer: FSP40

## Test Result: Pass

BlueAsia of Technical Services (Shenzhen) Co.,Ltd.

Tel: +86-755-23059481

Email: [marketing@cblueasia.com](mailto:marketing@cblueasia.com) www.cblueasia.com

[Test mode: TX middle channel]; [Polarity: Horizontal]

## Radiated Emission Measurement

Project No.: RE

Data :#4

2024/6/3



---

## Site

Polarization: *Horizontal*

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: Bluetooth Module

M/N: BLUENRG1-ESC

Mode: BLE 1M TX 2442

**Note:**

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
			Level	Factor	ment		dB	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4884.000	43.80	5.75	49.55	74.00	-24.45	peak	
2		5876.250	38.33	8.54	46.87	74.00	-27.13	peak	
3		7326.000	37.02	9.43	46.45	74.00	-27.55	peak	
4		8931.250	38.11	12.19	50.30	74.00	-23.70	peak	
5		9768.000	35.62	12.22	47.84	74.00	-26.16	peak	
6	*	11340.00	37.75	12.67	50.42	74.00	-23.58	peak	

\*:Maximum data    x:Over limit    !:over margin

⟨Reference Only

Receiver: ESR\_1

Spectrum Analyzer: FSP40

## Test Result: Pass

BlueAsia of Technical Services (Shenzhen) Co.,Ltd.

Tel: +86-755-23059481

Email: [marketing@cblueasia.com](mailto:marketing@cblueasia.com) www.cblueasia.com

**[Test mode: TX middle channel]; [Polarity: Vertical]**
**Radiated Emission Measurement**

Project No.: RE

Data #:7

2024/6/3



Site

Polarization: **Vertical**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: Bluetooth Module

M/N: BLUENRG1-ESC

Mode: BLE 1M TX 2442

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4877.500	41.83	5.72	47.55	74.00	-26.45	peak	
2		5653.000	39.36	7.76	47.12	74.00	-26.88	peak	
3		7326.000	36.67	9.43	46.10	74.00	-27.90	peak	
4		8802.000	38.35	11.68	50.03	74.00	-23.97	peak	
5		9768.000	35.54	12.22	47.76	74.00	-26.24	peak	
6	*	10635.00	37.25	12.82	50.07	74.00	-23.93	peak	

\*:Maximum data x:Over limit !:over margin

⟨Reference Only⟩

Receiver: ESR\_1

Spectrum Analyzer: FSP40

**Test Result: Pass**

**[Test mode: TX High channel]; [Polarity: Horizontal]**
**Radiated Emission Measurement**


Site

Polarization: **Horizontal**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: Bluetooth Module

M/N: BLUENRG1-ESC

Mode: BLE 1M TX 2480

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4959.750	42.05	6.60	48.65	74.00	-25.35	peak	
2		6017.250	41.44	5.63	47.07	74.00	-26.93	peak	
3		7440.000	37.69	9.64	47.33	74.00	-26.67	peak	
4		8931.250	37.84	12.19	50.03	74.00	-23.97	peak	
5		9920.000	34.88	12.14	47.02	74.00	-26.98	peak	
6	*	11328.25	37.39	12.67	50.06	74.00	-23.94	peak	

\*:Maximum data    x:Over limit    !:over margin

⟨Reference Only⟩

Receiver: ESR\_1

Spectrum Analyzer: FSP40

**Test Result: Pass**

[Test mode: TX High channel]; [Polarity: Vertical]

## Radiated Emission Measurement

Project No.: RE

Data :#6

2024/6/3



### Site

Polarization: **Vertical**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

## EUT: Bluetooth Module

M/N: BLUENRG1-ESC

Mode: BLE 1M TX 2480

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit			Over			
						MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	4969.750	46.31	6.60	52.91	74.00	-21.09				peak	
2		5876.250	38.36	8.54	46.90	74.00	-27.10				peak	
3		7440.000	37.56	9.64	47.20	74.00	-26.80				peak	
4		8907.750	38.49	12.10	50.59	74.00	-23.41				peak	
5		9920.000	35.72	12.14	47.86	74.00	-26.14				peak	
6		11340.00	38.19	12.67	50.86	74.00	-23.14				peak	

\*:Maximum data    x:Over limit    !:over margin

⟨Reference Only

Receiver: ESR\_1

Spectrum Analyzer: FSP40

## Test Result: Pass

BlueAsia of Technical Services (Shenzhen) Co.,Ltd.

Tel: +86-755-23059481

Email: [marketing@cblueasia.com](mailto:marketing@cblueasia.com) www.cblueasia.com

## 6.9 Radiated emissions which fall in the restricted bands

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.10.5
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX


### 6.9.1 Limit

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


*Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.*

### 6.9.2 Test setup


Below 1GHz:



30MHz-1GHz:



Above 1GHz:



### 6.9.3 Procedure

- a) For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c) The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d) The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g) If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h) Test the EUT in the lowest channel, the middle channel, the highest channel.
- i) The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j) Repeat above procedures until all frequencies measured was complete.


Note 1: Level (dBuV) = Reading (dBuV) + Factor (dB/m)

Note 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

### 6.9.4 Test data

[Test mode: TX low channel]; [Polarity: Horizontal]

#### Radiated Emission Measurement



\*:Maximum data x:Over limit !:over margin  
Receiver: ESR\_1

Spectrum Analyzer: FSP40

(Reference Only)


**Test Result: Pass**

**[Test mode:TX low channel]; [Polarity: Vertical]**
**Radiated Emission Measurement**

Project No.: RE

Data #:9

2024/6/3



Site

Polarization: **Vertical**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: Bluetooth Module

M/N: BLUENRG1-ESC

Mode: BLE 1M TX 2402

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		2310.000	41.64	-2.89	38.75	74.00	-35.25	peak	
2	*	2390.000	41.80	-2.70	39.10	74.00	-34.90	peak	

\*:Maximum data x:Over limit !:over margin

⟨Reference Only⟩

Receiver: ESR\_1

Spectrum Analyzer: FSP40

**Test Result: Pass**
*BlueAsia of Technical Services (Shenzhen) Co.,Ltd.*

Tel: +86-755-23059481

Email: [marketing@cblueasia.com](mailto:marketing@cblueasia.com) [www.cblueasia.com](http://www.cblueasia.com)

**[Test mode: TX High channel]; [Polarity: Horizontal]**
**Radiated Emission Measurement**

Project No.: RE

Data #:2

2024/6/3



Site

Polarization: **Horizontal**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: Bluetooth Module

M/N: BLUENRG1-ESC

Mode: BLE 1M TX 2480

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	2483.500	53.76	-2.91	50.85	74.00	-23.15	peak	
2		2500.000	42.32	-3.00	39.32	74.00	-34.68	peak	

\*:Maximum data x:Over limit !:over margin

⟨Reference Only⟩

Receiver: ESR\_1

Spectrum Analyzer: FSP40

**Test Result: Pass**

[Test mode:TX High channel]; [Polarity: Vertical]

### Radiated Emission Measurement

Project No.: RE

Data :#10

2024/6/3



---

## Site

Polarization: **Vertical**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: Bluetooth Module

M/N: BLUENRG1-ESC

Mode: BLE 1M TX 2480

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over							
							MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	2483.500	46.81	-2.91	43.90	74.00	-30.10	peak						
2		2500.000	41.61	-3.00	38.61	74.00	-35.39	peak						

\*:Maximum data    x:Over limit    !:over margin

⟨Reference Only

Receiver: ESR\_1

Spectrum Analyzer: FSP40

## Test Result: Pass

BlueAsia of Technical Services (Shenzhen) Co.,Ltd.

Tel: +86-755-23059481


Email: [marketing@cblueasia.com](mailto:marketing@cblueasia.com) www.cblueasia.com

## 7 Appendix A


### Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE	2402	Ant1	1.04	30	Pass
NVNT	BLE	2442	Ant1	0.721	30	Pass
NVNT	BLE	2480	Ant1	1.049	30	Pass


Power NVNT BLE 2402MHz Ant1



Power NVNT BLE 2442MHz Ant1



Power NVNT BLE 2480MHz Ant1




**-6dB Bandwidth**


Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE	2402	Ant1	0.658	0.5	Pass
NVNT	BLE	2442	Ant1	0.652	0.5	Pass
NVNT	BLE	2480	Ant1	0.654	0.5	Pass

**-6dB Bandwidth NVNT BLE 2402MHz Ant1**

**-6dB Bandwidth NVNT BLE 2442MHz Ant1**





-6dB Bandwidth NVNT BLE 2480MHz Ant1



**Occupied Channel Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	BLE	2402	Ant1	1.0368
NVNT	BLE	2442	Ant1	1.0427
NVNT	BLE	2480	Ant1	1.0413

**OBW NVNT BLE 2402MHz Ant1**

**OBW NVNT BLE 2442MHz Ant1**




### OBW NVNT BLE 2480MHz Ant1




**Maximum Power Spectral Density Level**

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE	2402	Ant1	-14.919	8	Pass
NVNT	BLE	2442	Ant1	-15.275	8	Pass
NVNT	BLE	2480	Ant1	-14.752	8	Pass

**PSD NVNT BLE 2402MHz Ant1**

**PSD NVNT BLE 2442MHz Ant1**





## PSD NVNT BLE 2480MHz Ant1




**Band Edge**

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE	2402	Ant1	-53.77	-20	Pass
NVNT	BLE	2480	Ant1	-44.94	-20	Pass


**Band Edge NVNT BLE 2402MHz Ant1 Ref**

**Band Edge NVNT BLE 2402MHz Ant1 Emission**



Band Edge NVNT BLE 2480MHz Ant1 Ref



Band Edge NVNT BLE 2480MHz Ant1 Emission




**Conducted RF Spurious Emission**

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE	2402	Ant1	-46.07	-20	Pass
NVNT	BLE	2442	Ant1	-45.05	-20	Pass
NVNT	BLE	2480	Ant1	-45.57	-20	Pass

**Tx. Spurious NVNT BLE 2402MHz Ant1 Ref**

**Tx. Spurious NVNT BLE 2402MHz Ant1 Emission**



Tx. Spurious NVNT BLE 2442MHz Ant1 Ref




Tx. Spurious NVNT BLE 2442MHz Ant1 Emission




Tx. Spurious NVNT BLE 2480MHz Ant1 Ref




Tx. Spurious NVNT BLE 2480MHz Ant1 Emission





## Appendix B: photographs of test setup







Blue Asia

## Appendix C: photographs of EUT





----END OF REPORT----

The test report is effective only with both signature and specialized stamp, the result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.

BlueAsia