

RF EXPOSURE EVALUATION

KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

EUT Specification

FCC ID	2BCAX-HY300MAX
EUT	Smart Projector
Frequency band (Operating)	<input checked="" type="checkbox"/> BT: 2.402GHz ~ 2.480GHz <input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input checked="" type="checkbox"/> RLAN: 5.180GHz ~ 5.240GHz <input checked="" type="checkbox"/> RLAN: 5.260GHz ~ 5.320GHz <input checked="" type="checkbox"/> RLAN: 5.500GHz ~ 5.700GHz <input checked="" type="checkbox"/> RLAN: 5.745GHz ~ 5.825GHz <input type="checkbox"/> Others:
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Antenna gain (Max)	Wi-Fi 2.4G/BT: 3.41dBi Wi-Fi 5.2G: 3.41dBi Wi-Fi 5.3G: 3.8dBi Wi-Fi 5.6G: 4.4dBi Wi-Fi 5.8G: 4.9dBi
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Shenzhen Anbotek Compliance Laboratory Limited



Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm^2

P_{out} = output power to antenna in Mw

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, $1mW/cm^2$. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Max Measurement Result

Operating Mode	Measured Power	Tune up tolerance	Max. Tune up Power	Max. Tune up Power	Antenna Gain	Antenna Gain in linear	Power density at 20cm	Power density Limits
	(dBm)	(dBm)	(dBm)	(mW)	(dBi)	(Numerical value)	(mW/cm ²)	(mW/cm ²)
BDR&EDR	-0.08	-0.08 ±1	0.92	1.2359	3.41	2.1928	0.0005	1
BLE	-1.03	-1.03 ±1	-0.03	0.9931	3.41	2.1928	0.0004	1
WiFi 2.4G	14.45	14.45 ±1	15.45	35.0752	3.41	2.1928	0.0153	1
WiFi 5.2G	14.71	14.71 ±1	15.71	37.2392	3.41	2.1928	0.0163	1
WiFi 5.3G	14.15	14.15 ±1	15.15	32.7341	3.8	2.3988	0.0156	1
WiFi 5.6G	14.43	14.43 ±1	15.43	34.9140	4.46	2.7925	0.0194	1
WiFi 5.8G	14.32	14.32 ±1	15.32	34.0408	4.9	3.0903	0.0209	1

The Maximum simultaneous transmission for BDR&EDR+WiFi 5.8G

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

= $S_{BDR\&EDR} / S_{limit} + S_{WiFi5.8G} / S_{limit}$

= $0.0005/1 + 0.0209/1$

= 0.0214

< 1.0

Result: No Standalone SAR test is required.

