

# FCC Test Report

Report No. : 1812C50391512503

Applicant : GuangDong SINOY Smart Technology CO., LTD

5TH Floor, Building #2, RunFengZhiGu

Address : Industrial Park Changpin Town, Dong Guan City,

Guangdong DongGuan,523000 China

**Product Name : Smart Projector** 

Report Date : 2025-09-03

**Shenzhen Anbotek Compliance Laboratory Limited** 






# **Contents**


1. General Information	6
1.1. Client Information 1.2. Description of Device (EUT) 1.3. Auxiliary Equipment Used During Test 1.4. Operation channel list. 1.5. Description of Test Modes 1.6. Measurement Uncertainty 1.7. Additional Instructions 1.8. Test Summary 1.9. Description of Test Facility 1.10. Disclaimer 1.11. Test Equipment List	6 7 8 10
2. Antenna requirement	14
2.1. Conclusion	14
3. Conducted Emission at AC power line	15
3.1. EUT Operation	
3.2. Test Setup	
4. 6dB Bandwidth	
4.1. EUT Operation	
4.3. Test Data	
5. Maximum Conducted Output Power	20
5.1. EUT Operation	20
5.2. Test Setup	
6. Power Spectral Density	
6.1. EUT Operation	
6.3. Test Data	
7. Emissions in non-restricted frequency bands	22
7.1. EUT Operation	22
7.2. Test Setup	
7.3. Test Data	
8. Band edge emissions (Radiated)	
8.1. EUT Operation	
8.3. Test Data	
9. Emissions in restricted frequency bands (below 1GHz)	
9.1. EUT Operation	
9.2. Test Setup	
9.3 Test Data	31


#### **Shenzhen Anbotek Compliance Laboratory Limited**





10. Emissions in restricted frequency bands (above 1GHz)	33
10.1. EUT Operation	33
10.2. Test Setup	
10.3. Test Data	35
APPENDIX I TEST SETUP PHOTOGRAPH	38
APPENDIX II EXTERNAL PHOTOGRAPH	38
APPENDIX III INTERNAL PHOTOGRAPH	38







# **TEST REPORT**

Applicant : GuangDong SINOY Smart Technology CO., LTD

Manufacturer : GuangDong SINOY Smart Technology CO., LTD

Product Name : Smart Projector

Model No. : HY300Max, Gimbal 3 MAX, M5, W300, X8, BSK01, M6, SMOON 330

Trade Mark : N/A

Date of Receipt:

Rating(s) : Input1: 45Vdc 0.95A Input2: 12Vdc 1.1A

47 CFR Part 15.247

Test Standard(s) : ANSI C63.10-2020

KDB 558074 D01 15.247 Meas Guidance v05r02

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with above listed standard(s) requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

2 d. 0 0 1 1 0 0 0 . p t.		
Date of Test:	2025-08-07 to 2025-08-18	
Prepared By:	Cecilia Chen	
<u> </u>	(Cecilia Chen)	
Approved & Authorized Signer:	Augo Chen	
	(Hugo Chen)	

2025-08-07



# **Revision History**

Report Version	Description	Issued Date
R00	Original Issue.	2025-09-03



## 1. General Information

#### 1.1. Client Information

Applicant	:	GuangDong SINOY Smart Technology CO., LTD
Address	:	5TH Floor, Building #2, RunFengZhiGu Industrial Park Changpin Town,DongGuan City, Guangdong DongGuan,523000 China
Manufacturer	:	GuangDong SINOY Smart Technology CO., LTD
Address	:	5TH Floor, Building #2, RunFengZhiGu Industrial Park Changpin Town,DongGuan City, Guangdong DongGuan,523000 China
Factory	:	GuangDong SINOY Smart Technology CO., LTD
Address	:	Dongguan Changping Run FengZhigu factory building 2, 3rd floor, 5th floor, 501, 3rd floor, 3rd floor, 4th floor, China

## 1.2. Description of Device (EUT)

Product Name	:	Smart Projector
Model No.	:	HY300Max, Gimbal 3 MAX, M5, W300, X8, BSK01, M6, SMOON 330 (Note: All samples are the same except the model number and appearance color, so we prepare "HY300Max" for test only.)
Trade Mark	:	N/A
Test Power Supply	:	AC 120V/60Hz for Adapter
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	Manufacturer: Guangdong Mingxin Power Technologies Co.,Ltd Model: MX60WB-4500950U -1201100U Input: 100-240V~, 50/60Hz, 1.5A Max Output1: 45.0V=0.95A Output2: 12.0V=1.1A
RF Specification	•	
Operation Frequency	:	802.11b/g/n(HT20)/ax(HEW20): 2412MHz to 2462MHz; 802.11n(HT40)/ax(HEW40): 2422MHz to 2452MHz
Number of Channel	:	802.11b/g/n(HT20)/ax(HEW20): 11 Channels; 802.11n(HT40)/ax(HEW40): 7 Channels
Modulation Type	:	802.11b: DSSS(CCK, DQPSK, DBPSK); 802.11g: OFDM(BPSK, QPSK, 16QAM, 64QAM); 802.11n(HT20 and HT40): OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ax(HEW20 and HEW40): OFDMA(BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Antenna Type	:	PCB Antenna
Antenna Gain(Peak)	:	3.41dBi
D		

#### Remark

- (1) All of the RF specification are provided by customer.
- (2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- (3) 802.11ax mode only support full resource unit size.

#### **Shenzhen Anbotek Compliance Laboratory Limited**



# 1.3. Auxiliary Equipment Used During Test

Title	Manufacturer	Model No.	Serial No.
1	1	1	1

## 1.4. Operation channel list

Operation Band:

operation barra.					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447	1	1

## 1.5. Description of Test Modes

Pretest Modes	Descriptions
TM1	Keep the EUT in 802.11b transmitting mode.
TM2	Keep the EUT in 802.11g transmitting mode.
TM3	Keep the EUT in 802.11n(HT20) transmitting mode.
TM4	Keep the EUT in 802.11n(HT40) transmitting mode.
TM5	Keep the EUT in 802.11ax(HEW20) transmitting mode.
TM6	Keep the EUT in 802.11ax(HEW40) transmitting mode.



# 1.6. Measurement Uncertainty

Parameter	Uncertainty	
Conducted emissions (AMN 150kHz~30MHz)	3.2dB	
Occupied Bandwidth	925Hz	
Conducted Output Power	0.76dB	
Power Spectral Density	0.76dB	
Conducted Spurious Emission	1.24dB	
Radiated spurious emissions (above 1GHz)	1G-6GHz: 4.64dB; 6G-18GHz: 4.82dB 18G-40GHz: 5.62dB	
Radiated emissions (Below 30MHz)	3.26dB	
Radiated spurious emissions (30MHz~1GHz)	Horizontal: 3.70dB; Vertical: 4.42dB	
The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032.		

The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



#### 1.7. Additional Instructions

Power level setup in software: Set the frequency through adb command. Operation Band:

Operation Band:			
Mode	Channel(MHz)	Power level	Transmitting type
802.11b	2412	default	data pack TX
802.11b	2437	default	data pack TX
802.11b	2462	default	data pack TX
802.11g	2412	default	data pack TX
802.11g	2437	default	data pack TX
802.11g	2462	default	data pack TX
802.11n(HT20)	2412	default	data pack TX
802.11n(HT20)	2437	default	data pack TX
802.11n(HT20)	2462	default	data pack TX
802.11n(HT40)	2422	default	data pack TX
802.11n(HT40)	2437	default	data pack TX
802.11n(HT40)	2452	default	data pack TX
802.11ax(VHT20)	2412	default	data pack TX
802.11ax(VHT20)	2437	default	data pack TX
802.11ax(VHT20)	2462	default	data pack TX
802.11ax(VHT40)	2422	default	data pack TX
802.11ax(VHT40)	2437	default	data pack TX
802.11ax(VHT40)	2452	default	data pack TX



# 1.8. Test Summary

Test Items	Test Modes	Status
Antenna requirement	1	Р
Conducted Emission at AC power line	Mode1,2,3,4,5,6	Р
6dB Bandwidth	Mode1,2,3,4,5,6	Р
Maximum Conducted Output Power	Mode1,2,3,4,5,6	Р
Power Spectral Density	Mode1,2,3,4,5,6	Р
Emissions in non-restricted frequency bands	Mode1,2,3,4,5,6	Р
Band edge emissions (Radiated)	Mode1,2,3,4,5,6	Р
Emissions in restricted frequency bands (below 1GHz)	Mode1,2,3,4,5,6	Р
Emissions in restricted frequency bands (above 1GHz)	Mode1,2,3,4,5,6	Р
Note: P: Pass		1

N: N/A, not applicable

Page 11 of 38

#### 1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### FCC-Registration No.:279531

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 279531.

#### **Test Location**

Shenzhen Anbotek Compliance Laboratory Limited.

Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.

#### 1.10. Disclaimer

- 1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- 2. The test report is invalid if there is any evidence and/or falsification.
- 3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- 4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
- 5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- 6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.
- 7. The data in this report will be synchronized with the corresponding national market supervision and management departments and cross-border e-commerce platforms as required by regulatory agencies.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.



# 1.11. Test Equipment List

Cond	Conducted Emission at AC power line					
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due Date
1	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	2024-09-09	2025-09-08
2	Software Name EZ-EMC	Farad Technology	ANB-03A	N/A	1	/
3	EMI Test Receiver(CE2#)	Rohde & Schwarz	ESPI3	100926	2024-09-09	2025-09-08
4	Three Phase V- type Artificial Power Network LISN 200A	EMtrace	PWL-50- 3200A	2404	2025-02-21	2026-02-20

6dB Bandwidth

Maximum Conducted Output Power

Power Spectral Density

Emis	Emissions in non-restricted frequency bands					
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due Date
1	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ- KHWS80B	N/A	2024-10-14	2025-10-13
2	DC Power Supply	IVYTECH	IV3605	1804D360 510	2024-09-09	2025-09-08
3	Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102150	2025-04-25	2026-04-24
4	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY505318 23	2024-09-09	2025-09-08
5	Oscilloscope	Tektronix	MDO3012	C020298	2024-10-10	2025-10-09
6	MXG RF Vector Signal Generator	Agilent	N5182A	MY474206 47	2025-01-14	2026-01-13



	Band edge emissions (Radiated) Emissions in frequency bands (above 1GHz)					
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due Date
1	EMI Test Receiver(RE2/3#)	Rohde & Schwarz	ESR26	101481	2025-01-14	2026-01-13
2	EMI Preamplifier	SKET Electronic	LNPA- 0118G-45	SKET-PA- 002	2025-01-13	2026-01-12
3	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	2022-10-16	2025-10-15
4	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	1	1
5	Horn Antenna	A-INFO	LB-180400- KF	J2110606 28	2024-01-22	2027-01-21
6	Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102150	2025-04-25	2026-04-24
7	Amplifier	Talent Microwave	TLLA18G40 G-53-30	23022802	2025-02-24	2026-02-23

Emis	Emissions in frequency bands (below 1GHz)					
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due Date
1	EMI Test Receiver(RE2/3#)	Rohde & Schwarz	ESR26	101481	2025-01-14	2026-01-13
2	Pre-amplifier	SONOMA	310N	186860	2025-01-14	2026-01-13
3	Bilog Broadband Antenna	Schwarzbeck	VULB9163	345	2022-10-23	2025-10-22
4	Loop Antenna (9K-30M)	Schwarzbeck	FMZB1519 B	00053	2024-09-12	2025-09-11
5	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	1	1



Page 14 of 38

# 2. Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be
	considered sufficient to comply with the provisions of this section.

#### 2.1. Conclusion

The antenna is a PCB Antenna which permanently attached, and the best case gain of the antenna is 3.41dBi. It complies with the standard requirement.




# 3. Conducted Emission at AC power line

Test Requirement:	Refer to 47 CFR 15.207(a), Except as shown in paragraphs (b)and (c)of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 µH/50 ohms line impedance stabilization network (LISN).				
	Frequency of emission (MHz) Conducted limit (dBµV)				
		Quasi-peak	Average		
T ( 1 ! ! !	0.15-0.5	66 to 56*	56 to 46*		
Test Limit:	0.5-5	56	46		
	5-30	60	50		
	*Decreases with the logarithm of t	he frequency.			
Test Method:	ANSI C63.10-2020 section 6.2				
Procedure:	Refer to ANSI C63.10-2020 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices				

## 3.1. EUT Operation

Operating Environment:					
Test mode:	1: 802.11b mode: Keep the EUT in 802.11b transmitting mode. 2: 802.11g mode: Keep the EUT in 802.11g transmitting mode. 3: 802.11n(HT20) mode: Keep the EUT in 802.11n(HT20) transmitting mode. 4: 802.11n(HT40) mode: Keep the EUT in 802.11n(HT40) transmitting mode. 5: 802.11ax(HEW20): Keep the EUT in 802.11ax(HEW20) transmitting mode. 6: 802.11ax(HEW40): Keep the EUT in 802.11ax(HEW40) transmitting mode.				


## 3.2. Test Setup






#### 3.3. Test Data

Temperature: 25 °C Humidity: 59 % Atmospheric Pressure: 101 kPa





Temperature:	25 °C	Humidity:	59 %	Atmospheric Pressure:	101 kPa
--------------	-------	-----------	------	-----------------------	---------



#### Note:

- 1. Only record the worst data in the report.
- 2. Result(dB $\mu$ V) = Reading(dB $\mu$ V) + Factor(dB); Over Limit(dB) = Result(dB $\mu$ V) - Limit(dB $\mu$ V)



# 4. 6dB Bandwidth

Test Requirement:	47 CFR 15.247(a)(2)
Test Limit:	Refer to 47 CFR 15.247(a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Test Method:	ANSI C63.10-2020, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	11.8.1 Option 1 The steps for the first option are as follows: a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz. b) Set the VBW ≥ [3 × RBW]. c) Detector = peak. d) Trace mode = max-hold. e) Sweep = No faster than coupled (auto) time. f) Allow the trace to stabilize. g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the "-6 dB down amplitude". If a marker is below this "-6 dB down amplitude" value, then it shall be as close as possible to this value.  11.8.2 Option 2 The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW ≥ 3 × RBW, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.


# 4.1. EUT Operation

Operating Environment:					
Test mode:	1: 802.11b mode: Keep the EUT in 802.11b transmitting mode. 2: 802.11g mode: Keep the EUT in 802.11g transmitting mode. 3: 802.11n(HT20) mode: Keep the EUT in 802.11n(HT20) transmitting mode. 4: 802.11n(HT40) mode: Keep the EUT in 802.11n(HT40) transmitting mode. 5: 802.11ax(HEW20): Keep the EUT in 802.11ax(HEW20) transmitting mode. 6: 802.11ax(HEW40): Keep the EUT in 802.11ax(HEW40) transmitting mode.				





# 4.2. Test Setup



#### 4.3. Test Data

Temperature: 25.9 °C	Humidity:	58 %	Atmospheric Pressure:	101 kPa
----------------------	-----------	------	-----------------------	---------

Please Refer to Appendix for Details.




# 5. Maximum Conducted Output Power

Test Requirement:	47 CFR 15.247(b)(3)
Test Limit:	Refer to 47 CFR 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Test Method:	ANSI C63.10-2020, section 11.9.2 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020, section 11.9.2 Maximum conducted (average) output power

#### 5.1. EUT Operation

Operating Environment:			
Test mode:	1: 802.11b mode: Keep the EUT in 802.11b transmitting mode. 2: 802.11g mode: Keep the EUT in 802.11g transmitting mode. 3: 802.11n(HT20) mode: Keep the EUT in 802.11n(HT20) transmitting mode. 4: 802.11n(HT40) mode: Keep the EUT in 802.11n(HT40) transmitting mode. 5: 802.11ax(HEW20): Keep the EUT in 802.11ax(HEW20) transmitting mode. 6: 802.11ax(HEW40): Keep the EUT in 802.11ax(HEW40) transmitting mode.		

#### 5.2. Test Setup



## 5.3. Test Data

Temperature: 25.9 °C	Humidity: 58 %	Atmospheric Pressure: 101 kPa
----------------------	----------------	-------------------------------

Please Refer to Appendix for Details.

#### **Shenzhen Anbotek Compliance Laboratory Limited**




# 6. Power Spectral Density

Test Requirement:	47 CFR 15.247(e)
Test Limit:	Refer to 47 CFR 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Test Method:	ANSI C63.10-2020, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020, section 11.10, Maximum power spectral density level in the fundamental emission

## 6.1. EUT Operation

Operating Environment:				
Test mode:	1: 802.11b mode: Keep the EUT in 802.11b transmitting mode. 2: 802.11g mode: Keep the EUT in 802.11g transmitting mode. 3: 802.11n(HT20) mode: Keep the EUT in 802.11n(HT20) transmitting mode. 4: 802.11n(HT40) mode: Keep the EUT in 802.11n(HT40) transmitting mode. 5: 802.11ax(HEW20): Keep the EUT in 802.11ax(HEW20) transmitting mode. 6: 802.11ax(HEW40): Keep the EUT in 802.11ax(HEW40) transmitting mode.			

## 6.2. Test Setup



#### 6.3. Test Data

Temperature: 25.9 °C	Humidity:	58 %	Atmospheric Pressure:	101 kPa
----------------------	-----------	------	-----------------------	---------

Please Refer to Appendix for Details.




# 7. Emissions in non-restricted frequency bands

Test Requirement:	47 CFR 15.247(d)
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	ANSI C63.10-2020 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020 Section 11.11.1, Section 11.11.2, Section 11.11.3

## 7.1. EUT Operation

Operating Environment:				
Test mode:  1: 802.11b mode: Keep the EUT in 802.11b transmitting mode. 2: 802.11g mode: Keep the EUT in 802.11g transmitting mode. 3: 802.11n(HT20) mode: Keep the EUT in 802.11n(HT20) transmitting mode. 4: 802.11n(HT40) mode: Keep the EUT in 802.11n(HT40) transmitting mode. 5: 802.11ax(HEW20): Keep the EUT in 802.11ax(HEW20) transmitting mode. 6: 802.11ax(HEW40): Keep the EUT in 802.11ax(HEW40) transmitting mode.				

## 7.2. Test Setup



#### 7.3. Test Data

Temperature:	25.9 °C	Humidity:	58 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

Please Refer to Appendix for Details.

#### **Shenzhen Anbotek Compliance Laboratory Limited**



# 8. Band edge emissions (Radiated)


Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`				
	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)		
	0.009-0.490	2400/F(kHz)	300		
	0.490-1.705	24000/F(kHz)	30		
	1.705-30.0	30	30		
	30-88	100 **	3		
	88-216	150 **	3		
	216-960	200 **	3		
	Above 960	500	3		
Test Limit:	** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.				
Test Method:	ANSI C63.10-2020 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02				
Procedure:	ANSI C63.10-2020 section 6.10.5.2				

## 8.1. EUT Operation

Operating Environment:			
Test mode:	1: 802.11b mode: Keep the EUT in 802.11b transmitting mode. 2: 802.11g mode: Keep the EUT in 802.11g transmitting mode. 3: 802.11n(HT20) mode: Keep the EUT in 802.11n(HT20) transmitting mode. 4: 802.11n(HT40) mode: Keep the EUT in 802.11n(HT40) transmitting mode. 5: 802.11ax(HEW20): Keep the EUT in 802.11ax(HEW20) transmitting mode. 6: 802.11ax(HEW40): Keep the EUT in 802.11ax(HEW40) transmitting mode.		



# 8.2. Test Setup





#### 8.3. Test Data

TM1 / CH: L						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	38.11	9.73	47.84	74.00	-26.16	Horizontal
2390.00	37.96	9.7	47.66	74.00	-26.34	Horizontal
2310.00	39.54	9.73	49.27	74.00	-24.73	Vertical
2390.00	36.54	9.7	46.24	74.00	-27.76	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	29.61	9.58	39.19	54.00	-14.81	Horizontal
2390.00	36.88	9.73	46.61	54.00	-7.39	Horizontal
2310.00	30.62	9.58	40.20	54.00	-13.80	Vertical
2390.00	39.25	9.73	48.98	54.00	-5.02	Vertical

			TM1 / CH: H			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	40.88	9.91	50.79	74.00	-23.21	Horizontal
2500.00	42.98	9.91	52.89	74.00	-21.11	Horizontal
2483.50	40.68	9.91	50.59	74.00	-23.41	Vertical
2500.00	39.33	9.91	49.24	74.00	-24.76	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	38.13	9.91	48.04	54.00	-5.96	Horizontal
2500.00	30.12	9.94	40.06	54.00	-13.94	Horizontal
2483.50	39.93	9.91	49.84	54.00	-4.16	Vertical
2500.00	30.34	9.94	40.28	54.00	-13.72	Vertical

Remark: 1. Result=Reading + Factor



			TM2 / CH: L			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	37.55	9.58	47.13	74.00	-26.87	Horizontal
2390.00	41.50	9.73	51.23	74.00	-22.77	Horizontal
2310.00	40.17	9.58	49.75	74.00	-24.25	Vertical
2390.00	44.09	9.73	53.82	74.00	-20.18	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	30.38	9.58	39.96	54.00	-14.04	Horizontal
2390.00	37.13	9.73	46.86	54.00	-7.14	Horizontal
2310.00	31.02	9.58	40.60	54.00	-13.40	Vertical
2390.00	36.50	9.73	46.23	54.00	-7.77	Vertical

			TM2 / CH: H			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	46.74	9.91	56.65	74.00	-17.35	Horizontal
2500.00	41.15	9.94	51.09	74.00	-22.91	Horizontal
2483.50	46.89	9.91	56.80	74.00	-17.20	Vertical
2500.00	40.73	9.94	50.67	74.00	-23.33	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	36.30	9.91	46.21	54.00	-7.79	Horizontal
2500.00	29.22	9.94	39.16	54.00	-14.84	Horizontal
2483.50	38.88	9.91	48.79	54.00	-5.21	Vertical
2500.00	29.87	9.94	39.81	54.00	-14.19	Vertical

Remark: 1. Result=Reading + Factor



			TM3 / CH: L			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	35.55	9.58	45.13	74.00	-28.87	Horizontal
2390.00	39.50	9.73	49.23	74.00	-24.77	Horizontal
2310.00	39.17	9.58	48.75	74.00	-25.25	Vertical
2390.00	42.09	9.73	51.82	74.00	-22.18	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	29.06	9.58	38.64	54.00	-15.36	Horizontal
2390.00	34.51	9.73	44.24	54.00	-9.76	Horizontal
2310.00	28.63	9.58	38.21	54.00	-15.79	Vertical
2390.00	34.50	9.73	44.23	54.00	-9.77	Vertical

	TM3 / CH: H					
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	44.47	9.91	54.38	74.00	-19.62	Horizontal
2500.00	39.06	9.94	49.00	74.00	-25.00	Horizontal
2483.50	46.06	9.91	55.97	74.00	-18.03	Vertical
2500.00	40.77	9.94	50.71	74.00	-23.29	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	34.28	9.91	44.19	54.00	-9.81	Horizontal
2500.00	29.37	9.94	39.31	54.00	-14.69	Horizontal
2483.50	35.70	9.91	45.61	54.00	-8.39	Vertical
2500.00	30.01	9.94	39.95	54.00	-14.05	Vertical

Remark: 1. Result=Reading + Factor



			TM4 / CH: L			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	38.02	9.58	47.60	74.00	-26.40	Horizontal
2390.00	42.50	9.73	52.23	74.00	-21.77	Horizontal
2310.00	41.17	9.58	50.75	74.00	-23.25	Vertical
2390.00	44.30	9.73	54.03	74.00	-19.97	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	29.98	9.58	39.56	54.00	-14.44	Horizontal
2390.00	35.19	9.73	44.92	54.00	-9.08	Horizontal
2310.00	29.83	9.58	39.41	54.00	-14.59	Vertical
2390.00	33.90	9.73	43.63	54.00	-10.37	Vertical

	TM4 / CH: H					
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	44.38	9.91	54.29	74.00	-19.71	Horizontal
2500.00	39.74	9.94	49.68	74.00	-24.32	Horizontal
2483.50	46.19	9.91	56.10	74.00	-17.90	Vertical
2500.00	41.27	9.94	51.21	74.00	-22.79	Vertical
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	33.98	9.91	43.89	54.00	-10.11	Horizontal
2500.00	31.37	9.94	41.31	54.00	-12.69	Horizontal
2483.50	35.70	9.91	45.61	54.00	-8.39	Vertical
2500.00	31.01	9.94	40.95	54.00	-13.05	Vertical

Remark: 1. Result=Reading + Factor



# 9. Emissions in restricted frequency bands (below 1GHz)


Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).			
	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	
	0.009-0.490	2400/F(kHz)	300	
	0.490-1.705	24000/F(kHz)	30	
	1.705-30.0	30	30	
	30-88	100 **	3	
	88-216	150 **	3	
	216-960	200 **	3	
	Above 960	500	3	
Test Limit:	** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020 sec KDB 558074 D01 15.24	tion 6.6.4 17 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2020 sec	tion 6.6.4		

## 9.1. EUT Operation

Operating Environment:					
Test mode:	1: 802.11b mode: Keep the EUT in 802.11b transmitting mode. 2: 802.11g mode: Keep the EUT in 802.11g transmitting mode. 3: 802.11n(HT20) mode: Keep the EUT in 802.11n(HT20) transmitting mode. 4: 802.11n(HT40) mode: Keep the EUT in 802.11n(HT40) transmitting mode. 5: 802.11ax(HEW20): Keep the EUT in 802.11ax(HEW20) transmitting mode. 6: 802.11ax(HEW40): Keep the EUT in 802.11ax(HEW40) transmitting mode.				



# 9.2. Test Setup






#### 9.3. Test Data

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.


Temperature: 22.5 °C Humidity: 55 % Atmospheric Pressure: 101 kPa







ıre: 22.5 °C Humidity: 55 %	Atmospheric Pressure:	101 kPa
-----------------------------	-----------------------	---------



#### Note:

- 1. Only record the worst data in the report.
- 2. Result(dBμV/m) = Reading(dBμV) + Factor(dB/m); Over Limit(dB) = Result(dBμV/m) - Limit(dBμV/m)



# 10. Emissions in restricted frequency bands (above 1GHz)


Test Requirement:	restricted bands, as define	, in addition, radiated emissions d in § 15.205(a), must also comp ecified in § 15.209(a)(see § 15.2	oly with the	
	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	
	0.009-0.490	2400/F(kHz)	300	
	0.490-1.705	24000/F(kHz)	30	
	1.705-30.0	30	30	
	30-88	100 **	3	
	88-216	150 **	3	
	216-960	200 **	3	
	Above 960	500	3	
** Except as provided in paragraph (g), fundamental emissions frintentional radiators operating under this section shall not be local frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-8 However, operation within these frequency bands is permitted unsections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band of the emission limits shown in the above table are based on measuremploying a CISPR quasi-peak detector except for the frequency 90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission I these three bands are based on measurements employing an avidetector.				
Test Method:	ANSI C63.10-2020 section KDB 558074 D01 15.247 M			
Procedure:	ANSI C63.10-2020 section	6.6.4		

# 10.1. EUT Operation

Operating Envi	ronment:
Test mode:	1: 802.11b mode: Keep the EUT in 802.11b transmitting mode. 2: 802.11g mode: Keep the EUT in 802.11g transmitting mode. 3: 802.11n(HT20) mode: Keep the EUT in 802.11n(HT20) transmitting mode. 4: 802.11n(HT40) mode: Keep the EUT in 802.11n(HT40) transmitting mode. 5: 802.11ax(HEW20): Keep the EUT in 802.11ax(HEW20) transmitting mode. 6: 802.11ax(HEW40): Keep the EUT in 802.11ax(HEW40) transmitting mode.



# 10.2. Test Setup





#### 10.3. Test Data

Temperature:	25.9 °C	Humidity:	58 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

TM1 / CH: L								
Peak value:								
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization		
4824.00	28.53	15.31	43.84	74.00	-30.16	Vertical		
7236.00	30.03	18.06	48.09	74.00	-25.91	Vertical		
9648.00	30.02	23.77	53.79	74.00	-20.21	Vertical		
12060.00	*			74.00		Vertical		
14472.00	*			74.00		Vertical		
4824.00	27.95	15.31	43.26	74.00	-30.74	Horizontal		
7236.00	30.33	18.06	48.39	74.00	-25.61	Horizontal		
9648.00	28.23	23.77	52.00	74.00	-22.00	Horizontal		
12060.00	*			74.00		Horizontal		
14472.00	*			74.00		Horizontal		
Average value:	Average value:							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization		
4824.00	20.55	15.31	35.86	54.00	-18.14	Vertical		
7236.00	21.81	18.06	39.87	54.00	-14.13	Vertical		
9648.00	21.92	23.77	45.69	54.00	-8.31	Vertical		
12060.00	*			54.00		Vertical		
14472.00	*			54.00		Vertical		
4824.00	20.46	15.31	35.77	54.00	-18.23	Horizontal		
7236.00	22.90	18.06	40.96	54.00	-13.04	Horizontal		
9648.00	19.97	23.77	43.74	54.00	-10.26	Horizontal		
12060.00	*			54.00		Horizontal		
14472.00	*			54.00		Horizontal		

#### **Shenzhen Anbotek Compliance Laboratory Limited**




TM1 / CH: M Peak value:							
4874.00	28.48	15.41	43.89	74.00	-30.11	Vertical	
7311.00	28.38	18.01	46.39	74.00	-27.61	Vertical	
9748.00	29.96	23.79	53.75	74.00	-20.25	Vertical	
12185.00	*			74.00		Vertical	
14622.00	*			74.00		Vertical	
4874.00	27.75	15.41	43.16	74.00	-30.84	Horizontal	
7311.00	29.25	18.01	47.26	74.00	-26.74	Horizontal	
9748.00	28.53	23.79	52.32	74.00	-21.68	Horizontal	
12185.00	*			74.00		Horizontal	
14622.00	*			74.00		Horizontal	
Average value:							
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization	
4874.00	19.30	15.41	34.71	54.00	-19.29	Vertical	
7311.00	19.28	18.01	37.29	54.00	-16.71	Vertical	
9748.00	20.21	23.79	44.00	54.00	-10.00	Vertical	
12185.00	*			54.00		Vertical	
14622.00	*			54.00		Vertical	
4874.00	18.85	15.41	34.26	54.00	-19.74	Horizontal	
7311.00	19.33	18.01	37.34	54.00	-16.66	Horizontal	
9748.00	19.24	23.79	43.03	54.00	-10.97	Horizontal	
12185.00	*			54.00		Horizontal	
14622.00	*			54.00		Horizontal	



			TM1 / CH: H			
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4924.00	28.34	15.51	43.85	74.00	-30.15	Vertical
7386.00	28.32	17.97	46.29	74.00	-27.71	Vertical
9848.00	29.40	23.82	53.22	74.00	-20.78	Vertical
12310.00	*			74.00		Vertical
14772.00	*			74.00		Vertical
4924.00	28.41	15.51	43.92	74.00	-30.08	Horizontal
7386.00	29.60	17.97	47.57	74.00	-26.43	Horizontal
9848.00	29.03	23.82	52.85	74.00	-21.15	Horizontal
12310.00	*			74.00		Horizontal
14772.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4924.00	19.13	15.51	34.64	54.00	-19.36	Vertical
7386.00	18.72	17.97	36.69	54.00	-17.31	Vertical
9848.00	20.65	23.82	44.47	54.00	-9.53	Vertical
12310.00	*			54.00		Vertical
14772.00	*			54.00		Vertical
4924.00	18.66	15.51	34.17	54.00	-19.83	Horizontal
7386.00	19.71	17.97	37.68	54.00	-16.32	Horizontal
9848.00	19.47	23.82	43.29	54.00	-10.71	Horizontal
12310.00	*			54.00		Horizontal
14772.00	*			54.00		Horizontal

#### Remark:

- 1. Result =Reading + Factor
- 2. Test frequency are from 1GHz to 25GHz, "\*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.
- 3. Only the worst case is recorded in the report.





#### APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph\_RF

#### APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

## **APPENDIX III -- INTERNAL PHOTOGRAPH**

Please refer to separated files Appendix III -- Internal Photograph

