

# RF EXPOSURE REPORT

FCC ID: 2BCFYHT-6766BE

Product(s) Name......: Wireless Home Gateway

Model(s)..... HT-6766BE, HT-6766BDM

Trade Mark..... HEIGHTS

Applicant..... Heights Telecom T LTD

Address...... Ha-Sakhlav 6, Irus, 7680900, Israel

Receipt Date..... 2025.06.24

Test Date...... 2025.06.24~2025.07.29

Issued Date...... 2025.09.12

Standards...... FCC Guidelines for Human Exposure IEEE C95.1

FCC Title 47 Part 2.1091

KDB 447498 D01 General RF Exposure Guidance v06

Testing Laboratory.....: Shenzhen Haiyun Standard Technical Co., Ltd.

Prepared By:	Checked By:	Approved By:	Standard
Albert Fan	Black Ding	Tim Zhang	THE COMMENT
Albert Fan	Black Ding	7in.zhanj	HAIYUN Report Sea



# History of this test report

Original Report Issue Date: 2025.09.12

- No additional attachment
- O Additional attachments were issued following record

Attachment No.	Issue Date	Description



#### 1.. MPE CALCULATION METHOD

#### **Radio Frequency Exposure Limit**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)
300-1,500			f/1500
1,500-100,000			1.0

#### **Calculation Method of RF Safety Distance:**

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

#### **Table for Filed Antenna**

#### For BLE:

Antenna	Antenna gain	Antenna Type
Ant1	3.67dBi	PCB Antenna
Ant2	3.81dBi	PCB Antenna

### For 2.4GHz\_WiFi:

Antenna	Antenna gain	Antenna Type
Ant1	3.67dBi	PCB Antenna
Ant2	3.72dBi	PCB Antenna

#### For 5GHz WiFi:

Antenna	Antenna gain	Antenna Type
Ant1	4.42dBi	PCB Antenna
Ant2	4.48dBi	PCB Antenna
Ant3	4.43dBi	PCB Antenna
Ant4	4.19dBi	PCB Antenna



#### 2.. TEST RESULTS

Worst case as below

Operating Mode	Freq.	Maximum conducted output power	Directional Antenna Gain		I maximum RP	MPE Limit	MPE Value
	(MHz)	(dBm)	(dBi)	(dBm)	(mW)	(m\	N/cm <sup>2</sup> )
2.4G Wifi Ant1	2412-2462	26.16	3.67	29.83	961.612	1	0.122
2.4G Wifi Ant2	2412-2462	26.45	3.72	30.17	1039.920	1	0.132
5G Wifi Ant1	5180-5825	23.44	4.42	27.86	610.942	1	0.078
5G Wifi Ant2	5180-5825	24.54	4.48	29.02	797.995	1	0.102
5G Wifi Ant3	5180-5825	23.40	4.43	27.83	606.736	1	0.077
5G Wifi Ant4	5180-5825	23.30	4.19	27.49	561.048	1	0.071
BLE Ant1	2402-2480	9.36	3.67	13.03	20.091	1	0.003
BLE Ant2	2402-2480	9.37	3.81	13.18	20.797	1	0.003

Note: 1. The calculated distance is 25 cm.

The ratio= MPE $_{2.4G}$  Wifi Ant//limit+MPE $_{2.4G}$  Wifi Ant//limit+MPE $_{5G}$  Wifi Ant//limit+MPE $_$ 

As the sum of MPE ratios for all simultaneous transmitting antennas is  $\leq$  1.0, simultaneous transmission MPE test exclusion will be applied.

Result: Complies

<sup>2.</sup> The Wifi function can transmit at the same time with the BLE function



### **Statement**

- 1. The report is invalid without the official seal or special seal of Shenzhen Haiyun Standard Technical Co., Ltd. (hereinafter referred to as the unit).
- 2. The report is invalid without the signature of the approver.
- 3. The report is invalid if altered arbitrarily.
- 4. The report shall not be partially copied without the written approval of the unit.
- 5. The reported test results are only valid for the tested samples.
- 6. If there is any objection to the test report, it shall be submitted to the test unit within 15 days from the date of receiving the report, and the overdue shall not be accepted.

## Shenzhen Haiyun Standard Technical Co., Ltd.

Address: Room 110, 111, 112, 113, 115, 116, Block B, Jinyuan Business Building, No. 302, Xixiang Avenue, Labor Community, Xixiang Street, Baoan District, Shenzhen, China

Tel: 0755-26024411

Email: service@hy-lab.cn

(END OF REPORT)