

1		2		3		4		5		6																																																																																																														
								Remark	Description		Editor	Date																																																																																																												
A												A																																																																																																												
B												B																																																																																																												
C	0 -0.2 26.72 mm 0 -0.2 94.96 mm HEIGHTS Model Name: HT-880BEI FCC ID: 2BCFYHT-880BEI Manufacturer: HEIGHTS TELECOM T LTD Manufacturing Year: 202X S/N: HTBIYMMXXXXX  Web GUI IP: XXX.XXX.XXX.XXX Web GUI Password: XXXXXX WiFi Name: XXXXXXXX WiFi Password: XXXXXXXX  FC Made in Vietnam 12V 4A  Serial Number(S/N)编码规则： HTBIYMMXXXXX HTBI: permanent Y: last data of production year, eg, year 2023 here select 3 MM: produciton month XXXXXX: Hexadecimal serial number (00001 to FFFFF)											C																																																																																																												
D	NOTES(技术要求): 1. 黑色印刷, 无边框 (Black printing,no frame) 2.材料:50#亮白压花格底PET,UV油墨,背胶 (Material:50# bright white embossing PET, with UV ink,adhesive) 3. 原材料及后处理工艺均能满足我司《环保技术标准》要求. (Raw materials and the corresponding post processing should meet requirements defined in the T&W Environmental Protection Technical Standards) 条码类型: CODE 128 <table><tr><td colspan="2">DIM</td><td colspan="2">TOL±</td><td colspan="2">△</td><td colspan="2"></td><td colspan="4">T&W 同维</td></tr><tr><td colspan="2">RANGE</td><td>C1</td><td>C2</td><td>C3</td><td>C4</td><td colspan="4">SHENZHEN GONGJIN ELECTRONICS CO., LTD.</td></tr><tr><td colspan="2">0~6</td><td>0.1</td><td>0.1</td><td>0.15</td><td>0.2</td><td colspan="2">TITLE:</td><td colspan="2">对应标识标贴料号:</td></tr><tr><td colspan="2">6~30</td><td>0.2</td><td>0.3</td><td>0.4</td><td>0.5</td><td colspan="2">盒底标贴</td><td colspan="2"></td></tr><tr><td colspan="2">30~80</td><td>0.25</td><td>0.5</td><td>0.9</td><td>1.2</td><td colspan="2">SCALE</td><td>1:1</td><td>UNIT'S</td><td>mm</td></tr><tr><td colspan="2">80~180</td><td>0.3</td><td>0.8</td><td>1.2</td><td>1.5</td><td colspan="2"></td><td colspan="2"></td><td></td></tr><tr><td colspan="2">180~315</td><td>0.5</td><td>1.3</td><td>1.8</td><td>3</td><td colspan="2"></td><td colspan="2"></td><td></td></tr><tr><td colspan="2">315~500</td><td>0.7</td><td>1.5</td><td>2.5</td><td>4</td><td colspan="2"></td><td colspan="2"></td><td></td></tr><tr><td colspan="2">500~800</td><td>0.9</td><td>1.8</td><td>3</td><td>5</td><td colspan="2"></td><td colspan="2"></td><td></td></tr><tr><td colspan="2">ANG.TOL±</td><td colspan="2">0°~30°/0.1°</td><td colspan="2">30°~60°/0.3°</td><td colspan="2">60°~90°/0.5°</td><td colspan="2"></td><td></td></tr></table>											DIM		TOL±		△				T&W 同维				RANGE		C1	C2	C3	C4	SHENZHEN GONGJIN ELECTRONICS CO., LTD.				0~6		0.1	0.1	0.15	0.2	TITLE:		对应标识标贴料号:		6~30		0.2	0.3	0.4	0.5	盒底标贴				30~80		0.25	0.5	0.9	1.2	SCALE		1:1	UNIT'S	mm	80~180		0.3	0.8	1.2	1.5						180~315		0.5	1.3	1.8	3						315~500		0.7	1.5	2.5	4						500~800		0.9	1.8	3	5						ANG.TOL±		0°~30°/0.1°		30°~60°/0.3°		60°~90°/0.5°					D
DIM		TOL±		△				T&W 同维																																																																																																																
RANGE		C1	C2	C3	C4	SHENZHEN GONGJIN ELECTRONICS CO., LTD.																																																																																																																		
0~6		0.1	0.1	0.15	0.2	TITLE:		对应标识标贴料号:																																																																																																																
6~30		0.2	0.3	0.4	0.5	盒底标贴																																																																																																																		
30~80		0.25	0.5	0.9	1.2	SCALE		1:1	UNIT'S	mm																																																																																																														
80~180		0.3	0.8	1.2	1.5																																																																																																																			
180~315		0.5	1.3	1.8	3																																																																																																																			
315~500		0.7	1.5	2.5	4																																																																																																																			
500~800		0.9	1.8	3	5																																																																																																																			
ANG.TOL±		0°~30°/0.1°		30°~60°/0.3°		60°~90°/0.5°																																																																																																																		
1		2		3		4		5		6																																																																																																														

