

FCC RF Exposure

EUT Description: Ventilator, Fan

Model No.: BT-DF0410RCA

FCC ID: 2BCGA-BT-DF0410RCA

1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1 - g and 10 - g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max power of channel, including tune - up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1 - g SAR and ≤ 7.5 for 10 - g extremity SAR,

Where:

Result= $P/D \cdot \sqrt{F}$

F= the RF channel transmit frequency in GHz

P=Maximum turn - up power in mw

D=Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

EIRP(dBm)=67.62(dBuV/m)-95.3=-27.68(dBm)

Frequency (MHz)	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit (mW/cm ²)	SAR Test Exclusion
433.97	-27.68	-27 $\pm$ 1	-26/0.003	5	0.0003	3.0	Pass
Note: PK Output power= conducted power. Conducted power see the test report HK2304261655-E , antenna gain= 0dBi							

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.0003 which is ≤ 3 , RF Exposure testing is not required.

Note: Exclusion Thresholds Results= $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Distance=5mm