
FCC ID: 2BCGFPT2301

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BLE 1Mbps:

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-6.779	0.21	-6±1	-5.00	0.32	<5	0.09802	3.00	YES
	2.44	-6.874	0.21	-6±1	-5.00	0.32	<5	0.09879	3.00	YES
	2.480	-5.925	0.26	-6±1	-5.00	0.32	<5	0.09960	3.00	YES

BLE 2Mbps:

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-7.102	0.19	-7±1	-6.00	0.25	<5	0.07786	3.00	YES
	2.44	-7.09	0.20	-7±1	-6.00	0.25	<5	0.07847	3.00	YES
	2.480	-6.036	0.25	-6±1	-5.00	0.32	<5	0.09960	3.00	YES

Conclusion:

For the max result : $0.09960 \leq$ FCC Limit 3.0 for 1g SAR.