



Report No.: PTC23071005601E-FC03

FCC TEST REPORT

FCC ID: 2BCIC-M1

Product	:	projector
Model Name	:	M1,M2, M3, Y1, Y2, Y3, Z1, Z2, Z3
Brand	:	N/A
Report No.	:	PTC23071005601E-FC03
Prepared for		
SHEN ZHEN GUO WEI NETWORK SERVICE LIMITED		
FLAT/RM D18 3/F WONG KING INDUSTRIAL BUILDING NO.2 TAI YAU STREET KL		
Prepared by		
Precise Testing & Certification Co., Ltd.		
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.		



Report No.: PTC23071005601E-FC03

TEST RESULT CERTIFICATION

Applicant's name : SHEN ZHEN GUO WEI NETWORK SERVICE LIMITED

Address : FLAT/RM D18 3/F WONG KING INDUSTRIAL BUILDING NO.2
TAI YAU STREET KL

Manufacture's name : SHEN ZHEN GUO WEI NETWORK SERVICE LIMITED

Address : FLAT/RM D18 3/F WONG KING INDUSTRIAL BUILDING NO.2
TAI YAU STREET KL

Product name : projector

Model name : M1,M2, M3, Y1, Y2, Y3, Z1, Z2, Z3

Test procedure : FCC CFR47 Part 1.1307(b)(1)

Test Date : Jul. 12, 2023 to Aug. 12, 2023

Date of Issue : Aug. 22, 2023

Test Result : PASS

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink that reads "Simon Pu".

Simon Pu / Engineer

Technical Manager:

A handwritten signature in black ink that reads "Ronnie Liu".

Ronnie Liu / Manager



Contents

	Page
2 TEST SUMMARY	4
3 GENERAL INFORMATION	5
3.1 GENERAL DESCRIPTION OF E.U.T.....	5
4 RF EXPOSURE	6
4.1 REQUIREMENTS.....	6
4.2 THE PROCEDURES / LIMIT	6
4.3 MPE CALCULATION METHOD	7
4.4 TEST RESULT	7



Report No.: PTC23071005601E-FC03

2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	15.247 (i)	PASS
Remark:		
N/A: Not Applicable		



3 General Information

3.1 General Description of E.U.T.

Product Name	:	projector
Model Name	:	M1
Additional model	:	M2, M3, Y1, Y2, Y3, Z1, Z2, Z3
Model difference	:	The difference between the additional model M2, M3, Y1, Y2, Y3, Z1, Z2, Z3 and the test model M1 is only the model name and appearance color are different, and the rest are the same.
Specification	:	802.11b/g/n HT20/HT40 BT BDR+EDR
Operation Frequency	:	2412-2462MHz for 802.11b/g/ n(HT20/HT40) 2402-2480MHz
Number of Channel	:	11 channels for 802.11b/g/ n(HT20/HT40) 79 channels for BDR+EDR
Type of Modulation	:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Antenna installation	:	FPC antenna
Antenna Gain	:	2.07 dBi
Power supply	:	Input:19.0V $\overline{\text{---}}$ 3.42A
Hardware Version	:	VER00.02
Software Version	:	Ver 2.1.3.0 Git 6dce6e, May 12 2023, 07:18:47



4 RF Exposure

Test Requirement : FCC Part 1.1307(b)(1)

Evaluation Method : KDB 447498 D01 General RF Exposure Guidance v06

4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

4.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density



4.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = \frac{30 \times P \times G}{377 \times d^2} \theta \phi$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

4.4 Test Result

Mode	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Result
2402(BDR)	1.61	2.18	2.18 ± 1	2.079697	0.000666	1	Pass
Wi-Fi(2412)	1.61	19.42	19.42 ± 1	110.153931	0.035296	1	Pass

*******THE END REPORT*******