

TEST REPORT

For WiFi-2.4GHz Band



Report No. : **CHEW23110047** Report Verification: 

Project No...... : **SHT2310045701EW**

FCC ID..... : **2BCINEC2**

Applicant's name..... : **SENTRY CS LTD**

Address..... : **5 Derech Hashalom, Tel Aviv, Israel**

Product Name : **Eclipse II (Drone tracking system)**

Trade Mark : **-**

Model No. : **CVX-EC2-BU (Antenna model: CVX-EC2-D-ANT)**

Listed Model(s) : **-**


Standard : **FCC CFR Title 47 Part 15 Subpart C § 15.247**

Date of receipt of test sample..... : **Apr. 06, 2023**

Date of testing..... : **Apr. 06, 2023- Jun. 28, 2024**

Date of issue..... : **Jul. 01, 2024**

Result..... : **PASS**

Compiled by (Position+Printed name+Signature):	File administrator Xiaodong Zhao	
Supervised by (Position+Printed name+Signature):	Project Engineer Xiaodong Zhao	
Approved by (Position+Printed name+Signature):	RF Manager Xu Yang	

Testing Laboratory Name : **Shenzhen Huatongwei International Inspection Co., Ltd.**

Old Address..... : **1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China**

New Address : **Building 7, Baiwang Idea Factory, No.1051, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong, China**

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. The test report merely correspond to the test sample.

Contents

<u>1.</u>	<u>TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Report version	3
<u>2.</u>	<u>TEST DESCRIPTION</u>	<u>4</u>
<u>3.</u>	<u>SUMMARY</u>	<u>5</u>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Radio Specification Description	5
3.4.	Testing Laboratory Information	6
<u>4.</u>	<u>TEST CONFIGURATION</u>	<u>7</u>
4.1.	Test frequency list	7
4.2.	Test mode	7
4.3.	Test sample information	7
4.4.	Support unit used in test configuration and system	8
4.5.	Testing environmental condition	8
4.6.	Statement of the measurement uncertainty	8
4.7.	Equipment Used during the Test	9
<u>5.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>11</u>
5.1.	Antenna Requirement	11
5.2.	AC Conducted Emission	12
5.3.	Peak Output Power	14
5.4.	Power Spectral Density	15
5.5.	6dB bandwidth	16
5.6.	99% Occupied Bandwidth	17
5.7.	Duty Cycle	18
5.8.	Conducted Band edge and Spurious Emission	19
5.9.	Radiated Band edge Emission	21
5.10.	Radiated Spurious Emission	25
<u>6.</u>	<u>TEST SETUP PHOTOS.....</u>	<u>31</u>
<u>7.</u>	<u>EXTERNAL AND INTERNAL PHOTOS.....</u>	<u>31</u>

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

- [FCC CFR Title 47 Part 15 Subpart C § 15.247](#): Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz
- [ANSI C63.10:2020](#): American National Standard for Testing Unlicensed Wireless Devices
- [KDB 558074 D01 15.247 Meas Guidance v05r02](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules
- [KDB662911 D01 Multiple Transmitter Output v02r01](#): Emissions Testing of Transmitters with Multiple Outputs in the Same Band (e.g., MIMO, Smart Antenna, etc)
- [KDB662911 D02 MIMO with Cross-Polarized Antennas v01](#): MIMO with Cross-Polarized Antenna

1.2. Report version

Revision No.	Date of issue	Description
N/A	2024-07-01	Original

2. TEST DESCRIPTION

Report clause	Test Items	Standard Requirement	Result	Test Engineer
5.1	Antenna Requirement	15.203/15.247(c)	PASS	Xiaoqin Li
5.2	AC Conducted Emission	15.207	PASS*	Quanhai Deng
5.3	Peak Output Power	15.247(b)(3)	PASS**	Chenxin Ling
5.4	Power Spectral Density	15.247(e)	PASS**	Chenxin Ling
5.5	6dB Bandwidth	15.247(a)(2)	PASS**	Chenxin Ling
5.6	Conducted Band Edge and Spurious Emission	15.247(d)/15.205	PASS**	Chenxin Ling
5.7	Radiated Band Edge Emission	15.205/15.209	PASS*	Yifang Wang
5.8	Radiated Spurious Emission	15.247(d)/15.205/15.209	PASS*	Yifang Wang

Note:

- The measurement uncertainty is not included in the test result.
- *: These tests were done at the old lab location. The test runs from April 6, 2023 to May 15, 2023.
- **: These tests were done at the new lab location. The test took place on June 28, 2024.

3. SUMMARY

3.1. Client Information

Applicant:	SENTRY CS LTD
Address:	5 Derech Hashalom, Tel Aviv, Israel
Manufacturer:	SENTRY CS LTD
Address:	5 Derech Hashalom, Tel Aviv, Israel

3.2. Product Description

Main unit information:	
Product Name:	Eclipse II (Drone tracking system)
Trade Mark:	-
Model No.:	CVX-EC2-BU (Antenna model: CVX-EC2-D-ANT)
Listed Model(s):	-
Power supply:	AC 100-240V 50Hz/60Hz
Test voltage:	AC 120V 60Hz
Hardware version:	Eclipse II
Software version:	Eclipse II

3.3. Radio Specification Description

Support type:	☐ 802.11b	☒ 802.11g	☒ 802.11n
Support bandwidth:	☒ 20MHz	☒ 40MHz	
Modulation:	802.11g/n:	BPSK, QPSK, 16QAM, 64QAM	
Operation frequency:	802.11g/n(HT20):	2412MHz~2462MHz	
	802.11n(HT40)	2422MHz~2452MHz	
Channel number:	802.11g/n(HT20):	11	
	802.11n(HT40)	7	
Channel separation:	5MHz		
Antenna technology:	☐ SISO	☒ MIMO	
Antenna Delivery:	☐ 1*TX+1*RX	☒ 2*TX+2*RX	☐ 3*TX+3*RX
Antenna type:	FRP Antenna (Model No.: AOA-2458-79AM)		
Antenna gain:	6.5dBi		

3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location (Old)	1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China	
Laboratory Location (New)	Building 7, Baiwang Idea Factory, No.1051, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong, China	
Contact information:	Phone: 86-755-26715499 E-mail: cs@szhtw.com.cn http://www.szhtw.com.cn	
Qualifications	Type	Accreditation Number
	FCC	762235

4. TEST CONFIGURATION

4.1. Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channels which were tested. The Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the below blue front.

802.11802.11g/802.11n(HT20)		802.11n(HT40)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	03	2422
02	2417	04	2427
· : ·	· : ·	· : ·	· : ·
06	2437	06	2437
· : ·	· : ·	· : ·	· : ·
10	2457	08	2447
11	2462	09	2452

4.2. Test mode

For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated spurious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data Recorded in the report.

Preliminary tests were performed in different data rates, final test modes are considering the modulation and worse data rates as below table.

Modulation	Data rate
802.11g	6Mbps
802.11n(HT20)	MCS0
802.11n(HT40)	MCS0

4.3. Test sample information

Test item	HTW sample no.
RF Conducted test items	Please refer to the description in the appendix report
RF Radiated test items	YPHT23040066001
EMI test items	YPHT23040066001

Note:

RF Conducted test items: Peak Output Power, Power Spectral Density, 6dB Bandwidth, Duty cycle, Conducted Band Edge and Spurious Emission

RF Radiated test items: Radiated Band Edge Emission, Radiated Spurious Emission

EMI test items: AC Conducted Emission

4.4. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whether support unit is used?			
✓ No			
Item	Equipment	Trade Name	Model No.
1			
2			

4.5. Testing environmental condition

Type	Requirement	Actual
Temperature:	15~35°C	25°C
Relative Humidity:	25~75%	50%
Air Pressure:	860~1060mbar	1000mbar

4.6. Statement of the measurement uncertainty

No.	Test Items	Measurement Uncertainty
1	AC Conducted Emission	3.21dB
2	Radiated Band Edge Emission	4.54dB for 30MHz-1GHz 5.10dB for above 1GHz
3	Radiated Spurious Emission	4.54dB for 30MHz-1GHz 5.10dB for above 1GHz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

4.7. Equipment Used during the Test

● Conducted Emission

Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Shielded Room	Albatross projects	HTWE0114	N/A	N/A	2018/09/28	2023/09/27
●	EMI Test Receiver	R&S	HTWE0111	ESCI	101247	2022/08/30	2023/08/29
●	Artificial Mains	SCHWARZBECK	HTWE0113	NNLK 8121	573	2022/08/29	2023/08/28
●	Pulse Limiter	R&S	HTWE0193	ESH3-Z2	101447	2022/08/29	2023/08/28
●	RF Connection Cable	HUBER+SUHNER	HTWE0113-02	ENVIROFLEX 142	EF-NM-BNCM-2M	2022/09/17	2023/09/16
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission- Below 1GHz

Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2018/09/30	2023/09/29
●	EMI Test Receiver	R&S	HTWE0099	ESCI	100900	2022/08/30	2023/08/29
●	Loop Antenna	R&S	HTWE0546	HFH2-Z2E	101073	2021/05/25	2024/05/24
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0547	VULB9163	945	2022/05/23	2025/05/22
●	Pre-Amplifier	SCHWARZBECK	HTWE0295	BBV 9742	N/A	2022/11/04	2023/11/03
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-01	N/A	N/A	2023/02/24	2024/02/23
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-02	SUCOFLEX104	501184/4	2023/02/24	2024/02/23
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission- Above 1GHz

Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	C11121	2018/09/27	2023/09/26
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2022/08/25	2023/08/24
●	Horn Antenna	ETS	HTWE0548	3117	240120	2022/05/20	2025/05/19
●	Horn Antenna	STEATITE	HTWE0549	QMS-00880	25661	2022/05/20	2025/05/19
●	Pre-amplifier	CD	HTWE0071	PAP-0102	12004	2022/11/04	2023/11/03
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0201	BBV 9718	9718-248	2023/02/27	2024/02/26
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-01	6m 18GHz S Serisa	N/A	2023/02/24	2024/02/23
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-02	6m 3GHz RG Serisa	N/A	2023/02/24	2024/02/23
●	RF Connection Cable	HUBER+SUHNER	HTWE0119-05	6m 3GHz RG Serisa	N/A	2023/02/24	2024/02/23
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-04	6m 3GHz RG Serisa	N/A	2023/02/24	2024/02/23
●	Test Software	Audix	N/A	E3	N/A	N/A	N/A

● RF Conducted test item							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal and spectrum Analyzer	R&S	HTWE0242	FSV40	100048	2023/08/22	2024/08/21
●	Signal & Spectrum Analyzer	R&S	HTWE0262	FSW26	103440	2023/08/22	2024/08/21
●	Vector signal generator	R&S	HTWE0244	SMBV100A	260790	2023/05/23	2024/05/22
●	Test software	Tonscend	N/A	JS1120	N/A	N/A	N/A

5. TEST CONDITIONS AND RESULTS

5.1. Antenna Requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

The antenna type is FRP Antenna, please refer to Appendix G for antenna photos.

5.2. AC Conducted Emission


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:


Refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

Test Line:


L

**Final Result**

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.259500	39.53	---	61.45	21.92	L1	10.2
0.835500	38.47	---	56.00	17.53	L1	10.3
1.291500	35.57	---	56.00	20.43	L1	10.3
4.643500	31.39	---	56.00	24.61	L1	10.4
5.959500	27.68	---	60.00	32.32	L1	10.4
6.331500	---	33.32	50.00	16.68	L1	10.4
6.331500	35.63	---	60.00	24.37	L1	10.4
6.543500	---	34.34	50.00	15.66	L1	10.4
6.751500	---	31.27	50.00	18.73	L1	10.4
7.175500	---	32.60	50.00	17.40	L1	10.4
7.387500	---	34.21	50.00	15.79	L1	10.4
8.231500	---	32.81	50.00	17.19	L1	10.5

Test Line:

N

**Final Result**

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.271500	44.62	---	61.07	16.45	N	10.2
1.963500	37.17	---	56.00	18.83	N	10.3
2.519500	36.69	---	56.00	19.31	N	10.3
3.655500	35.23	---	56.00	20.77	N	10.4
4.183500	35.19	---	56.00	20.81	N	10.4
4.775500	36.34	---	56.00	19.66	N	10.4
7.387500	---	33.80	50.00	16.20	N	10.4
8.231500	---	34.46	50.00	15.55	N	10.4
9.075500	---	33.86	50.00	16.14	N	10.5
13.295500	---	34.97	50.00	15.03	N	10.6
13.507500	---	34.78	50.00	15.22	N	10.6
14.139500	---	34.47	50.00	15.53	N	10.6

5.3. Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): 30dBm

Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Refer to KDB 662911 D01 Multiple Transmitter Output v02r01:

For power measurements on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less, for 20-MHz channel widths with $N_{ANT} \geq 5$.

Directional gain = $G_{ant} + \text{Array Gain} = 6.5\text{dBi}$, so limit of conducted output power is $30 - ((6.5 - 6) / 3) = 29.83\text{dBm}$

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10 and KDB 558074 D01 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.
4. Record the measurement data.

TEST MODE:

Refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST DATA

Refer to the appendix report

5.4. Power Spectral Density

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e):

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.


Refer to KDB 662911 D01 Multiple Transmitter Output v02r01:

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log (N_{ANT}/N_{SS})$ dB.

Directional gain = $G_{ant} + \text{Array Gain} = 9.51\text{dBi}$, so limit of power spectral density is $8-(9.51-6) = 4.49$

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:
Center frequency=DTS channel center frequency
Span =1.5 times the DTS bandwidth
RBW = 3 kHz ≤ RBW ≤ 100 kHz, VBW ≥ 3 × RBW
Sweep time = auto couple
Detector = peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST MODE:

Refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST DATA

Refer to the appendix report


5.5. 6dB bandwidth

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = DTS channel center frequency
Span = 2 x DTS bandwidth
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

TEST MODE:

Refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST DATA

Refer to the appendix report


Note:

5.6. 99% Occupied Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = channel center frequency
Span $\geq 1.5 \times \text{OBW}$
RBW = 1%~5%OBW
VBW $\geq 3 \times \text{RBW}$
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.

TEST MODE

Refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST DATA


Refer to the appendix report

5.7. Duty Cycle

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span=zero span, Frequency=centered channel, RBW= 1 MHz, VBW $\geq$ RBW
Sweep=as necessary to capture the entire dwell time,
Detector function = peak, Trigger mode
4. Measure and record the duty cycle data

TEST MODE

Refer to the clause 4.2

TEST DATA


Refer to the appendix report

5.8. Conducted Band edge and Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Establish a reference level by using the following procedure
Center frequency=DTS channel center frequency
The span = 1.5 times the DTS bandwidth.
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum PSD level

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

3. Emission level measurement
Set the center frequency and span to encompass frequency range to be measured
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum amplitude level.
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
5. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.

TEST MODE:

Refer to the clause 4.2

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

TEST DATA

Refer to the appendix report


5.9. Radiated Band edge Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10 on radiated measurement.
5. Use the following spectrum analyzer settings:
 - a) Span shall be wide enough to fully capture the emission being measured
 - b) Set RBW=100kHz for <1GHz, VBW=3*RBW, Sweep time=auto, Detector=peak, Trace=max hold
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurementFor average measurement:
 - VBW=10Hz, When duty cycle is no less than 98 percent
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.7 duty cycle.

TEST MODE:

Refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

Note:

- 1) Level= Reading + Factor; Factor =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level– Limit
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m).
- 4) Pre-scan all modulation mode and antenna. 802.11g/n in the report only displays the worst antenna information. The worst result is the simultaneous transmission of two antennas.

Type		802.11g		Test channel		CH01		Polarity		Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	40.64	27.96	3.89	37.56	20.00	54.93	74.00	-19.07	Peak	
2	2389.79	47.75	27.72	3.99	37.45	20.00	62.01	74.00	-11.99	Peak	
3	2390.01	44.39	27.72	3.99	37.45	20.00	58.65	74.00	-15.35	Peak	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	29.34	27.96	3.89	37.56	20.00	43.63	54.00	-10.37	Average	
2	2390.01	31.73	27.72	3.99	37.45	20.00	45.99	54.00	-8.01	Average	
Type		802.11g		Test channel		CH01		Polarity		Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	40.18	27.96	3.89	37.56	20.00	54.47	74.00	-19.53	Peak	
2	2390.01	42.19	27.72	3.99	37.45	20.00	56.45	74.00	-17.55	Peak	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	29.35	27.96	3.89	37.56	20.00	43.64	54.00	-10.36	Average	
2	2390.01	30.71	27.72	3.99	37.45	20.00	44.97	54.00	-9.03	Average	

Type		802.11g		Test channel		CH11		Polarity		Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	44.80	27.43	4.03	37.26	20.00	59.00	74.00	-15.00	Peak	
2	2500.00	40.79	27.40	4.04	37.26	20.00	54.97	74.00	-19.03	Peak	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	30.61	27.43	4.03	37.26	20.00	44.81	54.00	-9.19	Average	
2	2500.00	28.98	27.40	4.04	37.26	20.00	43.16	54.00	-10.84	Average	
Type		802.11g		Test channel		CH11		Polarity		Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	43.85	27.43	4.03	37.26	20.00	58.05	74.00	-15.95	Peak	
2	2500.00	39.82	27.40	4.04	37.26	20.00	54.00	74.00	-20.00	Peak	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	32.65	27.43	4.03	37.26	20.00	46.85	54.00	-7.15	Average	
2	2500.00	29.04	27.40	4.04	37.26	20.00	43.22	54.00	-10.78	Average	

Type	802.11n(HT20)		Test channel		CH01		Polarity		Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	40.68	27.96	3.89	37.56	20.00	54.97	74.00	-19.03	Peak
2	2390.01	45.62	27.72	3.99	37.45	20.00	59.88	74.00	-14.12	Peak
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	29.47	27.96	3.89	37.56	20.00	43.76	54.00	-10.24	Average
2	2390.01	33.99	27.72	3.99	37.45	20.00	48.25	54.00	-5.75	Average
Type	802.11n(HT20)		Test channel		CH01		Polarity		Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	40.17	27.96	3.89	37.56	20.00	54.46	74.00	-19.54	Peak
2	2390.01	44.24	27.72	3.99	37.45	20.00	58.50	74.00	-15.50	Peak
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	29.42	27.96	3.89	37.56	20.00	43.71	54.00	-10.29	Average
2	2390.01	31.70	27.72	3.99	37.45	20.00	45.96	54.00	-8.04	Average

Type	802.11n(HT20)		Test channel		CH11		Polarity		Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.49	50.24	27.43	4.03	37.26	20.00	64.44	74.00	-9.56	Peak
2	2500.00	40.93	27.40	4.04	37.26	20.00	55.11	74.00	-18.89	Peak
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.49	33.45	27.43	4.03	37.26	20.00	47.65	54.00	-6.35	Average
2	2500.00	29.02	27.40	4.04	37.26	20.00	43.20	54.00	-10.80	Average
Type	802.11n(HT20)		Test channel		CH11		Polarity		Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.49	45.04	27.43	4.03	37.26	20.00	59.24	74.00	-14.76	Peak
2	2500.00	40.40	27.40	4.04	37.26	20.00	54.58	74.00	-19.42	Peak
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.49	31.20	27.43	4.03	37.26	20.00	45.40	54.00	-8.60	Average
2	2500.00	29.07	27.40	4.04	37.26	20.00	43.25	54.00	-10.75	Average

Type	802.11n(HT40)		Test channel		CH03		Polarity		Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	41.14	31.62	3.92	42.24	20.00	54.44	74.00	-19.56	Peak
2	2321.10	50.03	31.64	3.92	42.24	20.00	63.35	74.00	-10.65	Peak
3	2389.99	52.99	32.02	3.97	42.21	20.00	66.77	74.00	-7.23	Peak
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	30.39	31.62	3.92	42.24	20.00	43.69	54.00	-10.31	Average
2	2389.99	35.33	32.02	3.97	42.21	20.00	49.11	54.00	-4.89	Average

Type	802.11n(HT40)		Test channel		CH03		Polarity		Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	42.01	31.62	3.92	42.24	20.00	55.31	74.00	-18.69	Peak
2	2338.94	50.27	31.68	3.94	42.23	20.00	63.66	74.00	-10.34	Peak
3	2389.99	43.31	32.02	3.97	42.21	20.00	57.09	74.00	-16.91	Peak
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	29.66	31.62	3.92	42.24	20.00	42.96	54.00	-11.04	Average
2	2389.99	31.93	32.02	3.97	42.21	20.00	45.71	54.00	-8.29	Average

Type	802.11n(HT40)		Test channel		CH09		Polarity		Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.50	54.23	32.70	4.04	42.14	20.00	68.83	74.00	-5.17	Peak
2	2499.20	51.92	32.80	4.05	42.12	20.00	66.65	74.00	-7.35	Peak
3	2500.00	44.75	32.80	4.05	42.12	20.00	59.48	74.00	-14.52	Peak
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2482.17	36.21	32.69	4.04	42.14	20.00	50.80	54.00	-3.20	Average
2	2500.00	33.78	32.80	4.05	42.12	20.00	48.51	54.00	-5.49	Average

Type	802.11n(HT40)		Test channel		CH09		Polarity		Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.50	42.44	32.70	4.04	42.14	20.00	57.04	74.00	-16.96	Peak
2	2494.86	48.75	32.77	4.05	42.13	20.00	63.44	74.00	-10.56	Peak
3	2500.00	43.10	32.80	4.05	42.12	20.00	57.83	74.00	-16.17	Peak
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.50	31.73	32.70	4.04	42.14	20.00	46.33	54.00	-7.67	Average
2	2500.00	29.77	32.80	4.05	42.12	20.00	44.50	54.00	-9.50	Average

5.10. Radiated Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dBuV/m)	Value
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak


Note: Limit dBuV/m @3m = Limit dBuV/m @300m + $40 \cdot \log(300/3)$ = Limit dBuV/m @300m +80,

Limit dBuV/m @3m = Limit dBuV/m @30m + $40 \cdot \log(30/3)$ = Limit dBuV/m @30m + 40.


Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


- 9 kHz ~ 30 MHz



- 30 MHz ~ 1 GHz



- Above 1 GHz



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - a) Span shall wide enough to fully capture the emission being measured;
 - b) Below 1 GHz:

RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;

If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement:

 - VBW=10Hz, When duty cycle is no less than 98 percent
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.7 duty cycle.

TEST MODE:

Refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

Note:

- 1) Level= Reading + Factor/Transd; Factor/Transd =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level– Limit
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m) for above 1GHz.

FOR 9 kHz ~ 30 MHz


The EUT was pre-scanned this frequency band, found the radiated level 20dB lower than the limit, so don't show data on this report.

FOR 30 MHz ~ 1000 MHz

Have pre-scan all test channel, found CH06 of 802.11n(HT40) which it was worst case, so only show the worst case's data on this report.

Polarization:


Horizontal

**Final Result**

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
175.985000	33.42	43.50	10.08	300.0	H	68.0	-11.6
181.562500	32.46	43.50	11.04	100.0	H	134.0	-11.4
279.896250	34.45	46.00	11.55	100.0	H	220.0	-7.4
304.388750	34.16	46.00	11.84	100.0	H	65.0	-6.3
491.113750	35.34	46.00	10.66	100.0	H	314.0	-1.6
555.255000	34.74	46.00	11.26	300.0	H	113.0	0.1

Polarization:

Vertical

**Final Result**

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
174.651250	31.73	43.50	11.77	100.0	V	35.0	-11.6
464.681250	32.34	46.00	13.66	100.0	V	160.0	-2.0
866.746250	33.51	46.00	12.49	100.0	V	323.0	3.9
888.086250	32.58	46.00	13.42	100.0	V	328.0	4.1
933.433750	33.89	46.00	12.11	100.0	V	323.0	4.4
997.453750	41.32	54.00	12.68	100.0	V	359.0	5.0

FOR 1 GHz ~ 25 GHz

The EUT was pre-scanned all modulation mode and antenna. 802.11g/n in the report only displays the worst antenna information. The worst result is the simultaneous transmission of two antennas.

Type	802.11g		Test channel	CH01		Polarity		Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1254.27	39.51	25.91	2.81	36.48	31.75	74.00	-42.25	Peak
2	4821.76	39.13	31.40	5.74	35.24	41.03	74.00	-32.97	Peak
3	7432.62	35.83	36.60	7.33	33.98	45.78	74.00	-28.22	Peak
4	10888.51	34.97	40.57	9.10	36.76	47.88	74.00	-26.12	Peak
Type	802.11g		Test channel	CH01		Polarity		Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1303.09	39.15	26.02	2.85	36.30	31.72	74.00	-42.28	Peak
2	5099.49	37.94	32.20	5.91	35.48	40.57	74.00	-33.43	Peak
3	7508.69	34.97	36.58	7.39	33.87	45.07	74.00	-28.93	Peak
4	10860.83	34.66	40.48	9.09	36.78	47.45	74.00	-26.55	Peak
Type	802.11g		Test channel	CH06		Polarity		Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1192.01	40.90	25.57	2.77	36.65	32.59	74.00	-41.41	Peak
2	3672.11	41.25	29.40	4.95	37.03	38.57	74.00	-35.43	Peak
3	5099.49	37.35	32.20	5.91	35.48	39.98	74.00	-34.02	Peak
4	8063.40	35.17	37.20	7.65	33.32	46.70	74.00	-27.30	Peak
Type	802.11g		Test channel	CH06		Polarity		Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1251.08	40.21	25.90	2.81	36.50	32.42	74.00	-41.58	Peak
2	5112.49	37.10	32.15	5.92	35.47	39.70	74.00	-34.30	Peak
3	8125.22	34.48	37.10	7.69	33.36	45.91	74.00	-28.09	Peak
4	10888.51	35.92	40.57	9.10	36.76	48.83	74.00	-25.17	Peak
Type	802.11g		Test channel	CH11		Polarity		Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1207.28	40.28	25.64	2.78	36.64	32.06	74.00	-41.94	Peak
2	4920.96	38.96	31.44	5.85	35.21	41.04	74.00	-32.96	Peak
3	7489.60	35.07	36.60	7.37	33.94	45.10	74.00	-28.90	Peak
4	9228.06	36.71	38.91	8.38	36.04	47.96	74.00	-26.04	Peak
Type	802.11g		Test channel	CH11		Polarity		Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1293.17	39.08	25.99	2.84	36.32	31.59	74.00	-42.41	Peak
2	3168.08	41.11	28.96	4.63	37.12	37.58	74.00	-36.42	Peak
3	4664.81	39.06	31.26	5.69	35.94	40.07	74.00	-33.93	Peak
4	9636.16	36.51	39.34	8.55	36.89	47.51	74.00	-26.49	Peak

Type	802.11n(HT20)		Test channel	CH01			Polarity	Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1260.67	39.56	25.92	2.82	36.46	31.84	74.00	-42.16	Peak
2	5112.49	38.22	32.15	5.92	35.47	40.82	74.00	-33.18	Peak
3	7245.81	35.70	36.41	7.26	34.06	45.31	74.00	-28.69	Peak
4	10723.47	35.29	40.15	9.05	36.90	47.59	74.00	-26.41	Peak
Type	802.11n(HT20)		Test channel	CH01			Polarity	Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1329.89	38.74	26.18	2.90	36.37	31.45	74.00	-42.55	Peak
2	5125.52	37.33	32.10	5.94	35.46	39.91	74.00	-34.09	Peak
3	7432.62	35.45	36.60	7.33	33.98	45.40	74.00	-28.60	Peak
4	11486.41	34.52	40.86	9.45	36.38	48.45	74.00	-25.55	Peak
Type	802.11n(HT20)		Test channel	CH06			Polarity	Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1254.27	39.79	25.91	2.81	36.48	32.03	74.00	-41.97	Peak
2	4883.52	39.87	31.40	5.84	35.18	41.93	74.00	-32.07	Peak
3	7981.72	35.75	37.03	7.60	33.31	47.07	74.00	-26.93	Peak
4	9784.47	35.91	39.60	8.44	36.17	47.78	74.00	-26.22	Peak
Type	802.11n(HT20)		Test channel	CH06			Polarity	Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1228.98	39.33	25.78	2.80	36.58	31.33	74.00	-42.67	Peak
2	4034.78	40.33	29.97	5.26	36.30	39.26	74.00	-34.74	Peak
3	5762.24	36.44	31.92	6.63	34.86	40.13	74.00	-33.87	Peak
4	11515.68	34.37	40.85	9.47	36.37	48.32	74.00	-25.68	Peak
Type	802.11n(HT20)		Test channel	CH11			Polarity	Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1263.88	39.00	25.93	2.82	36.44	31.31	74.00	-42.69	Peak
2	5125.52	38.95	32.10	5.94	35.46	41.53	74.00	-32.47	Peak
3	8042.90	35.37	37.19	7.64	33.31	46.89	74.00	-27.11	Peak
4	9809.40	36.33	39.58	8.46	36.19	48.18	74.00	-25.82	Peak
Type	802.11n(HT20)		Test channel	CH11			Polarity	Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1188.98	40.35	25.56	2.77	36.66	32.02	74.00	-41.98	Peak
2	3993.90	39.33	29.90	5.29	36.37	38.15	74.00	-35.85	Peak
3	8022.46	34.38	37.14	7.62	33.31	45.83	74.00	-28.17	Peak
4	11341.14	34.33	40.48	9.36	36.46	47.71	74.00	-26.29	Peak

Type	802.11n(HT40)		Test channel	CH03		Polarity		Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2957.65	54.64	32.50	4.43	41.98	49.59	74.00	-24.41	Peak
2	4983.99	50.80	34.07	5.73	40.91	49.69	74.00	-24.31	Peak
3	7489.60	49.75	36.00	7.28	40.97	52.06	74.00	-21.94	Peak
4	10480.59	36.83	37.49	8.52	39.76	43.08	74.00	-30.92	Peak
Type	802.11n(HT40)		Test channel	CH03		Polarity		Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	3200.50	48.68	34.39	4.59	41.87	45.79	74.00	-28.21	Peak
2	4983.99	50.76	34.07	5.73	40.91	49.65	74.00	-24.35	Peak
3	7921.00	38.24	35.80	7.50	40.45	41.09	74.00	-32.91	Peak
4	10400.86	36.52	37.44	8.51	39.50	42.97	74.00	-31.03	Peak
Type	802.11n(HT40)		Test channel	CH06		Polarity		Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	3192.37	41.80	34.19	4.58	41.88	38.69	74.00	-35.31	Peak
2	5191.17	38.94	34.28	5.87	40.75	38.34	74.00	-35.66	Peak
3	5910.80	38.77	34.94	6.31	40.01	40.01	74.00	-33.99	Peak
4	11663.19	35.30	38.37	9.03	40.24	42.46	74.00	-31.54	Peak
Type	802.11n(HT40)		Test channel	CH06		Polarity		Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	3700.26	41.33	33.30	5.01	41.72	37.92	74.00	-36.08	Peak
2	4996.69	47.65	34.09	5.74	40.90	46.58	74.00	-27.42	Peak
3	6445.16	38.33	35.45	6.80	40.76	39.82	74.00	-34.18	Peak
4	10400.86	35.47	37.44	8.51	39.50	41.92	74.00	-32.08	Peak
Type	802.11n(HT40)		Test channel	CH09		Polarity		Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	4014.29	40.91	33.43	5.15	41.55	37.94	74.00	-36.06	Peak
2	4996.69	47.04	34.09	5.74	40.90	45.97	74.00	-28.03	Peak
3	7451.57	38.36	36.00	7.26	40.98	40.64	74.00	-33.36	Peak
4	10453.95	35.69	37.47	8.52	39.67	42.01	74.00	-31.99	Peak
Type	802.11n(HT40)		Test channel	CH09		Polarity		Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	3728.63	41.19	33.30	5.03	41.70	37.82	74.00	-36.18	Peak
2	4996.69	47.79	34.09	5.74	40.90	46.72	74.00	-27.28	Peak
3	7009.96	38.45	35.91	6.99	41.09	40.26	74.00	-33.74	Peak
4	10534.09	35.62	37.52	8.53	39.93	41.74	74.00	-32.26	Peak

6. TEST SETUP PHOTOS

Please refer to Appendix H

7. EXTERNAL AND INTERNAL PHOTOS

Please refer to Appendix I

-----End of Report-----