

9/3/2024

Tractian Technologies Inc.
1389 Peachtree St NE
Atlanta, GA 30309
USA

Dear Jorge Sousa,

Enclosed is the EMC test report for testing of the Tractian Technologies Inc., Uni Trac tested to the requirements of FCC Part 2.1091

Thank you for using the services of Eurofins E&E North America. If you have any questions regarding these results or if MET can be of further service to you, please do feel free to contact me.

Sincerely,



Nancy LaBrecque
Documentation Department
Eurofins Electrical and Electronic Testing NA, Inc.

Reference: WIRA132292- FCC_MPE



Certificates and reports shall not be reproduced except in full, without the written permission of Eurofins E&E North America. While use of the A2LA logo in this report reflects MET accreditation under these programs, the report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the Federal Government. This letter of transmittal is not a part of the attached report.

Eurofins MET Laboratories Inc. (Eurofins E&E North America) is part of the Eurofins Electrical & Electronics (E&E) global compliance network.

**RF Exposure Criteria
Test Report
Using Maximum Permissible Exposure (MPE) Calculations**

for the

**Tractian Technologies Inc.
Uni Trac**

Tested under

FCC Part 2.1091

Report: WIRA132292- FCC_MPE

9/3/2024



Bryan Taylor, Wireless Team Lead
Electromagnetic Compatibility Lab



Nancy LaBrecque
Documentation Department

Engineering Statement: The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.



Matthew Hinojosa
EMC Manager, Austin Electromagnetic Compatibility Lab

Report Status Sheet

Revision	Report Date	Reason for Revision
0	9/3/2024	Initial Issue.

Table of Contents

1.0 Requirements Summary.....	8
2.0 Equipment Configuration	9
2.1 Overview.....	9
2.2 Test Site	11
2.3 References.....	11
2.4 Description of Test Sample.....	12
2.5 Modifications	12
2.5.1 Modifications to EUT	12
2.5.2 Modifications to Test Standard.....	12
2.6 Disposition of EUT	12
3.0 Transmitter Requirements.....	13

List of Tables

Table 1. Summary of Test Results	8
Table 2. EUT Summary Table	10
Table 3. References	11

List of Terms and Abbreviations

AC	Alternating Current
ACF	Antenna Correction Factor
Cal	Calibration
<i>d</i>	Measurement Distance
dB	Decibels
dBμA	Decibels above one microamp
dBμV	Decibels above one microvolt
dBμA/m	Decibels above one microamp per meter
dBμV/m	Decibels above one microvolt per meter
DC	Direct Current
E	Electric Field
DSL	Digital Subscriber Line
ESD	Electrostatic Discharge
EUT	Equipment Under Test
<i>f</i>	Frequency
CISPR	Comite International Special des Perturbations Radioelectriques (International Special Committee on Radio Interference)
GRP	Ground Reference Plane
H	Magnetic Field
HCP	Horizontal Coupling Plane
Hz	Hertz
IEC	International Electrotechnical Commission
kHz	kiloHertz
kPa	kiloPascal
kV	kilovolt
LISN	Line Impedance Stabilization Network
MHz	MegaHertz
μH	microHenry
μF	microFarad
μs	microseconds
PRF	Pulse Repetition Frequency
RF	Radio Frequency
RMS	Root-Mean-Square
V/m	Volts per meter
VCP	Vertical Coupling Plane

1.0 Requirements Summary

Page Number	Test Name	Result
Error! Bookmark not defined.	FCC Part 2.1091 MPE Limits (For General Public Exposure)	Compliant

Table 1. Summary of Test Results

2.0 Equipment Configuration

2.1 Overview

Eurofins MET Labs was contracted by Tractian Technologies Inc. to perform testing on the Uni Trac, under Tractian Technologies Inc.'s purchase order number 1TRA2105.

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing of the Tractian Technologies Inc. Uni Trac.

The results obtained relate only to the item(s) tested.

Product Name:	Uni Trac	
Model(s) Tested:	Uni Trac	
Serial Number or Sample Number:	Conducted Sample: A00CER Radiated Sample: A010CER	
FCCID:	2BCIS-UNITRAC	
Primary Power:	5 – 24VDC	
EUT Specifications:	Type of Modulations:	O-QPSK
	Equipment Code:	DTS
	Peak RF Output Power:	18.15dBm
	EUT Frequency Ranges:	902MHz – 928MHz
	Antenna Gain ¹ :	2.1dBi
Analysis:	The results obtained relate only to the item(s) tested.	
Environmental Test Conditions:	Temperature: 15-35° C	
	Relative Humidity: 30-60%	
	Barometric Pressure: 860-1060 mbar	
Evaluated by:	Bryan Taylor and Sergio Gutierrez	
Report Date(s):	7/3/2024 through 7/16/2024	

Table 2. EUT Summary Table

¹ The antenna gain information was provided by Tractian Technologies Inc. and may affect compliance.

2.2 Test Site

All testing was performed at Eurofins MET Labs, 13501 McCallen Pass, Austin, TX 78753. All equipment used in making physical determinations is accurate and bears recent traceability to the National Institute of Standards and Technology.

Radiated Emissions measurements were performed in a 10 meter semi-anechoic chamber (equivalent to an Open Area Test Site). In accordance with §2.948(a)(3), a complete site description is contained at MET Laboratories.

FCC Lab Info:

Designation Number: US1127

2.3 References

FCC Part 2.1091	Radiofrequency radiation exposure evaluation: mobile devices.
------------------------	---

Table 3. References

2.4 Description of Test Sample

The Uni Trac is a smart data collector for industrial assets.

2.5 Modifications

2.5.1 Modifications to EUT

No modifications were made to the EUT.

2.5.2 Modifications to Test Standard

No modifications were made to the test standard.

2.6 Disposition of EUT

The test sample including all support equipment submitted to the Electro-Magnetic Compatibility Lab for testing was returned to Tractian Technologies Inc. upon completion of testing.

3.0 Maximum Permissible Exposure Results

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

Test Procedure:

An MPE evaluation for was performed in order to show that the device was compliant with the general population exposure limits. The maximum power density was calculated for each transmitter band at a separation distance of 20cm using the maximum declared output power including tune up tolerance.

For each transmitter the maximum RF exposure at a 20 cm distance using the formula:

$$ConductedPower_{mW} = 10^{\frac{ConductedPower(dBm)}{10}}$$

$$PowerDensity = \frac{ConductedPower_{mW} \times Ant.Gain}{4\pi \times (20_{cm})^2}$$

For transmitters that could operate simultaneously, the MPE to limit ratio for each was calculated and then summed. If the sum of the MPE to limit ratios was less than 1, that specific combination of transmitters was deemed to comply.

Test Results:

The Uni Trac was **compliant** with FCC Part 2.1091 . The calculated maximum power density at 20cm distance was equal to or less than the required limits for general population exposure for FCC Part 2.1091 .

Test Data:

Duty Cycle	100 (%)						
Separation Dist.	20 (cm)						
Operating Mode	Frequency (MHz)	Declared Max Cond. Power (Inc. Tolerance) (dBm)	Duty Cycle Adjusted Cond. Output Power (dBm)	Antenna Gain (dB)	MPE Value (mW/cm ²)	MPE Limit (mW/cm ²)	Margin to Limit (mW/cm ²)
ISM Transmitter	903	18.51	18.51	2.1	0.0229	0.6020	0.5791

FCC MPE Data

Test Engineer(s): Bryan Taylor

Test Date(s): 7/16/2024