

FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID: 2BCJV-LP100

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: f is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

Test Result of RF Exposure Evaluation

	Modes& Channel Freq. (MHz)	Tune up Produce power	Maximu m peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm2)	Limit (mW / cm2)	Result
EDR	π /4DQPS K& LCH	1 ± 1	2	1.5849	2.5645 (4.09dBi)	0.0004	1	Pass
BLE	GFSK& MCH	8 ± 1	9	7.9433	2.5645 (4.09dBi)	0.002	1	Pass
2.4G WIFI	802.11g&2 437	14 ± 1	15	31.6228	2.6424 (4.22dBi)	0.0166	1	Pass
5.2GWIFI	802.11a20 &5240	14 ± 1	15	31.6228	2.3227 (3.66dBi)	0.0146	1	Pass
5.8GWIFI	802.11n(H T40)& 5755	12 ± 1	13	19.9526	2.9040 (4.63dBi)	0.0115	1	Pass

BT+WIFI supported simultaneous transmission:

BLE+2.4GWIFI: Σ MPE Ratio = $0.002/1 + 0.0166/1 = 0.0186 \leq 1$,

BLE+5GWIFI: Σ MPE Ratio = $0.002/1 + 0.0146/1 = 0.0166 \leq 1$,

So passed.