

RF Exposure Analysis

FCC ID: 2BCK5TLV20

Analysis for FCC portable use

Standalone SAR test exclusion considerations are defined in KDB 447498D01 (v06) Chapter 4.3.1 where the 1-g head or body and 10-g extremity SAR exclusion threshold is defined by the following formula:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

For the Lock GO:

The Operating frequency is 2402 – 2480MHz

The maximum conducted output power is +8.0 dBm (6.3mW).

Applying the above data using the given KDB 447498 D01 formula, and applying a minimum separation distance of 5mm, the following results:

$(6.3\text{mW} / 5 \text{ mm}) \times \sqrt{2.48 \text{ GHz}} = 2.0$ (i.e.: ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR)

This demonstrates the Lock GO meets the criteria for 1-g head/ body and 10-g extremity SAR test exemption.