



Report No.: TBR-C-202308-0074-1  
Page: 1 of 5

# RF Exposure Evaluation

## FCC ID: 2BCKS-PR02

### 1. Client Information

Applicant	:	Shenzhen iPeace Entity Co. Ltd
Address	:	702, Tower 3, Laizuoshan, Buji, Longgang District, Shenzhen, China.
Manufacturer	:	Shenzhen iPeace Entity Co. Ltd
Address	:	702, Tower 3, Laizuoshan, Buji, Longgang District, Shenzhen, China.

### 2. General Description of EUT

EUT Name	:	UHF RFID READER WRITER	
Model No.	:	PR02, PR01, PR03, PR04	
Model Different	:	All these models are identical in the same PCB, layout and electrical circuit, the only difference is Appearance and Model name.	
Sample ID	:	HC-C-202308-0074-01-01-1# & HC-C-202308-0074-01-01-2#	
Product Description	Operation Frequency:	RFID: 902.25MHz~909.25MHz Bluetooth 5.0(BLE): 2402MHz~2480MHz	
	Number of Channel:	RFID: 8channels BLE: 40channels	
	Antenna Gain:	3.5dBi Ceramic Antenna for RFID 1.5dBi PCB Antenna for Bluetooth	
Power Supply	:	Input: DC 5V DC 3.7V/3.8V by 10000mAh Rechargeable Li-ion battery	
Software Version	:	V1.0	
Hardware Version	:	----	

**Remark:** The antenna gain provided by the applicant, the adapter and verified for the RF conduction test and adapter provided by TOBY test lab.

**Note:** More test information about the EUT please refer the RF Test Report.

**TB-RF-074-1.0**

## The RF Exposure Evaluation for FCC:

### SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

- Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance  $\leq 5$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})]^* [\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR}$$
$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})]^* [\sqrt{f_{(\text{GHz})}}] \leq 7.5.0 \text{ for 10-g SAR}$$


## 2. Summary simultaneous transmission for SAR Exclusion

The SAR exemption limits outlined in clause 4.3.2(b) of KDB 447498 have been derived based on an approximate SAR value of 0.4 W/kg using half-wave dipole antennas Footnote 1. As such, when simultaneous transmitter SAR evaluations include transmitters that have been exempt from routine SAR evaluation, the SAR must be estimated based on the ratio between the maximum tune-up tolerance limit of the transmitter that has been exempt and the exemption limit at the specific distance and frequency for that transmitter. This ratio must be multiplied by 0.4 W/kg (2.0 W/kg for controlled use and 1.0 W/kg for limb worn devices) in order to calculate the estimated SAR level.

The estimated SAR value is calculated based on the following equation:

(maximum power level including tune-up tolerance for transmitter A / maximum power level of exemption at the same frequency and distance) \* 0.4W/kg

- 1)  $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}/x}] \text{ W/kg, for test separation distances} \leq 50 \text{ mm};$   
where  $x = 7.5$  for 1-g SAR and  $x = 18.75$  for 10-g SAR.
- 2) 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the *test separation distance* is  $> 50 \text{ mm}$ .<sup>37</sup>

The  $[\sum \text{ of (the highest measured or estimated SAR for each standalone antenna configuration, adjusted for maximum tune-up tolerance) / 1.6 W/kg} + [\sum \text{ of MPE ratios}]] \leq 1.0$ .

The SAR to peak location separation ratios of all simultaneously transmitting antenna pairs operating in portable device exposure conditions are all  $\leq 0.04$ , and the  $[\sum \text{ of MPE ratios}] \leq 1.0$ .



### 3. Calculation:

Test separation: 5mm						
BLE-1M						
Frequency (MHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	1.348	1±1	2	1.585	0.491	3.0
2.440	0.931	0±1	1	1.259	0.393	3.0
2.480	1.125	1±1	2	1.585	0.499	3.0
BLE-2M						
Frequency (MHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	1.419	1±1	2	1.585	0.491	3.0
2.440	0.987	0±1	1	1.259	0.393	3.0
2.480	1.172	1±1	2	1.585	0.499	3.0

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

RFID Worst Data							
Mode	Max. Output Power (dB $\mu$ V/m)	Max. Output Power (dBm)	Turn-up Power Tolerance (dBm)	Max tune up power (dBm)	Max power of tune up tolerance (mW)	Calculation Value	Threshold Value
909.25MHz	74.65	-25.30	-25±1	-24	0.004	0	3.0

**Note:**  
**N<sub>TX</sub>**= Number of Transmit Antennas  
For conducted measurements below 1000 MHz, the field strength shall be computed as specified in item d), and then an additional 4.7 dB shall be added as an upper bound on the field strength that would be observed on a test range with a ground plane for frequencies between 30 MHz and 1000 MHz, or an additional 6 dB shall be added for frequencies below 30MHz.

$E = \text{EIRP} - 20 \log d + 104.8$

where

$E$  is the electric field strength in dB $\mu$ V/m  
EIRP is the equivalent isotropically radiated power in dBm  
 $d$  is the specified measurement distance in m

So:  $\text{EIRP} = E + 20 \log 3 - 104.8 - (4.7 \text{ or } 6)$



#### 4. Summary simultaneous transmission results

##### Simultaneous Transmission for SAR Exclusion

The sample support one RFID modular and one BLE modular, they supports difference antenna, need consider simultaneous transmission;

$$\sum \text{ of (the highest measured or estimated SARRFID +SARBLE)}/1.6 = (0.0001+0.0668)/1.6 = 0.0418 < 1.0;$$

The measurement results comply with the FCC Limit per 47 CFR 2.1093 and the RSS-102§4 Table 4 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06, No SAR is required.

-----END OF THE REPORT-----

