





4.4 Maximum Conducted Output Power

Test Requirement:	FCC Part15 E Section 15.407, RSS-247 §6.2
Test Method:	KDB 789033 D02 General UNII Test Procedures New Rules v02r01
Limit:	For the band 5.15-5.25GHz, 5.25-5.35GHz, 5.47-5.725GHz, the maximum conducted output power over the frequency bands of operation shall not exceed 250mW. For the band 5.725-5.85GHz, the maximum conducted output power over the frequency bands of operation shall not exceed 1W. IC: For the 5.15–5.25 GHz band, For other devices, the maximum e.i.r.p. shall not exceed 200 mW or $10 + 10 \log_{10} B$, dBm, whichever power is less. B is the 99% emission bandwidth in MHz. For the 5.25–5.35 GHz band, Other than devices installed in vehicles, the maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever power is less. The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. For the 5.47–5.6 GHz and 5.65–5.725 GHz band, the maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever power is less. The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance. If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
Test setup:	 The diagram illustrates the test setup. A 'Power Meter' is connected to an 'E.U.T' (Equipment Under Test) by a red cable. Both components are positioned on a 'Non-Conducted Table'. This table is supported by a 'Ground Reference Plane'.
Test procedure:	Measurement using an RF average power meter

	(i) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied a) The EUT is configured to transmit continuously or to transmit with a constant duty cycle. b) At all times when the EUT is transmitting, it must be transmitting at its maximum power control level. c) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five. (ii) If the transmitter does not transmit continuously, measure the duty cycle, x, of the transmitter output signal as described in section B). (iii) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter. (iv) Adjust the measurement in dBm by adding $10 \log(1/x)$ where x is the duty cycle (e.g., $10 \log(1/0.25)$ if the duty cycle is 25 percent).
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Measurement Data**Band 1 (5150-5250 MHz) SISO:**

Condition	Antenna	Modulation	Frequency (MHz)	Conducted Power(dBm)	Duty factor(dB)	Total Power(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11a	5180.00	2.51	0.18	2.69	24	Pass
NVNT	ANT1	802.11a	5200.00	4.60	0.15	4.75	24	Pass
NVNT	ANT1	802.11a	5240.00	4.70	0.15	4.85	24	Pass
NVNT	ANT1	802.11n(HT20)	5180.00	2.18	0.20	2.38	24	Pass
NVNT	ANT1	802.11n(HT20)	5200.00	2.44	0.19	2.63	24	Pass
NVNT	ANT1	802.11n(HT20)	5240.00	3.01	0.20	3.21	24	Pass
NVNT	ANT1	802.11ac(VHT20)	5180.00	1.88	0.51	2.39	24	Pass
NVNT	ANT1	802.11ac(VHT20)	5200.00	1.71	0.43	2.14	24	Pass
NVNT	ANT1	802.11ac(VHT20)	5240.00	2.42	0.51	2.93	24	Pass
NVNT	ANT1	802.11n(HT40)	5190.00	2.26	0.39	2.65	24	Pass
NVNT	ANT1	802.11n(HT40)	5230.00	3.21	0.39	3.60	24	Pass
NVNT	ANT1	802.11ac(VHT40)	5190.00	1.90	0.90	2.80	24	Pass
NVNT	ANT1	802.11ac(VHT40)	5230.00	2.72	0.62	3.34	24	Pass
NVNT	ANT1	802.11ac(VHT80)	5210.00	1.22	1.25	2.47	24	Pass



Condition	Antenna	Modulation	Frequency (MHz)	Duty cycle(%)	Duty_factor
NVNT	ANT1	802.11a	5180.00	95.89	0.18
NVNT	ANT1	802.11a	5200.00	96.55	0.15
NVNT	ANT1	802.11a	5240.00	96.55	0.15
NVNT	ANT1	802.11n(HT20)	5180.00	96.32	0.16
NVNT	ANT1	802.11n(HT20)	5200.00	95.59	0.20
NVNT	ANT1	802.11n(HT20)	5240.00	95.59	0.20
NVNT	ANT1	802.11ac(VHT20)	5180.00	88.89	0.51
NVNT	ANT1	802.11ac(VHT20)	5200.00	90.57	0.43
NVNT	ANT1	802.11ac(VHT20)	5240.00	88.89	0.51
NVNT	ANT1	802.11n(HT40)	5190.00	91.43	0.39
NVNT	ANT1	802.11n(HT40)	5230.00	91.43	0.39
NVNT	ANT1	802.11ac(VHT40)	5190.00	81.25	0.90
NVNT	ANT1	802.11ac(VHT40)	5230.00	86.67	0.62
NVNT	ANT1	802.11ac(VHT80)	5210.00	75.00	1.25




Band 4 (5725 – 5850 MHz) SISO:

Condition	Antenna	Modulation	Frequency (MHz)	Conducted Power(dBm)	Duty factor(dB)	Total Power(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11a	5785.00	6.40	0.12	6.52	30	Pass
NVNT	ANT1	802.11a	5825.00	6.49	0.12	6.61	30	Pass
NVNT	ANT1	802.11n(HT20)	5745.00	4.91	0.20	5.11	30	Pass
NVNT	ANT1	802.11n(HT20)	5785.00	5.54	0.13	5.67	30	Pass
NVNT	ANT1	802.11n(HT20)	5825.00	5.24	0.20	5.44	30	Pass
NVNT	ANT1	802.11ac(VHT20)	5745.00	4.76	0.51	5.27	30	Pass
NVNT	ANT1	802.11ac(VHT20)	5785.00	5.70	0.35	6.05	30	Pass
NVNT	ANT1	802.11ac(VHT20)	5825.00	5.24	0.51	5.75	30	Pass
NVNT	ANT1	802.11n(HT40)	5755.00	4.84	0.26	5.10	30	Pass
NVNT	ANT1	802.11n(HT40)	5795.00	5.98	0.38	6.36	30	Pass
NVNT	ANT1	802.11ac(VHT40)	5755.00	4.65	0.90	5.55	30	Pass
NVNT	ANT1	802.11ac(VHT40)	5795.00	5.84	0.90	6.74	30	Pass
NVNT	ANT1	802.11ac(VHT80)	5775.00	4.44	1.38	5.82	30	Pass

Condition	Antenna	Modulation	Frequency (MHz)	Duty cycle(%)	Duty_factor
NVNT	ANT1	802.11a	5745.00	95.83	0.18
NVNT	ANT1	802.11a	5785.00	95.89	0.18
NVNT	ANT1	802.11a	5825.00	95.89	0.18
NVNT	ANT1	802.11n(HT20)	5745.00	95.59	0.20
NVNT	ANT1	802.11n(HT20)	5785.00	97.06	0.13
NVNT	ANT1	802.11n(HT20)	5825.00	95.59	0.20
NVNT	ANT1	802.11ac(VHT20)	5745.00	88.89	0.51
NVNT	ANT1	802.11ac(VHT20)	5785.00	92.31	0.35
NVNT	ANT1	802.11ac(VHT20)	5825.00	88.89	0.51
NVNT	ANT1	802.11n(HT40)	5755.00	94.29	0.26
NVNT	ANT1	802.11n(HT40)	5795.00	91.67	0.38
NVNT	ANT1	802.11ac(VHT40)	5755.00	81.25	0.90
NVNT	ANT1	802.11ac(VHT40)	5795.00	81.25	0.90
NVNT	ANT1	802.11ac(VHT80)	5775.00	72.73	1.38

Note: The measure-and-sum technique shall be used for measuring in-band transmit power of a device. Total power is the sum of the conducted power levels measured at the various output ports.

4.5 Power Spectral Density


Test Requirement:	FCC Part15 E Section 15.407, RSS-247 §6.2
Test Method:	KDB 789033 D02 General UNII Test Procedures New Rules v02r01
Limit:	FCC: 1. $\leq 11.00\text{dBm/MHz}$ for 5150MHz-5250MHz, 5250-5350MHz and 5470-5725 MHz 2. $\leq 30.00\text{dBm/500KHz}$ for 5725MHz-5850MHz IC: 1. For the 5.15-5.25 GHz, The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band. 2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test procedure:	1) Create an average power spectrum for the EUT operating mode being tested by following the instructions in section E)2) for measuring maximum conducted output power using a spectrum analyzer or EMI receiver: select the appropriate test method (SA-1, SA-2, SA-3, or alternatives to each) and apply it up to, but not including, the step labeled, "Compute power...". 2) Use the peak search function on the instrument to find the peak of the spectrum. 3) Make the following adjustments to the peak value of the spectrum, if applicable: a) If Method SA-2 or SA-2 Alternative was used, add $10 \log(1/x)$, where x is the duty cycle, to the peak of the spectrum. b) If Method SA-3 Alternative was used and the linear mode was used in step E)2)g)(viii), add 1 dB to the final result to compensate for the difference between linear averaging and power averaging. 4) The result is the PSD.
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Measurement Data**Band 1 (5150-5250 MHz) SISO:**


Condition	Antenna	Modulation	Frequency (MHz)	PSD(dBm/MHz)	Duty factor(dB)	Total PSD(dBm/MHz)	limit(dBm)	Result
NVNT	ANT1	802.11a	5180.00	-6.66	0.18	-6.48	11	Pass
NVNT	ANT1	802.11a	5200.00	-9.98	0.15	-9.83	11	Pass
NVNT	ANT1	802.11a	5240.00	-9.25	0.15	-9.10	11	Pass
NVNT	ANT1	802.11n(HT20)	5180.00	-12.22	0.16	-12.06	11	Pass
NVNT	ANT1	802.11n(HT20)	5200.00	-12.42	0.20	-12.22	11	Pass
NVNT	ANT1	802.11n(HT20)	5240.00	-11.51	0.20	-11.31	11	Pass
NVNT	ANT1	802.11ac(VHT20)	5180.00	-15.75	0.51	-15.24	11	Pass
NVNT	ANT1	802.11ac(VHT20)	5200.00	-15.84	0.43	-15.41	11	Pass
NVNT	ANT1	802.11ac(VHT20)	5240.00	-14.59	0.51	-14.08	11	Pass
NVNT	ANT1	802.11n(HT40)	5190.00	-16.39	0.39	-16.00	11	Pass
NVNT	ANT1	802.11n(HT40)	5230.00	-15.56	0.39	-15.17	11	Pass
NVNT	ANT1	802.11ac(VHT40)	5190.00	-20.17	0.90	-19.27	11	Pass
NVNT	ANT1	802.11ac(VHT40)	5230.00	-18.76	0.62	-18.14	11	Pass
NVNT	ANT1	802.11ac(VHT80)	5210.00	-29.09	1.25	-27.84	11	Pass




Power Spectral Density NVNT_ANT1_802_11a_5180




Power Spectral Density NVNT_ANT1_802_11a_5200




Power Spectral Density NVNT_ANT1_802_11a_5240




Power Spectral Density NVNT_ANT1_802_11n(HT20)_5180



Power Spectral Density NVNT_ANT1_802_11n(HT20)_5200



Power Spectral Density NVNT_ANT1_802_11n(HT20)_5240




Power Spectral Density_NVNT_ANT1_802_11ac(VHT20)_5180




Power Spectral Density_NVNT_ANT1_802_11ac(VHT20)_5200



Power Spectral Density_NVNT_ANT1_802_11ac(VHT20)_5240




Power Spectral Density_NVNT_ANT1_802_11n(HT40)_5190



Power Spectral Density_NVNT_ANT1_802_11n(HT40)_5230




Power Spectral Density_NVNT_ANT1_802_11ac(VHT40)_5190



Power Spectral Density_NVNT_ANT1_802_11ac(VHT40)_5230





Power Spectral Density_NVNT_ANT1_802_11ac(VHT80)_5210




Band 4 (5725 – 5850 MHz) SISO:

Antenna	Modulation	Frequency (MHz)	PSD_SA(dBm/RBW)	Duty factor(dB)	RB factor(dB)	PSD(dBm/500kHz)	limit(dBm/500kHz)	Result
ANT1	802.11a	5745.00	-10.63	0.18	-0	-10.54	30	Pass
ANT1	802.11a	5785.00	-10.66	0.18	-0	-10.57	30	Pass
ANT1	802.11a	5825.00	-9.74	0.18	-0	-9.65	30	Pass
ANT1	802.11n(HT20)	5745.00	-12.57	0.20	-0	-12.46	30	Pass
ANT1	802.11n(HT20)	5785.00	-10.58	0.13	-0	-10.54	30	Pass
ANT1	802.11n(HT20)	5825.00	-11.40	0.20	-0	-11.29	30	Pass
ANT1	802.11ac(VHT20)	5745.00	-15.13	0.51	-0	-14.70	30	Pass
ANT1	802.11ac(VHT20)	5785.00	-14.73	0.35	-0	-14.46	30	Pass
ANT1	802.11ac(VHT20)	5825.00	-13.40	0.51	-0	-12.98	30	Pass
ANT1	802.11n(HT40)	5755.00	-16.27	0.26	-0	-16.10	30	Pass
ANT1	802.11n(HT40)	5795.00	-15.39	0.38	-0	-15.10	30	Pass
ANT1	802.11ac(VHT40)	5755.00	-19.64	0.90	-0	-18.82	30	Pass
ANT1	802.11ac(VHT40)	5795.00	-19.53	0.90	-0	-18.71	30	Pass
ANT1	802.11ac(VHT80)	5775.00	-28.54	1.38	-0	-27.24	30	Pass








Power_Spectral_Density_NVNT_ANT1_802_11a_5825




Power Spectral Density NVNT_ANT1_802_11n(HT20)_5785




Power Spectral Density NVNT_ANT1_802_11ac(VHT20)_5745



Power Spectral Density NVNT_ANT1_802_11ac(VHT20)_5825




Power Spectral Density NVNT_ANT1_802_11n(HT40)_5795



Power Spectral Density_NVNT_ANT1_802_11ac(VHT40)_5795




Power Spectral Density_NVNT_ANT1_802_11ac(VHT80)_5775



4.6 Band Edge

Test Requirement:	FCC Part15 E Section 15.407 and 15.205, RSS-Gen §8.9																								
Test Method:	ANSI C63.10:2013																								
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																								
Receiver setup:	<table><tr><td>Frequency</td><td>Detector</td><td>RBW</td><td>VBW</td><td>Remark</td></tr><tr><td>30MHz-1GHz</td><td>Quasi-peak</td><td>100KHz</td><td>300KHz</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>Peak</td><td>1MHz</td><td>3MHz</td><td>Peak Value</td></tr><tr><td>AV</td><td>1MHz</td><td>3MHz</td><td>Average Value</td></tr></table>					Frequency	Detector	RBW	VBW	Remark	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value	AV	1MHz	3MHz	Average Value	
Frequency	Detector	RBW	VBW	Remark																					
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value																					
Above 1GHz	Peak	1MHz	3MHz	Peak Value																					
	AV	1MHz	3MHz	Average Value																					
Limit:	<table><tr><td>Frequency</td><td>Limit (dBuV/m @3m)</td><td>Remark</td></tr><tr><td>30MHz-88MHz</td><td>40.0</td><td>Quasi-peak Value</td></tr><tr><td>88MHz-216MHz</td><td>43.5</td><td>Quasi-peak Value</td></tr><tr><td>216MHz-960MHz</td><td>46.0</td><td>Quasi-peak Value</td></tr><tr><td>960MHz-1GHz</td><td>54.0</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>54.0</td><td>Average Value</td></tr><tr><td>68.2</td><td>Peak Value</td></tr></table> Undesirable emission limits: (1) For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz. (2) For transmitters operating in the 5.25-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5.25-5.35 GHz band that generate emissions in the 5.15-5.25 GHz band must meet all applicable technical requirements for operation in the 5.15-5.25 GHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5.15-5.25 GHz band. (3) For transmitters operating in the 5.47-5.725 GHz band: all emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz. (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.					Frequency	Limit (dBuV/m @3m)	Remark	30MHz-88MHz	40.0	Quasi-peak Value	88MHz-216MHz	43.5	Quasi-peak Value	216MHz-960MHz	46.0	Quasi-peak Value	960MHz-1GHz	54.0	Quasi-peak Value	Above 1GHz	54.0	Average Value	68.2	Peak Value
Frequency	Limit (dBuV/m @3m)	Remark																							
30MHz-88MHz	40.0	Quasi-peak Value																							
88MHz-216MHz	43.5	Quasi-peak Value																							
216MHz-960MHz	46.0	Quasi-peak Value																							
960MHz-1GHz	54.0	Quasi-peak Value																							
Above 1GHz	54.0	Average Value																							
	68.2	Peak Value																							
Test Procedure:	a. The EUT was placed on the top of a rotating table 1.5 m above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values																								

	of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test setup:	Above 1GHz 
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Remark:

According to KDB 789033 D02 v02r01 section G) 1) (d), for For measurements above 1000 MHz @ 3m distance, the limit of field strength is computed as follows:

$E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2,$

For example, if $\text{EIRP} = -27\text{dBm}$

$E[\text{dBuV/m}] = -27 + 95.2 = 68.2\text{dBuV/m}.$

Measurement Data:**Band1**

Mode:		802.11a		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	54.12	-13.16	40.96	68.20	-27.24	PK
V	5150.00	57.11	-13.16	43.95	68.20	-24.25	PK
Mode:		802.11a		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	46.34	-13.16	33.18	54.00	-20.82	AV
V	5150.00	46.24	-13.16	33.08	54.00	-20.92	AV
Mode:		802.11a		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	55.61	-12.62	42.99	68.20	-25.21	PK
V	5350.00	54.99	-12.62	42.37	68.20	-25.83	PK
Mode:		802.11a		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	47.49	-12.62	34.87	54.00	-19.13	AV
V	5350.00	48.02	-12.62	35.40	54.00	-18.60	AV

Mode:		802.11n(HT20)		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	54.30	-13.16	41.14	68.20	-27.06	PK
V	5150.00	55.19	-13.16	42.03	68.20	-26.17	PK
Mode:		802.11n(HT20)		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	46.84	-13.16	33.68	54.00	-20.32	AV
V	5150.00	48.97	-13.16	35.81	54.00	-18.19	AV
Mode:		802.11n(HT20)		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	53.74	-12.62	41.12	68.20	-27.08	PK
V	5350.00	60.14	-12.62	47.52	68.20	-20.68	PK
Mode:		802.11n(HT20)		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	47.26	-12.62	34.64	54.00	-19.36	AV
V	5350.00	46.90	-12.62	34.28	54.00	-19.72	AV

Mode:		802.11ac(HT20)		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	56.53	-13.16	43.37	68.20	-24.83	PK
V	5150.00	57.28	-13.16	44.12	68.20	-24.08	PK
Mode:		802.11ac(HT20)		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	46.94	-13.16	33.78	54.00	-20.22	AV
V	5150.00	47.10	-13.16	33.94	54.00	-20.06	AV
Mode:		802.11ac(HT20)		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	55.98	-12.62	43.36	68.20	-24.84	PK
V	5350.00	56.66	-12.62	44.04	68.20	-24.16	PK
Mode:		802.11ac(HT20)		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	47.02	-12.62	34.40	54.00	-19.60	AV
V	5350.00	47.72	-12.62	35.10	54.00	-18.90	AV



Mode:		802.11n(HT40)		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	56.98	-13.16	43.82	68.20	-24.38	PK
V	5150.00	56.63	-13.16	43.47	68.20	-24.73	PK
Mode:		802.11n(HT40)		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	47.96	-13.16	34.80	54.00	-19.20	AV
V	5150.00	47.83	-13.16	34.67	54.00	-19.33	AV
Mode:		802.11n(HT40)		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	54.59	-12.62	41.97	68.20	-26.23	PK
V	5350.00	59.25	-12.62	46.63	68.20	-21.57	PK
Mode:		802.11n(HT40)		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	47.57	-12.62	34.95	54.00	-19.05	AV
V	5350.00	46.54	-12.62	33.92	54.00	-20.08	AV



Mode:		802.11ac(HT40)		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	53.65	-13.16	40.49	68.20	-27.71	PK
V	5150.00	56.12	-13.16	42.96	68.20	-25.24	PK
Mode:		802.11ac(HT40)		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	44.85	-13.16	31.69	54.00	-22.31	AV
V	5150.00	46.70	-13.16	33.54	54.00	-20.46	AV
Mode:		802.11ac(HT40)		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	56.13	-12.62	43.51	68.20	-24.69	PK
V	5350.00	57.44	-12.62	44.82	68.20	-23.38	PK
Mode:		802.11ac(HT40)		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	44.72	-12.62	32.10	54.00	-21.90	AV
V	5350.00	46.23	-12.62	33.61	54.00	-20.39	AV



Mode:		802.11ac(HT80)		Frequency:		5210MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	56.42	-13.16	43.26	68.20	-24.94	PK
V	5150.00	55.90	-13.16	42.74	68.20	-25.46	PK
Mode:		802.11ac(HT80)		Frequency:		5210MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	44.66	-13.16	31.50	54.00	-22.50	AV
V	5150.00	46.59	-13.16	33.43	54.00	-20.57	AV
Mode:		802.11ac(HT80)		Frequency:		5210MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	55.65	-12.62	43.03	68.20	-25.17	PK
V	5350.00	57.30	-12.62	44.68	68.20	-23.52	PK
Mode:		802.11ac(HT80)		Frequency:		5210MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	46.18	-12.62	33.56	54.00	-20.44	AV
V	5350.00	48.62	-12.62	36.00	54.00	-18.00	AV



Band4



Condition	Antenna	Modulation	TX_Frequency (MHz)	Frequency Area(MHz)	Frequency(MHz)	Amplitude(dBm)	Limit(dBm)	Result
NVNT	ANT1	802.11a	LCH	5565-5655	5576.790	-51.06	-27.00	Pass
NVNT	ANT1	802.11a	LCH	5655-5700	5655.360	-51.13	-26.70	Pass
NVNT	ANT1	802.11a	LCH	5700-5720	5700.880	-51.03	10.25	Pass
NVNT	ANT1	802.11a	LCH	5720-5725	5720.570	-50.28	16.90	Pass
NVNT	ANT1	802.11a	HCH	5850-5855	5854.955	-49.79	15.70	Pass
NVNT	ANT1	802.11a	HCH	5855-5875	5872.380	-49.41	10.73	Pass
NVNT	ANT1	802.11a	HCH	5875-5920	5905.060	-50.13	-14.72	Pass
NVNT	ANT1	802.11a	HCH	5920-6005	5921.275	-45.91	-27.00	Pass
NVNT	ANT1	802.11n(HT20)	LCH	5565-5655	5580.930	-50.58	-27.00	Pass
NVNT	ANT1	802.11n(HT20)	LCH	5655-5700	5658.825	-50.73	-23.86	Pass
NVNT	ANT1	802.11n(HT20)	LCH	5700-5720	5706.240	-50.38	11.75	Pass
NVNT	ANT1	802.11n(HT20)	LCH	5720-5725	5721.475	-49.72	18.96	Pass
NVNT	ANT1	802.11n(HT20)	HCH	5850-5855	5854.720	-49.22	16.24	Pass
NVNT	ANT1	802.11n(HT20)	HCH	5855-5875	5874.400	-49.89	10.17	Pass
NVNT	ANT1	802.11n(HT20)	HCH	5875-5920	5905.690	-48.97	-15.23	Pass
NVNT	ANT1	802.11n(HT20)	HCH	5920-6005	5947.965	-46.22	-27.00	Pass
NVNT	ANT1	802.11ac(VHT20)	LCH	5565-5655	5637.900	-50.78	-27.00	Pass
NVNT	ANT1	802.11ac(VHT20)	LCH	5655-5700	5661.885	-50.38	-21.34	Pass
NVNT	ANT1	802.11ac(VHT20)	LCH	5700-5720	5700.420	-50.45	10.12	Pass
NVNT	ANT1	802.11ac(VHT20)	LCH	5720-5725	5720.685	-49.74	17.16	Pass
NVNT	ANT1	802.11ac(VHT20)	HCH	5850-5855	5854.985	-49.85	15.63	Pass
NVNT	ANT1	802.11ac(VHT20)	HCH	5855-5875	5873.220	-49.57	10.50	Pass
NVNT	ANT1	802.11ac(VHT20)	HCH	5875-5920	5917.480	-49.85	-24.93	Pass
NVNT	ANT1	802.11ac(VHT20)	HCH	5920-6005	5927.820	-45.54	-27.00	Pass
NVNT	ANT1	802.11n(HT40)	LCH	5595-5655	5627.100	-50.44	-27.00	Pass
NVNT	ANT1	802.11n(HT40)	LCH	5655-5700	5656.035	-50.24	-26.15	Pass
NVNT	ANT1	802.11n(HT40)	LCH	5700-5720	5704.360	-50.34	11.22	Pass
NVNT	ANT1	802.11n(HT40)	LCH	5720-5725	5723.190	-49.07	22.87	Pass
NVNT	ANT1	802.11n(HT40)	HCH	5850-5855	5854.325	-48.95	17.14	Pass
NVNT	ANT1	802.11n(HT40)	HCH	5855-5875	5873.340	-49.38	10.46	Pass
NVNT	ANT1	802.11n(HT40)	HCH	5875-5920	5907.580	-49.73	-16.79	Pass
NVNT	ANT1	802.11n(HT40)	HCH	5920-5955	5946.005	-44.47	-27.00	Pass
NVNT	ANT1	802.11ac(VHT40)	LCH	5595-5655	5614.320	-50.81	-27.00	Pass
NVNT	ANT1	802.11ac(VHT40)	LCH	5655-5700	5661.255	-50.69	-21.86	Pass
NVNT	ANT1	802.11ac(VHT40)	LCH	5700-5720	5702.940	-50.31	10.82	Pass
NVNT	ANT1	802.11ac(VHT40)	LCH	5720-5725	5720.870	-48.44	17.58	Pass
NVNT	ANT1	802.11ac(VHT40)	HCH	5850-5855	5854.985	-48.77	15.63	Pass
NVNT	ANT1	802.11ac(VHT40)	HCH	5855-5875	5874.940	-49.40	10.02	Pass
NVNT	ANT1	802.11ac(VHT40)	HCH	5875-5920	5905.600	-49.69	-15.16	Pass
NVNT	ANT1	802.11ac(VHT40)	HCH	5920-5955	5936.135	-45.53	-27.00	Pass
NVNT	ANT1	802.11ac(VHT80)	MCH	5650-5655	5650.875	-50.79	-27.00	Pass
NVNT	ANT1	802.11ac(VHT80)	MCH	5655-5700	5667.960	-50.74	-16.34	Pass
NVNT	ANT1	802.11ac(VHT80)	MCH	5700-5720	5711.580	-49.49	13.24	Pass
NVNT	ANT1	802.11ac(VHT80)	MCH	5720-5725	5721.525	-48.71	19.08	Pass
NVNT	ANT1	802.11ac(VHT80)	MCH	5850-5855	5854.435	-48.51	16.89	Pass
NVNT	ANT1	802.11ac(VHT80)	MCH	5855-5875	5872.660	-49.10	10.66	Pass
NVNT	ANT1	802.11ac(VHT80)	MCH	5875-5920	5920.000	-49.55	-27.00	Pass
NVNT	ANT1	802.11ac(VHT80)	MCH	5920-5925	5923.615	-44.68	-27.00	Pass
















4.7 Radiated Emission

Test Requirement:	FCC Part15 C Section 15.209 and 15.205, RSS-Gen §8.9				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	30MHz to 40GHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		AV	1MHz	3MHz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		74.0		Peak Value
			54.0		Average Value
Test Procedure:	Substitution method was performed to determine the actual ERP emission levels of the EUT. The following test procedure as below: 1>.Below 1GHz test procedure: 1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 2>.Above 1GHz test procedure: 1. On the test site as test setup graph above,the EUT shall be placed at the 1.5m support on the turntable and in the position closest to normal use as declared by the provider. 2. The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter.The output of the test antenna shall be connected to the measuring receiver.				

	3. The transmitter shall be switched on, if possible, without modulation and the measuring receiver shall be tuned to the frequency of the transmitter under test. 4. The test antenna shall be raised and lowered from 1m to 4m until a maximum signal level is detected by the measuring receiver. Then the turntable should be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver. 5. Repeat step 4 for test frequency with the test antenna polarized horizontally. 6. Remove the transmitter and replace it with a substitution antenna 7. Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a nonradiating cable. With the antennas at both ends vertically polarized, and with the signal generator tuned to a particular test frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output. 8. Repeat step 7 with both antennas horizontally polarized for each test frequency. 9. Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps 7 and 8 by the power loss in the cable between the generator and the antenna, and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna by the following formula: $\text{EIRP(dBm)} = \text{Pg(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dBi)}$ where: Pg is the generator output power into the substitution antenna.
Test setup:	Below 1GHz  Above 1GHz

	
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Measurement Data:**Below 1GHz**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
33.97	48.59	11.42	0.76	30.25	30.52	40	-9.48	Vertical
55.39	41.39	12.35	1.23	30.38	24.59	40	-15.41	Vertical
120.86	46.49	9.90	1.86	30.07	28.18	43.5	-15.32	Vertical
172.34	43.32	8.96	2.16	29.77	24.68	43.5	-18.82	Vertical
440.29	37.36	16.60	3.36	29.72	27.60	46	-18.40	Vertical
861.01	33.12	22.02	4.88	29.33	30.69	46	-15.31	Vertical
65.16	35.94	8.97	1.14	30.13	15.91	40	-24.09	Horizontal
99.89	33.87	11.98	1.44	29.95	17.35	43.5	-26.15	Horizontal
269.51	45.22	12.92	2.61	30.18	30.57	46	-15.43	Horizontal
351.06	37.12	14.84	2.96	30.07	24.85	46	-21.15	Horizontal
627.93	36.26	19.90	4.30	29.74	30.72	46	-15.28	Horizontal
956.14	40.62	22.59	5.11	29.15	39.18	46	-6.82	Horizontal

Above 1GHz:**802.11a 5180MHz**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.82	50.79	11.26	14.99	33.12	43.91	68.2	-24.29	Vertical
15540.04	51.23	12.10	17.67	34.84	46.17	74	-27.83	Vertical
10360.38	52.40	9.44	14.94	33.01	43.76	68.2	-24.44	Horizontal
15540.98	53.18	8.72	17.96	34.48	45.38	74	-28.62	Horizontal

802.11a 5200MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.39	50.23	11.35	14.69	32.87	43.40	68.2	-24.80	Vertical
15540.57	51.64	12.22	18.02	34.55	47.33	74	-26.67	Vertical
10360.79	52.44	9.67	15.11	33.14	44.08	68.2	-24.12	Horizontal
15540.32	53.94	8.52	18.05	34.85	45.66	74	-28.34	Horizontal

802.11a 5240MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.01	50.55	11.42	15.03	33.15	43.85	68.2	-24.35	Vertical
15540.68	51.61	12.31	17.68	34.59	47.01	74	-26.99	Vertical
10360.93	52.73	9.48	14.87	32.75	44.34	68.2	-23.86	Horizontal
15540.79	53.46	8.89	17.99	34.85	45.49	74	-28.51	Horizontal

802.11n(HT20) 5180MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.93	50.20	11.68	14.72	32.86	43.73	68.2	-24.47	Vertical
15540.92	51.42	12.36	18.08	34.85	47.01	74	-26.99	Vertical
10360.86	52.93	9.67	14.94	32.74	44.79	68.2	-23.41	Horizontal
15540.32	53.65	8.63	17.77	34.63	45.41	74	-28.59	Horizontal

802.11n(HT20) 5200MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.47	50.03	11.49	14.70	32.78	43.45	68.2	-24.75	Vertical
15540.79	51.09	12.20	17.67	34.50	46.47	74	-27.53	Vertical
10360.07	52.16	9.87	14.95	33.01	43.97	68.2	-24.23	Horizontal
15540.49	53.16	8.95	17.98	34.65	45.44	74	-28.56	Horizontal

802.11n(HT20) 5240MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.32	50.03	11.54	15.02	33.05	43.55	68.2	-24.65	Vertical
15540.77	51.08	12.33	17.95	34.79	46.57	74	-27.43	Vertical
10360.03	52.57	9.82	14.74	32.78	44.35	68.2	-23.85	Horizontal
15540.23	53.52	8.70	18.01	34.67	45.56	74	-28.44	Horizontal

802.11ac(HT20) 5180MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.65	50.01	11.73	14.63	33.07	43.30	68.2	-24.90	Vertical
15540.80	51.97	12.38	17.92	34.82	47.45	74	-26.55	Vertical
10360.21	52.35	9.81	14.81	33.10	43.87	68.2	-24.33	Horizontal
15540.01	53.30	8.81	18.12	34.56	45.67	74	-28.33	Horizontal

802.11ac(HT20) 5200MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.54	50.27	11.29	14.99	32.69	43.85	68.2	-24.35	Vertical
15540.81	51.69	11.98	18.06	34.57	47.17	74	-26.83	Vertical
10360.11	52.37	9.56	15.10	32.97	44.06	68.2	-24.14	Horizontal
15540.01	53.13	8.92	18.05	34.63	45.47	74	-28.53	Horizontal

802.11ac(HT20) 5240MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.94	50.66	11.47	15.11	32.67	44.57	68.2	-23.63	Vertical
15540.77	51.93	12.00	17.95	34.52	47.36	74	-26.64	Vertical
10360.39	52.94	9.58	14.75	32.80	44.46	68.2	-23.74	Horizontal
15540.33	53.52	8.80	18.13	34.83	45.63	74	-28.37	Horizontal

802.11n(HT40) 5190MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.44	50.48	11.32	15.09	32.90	44.00	68.2	-24.20	Vertical
15540.81	51.43	12.25	17.81	34.91	46.59	74	-27.41	Vertical
10360.77	52.95	9.82	14.95	33.03	44.69	68.2	-23.51	Horizontal
15540.55	53.55	8.89	17.69	34.95	45.19	74	-28.81	Horizontal

802.11n(HT40) 5230MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.00	50.47	11.34	14.87	32.87	43.81	68.2	-24.39	Vertical
15540.79	51.99	12.26	17.67	34.75	47.17	74	-26.83	Vertical
10360.19	52.52	9.79	14.80	33.10	44.01	68.2	-24.19	Horizontal
15540.25	53.74	8.72	17.81	34.55	45.72	74	-28.28	Horizontal

802.11ac(HT40) 5190MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.27	50.55	11.70	15.07	33.02	44.30	68.2	-23.90	Vertical
15540.71	51.59	12.33	17.79	34.82	46.89	74	-27.11	Vertical
10360.42	52.55	9.88	14.72	32.82	44.33	68.2	-23.87	Horizontal
15540.70	53.02	8.69	17.96	34.80	44.86	74	-29.14	Horizontal

802.11ac(HT40) 5230MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.98	50.92	11.61	15.06	33.10	44.48	68.2	-23.72	Vertical
15540.29	51.45	12.29	18.03	34.62	47.14	74	-26.86	Vertical
10360.88	52.09	9.42	14.91	33.06	43.37	68.2	-24.83	Horizontal
15540.29	53.59	8.76	17.71	34.86	45.20	74	-28.80	Horizontal

802.11ac(HT80) 5210MHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360.80	50.57	11.70	15.07	32.73	44.60	68.2	-23.60	Vertical
15540.43	51.63	12.13	18.03	34.84	46.95	74	-27.05	Vertical
10360.78	52.40	9.58	14.92	32.65	44.25	68.2	-23.95	Horizontal
15540.38	53.81	8.82	18.06	34.71	45.98	74	-28.02	Horizontal

Note:

1. Level = Read Level + Antenna Factor+ Cable loss- Preamp Factor.
2. The test trace is same as the ambient noise (the test frequency range: 18GHz~40GHz), therefore no data appear in the report.
3. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.
4. This Report only show the test plots of the worst case (U-NII-1).

4.8 Frequency stability

Test Standard	15.407(f), RSS-Gen §6.11
Test limit	Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.
Test results:	Pass

Measurement Data:

Mode	Voltage (V)	FHL (5180MHz)	Deviation (KHz)	FHH (5240MHz)	Deviation (KHz)
Band 1 (5150-5250 MHz)	DC 10.8V	5179.995	5	5239.994	6
	DC 12.0V	5179.993	7	5239.998	2
	DC 13.2V	5179.993	7	5239.991	9
Mode	Voltage (V)	FHL (5745MHz)	Deviation (KHz)	FHH (5825MHz)	Deviation (KHz)
Band 4 (5725-5850 MHz)	DC 10.8V	5744.998	2	5824.992	8
	DC 12.0V	5744.993	7	5824.993	7
	DC 13.2V	5744.999	1	5824.998	2

Mode	Temperature (°C)	FHL (5180MHz)	Deviation (KHz)	FHH (5240MHz)	Deviation (KHz)
Band 1 (5150-5250 MHz)	-10°C	5179.992	8	5239.993	7
	0°C	5179.993	7	5239.994	6
	+10°C	5179.993	7	5239.991	9
	+20°C	5179.999	1	5239.992	8
	+30°C	5179.992	8	5239.993	7
	+40°C	5179.997	3	5239.993	7
	+50°C	5179.991	9	5239.998	2
Mode	Temperature (°C)	FHL (5745MHz)	Deviation (KHz)	FHH (5825MHz)	Deviation (KHz)
Band 4 (5725-5850 MHz)	-10°C	5744.992	8	5824.997	3
	0°C	5744.995	5	5824.993	7
	+10°C	5744.993	7	5824.997	3
	+20°C	5744.991	9	5824.998	2
	+30°C	5744.994	6	5824.994	6
	+40°C	5744.998	2	5824.997	3
	+50°C	5744.993	7	5824.996	4

5 Photos Of Test Setup

Reference to the **appendix I Test Setup Photo** for details.

6 Photos Of EUT

Reference to the **appendix II external photos** and **appendix III internal photos** for details.

-----END OF REPORT-----

