



AUDEN COMMUNICATIONS&MULTIMEDIA
TECHNO (KUNSHAN) CO. LTD

Leopard Lync B920NA
BT Antenna specification

4 pages

(Including cover sheet)

Author Liu Jing




AUDEN COMMUNICATIONS&MULTIMEDIA TECHNO (KUNSHAN) CO. LTD

Catalogue

1. Antenna voltage standing wave ratio	3
2. Antenna efficiency and gains	3
3. Structure chart	4

AUDEN COMMUNICATIONS&MULTIMEDIA TECHNO (KUNSHAN) CO. LTD

1. Antenna voltage standing wave ratio







2. Antenna efficiency and gains

Frequency / MHz	Efficiency / dB	Efficiency / %	Gain/ dBi
2400	-4.74	33.57	-0.78
2410	-4.72	33.73	-1.09
2420	-4.69	33.96	-0.1
2430	-3.89	40.83	-0.1
2440	-3.94	40.36	-0.41
2450	-3.87	41.02	-0.58
2460	-3.82	41.5	-0.43
2470	-3.68	42.85	-0.14
2480	-3.89	40.83	0
2490	-3.75	42.17	-0.37
2500	-3.66	43.05	-0.16

AUDEN COMMUNICATIONS&MULTIMEDIA
TECHNO (KUNSHAN) CO. LTD

3. Structure chart

1		2		3		4	
Customer Part No	product name	Spec Type	ECN	EDITION	AREA	DATE	CONTENT OF CHANG
I.31.20.01.00246	MT116-BT-V2.0 BT	MT116-BT-V2.0		SP00		8/28/2023	New issue

A		B		C		D	
							

Requirements of environmental conditions:	
Qd	< 100 ppm
Ps	< 1000 ppm
Pa	< 1000 ppm
Q(V)	< 1000 ppm
PSB	< 1000 ppm
FEDEs	< 1000 ppm
DEHP	< 1000 ppm
BSP	< 1000 ppm
DBP	< 1000 ppm
DBP	< 1000 ppm

Assumes: The product must conform to the appearance of design. Inspection standard is not reliability test requirements.	
IF	IF
BR<900, CL<900, BRVCL<1600	IF

DIMENSION TOLERANCE	
≤6	±0.05
6<30	±0.1
30<120	±0.15
120<315	±0.20
315<1000	±0.3
1000<2000	±0.5





S/N		Material		Surface Treatment		Part No	
Name		Drawing No		Part No		Application No	
BT		SUS304		A42023-00		BT	
ASM		/		/		AUX02348	

Material		Unit		Document Number/Revision	
/		MM Scale 1:1		AD-QP-0002-24/B	

Total		Check		Approval	
1 pages		1 pages		pages 1	

auden		AUDEN TECHNO (KUNSHAN) CO. LTD	
AD-QP-0002-24/B		Approval	

1		2		3		4	
Customer Part No		product name		Spec Type		ECN	
I.31.20.01.00246		MT116-BT-V2.0 BT		MT116-BT-V2.0			

A		B		C		D	
							

Requirements of environmental conditions:	
Qd	< 100 ppm
Ps	< 1000 ppm
Pa	< 1000 ppm
Q(V)	< 1000 ppm
PSB	< 1000 ppm
FEDEs	< 1000 ppm
DEHP	< 1000 ppm
BSP	< 1000 ppm
DBP	< 1000 ppm
DBP	< 1000 ppm

Assumes: The product must conform to the appearance of design. Inspection standard is not reliability test requirements.	
IF	IF
BR<900, CL<900, BRVCL<1600	IF

DIMENSION TOLERANCE	
≤6	±0.05
6<30	±0.1
30<120	±0.15
120<315	±0.20
315<1000	±0.3
1000<2000	±0.5





S/N		Material		Surface Treatment		Part No	
Name		Drawing No		Part No		Application No	
BT		SUS304		A42023-00		BT	
ASM		/		/		AUX02348	

Material		Unit		Document Number/Revision	
/		MM Scale 1:1		AD-QP-0002-24/B	

Total		Check		Approval	
1 pages		1 pages		pages 1	

auden		AUDEN TECHNO (KUNSHAN) CO. LTD	
AD-QP-0002-24/B		Approval	

1		2		3		4	
Customer Part No		product name		Spec Type		ECN	
I.31.20.01.00246		MT116-BT-V2.0 BT		MT116-BT-V2.0			

A		B		C		D	
							

Requirements of environmental conditions:	
Qd	< 100 ppm
Ps	< 1000 ppm
Pa	< 1000 ppm
Q(V)	< 1000 ppm
PSB	< 1000 ppm
FEDEs	< 1000 ppm
DEHP	< 1000 ppm
BSP	< 1000 ppm
DBP	< 1000 ppm
DBP	< 1000 ppm

Assumes: The product must conform to the appearance of design. Inspection standard is not reliability test requirements.	
IF	IF
BR<900, CL<900, BRVCL<1600	IF

DIMENSION TOLERANCE	
≤6	±0.05
6<30	±0.1
30<120	±0.15
120<315	±0.20
315<1000	±0.3
1000<2000	±0.5





S/N		Material		Surface Treatment		Part No	
Name		Drawing No		Part No		Application No	
BT		SUS304		A42023-00		BT	
ASM		/		/		AUX02348	

Material		Unit		Document Number/Revision	
/		MM Scale 1:1		AD-QP-0002-24/B	

Total		Check		Approval	
1 pages		1 pages		pages 1	

auden		AUDEN TECHNO (KUNSHAN) CO. LTD	
AD-QP-0002-24/B		Approval	

1		2		3		4	
Customer Part No		product name		Spec Type		ECN	
I.31.20.01.00246		MT116-BT-V2.0 BT		MT116-BT-V2.0			

A		B		C		D	
							

Requirements of environmental conditions:	
Qd	< 100 ppm
Ps	< 1000 ppm
Pa	< 1000 ppm
Q(V)	< 1000 ppm
PSB	< 1000 ppm
FEDEs	< 1000 ppm
DEHP	< 1000 ppm
BSP	< 1000 ppm
DBP	< 1000 ppm
DBP	< 1000 ppm

Assumes: The product must conform to the appearance of design. Inspection standard is not reliability test requirements.	
IF	IF
BR<900, CL<900, BRVCL<1600	IF

DIMENSION TOLERANCE	
≤6	±0.05
6<30	±0.1
30<120	±0.15
120<315	±0.20
315<1000	±0.3
1000<2000	±0.5





S/N		Material		Surface Treatment		Part No	
Name		Drawing No		Part No		Application No	
BT		SUS304		A42023-00		BT	
ASM		/		/		AUX02348	

Material		Unit		Document Number/Revision	
/		MM Scale 1:1		AD-QP-0002-24/B	

Total		Check		Approval	
1 pages		1 pages		pages 1	

auden		AUDEN TECHNO (KUNSHAN) CO. LTD	
AD-QP-0002-24/B		Approval	

1		2		3		4	
Customer Part No		product name		Spec Type		ECN	
I.31.20.01.00246		MT116-BT-V2.0 BT		MT116-BT-V2.0			

A		B		C		D	
							

Requirements of environmental conditions:	
Qd	< 100 ppm
Ps	< 1000 ppm
Pa	< 1000 ppm
Q(V)	< 1000 ppm
PSB	< 1000 ppm
FEDEs	< 1000 ppm
DEHP	< 1000 ppm
BSP	< 1000 ppm
DBP	< 1000 ppm
DBP	< 1000 ppm

Assumes: The product must conform to the appearance of design. Inspection standard is not reliability test requirements.	
IF	IF
BR<900, CL<900, BRVCL<1600	IF

DIMENSION TOLERANCE	
≤6	±0.05
6<30	±0.1
30<120	±0.15
120<315	±0.20
315<1000	±0.3
1000<2000	±0.5





S/N		Material		Surface Treatment		Part No	
Name		Drawing No		Part No		Application No	
BT		SUS304		A42023-00		BT	
ASM		/		/		AUX02348	

Material		Unit		Document Number/Revision	
/		MM Scale 1:1		AD-QP-0002-24/B	

Total		Check		Approval	
1 pages		1 pages		pages 1	

auden		AUDEN TECHNO (KUNSHAN) CO. LTD	
AD-QP-0002-24/B		Approval	

1		2		3		4	
Customer Part No		product name		Spec Type		ECN	
I.31.20.01.00246		MT116-BT-V2.0 BT		MT116-BT-V2.0			

A		B		C		D	
							

Requirements of environmental conditions:	
Qd	< 100 ppm
Ps	< 1000 ppm
Pa	< 1000 ppm
Q(V)	< 1000 ppm
PSB	< 1000 ppm
FEDEs	< 1000 ppm
DEHP	< 1000 ppm
BSP	< 1000 ppm
DBP	< 1000 ppm
DBP	< 1000 ppm

Assumes: The product must conform to the appearance of design. Inspection standard is not reliability test requirements.	
IF	IF
BR<900, CL<900, BRVCL<1600	IF

DIMENSION TOLERANCE	
≤6	±0.05
6<30	±0.1
30<120	±0.15
120<315	±0.20
315<1000	±0.3
1000<2000	±0.5





S/N		Material		Surface Treatment		Part No	
Name		Drawing No		Part No		Application No	
BT		SUS304		A42023-00		BT	
ASM		/		/		AUX02348	

Material		Unit		Document Number/Revision	
/		MM Scale 1:1		AD-QP-0002-24/B	

Total		Check		Approval	
1 pages		1 pages		pages 1	

auden		AUDEN TECHNO (KUNSHAN) CO. LTD	
AD-QP-0002-24/B		Approval	

1		2		3		4	
Customer Part No		product name		Spec Type		ECN	
I.31.20.01.00246		MT116-BT-V2.0 BT		MT116-BT-V2.0			

A		B		C		D	
							

Requirements of environmental conditions:	
Qd	< 100 ppm
Ps	< 1000 ppm
Pa	< 1000 ppm
Q(V)	< 1000 ppm
PSB	< 1000 ppm
FEDEs	< 1000 ppm
DEHP	< 1000 ppm
BSP	< 1000 ppm
DBP	< 1000 ppm
DBP	< 1000 ppm

Assumes: The product must conform to the appearance of design. Inspection standard is not reliability test requirements.	
IF	IF
BR<900, CL<900, BRVCL<1600	IF

DIMENSION TOLERANCE	
≤6	±0.05
6<30	±0.1
30<120	±0.15
120<315	±0.20
315<1000	±0.3
1000<2000	±0.5

S/N		Material		Surface Treatment		Part No	
Name		Drawing No		Part No		Application No	
BT		SUS304		A42023-00		BT	
ASM		/		/		AUX02348	

Material		Unit		Document Number/Revision	
/		MM Scale 1:1		AD-QP-0002-24/B	

Total		Check		Approval	
1 pages		1 pages		pages 1	

auden		AUDEN TECHNO (KUNSHAN) CO. LTD	
AD-QP-0002-24/B		Approval	

1		2		3		4	
Customer Part No		product name		Spec Type		ECN	
I.31.20.01.00246		MT116-BT-V2.0 BT		MT116-BT-V2.0			

A		B		C		D	
