



RF TEST REPORT

For

Ligowave Corporation

Product Name: Broadband Digital Transmission System

Model(s): LigoVision 5-15ac Dual, LigoVision 5ac Dual

Report Reference No. : POCE230509562ZRW

FCC ID : 2BCOH-FWBD3210

Applicant's Name : Ligowave Corporation

Address : 1710 Cumberland Point Drive Suite 1 Marietta, GA 30067 United States

Testing Laboratory : Shenzhen POCE Technology Co., Ltd.

Address : 102 Building H1 & 1/F., Building H, Hongfa Science & Technology Park,
Tangtou, Shiyan, Bao'an District, Shenzhen, Guangdong, China

Test Specification Standard : 47 CFR Part 15E

Date of Receipt : May 9, 2023

Date of Test : May 9, 2023 to July 25, 2023

Data of Issue : July 25, 2023

Result : Pass

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen POCE Technology Co., Ltd. This document may be altered or revised by Shenzhen POCE Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample



Revision History Of Report

Version	Description	REPORT No.	Issue Date
V1.0	Original	POCE230509562ZRW	July 25, 2023

NOTE1:

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

Compiled by:

Amy Zhu / File administrators

Supervised by:

Stone Yin / Technique principal

Approved by:

Machael Mo / Manager

CONTENTS

1 TEST SUMMARY	5
1.1 TEST STANDARDS	5
1.2 SUMMARY OF TEST RESULT	5
2 GENERAL INFORMATION	6
2.1 CLIENT INFORMATION	6
2.2 DESCRIPTION OF DEVICE (EUT)	6
2.3 DESCRIPTION OF TEST MODES	8
2.4 DESCRIPTION OF SUPPORT UNITS	8
2.5 EQUIPMENTS USED DURING THE TEST	9
2.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY	13
2.7 IDENTIFICATION OF TESTING LABORATORY	13
2.8 ANNOUNCEMENT	13
3 EVALUATION RESULTS (EVALUATION)	14
3.1 ANTENNA REQUIREMENT	14
3.1.1 Conclusion:	14
4 RADIO SPECTRUM MATTER TEST RESULTS (RF)	15
4.1 CONDUCTED EMISSION AT AC POWER LINE	15
4.1.1 E.U.T. Operation:	15
4.1.2 Test Setup Diagram:	15
4.1.3 Test Data:	16
4.2 DUTY CYCLE	18
4.2.1 E.U.T. Operation:	18
4.2.2 Test Setup Diagram:	18
4.2.3 Test Data:	18
4.3 MAXIMUM CONDUCTED OUTPUT POWER	19
4.3.1 E.U.T. Operation:	20
4.3.2 Test Setup Diagram:	20
4.3.3 Test Data:	20
4.4 POWER SPECTRAL DENSITY	21
4.4.1 E.U.T. Operation:	22
4.4.2 Test Setup Diagram:	22
4.4.3 Test Data:	22
4.5 EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH	23
4.5.1 E.U.T. Operation:	24
4.5.2 Test Setup Diagram:	24
4.5.3 Test Data:	24
4.6 BAND EDGE EMISSIONS (RADIATED)	25
4.6.1 E.U.T. Operation:	26
4.6.2 Test Setup Diagram:	27
4.6.3 Test Data:	28
4.7 UNDESIRABLE EMISSION LIMITS (BELOW 1GHz)	31
4.7.1 E.U.T. Operation:	32
4.7.2 Test Setup Diagram:	33
4.7.3 Test Data:	34
4.8 UNDESIRABLE EMISSION LIMITS (ABOVE 1GHz)	36
4.8.1 E.U.T. Operation:	37
4.8.2 Test Setup Diagram:	38
4.8.3 Test Data:	39
5 TEST SETUP PHOTOS	43



6 PHOTOS OF THE EUT	45
APPENDIX	53
1. -26dB AND 99% EMISSION BANDWIDTH	54
2. -6dB EMISSION BANDWIDTH	91
3. MAXIMUM CONDUCTED OUTPUT POWER	101
4. POWER SPECTRAL DENSITY	103
5. FREQUENCY STABILITY	122

1 TEST SUMMARY

1.1 Test Standards

The tests were performed according to following standards:

47 CFR Part 15E: Unlicensed National Information Infrastructure Devices

1.2 Summary of Test Result

Item	Standard	Requirement	Result
Antenna requirement	47 CFR Part 15E	Part 15.203	Pass
Duty Cycle	47 CFR Part 15E		Pass
Maximum conducted output power	47 CFR Part 15E	47 CFR Part 15.407(a)(1)(i) 47 CFR Part 15.407(a)(3)(i)	Pass
Power spectral density	47 CFR Part 15E	47 CFR Part 15.407(a)(1)(i) 47 CFR Part 15.407(a)(3)(i)	Pass
Emission bandwidth and occupied bandwidth	47 CFR Part 15E	U-NII 1, U-NII 2A, U-NII 2C: No limits, only for report use. 47 CFR Part 15.407(e)	Pass
Band edge emissions (Radiated)	47 CFR Part 15E	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)	Pass
Undesirable emission limits (below 1GHz)	47 CFR Part 15E	47 CFR Part 15.407(b)(9)	Pass
Undesirable emission limits (above 1GHz)	47 CFR Part 15E	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)	Pass
Conducted Emission at AC power line	47 CFR Part 15E	47 CFR Part 15.207(a)	Pass

2 GENERAL INFORMATION

2.1 Client Information

Applicant's Name : Ligowave Corporation
Address : 1710 Cumberland Point Drive Suite 1 Marietta, GA 30067 United States

Manufacturer : Ligowave Corporation
Address : 1710 Cumberland Point Drive Suite 1 Marietta, GA 30067 United States

2.2 Description of Device (EUT)

Product Name:	Broadband Digital Transmission System
Model/Type reference:	LigoVision 5ac Dual
Series Model:	LigoVision 5-15ac Dual
Model difference:	Item No.: LigoVision 5ac Dual, LigoVision 5-15ac Dual were identical inside, the electrical circuit design, layout, wiring, with only difference being as below: 1. antenna gain : LigoVision 5-15ac Dual used 15dBi antenna, LigoVision 5ac Dual used 7dBi antenna. 2. Plastic enclosure
Trade Mark:	N/A
Power Supply:	POE:48V/0.5A from adapter
Power Adaptor:	POE POWER ADAPTER MODEL:GRT-POE20-480050A INPUT:100-240V~50/60Hz 0.5A OUTPUT:48V--0.5A
Operation Frequency:	802.11a/n(HT20)/ac(HT20): U-NII Band 1: 5180MHz to 5240MHz; U-NII Band 3: 5745MHz to 5825MHz; 802.11n(HT40)/ac(HT40): U-NII Band 1: 5190MHz to 5230MHz; U-NII Band 3: 5755MHz to 5795MHz; 802.11ac(HT80): U-NII Band 1: 5210MHz; U-NII Band 3: 5775MHz
Number of Channels:	802.11a/n(HT20)/ac(HT20): U-NII Band 1: 4; U-NII Band 3: 5; 802.11n(HT40)/ac(HT40): U-NII Band 1: 2; U-NII Band 3: 2; 802.11ac(HT80): U-NII Band 1: 1; U-NII Band 3: 1
Modulation Type:	802.11a: OFDM(BPSK, QPSK, 16QAM, 64QAM); 802.11n: OFDM(BPSK, QPSK, 16QAM, 64QAM); 802.11ac: OFDM(BPSK, QPSK, 16QAM, 64QAM, 256QAM);
Antenna Type:	dual-polarized directional panel antenna
Antenna Gain:	2 MIMO antenna:15dBi

Operation Frequency each of channel

Band 1					
802.11a/802.11n20		802.11n40		802.11ac	
Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180MHz	39	5190MHz	42	5210MHz
40	5200MHz	45	5230MHz		
44	5220MHz				
48	5240MHz				
Band 4					
802.11a/802.11n20		802.11n40		802.11ac	
Channel	Frequency	Channel	Frequency	Channel	Frequency
149	5745MHz	151	5755MHz	155	5775MHz
153	5765MHz	159	5795MHz		
157	5785MHz				
161	5805MHz				
165	5825MHz				

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Band 1					
802.11a/802.11n20		802.11n40		802.11ac80	
Channel	Frequency	Channel	Frequency	Channel	Frequency
The lowest channel	5180MHz	The lowest channel	5190MHz	The middle channel	5210MHz
The middle channel	5200MHz	The highest channel	5230MHz		
The highest channel	5240MHz				
Band 4					
802.11a/802.11n20		802.11n40		802.11ac80	
Channel	Frequency	Channel	Frequency	Channel	Frequency
The lowest channel	5745MHz	The lowest channel	5755MHz	The middle channel	5775MHz
The middle channel	5785MHz	The highest channel	5795MHz		
The highest channel	5825MHz				

2.3 Description of Test Modes

No	Title	Description
TM1	802.11a mode	Keep the EUT in continuously transmitting mode with 802.11a modulation type. Keep the EUT in 100% duty cycle transmitting with modulation. All data rates has been tested and found the data rate @ 6Mbps is the worst case.
TM2	802.11n mode	Keep the EUT in continuously transmitting mode with 802.11n modulation type. Keep the EUT in 100% duty cycle transmitting with modulation. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case.
TM3	802.11ac mode	Keep the EUT in continuously transmitting mode with 802.11ac modulation type. Keep the EUT in 100% duty cycle transmitting with modulation. All bandwidth and data rates has been tested and found the data rate @ MCS0 is the worst case.

Only the data of worst case is recorded in the report.

2.4 Description of Support Units

Title	Manufacturer	Model No.	Serial No.
PC	Lenovo	Air 14 Plus	

2.5 Equipments Used During The Test

Duty Cycle					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RF Test Software	TACHOY	RTS-01	V2.0.0.0	/	/
High Pass filter	ZHINAN	OQHPF1-M1.5-18G-224	6210075	/	/
Power divider	MIDEWEST	PWD-2533	SMA-79	2023-05-11	2026-05-10
DC power	HP	66311B	38444359	/	/
RF Sensor Unit	Tachoy Information Technology(shenzhen) Co.,Ltd.	TR1029-2	000001	/	/
Wideband radio communication tester	R&S	CMW500	113410	2023-06-13	2024-06-12
Vector signal generator	Keysight	N5181A	MY48180415	2022-12-10	2023-12-09
Signal generator	Keysight	N5182A	MY50143455	2022-12-29	2023-12-28
Spectrum Analyzer	Keysight	N9020A	MY53420323	2022-12-29	2023-12-28

Maximum conducted output power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RF Test Software	TACHOY	RTS-01	V2.0.0.0	/	/
High Pass filter	ZHINAN	OQHPF1-M1.5-18G-224	6210075	/	/
Power divider	MIDEWEST	PWD-2533	SMA-79	2023-05-11	2026-05-10
DC power	HP	66311B	38444359	/	/
RF Sensor Unit	Tachoy Information Technology(shenzhen) Co.,Ltd.	TR1029-2	000001	/	/
Wideband radio communication tester	R&S	CMW500	113410	2023-06-13	2024-06-12
Vector signal generator	Keysight	N5181A	MY48180415	2022-12-10	2023-12-09
Signal generator	Keysight	N5182A	MY50143455	2022-12-29	2023-12-28
Spectrum Analyzer	Keysight	N9020A	MY53420323	2022-12-29	2023-12-28

Power spectral density					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RF Test Software	TACHOY	RTS-01	V2.0.0.0	/	/
High Pass filter	ZHINAN	OQHPF1-M1.5-18G-224	6210075	/	/
Power divider	MIDEWEST	PWD-	SMA-79	2023-05-11	2026-05-10

		2533			
DC power	HP	66311B	38444359	/	/
RF Sensor Unit	Tachoy Information Technology(shenzhen) Co.,Ltd.	TR1029-2	000001	/	/
Wideband radio communication tester	R&S	CMW500	113410	2023-06-13	2024-06-12
Vector signal generator	Keysight	N5181A	MY48180415	2022-12-10	2023-12-09
Signal generator	Keysight	N5182A	MY50143455	2022-12-29	2023-12-28
Spectrum Analyzer	Keysight	N9020A	MY53420323	2022-12-29	2023-12-28

Emission bandwidth and occupied bandwidth

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RF Test Software	TACHOY	RTS-01	V2.0.0.0	/	/
High Pass filter	ZHINAN	OQHPF1-M1.5-18G-224	6210075	/	/
Power divider	MIDEWEST	PWD-2533	SMA-79	2023-05-11	2026-05-10
DC power	HP	66311B	38444359	/	/
RF Sensor Unit	Tachoy Information Technology(shenzhen) Co.,Ltd.	TR1029-2	000001	/	/
Wideband radio communication tester	R&S	CMW500	113410	2023-06-13	2024-06-12
Vector signal generator	Keysight	N5181A	MY48180415	2022-12-10	2023-12-09
Signal generator	Keysight	N5182A	MY50143455	2022-12-29	2023-12-28
Spectrum Analyzer	Keysight	N9020A	MY53420323	2022-12-29	2023-12-28

Band edge emissions (Radiated)

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test software	Farad	EZ -EMC	V1.1.42	/	/
Positioning Controller	/	MF-7802	/	/	/
High Pass filter	ZHINAN	OQHPF1-M1.5-18G-224	6210075	/	/
Amplifier(18-40G)	COM-POWER	AH-1840	10100008-1	2022-04-05	2025-04-04
Horn antenna	COM-POWER	AH-1840 (18-40G)	10100008	2023-04-05	2025-04-04
Loop antenna	ZHINAN	ZN30900 C	ZN30900C	2021-07-05	2024-07-04
Cable(LF)#2	Schwarzbeck	/	/	2023-02-27	2024-02-26
Cable(LF)#1	Schwarzbeck	/	/	2023-02-27	2024-02-26

Cable(HF)#2	Schwarzbeck	AK9515E	96250	2023-02-28	2024-02-27
Cable(HF)#1	Schwarzbeck	SYV-50-3-1	/	2023-02-27	2024-02-26
Power amplifier(LF)	Schwarzbeck	BBV9743	9743-151	2023-06-13	2024-06-12
Power amplifier(HF)	Schwarzbeck	BBV9718	9718-282	2023-06-13	2024-06-12
Wideband radio communication tester	R&S	CMW500	113410	2023-06-13	2024-06-12
Spectrum Analyzer	R&S	FSP30	1321.3008K40-101729-jR	2023-06-14	2024-06-13
Horn Antenna	Sunol Sciences	DRH-118	A091114	2023-05-13	2025-05-12
Broadband Antenna	Sunol Sciences	JB6 Antenna	A090414	2023-05-21	2025-05-20
Test Receiver	R&S	ESCI	102109	2023-06-13	2024-06-12

Undesirable emission limits (below 1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test software	Farad	EZ -EMC	V1.1.42	/	/
Positioning Controller	/	MF-7802	/	/	/
High Pass filter	ZHINAN	OQHPF1-M1.5-18G-224	6210075	/	/
Amplifier(18-40G)	COM-POWER	AH-1840	10100008-1	2022-04-05	2025-04-04
Horn antenna	COM-POWER	AH-1840 (18-40G)	10100008	2023-04-05	2025-04-04
Loop antenna	ZHINAN	ZN30900 C	ZN30900C	2021-07-05	2024-07-04
Cable(LF)#2	Schwarzbeck	/	/	2023-02-27	2024-02-26
Cable(LF)#1	Schwarzbeck	/	/	2023-02-27	2024-02-26
Cable(HF)#2	Schwarzbeck	AK9515E	96250	2023-02-28	2024-02-27
Cable(HF)#1	Schwarzbeck	SYV-50-3-1	/	2023-02-27	2024-02-26
Power amplifier(LF)	Schwarzbeck	BBV9743	9743-151	2023-06-13	2024-06-12
Power amplifier(HF)	Schwarzbeck	BBV9718	9718-282	2023-06-13	2024-06-12
Wideband radio communication tester	R&S	CMW500	113410	2023-06-13	2024-06-12
Spectrum Analyzer	R&S	FSP30	1321.3008K40-101729-jR	2023-06-14	2024-06-13
Horn Antenna	Sunol Sciences	DRH-118	A091114	2023-05-13	2025-05-12
Broadband Antenna	Sunol Sciences	JB6 Antenna	A090414	2023-05-21	2025-05-20
Test Receiver	R&S	ESCI	102109	2023-06-13	2024-06-12

Undesirable emission limits (above 1GHz)
--

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test software	Farad	EZ -EMC	V1.1.42	/	/
Positioning Controller	/	MF-7802	/	/	/
High Pass filter	ZHINAN	OQHPF1-M1.5-18G-224	6210075	/	/
Amplifier(18-40G)	COM-POWER	AH-1840	10100008-1	2022-04-05	2025-04-04
Horn antenna	COM-POWER	AH-1840 (18-40G)	10100008	2023-04-05	2025-04-04
Loop antenna	ZHINAN	ZN30900 C	ZN30900C	2021-07-05	2024-07-04
Cable(LF)#2	Schwarzbeck	/	/	2023-02-27	2024-02-26
Cable(LF)#1	Schwarzbeck	/	/	2023-02-27	2024-02-26
Cable(HF)#2	Schwarzbeck	AK9515E	96250	2023-02-28	2024-02-27
Cable(HF)#1	Schwarzbeck	SYV-50-3-1	/	2023-02-27	2024-02-26
Power amplifier(LF)	Schwarzbeck	BBV9743	9743-151	2023-06-13	2024-06-12
Power amplifier(HF)	Schwarzbeck	BBV9718	9718-282	2023-06-13	2024-06-12
Wideband radio communication tester	R&S	CMW500	113410	2023-06-13	2024-06-12
Spectrum Analyzer	R&S	FSP30	1321.3008K40-101729-jR	2023-06-14	2024-06-13
Horn Antenna	Sunol Sciences	DRH-118	A091114	2023-05-13	2025-05-12
Broadband Antenna	Sunol Sciences	JB6 Antenna	A090414	2023-05-21	2025-05-20
Test Receiver	R&S	ESCI	102109	2023-06-13	2024-06-12

2.6 Statement Of The Measurement Uncertainty

Test Item	Measurement Uncertainty
Duty cycle	$\pm 3.1\%$
RF conducted power	$\pm 0.733\text{dB}$
RF power density	$\pm 0.234\%$
Occupied Bandwidth	$\pm 3.63\%$
Radiated Emission (Above 1GHz)	$\pm 5.46\text{dB}$
Radiated Emission (Below 1GHz)	$\pm 5.79\text{dB}$
Note: (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.	

2.7 Identification of Testing Laboratory

Company Name:	Shenzhen POCE Technology Co., Ltd.
Address:	101-102 Building H5 & 1/F., Building H, Hongfa Science & Technology Park, Tangtou, Shiyan, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252

Identification of the Responsible Testing Location

Company Name:	Shenzhen POCE Technology Co., Ltd.
Address:	101-102 Building H5 & 1/F., Building H, Hongfa Science & Technology Park, Tangtou, Shiyan, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252
FCC Registration Number:	0032847402
Designation Number:	CN1342

2.8 Announcement


- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by POCE and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

3 Evaluation Results (Evaluation)

3.1 Antenna requirement


Test Requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	--

3.1.1 Conclusion:




4.1.3 Test Data:

TM1 / Line: Line / Band: U-NII 1 / BW: 20 / CH: L
POWER:AC120V60Hz



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Antenna Height cm	Table Degree	
							Detector	degree	Comment
1	60.4919	40.59	-10.07	30.52	40.00	-9.48	QP	147	
2	75.9773	43.27	-10.04	33.23	40.00	-6.77	QP	212	
3	188.4125	42.18	-5.48	36.70	43.50	-6.80	QP	221	
4	! 284.9767	42.45	-2.09	40.36	46.00	-5.64	QP	237	
5	* 487.3151	39.82	2.04	41.86	46.00	-4.14	QP	147	
6	651.9417	33.21	4.18	37.39	46.00	-8.61	QP	210	

TM1 / Line: Neutral / Band: U-NII 1 / BW: 20 / CH: L
POWER:AC120V60Hz



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1	!	43.5057	47.25	-11.43	35.82	40.00	-4.18	QP	100	44
2	*	59.0251	46.41	-9.99	36.42	40.00	-3.58	QP	100	257
3	!	74.6569	45.40	-9.38	36.02	40.00	-3.98	QP	100	56
4	!	188.4125	44.47	-5.33	39.14	43.50	-4.36	QP	100	221
5		495.9344	37.36	2.44	39.80	46.00	-6.20	QP	100	278
6		651.9417	33.23	4.87	38.10	46.00	-7.90	QP	100	128

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor, Over = Limit - Measurement
4. The test data shows only the worst case (802.11a mode)


4.2 Duty Cycle

Test Requirement:	All measurements are to be performed with the EUT transmitting at 100% duty cycle at its maximum power control level; however, if 100% duty cycle cannot be achieved, measurements of duty cycle, x, and maximum-power transmission duration, T, are required for each tested mode of operation.
Test Limit:	No limits, only for report use.
Test Method:	ANSI C63.10-2013 section 12.2 (b)
Procedure:	i) Set the center frequency of the instrument to the center frequency of the transmission. ii) Set RBW $\geq$ EBW if possible; otherwise, set RBW to the largest available value. iii) Set VBW $\geq$ RBW. iv) Set detector = peak. v) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$, where T is defined in item a1) of 12.2, and the number of sweep points across duration T exceeds 100.

4.2.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.2 °C	Humidity:	50.5 %	Atmospheric Pressure:	101.6 kPa
Pre test mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

4.2.2 Test Setup Diagram:



4.2.3 Test Data:

Please Refer to Appendix for Details.


4.3 Maximum conducted output power

Test Requirement:	47 CFR Part 15.407(a)(1)(i) 47 CFR Part 15.407(a)(3)(iii)
Test Limit:	For fixed point-to-point access points operating in the band 5.15–5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
Test Method:	ANSI C63.10-2013, section 12.3
Procedure:	Method SA-1 a) Set span to encompass the entire 26 dB EBW or 99% OBW of the signal. b) Set RBW = 1 MHz. c) Set VBW $\geq$ 3 MHz. d) Number of points in sweep $\geq$ $[2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq$ RBW / 2, so that narrowband signals are not lost between frequency bins.) e) Sweep time = auto. f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode. g) If transmit duty cycle $<$ 98%, use a video trigger with the trigger level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no OFF intervals) or at duty cycle $\geq$ 98%, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run.” h) Trace average at least 100 traces in power averaging (rms) mode. i) Compute power by integrating the spectrum across the 26 dB EBW or 99% OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the EBW or OBW band edges. If the instrument does not have a band power function, then sum the spectrum levels (in power units) at 1 MHz intervals extending across the 26 dB EBW or 99% OBW of the spectrum.

4.3.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.2 °C	Humidity:	50.5 %	Atmospheric Pressure:	101.6 kPa
Pre test mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

4.3.2 Test Setup Diagram:



4.3.3 Test Data:

Please Refer to Appendix for Details.


4.4 Power spectral density

Test Requirement:	47 CFR Part 15.407(a)(1)(i) 47 CFR Part 15.407(a)(3)(i)
Test Limit:	For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. For the band 5.725-5.850 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple colocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
Test Method:	ANSI C63.10-2013, section 12.5
Procedure:	a) Create an average power spectrum for the EUT operating mode being tested by following the instructions in 12.3.2 for measuring maximum conducted output power using a spectrum analyzer or EMI receiver; that is, select the appropriate test method (SA-1, SA-2, SA-3, or their respective alternatives) and apply it up to, but not including, the step labeled, "Compute power...." (This procedure is required even if the maximum conducted output power measurement was performed using the power meter method PM.) b) Use the peak search function on the instrument to find the peak of the spectrum. c) Make the following adjustments to the peak value of the spectrum, if applicable: 1) If method SA-2 or SA-2A was used, then add $[10 \log (1 / D)]$, where D is the duty cycle, to the peak of the spectrum. 2) If method SA-3A was used and the linear mode was used in step h) of 12.3.2.7, add 1 dB to the final result to compensate for the difference between linear averaging and power averaging. d) The result is the PPSD. e) The procedure in item a) through item c) requires the use of 1 MHz resolution bandwidth to satisfy the 1 MHz measurement bandwidth specified by some regulatory authorities. This requirement also permits use of resolution bandwidths less than 1 MHz "provided that the measured power is integrated to show the total power over the measurement bandwidth" (i.e., 1 MHz). If measurements are performed using a reduced resolution bandwidth and integrated over 1 MHz bandwidth, the following adjustments to the procedures apply: 1) Set $RBW \geq 1 / T$, where T is defined in 12.2 a). 2) Set $VBW \geq [3 \times RBW]$. 3) Care shall be taken such that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

4.4.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.2 °C	Humidity:	50.5 %	Atmospheric Pressure:	101.6 kPa
Pre test mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

4.4.2 Test Setup Diagram:



4.4.3 Test Data:

Please Refer to Appendix for Details.

4.5 Emission bandwidth and occupied bandwidth

Test Requirement:	U-NII 1, U-NII 2A, U-NII 2C: No limits, only for report use. U-NII 3, U-NII 4: 47 CFR Part 15.407(e)
Test Limit:	U-NII 1, U-NII 2A, U-NII 2C: No limits, only for report use. U-NII 3, U-NII 4: Within the 5.725-5.850 GHz and 5.850-5.895 GHz bands, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.
Test Method:	ANSI C63.10-2013, section 6.9.3 & 12.4 KDB 789033 D02, Clause C.2
Procedure:	Emission bandwidth: - Set RBW = approximately 1% of the emission bandwidth. - Set the VBW > RBW. - Detector = peak. - Trace mode = max hold. - Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%. Occupied bandwidth: - The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW. - The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement. - Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2. - Step a) through step c) might require iteration to adjust within the specified range. - Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used. - Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth. - If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.

h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

6 dB emission bandwidth:

a) Set RBW = 100 kHz.

b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.

c) Detector = Peak.

d) Trace mode = max hold.

e) Sweep = auto couple.

f) Allow the trace to stabilize.

g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.5.1 E.U.T. Operation:


Operating Environment:

Temperature:	23.2 °C	Humidity:	50.5 %	Atmospheric Pressure:	101.6 kPa
--------------	---------	-----------	--------	-----------------------	-----------

Pre test mode:	TM1, TM2, TM3
----------------	---------------

Final test mode:	TM1, TM2, TM3
------------------	---------------

4.5.2 Test Setup Diagram:



4.5.3 Test Data:

Please Refer to Appendix for Details.

4.6 Band edge emissions (Radiated)


Test Requirement:	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)																																																																																																			
Test Limit:	For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. For transmitters operating solely in the 5.725-5.850 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. <table><tr><th>MHz</th><th>MHz</th><th>MHz</th><th>GHz</th></tr><tr><td>0.090-0.110</td><td>16.42-16.423</td><td>399.9-410</td><td>4.5-5.15</td></tr><tr><td>¹0.495-0.505</td><td>16.69475-16.69525</td><td>608-614</td><td>5.35-5.46</td></tr><tr><td>2.1735-2.1905</td><td>16.80425-16.80475</td><td>960-1240</td><td>7.25-7.75</td></tr><tr><td>4.125-4.128</td><td>25.5-25.67</td><td>1300-1427</td><td>8.025-8.5</td></tr><tr><td>4.17725-4.17775</td><td>37.5-38.25</td><td>1435-1626.5</td><td>9.0-9.2</td></tr><tr><td>4.20725-4.20775</td><td>73-74.6</td><td>1645.5-1646.5</td><td>9.3-9.5</td></tr><tr><td>6.215-6.218</td><td>74.8-75.2</td><td>1660-1710</td><td>10.6-12.7</td></tr><tr><td>6.26775-6.26825</td><td>108-121.94</td><td>1718.8-1722.2</td><td>13.25-13.4</td></tr><tr><td>6.31175-6.31225</td><td>123-138</td><td>2200-2300</td><td>14.47-14.5</td></tr><tr><td>8.291-8.294</td><td>149.9-150.05</td><td>2310-2390</td><td>15.35-16.2</td></tr><tr><td>8.362-8.366</td><td>156.52475-156.52525</td><td>2483.5-2500</td><td>17.7-21.4</td></tr><tr><td>8.37625-8.38675</td><td>156.7-156.9</td><td>2690-2900</td><td>22.01-23.12</td></tr><tr><td>8.41425-8.41475</td><td>162.0125-167.17</td><td>3260-3267</td><td>23.6-24.0</td></tr><tr><td>12.29-12.293</td><td>167.72-173.2</td><td>3332-3339</td><td>31.2-31.8</td></tr><tr><td>12.51975-12.52025</td><td>240-285</td><td>3345.8-3358</td><td>36.43-36.5</td></tr><tr><td>12.57675-12.57725</td><td>322-335.4</td><td>3600-4400</td><td>(²)</td></tr><tr><td>13.36-13.41</td><td></td><td></td><td></td></tr></table> ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz. ²Above 38.6 The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in § 15.35 apply to these measurements. Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table: <table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100 **</td><td>3</td></tr><tr><td>88-216</td><td>150 **</td><td>3</td></tr><tr><td>216-960</td><td>200 **</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>3</td></tr></table>				MHz	MHz	MHz	GHz	0.090-0.110	16.42-16.423	399.9-410	4.5-5.15	¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46	2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75	4.125-4.128	25.5-25.67	1300-1427	8.025-8.5	4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2	4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5	6.215-6.218	74.8-75.2	1660-1710	10.6-12.7	6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4	6.31175-6.31225	123-138	2200-2300	14.47-14.5	8.291-8.294	149.9-150.05	2310-2390	15.35-16.2	8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4	8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12	8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0	12.29-12.293	167.72-173.2	3332-3339	31.2-31.8	12.51975-12.52025	240-285	3345.8-3358	36.43-36.5	12.57675-12.57725	322-335.4	3600-4400	(²)	13.36-13.41				Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100 **	3	88-216	150 **	3	216-960	200 **	3	Above 960	500	3
MHz	MHz	MHz	GHz																																																																																																	
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15																																																																																																	
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46																																																																																																	
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75																																																																																																	
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5																																																																																																	
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2																																																																																																	
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5																																																																																																	
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7																																																																																																	
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4																																																																																																	
6.31175-6.31225	123-138	2200-2300	14.47-14.5																																																																																																	
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2																																																																																																	
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4																																																																																																	
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12																																																																																																	
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0																																																																																																	
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8																																																																																																	
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5																																																																																																	
12.57675-12.57725	322-335.4	3600-4400	(²)																																																																																																	
13.36-13.41																																																																																																				
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																																																																																																		
0.009-0.490	2400/F(kHz)	300																																																																																																		
0.490-1.705	24000/F(kHz)	30																																																																																																		
1.705-30.0	30	30																																																																																																		
30-88	100 **	3																																																																																																		
88-216	150 **	3																																																																																																		
216-960	200 **	3																																																																																																		
Above 960	500	3																																																																																																		

Test Method:	ANSI C63.10-2013, section 12.7.4, 12.7.5, 12.7.6
Procedure:	Above 1GHz: - For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. - If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet. - Test the EUT in the lowest channel, the middle channel, the Highest channel. - The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. - Repeat above procedures until all frequencies measured was complete. Remark: - Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor - Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. - As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. - The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.

4.6.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.2 °C	Humidity:	50.5 %	Atmospheric Pressure:	101.6 kPa
Pre test mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

4.6.2 Test Setup Diagram:



4.6.3 Test Data:

Band 1:

UNII-1_20M_5180MHz_Horizontal--ANT1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5100	51.59	0.43	52.02	68.2	-16.18	peak	P
2	5150	54.26	0.43	54.69	68.2	-13.51	peak	P
3	5135	56.26	0.43	56.69	68.2	-11.51	peak	P

UNII-1_20M_5180MHz_Vertical--ANT1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5300	51.61	0.56	52.17	68.2	-16.03	peak	P
2	5330	51.25	0.58	51.83	68.2	-16.37	peak	P
3	5350	53.25	0.6	53.85	68.2	-14.35	peak	P

UNII-3_20M_5240MHz_Horizontal--ANT1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5100	52.87	0.91	53.78	68.2	-14.42	peak	P
2	5150	51.09	0.91	52.00	68.2	-16.20	peak	P
3	5135	53.54	0.9	54.44	68.2	-13.76	peak	P

UNII-1_20M_5240MHz_Vertical--ANT1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5300	56.51	0.91	57.42	68.2	-10.78	peak	P
2	5330	53.52	0.91	54.43	68.2	-13.77	peak	P
3	5350	52.17	0.9	53.07	68.2	-15.13	peak	P

UNII-1_20M_5180MHz_Horizontal--ANT2

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5100	53.25	0.43	53.68	68.2	-14.52	peak	P
2	5150	54.80	0.43	55.23	68.2	-12.97	peak	P
3	5135	55.48	0.43	55.91	68.2	-12.29	peak	P

UNII-1_20M_5180MHz_Vertical--ANT2

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5300	51.22	0.56	51.78	68.2	-16.42	peak	P
2	5330	53.21	0.58	53.79	68.2	-14.41	peak	P
3	5350	52.72	0.6	53.32	68.2	-14.88	peak	P

UNII-3_20M_5240MHz_Horizontal--ANT2

No.	Frequency	Reading	Factor	Level	Limit	Margin	Detector	P/F
-----	-----------	---------	--------	-------	-------	--------	----------	-----

	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)		
1	5100	52.62	0.91	53.53	68.2	-14.67	peak	P
2	5150	52.58	0.91	53.49	68.2	-14.71	peak	P
3	5135	53.44	0.9	54.34	68.2	-13.86	peak	P

UNII-1_20M_5240MHz_Vertical--ANT2

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5300	57.04	0.91	57.95	68.2	-10.25	peak	P
2	5330	53.05	0.91	53.96	68.2	-14.24	peak	P
3	5350	52.08	0.9	52.98	68.2	-15.22	peak	P

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. Correct factor = Antenna Factor + Cable Loss – Preamplifier Factor
4. The test data shows only the worst case (802.11a mode)

Band 4:

UNII-3_20M_5745MHz_Horizontal--ANT1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5650	51.26	0.91	52.17	122.2	-70.03	peak	P
2	5700	54.38	0.91	55.29	110.8	-55.51	peak	P
3	5720	59.56	0.9	60.46	68.2	-7.74	peak	P

UNII-3_20M_5745MHz_Vertical--ANT1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5650	51.26	0.91	52.17	122.2	-70.03	peak	P
2	5700	54.31	0.91	55.22	110.8	-55.58	peak	P
3	5720	60.55	0.9	61.45	68.2	-6.75	peak	P

UNII-3_20M_5825MHz_Horizontal--ANT1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5850	60.56	0.91	61.47	122.2	-60.73	peak	P
2	5875	55.12	0.91	56.03	110.8	-54.77	peak	P
3	5925	51.42	0.9	52.32	68.2	-15.88	peak	P

UNII-3_20M_5825MHz_Vertical--ANT1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5850	51.01	0.91	51.92	122.2	-70.28	peak	P
2	5875	51.11	0.91	52.02	110.8	-58.78	peak	P
3	5925	49.86	0.9	50.76	68.2	-17.44	peak	P

UNII-3_20M_5745MHz_Horizontal--ANT2

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5650	52.73	0.91	53.64	122.2	-68.56	peak	P
2	5700	55.42	0.91	56.33	110.8	-54.47	peak	P
3	5720	60.22	0.9	61.12	68.2	-7.08	peak	P

UNII-3_20M_5745MHz_Vertical--ANT2

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5650	51.29	0.91	52.20	122.2	-70.00	peak	P
2	5700	54.61	0.91	55.52	110.8	-55.28	peak	P
3	5720	58.27	0.9	59.17	68.2	-9.03	peak	P

UNII-3_20M_5825MHz_Horizontal--ANT2

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5850	58.42	0.91	59.33	122.2	-62.87	peak	P
2	5875	53.48	0.91	54.39	110.8	-56.41	peak	P
3	5925	53.59	0.9	54.49	68.2	-13.71	peak	P

UNII-3_20M_5825MHz_Vertical--ANT2

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	5850	52.91	0.91	53.82	122.2	-68.38	peak	P
2	5875	51.99	0.91	52.90	110.8	-57.90	peak	P
3	5925	48.81	0.9	49.71	68.2	-18.49	peak	P

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. Correct factor = Antenna Factor + Cable Loss – Preamplifier Factor
4. The test data shows only the worst case (802.11a mode)

4.7 Undesirable emission limits (below 1GHz)

Test Requirement:	47 CFR Part 15.407(b)(9)																										
Test Limit:	Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209. Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table: <table><tr><td>Frequency (MHz)</td><td>Field strength (microvolts/meter)</td><td>Measurement distance (meters)</td></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100 **</td><td>3</td></tr><tr><td>88-216</td><td>150 **</td><td>3</td></tr><tr><td>216-960</td><td>200 **</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>3</td></tr></table>			Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100 **	3	88-216	150 **	3	216-960	200 **	3	Above 960	500	3
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																									
0.009-0.490	2400/F(kHz)	300																									
0.490-1.705	24000/F(kHz)	30																									
1.705-30.0	30	30																									
30-88	100 **	3																									
88-216	150 **	3																									
216-960	200 **	3																									
Above 960	500	3																									
Test Method:	ANSI C63.10-2013, section 12.7.4, 12.7.5, 12.7.6																										
Procedure:	Below 1GHz: a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Remark: 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. Above 1GHz: a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which																										

was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.

g. Test the EUT in the lowest channel, the middle channel, the Highest channel.

h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.

i. Repeat above procedures until all frequencies measured was complete.


Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.

4.7.1 E.U.T. Operation:


Operating Environment:					
Temperature:	23.2 °C	Humidity:	50.5 %	Atmospheric Pressure:	101.6 kPa
Pre test mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

4.7.2 Test Setup Diagram:




4.7.3 Test Data:

TM1 / Polarization: Horizontal / Band: U-NII 1 / BW: 20 / CH: L



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		60.4919	40.59	-10.07	30.52	40.00	-9.48	QP	100	147
2		75.9773	43.27	-10.04	33.23	40.00	-6.77	QP	100	212
3		188.4125	42.18	-5.48	36.70	43.50	-6.80	QP	100	221
4	!	284.9767	42.45	-2.09	40.36	46.00	-5.64	QP	100	237
5	*	487.3151	39.82	2.04	41.86	46.00	-4.14	QP	100	147
6		651.9417	33.21	4.18	37.39	46.00	-8.61	QP	100	210

TM1 / Polarization: Vertical / Band: U-NII 1 / BW: 20 / CH: L



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1	!	43.5057	47.25	-11.43	35.82	40.00	-4.18	QP	100	44
2	*	59.0251	46.41	-9.99	36.42	40.00	-3.58	QP	100	257
3	!	74.6569	45.40	-9.38	36.02	40.00	-3.98	QP	100	56
4	!	188.4125	44.47	-5.33	39.14	43.50	-4.36	QP	100	221
5		495.9344	37.36	2.44	39.80	46.00	-6.20	QP	100	278
6		651.9417	33.23	4.87	38.10	46.00	-7.90	QP	100	128

4.8 Undesirable emission limits (above 1GHz)


Test Requirement:	47 CFR Part 15.407(b)(1) 47 CFR Part 15.407(b)(4) 47 CFR Part 15.407(b)(10)																																																																																													
Test Limit:	For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. For transmitters operating solely in the 5.725-5.850 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. <table><tr><th>MHz</th><th>MHz</th><th>MHz</th><th>GHz</th></tr><tr><td>0.090-0.110</td><td>16.42-16.423</td><td>399.9-410</td><td>4.5-5.15</td></tr><tr><td>¹0.495-0.505</td><td>16.69475-16.69525</td><td>608-614</td><td>5.35-5.46</td></tr><tr><td>2.1735-2.1905</td><td>16.80425-16.80475</td><td>960-1240</td><td>7.25-7.75</td></tr><tr><td>4.125-4.128</td><td>25.5-25.67</td><td>1300-1427</td><td>8.025-8.5</td></tr><tr><td>4.17725-4.17775</td><td>37.5-38.25</td><td>1435-1626.5</td><td>9.0-9.2</td></tr><tr><td>4.20725-4.20775</td><td>73-74.6</td><td>1645.5-1646.5</td><td>9.3-9.5</td></tr><tr><td>6.215-6.218</td><td>74.8-75.2</td><td>1660-1710</td><td>10.6-12.7</td></tr><tr><td>6.26775-6.26825</td><td>108-121.94</td><td>1718.8-1722.2</td><td>13.25-13.4</td></tr><tr><td>6.31175-6.31225</td><td>123-138</td><td>2200-2300</td><td>14.47-14.5</td></tr><tr><td>8.291-8.294</td><td>149.9-150.05</td><td>2310-2390</td><td>15.35-16.2</td></tr><tr><td>8.362-8.366</td><td>156.52475-156.52525</td><td>2483.5-2500</td><td>17.7-21.4</td></tr><tr><td>8.37625-8.38675</td><td>156.7-156.9</td><td>2690-2900</td><td>22.01-23.12</td></tr><tr><td>8.41425-8.41475</td><td>162.0125-167.17</td><td>3260-3267</td><td>23.6-24.0</td></tr><tr><td>12.29-12.293</td><td>167.72-173.2</td><td>3332-3339</td><td>31.2-31.8</td></tr><tr><td>12.51975-12.52025</td><td>240-285</td><td>3345.8-3358</td><td>36.43-36.5</td></tr><tr><td>12.57675-12.57725</td><td>322-335.4</td><td>3600-4400</td><td>(²)</td></tr><tr><td>13.36-13.41</td><td></td><td></td><td></td></tr></table> ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz. ²Above 38.6 The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in § 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in § 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in § 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in § 15.35 apply to these measurements. Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table: <table><tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr><tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr><tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr><tr><td>1.705-30.0</td><td>30</td><td>30</td></tr><tr><td>30-88</td><td>100 **</td><td>3</td></tr><tr><td>88-216</td><td>150 **</td><td>3</td></tr></table>				MHz	MHz	MHz	GHz	0.090-0.110	16.42-16.423	399.9-410	4.5-5.15	¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46	2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75	4.125-4.128	25.5-25.67	1300-1427	8.025-8.5	4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2	4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5	6.215-6.218	74.8-75.2	1660-1710	10.6-12.7	6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4	6.31175-6.31225	123-138	2200-2300	14.47-14.5	8.291-8.294	149.9-150.05	2310-2390	15.35-16.2	8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4	8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12	8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0	12.29-12.293	167.72-173.2	3332-3339	31.2-31.8	12.51975-12.52025	240-285	3345.8-3358	36.43-36.5	12.57675-12.57725	322-335.4	3600-4400	(²)	13.36-13.41				Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)	0.009-0.490	2400/F(kHz)	300	0.490-1.705	24000/F(kHz)	30	1.705-30.0	30	30	30-88	100 **	3	88-216	150 **	3
MHz	MHz	MHz	GHz																																																																																											
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15																																																																																											
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46																																																																																											
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75																																																																																											
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5																																																																																											
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2																																																																																											
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5																																																																																											
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7																																																																																											
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4																																																																																											
6.31175-6.31225	123-138	2200-2300	14.47-14.5																																																																																											
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2																																																																																											
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4																																																																																											
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12																																																																																											
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0																																																																																											
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8																																																																																											
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5																																																																																											
12.57675-12.57725	322-335.4	3600-4400	(²)																																																																																											
13.36-13.41																																																																																														
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)																																																																																												
0.009-0.490	2400/F(kHz)	300																																																																																												
0.490-1.705	24000/F(kHz)	30																																																																																												
1.705-30.0	30	30																																																																																												
30-88	100 **	3																																																																																												
88-216	150 **	3																																																																																												

	216-960	200 **	3
	Above 960	500	3
Test Method:	ANSI C63.10-2013, section 12.7.4, 12.7.5, 12.7.6		
Procedure:	Above 1GHz: a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete. Remark: 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor 2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report. 4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.		

4.8.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.2 °C	Humidity:	50.5 %	Atmospheric Pressure:	101.6 kPa
Pre test mode:		TM1, TM2, TM3			
Final test mode:		TM1, TM2, TM3			

4.8.2 Test Setup Diagram:



4.8.3 Test Data:

Band1

802.11a mode Lowest channel (Peak Value)--ANT1						
Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360	45.47	9.54	55.01	68.2	-13.19	Vertical
10360	46.29	9.54	55.83	68.2	-12.37	Horizontal

802.11a mode Lowest channel (Average Value)--ANT1						
Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360	32.78	9.54	42.32	54	-11.68	Vertical
10360	33.11	9.54	42.65	54	-11.35	Horizontal

802.11a mode Middle channel (Peak Value)--ANT1						
Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10400	46.89	9.64	56.53	68.2	-11.67	Vertical
10400	45.12	9.64	54.76	68.2	-13.44	Horizontal

802.11a mode Middle channel (Average Value)--ANT1						
Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10400	31.93	9.64	41.57	54	-12.43	Vertical
10400	32.02	9.64	41.66	54	-12.34	Horizontal

802.11a mode Highest channel (Peak Value)--ANT1						
Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10480	46.72	9.74	56.46	68.2	-11.74	Vertical
10480	46.31	9.74	56.05	68.2	-12.15	Horizontal

802.11a mode Highest channel (Average Value)--ANT1						
Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10480	33.30	9.74	43.04	54	-10.96	Vertical
10480	32.67	9.74	42.41	54	-11.59	Horizontal

802.11a mode Lowest channel (Peak Value)--ANT2						
Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360	47.40	9.54	56.94	68.2	-11.26	Vertical
10360	45.53	9.54	55.07	68.2	-13.13	Horizontal
802.11a mode Lowest channel (Average Value)						
Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10360	31.38	9.54	40.92	54	-13.08	Vertical
10360	31.33	9.54	40.87	54	-13.13	Horizontal

802.11a mode Middle channel (Peak Value)						
Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10400	45.31	9.64	54.95	68.2	-13.25	Vertical
10400	47.00	9.64	56.64	68.2	-11.56	Horizontal
802.11a mode Middle channel (Average Value)						
Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10400	32.63	9.64	42.27	54	-11.73	Vertical
10400	31.31	9.64	40.95	54	-13.05	Horizontal

802.11a mode Highest channel (Peak Value)						
Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10480	45.14	9.74	54.88	68.2	-13.32	Vertical
10480	46.66	9.74	56.40	68.2	-11.80	Horizontal
802.11a mode Highest channel (Average Value)						
Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
10480	31.21	9.74	40.95	54	-13.05	Vertical
10480	31.64	9.74	41.38	54	-12.62	Horizontal

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. During the test, pre-scan the 802.11a/n/ac mode, and found the 802.11a mode which it is worse case.

Band4

802.11a mode Lowest channel (Peak Value)--ANT1

Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11490	47.04	9.54	56.58	68.2	-11.62	Vertical
11490	46.21	9.54	55.75	68.2	-12.45	Horizontal

802.11a mode Lowest channel (Average Value)--ANT1

Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11490	32.24	9.54	41.78	54	-12.22	Vertical
11490	33.28	9.54	42.82	54	-11.18	Horizontal

802.11a mode Middle channel (Peak Value)--ANT1

Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11570	46.34	9.64	55.98	68.2	-12.22	Vertical
11570	45.54	9.64	55.18	68.2	-13.02	Horizontal

802.11a mode Middle channel (Average Value)--ANT1

Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11570	31.32	9.64	40.96	54	-13.04	Vertical
11570	33.39	9.64	43.03	54	-10.97	Horizontal

802.11a mode Highest channel (Peak Value)--ANT1

Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11650	46.73	9.74	56.47	68.2	-11.73	Vertical
11650	47.28	9.74	57.02	68.2	-11.18	Horizontal

802.11a mode Highest channel (Average Value)--ANT1

Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11650	31.74	9.74	41.48	54	-12.52	Vertical
11650	31.07	9.74	40.81	54	-13.19	Horizontal

802.11a mode Lowest channel (Peak Value)						
Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11490	45.93	9.54	55.47	68.2	-12.73	Vertical
11490	47.19	9.54	56.73	68.2	-11.47	Horizontal
802.11a mode Lowest channel (Average Value)						
Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11490	32.09	9.54	41.63	54	-12.37	Vertical
11490	33.36	9.54	42.90	54	-11.10	Horizontal
802.11a mode Middle channel (Peak Value)						
Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11570	46.63	9.64	56.27	68.2	-11.93	Vertical
11570	47.36	9.64	57.00	68.2	-11.20	Horizontal
802.11a mode Middle channel (Average Value)						
Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11570	33.60	9.64	43.24	54	-10.76	Vertical
11570	31.42	9.64	41.06	54	-12.94	Horizontal
802.11a mode Highest channel (Peak Value)						
Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11650	46.27	9.74	56.01	68.2	-12.19	Vertical
11650	46.85	9.74	56.59	68.2	-11.61	Horizontal
802.11a mode Highest channel (Average Value)						
Frequency (MHz)	Read Level (dBuV)	Correct factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
11650	31.14	9.74	40.88	54	-13.12	Vertical
11650	32.03	9.74	41.77	54	-12.23	Horizontal

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. During the test, pre-scan the 802.11a/n/ac mode, and found the 802.11a mode which it is worse case.

5 TEST SETUP PHOTOS

Conducted Emission at AC power line



Emissions in restricted frequency bands (below 1GHz)



Emissions in restricted frequency bands (above 1GHz)



6 PHOTOS OF THE EUT

External















Internal












Appendix


1. -26dB and 99% Emission Bandwidth

Condition	Antenna	Modulation	Frequency(MHz)	-26dB_Emission_Bandwidth(MHz)	Occupied Bandwidth(MHz)
NVNT	ANT1	802.11a	5180.00	26.24	16.60
NVNT	ANT1	802.11a	5200.00	26.69	16.60
NVNT	ANT1	802.11a	5240.00	26.35	16.58
NVNT	ANT1	802.11ac(VHT20)	5180.00	23.15	17.74
NVNT	ANT1	802.11ac(VHT20)	5200.00	23.70	17.71
NVNT	ANT1	802.11ac(VHT20)	5240.00	23.88	17.72
NVNT	ANT1	802.11ac(VHT40)	5190.00	44.54	36.26
NVNT	ANT1	802.11ac(VHT40)	5230.00	46.41	36.33
NVNT	ANT1	802.11ac(VHT80)	5210.00	89.65	75.91
NVNT	ANT2	802.11a	5180.00	22.30	16.54
NVNT	ANT2	802.11a	5200.00	23.10	16.54
NVNT	ANT2	802.11a	5240.00	23.00	16.55
NVNT	ANT2	802.11ac(VHT20)	5180.00	23.05	17.74
NVNT	ANT2	802.11ac(VHT20)	5200.00	23.54	17.73
NVNT	ANT2	802.11ac(VHT20)	5240.00	23.97	17.75
NVNT	ANT2	802.11ac(VHT40)	5190.00	45.66	36.26
NVNT	ANT2	802.11ac(VHT40)	5230.00	46.55	36.32
NVNT	ANT2	802.11ac(VHT80)	5210.00	90.40	75.93
Condition	Antenna	Modulation	Frequency(MHz)	-26dB_Emission_Bandwidth(MHz)	Occupied Bandwidth(MHz)
NVNT	ANT1	802.11a	5745.00	22.73	16.50
NVNT	ANT1	802.11a	5785.00	22.09	16.54
NVNT	ANT1	802.11a	5825.00	22.86	16.51
NVNT	ANT1	802.11ac(VHT20)	5745.00	23.17	17.68
NVNT	ANT1	802.11ac(VHT20)	5785.00	23.41	17.75
NVNT	ANT1	802.11ac(VHT20)	5825.00	23.84	17.72
NVNT	ANT1	802.11ac(VHT40)	5755.00	44.68	36.32
NVNT	ANT1	802.11ac(VHT40)	5795.00	44.40	36.27
NVNT	ANT1	802.11ac(VHT80)	5775.00	89.30	75.91
NVNT	ANT2	802.11a	5745.00	21.97	16.50
NVNT	ANT2	802.11a	5785.00	22.49	16.52
NVNT	ANT2	802.11a	5825.00	22.50	16.52
NVNT	ANT2	802.11ac(VHT20)	5745.00	22.90	17.70
NVNT	ANT2	802.11ac(VHT20)	5785.00	24.11	17.71
NVNT	ANT2	802.11ac(VHT20)	5825.00	24.16	17.70
NVNT	ANT2	802.11ac(VHT40)	5755.00	44.79	36.30
NVNT	ANT2	802.11ac(VHT40)	5795.00	44.90	36.26
NVNT	ANT2	802.11ac(VHT80)	5775.00	91.01	75.89

99%_OCB_NVNT_ANT1_802_11a_5180



-26BW_NVNT_ANT1_802_11a_5180




99%_OCB_NVNT_ANT1_802_11a_5200




-26BW_NVNT_ANT1_802_11a_5200




99%_OCB_NVNT_ANT1_802_11a_5240




-26BW_NVNT_ANT1_802_11a_5240




99%_OCB_NVNT_ANT1_802_11ac(VHT20)_5180



-26BW_NVNT_ANT1_802_11ac(VHT20)_5180



99%_OCB_NVNT_ANT1_802_11ac(VHT20)_5200




-26BW_NVNT_ANT1_802_11ac(VHT20)_5200




99%_OCB_NVNT_ANT1_802_11ac(VHT20)_5240




-26BW_NVNT_ANT1_802_11ac(VHT20)_5240




99%_OCB_NVNT_ANT1_802_11ac(VHT40)_5190




-26BW NVNT ANT1_802_11ac(VHT40)_5190




99%_OCB_NVNT_ANT1_802_11ac(VHT40)_5230




-26BW_NVNT_ANT1_802_11ac(VHT40)_5230



99%_OCB_NVNT_ANT1_802_11ac(VHT80)_5210



-26BW_NVNT_ANT1_802_11ac(VHT80)_5210



99%_OCB_NVNT_ANT2_802_11a_5180



-26BW_NVNT_ANT2_802_11a_5180




99%_OCB_NVNT_ANT2_802_11a_5200




-26BW_NVNT_ANT2_802_11a_5200




99%_OCB_NVNT_ANT2_802_11a_5240



-26BW_NVNT_ANT2_802_11a_5240



99%_OCB_NVNT_ANT2_802_11ac(VHT20)_5180



-26BW_NVNT_ANT2_802_11ac(VHT20)_5180



99%_OCB_NVNT_ANT2_802_11ac(VHT20)_5200



-26BW_NVNT_ANT2_802_11ac(VHT20)_5200



99%_OCB_NVNT_ANT2_802_11ac(VHT20)_5240




-26BW_NVNT_ANT2_802_11ac(VHT20)_5240




99%_OCB_NVNT_ANT2_802_11ac(VHT40)_5190




-26BW_NVNT_ANT2_802_11ac(VHT40)_5190



99%_OCB_NVNT_ANT2_802_11ac(VHT40)_5230




-26BW_NVNT_ANT2_802_11ac(VHT40)_5230




99%_OCB_NVNT_ANT2_802_11ac(VHT80)_5210




-26BW_NVNT_ANT2_802_11ac(VHT80)_5210




99%_OCB_NVNT_ANT1_802_11a_5745



-26BW_NVNT_ANT1_802_11a_5745



99%_OCB_NVNT_ANT1_802_11a_5785




-26BW_NVNT_ANT1_802_11a_5785




99%_OCB_NVNT_ANT1_802_11a_5825



-26BW_NVNT_ANT1_802_11a_5825




99%_OCB_NVNT_ANT1_802_11ac(VHT20)_5745



-26BW_NVNT_ANT1_802_11ac(VHT20)_5745




99%_OCB_NVNT_ANT1_802_11ac(VHT20)_5785




-26BW_NVNT_ANT1_802_11ac(VHT20)_5785




99%_OCB_NVNT_ANT1_802_11ac(VHT20)_5825




-26BW_NVNT_ANT1_802_11ac(VHT20)_5825




99%_OCB_NVNT_ANT1_802_11ac(VHT40)_5755




-26BW_NVNT_ANT1_802_11ac(VHT40)_5755



99%_OCB_NVNT_ANT1_802_11ac(VHT40)_5795




-26BW_NVNT_ANT1_802_11ac(VHT40)_5795




99%_OCB_NVNT_ANT1_802_11ac(VHT80)_5775




-26BW_NVNT_ANT1_802_11ac(VHT80)_5775




99%_OCB_NVNT_ANT2_802_11a_5745




-26BW_NVNT_ANT2_802_11a_5745




99%_OCB_NVNT_ANT2_802_11a_5785




-26BW_NVNT_ANT2_802_11a_5785




99%_OCB_NVNT_ANT2_802_11a_5825




-26BW_NVNT_ANT2_802_11a_5825




99%_OCB_NVNT_ANT2_802_11ac(VHT20)_5745




-26BW_NVNT_ANT2_802_11ac(VHT20)_5745




99%_OCB_NVNT_ANT2_802_11ac(VHT20)_5785




-26BW_NVNT_ANT2_802_11ac(VHT20)_5785




99%_OCB_NVNT_ANT2_802_11ac(VHT20)_5825




-26BW NVNT ANT2_802_11ac(VHT20)_5825




99%_OCB_NVNT_ANT2_802_11ac(VHT40)_5755




-26BW NVNT ANT2_802_11ac(VHT40)_5755




99%_OCB_NVNT_ANT2_802_11ac(VHT40)_5795



-26BW_NVNT_ANT2_802_11ac(VHT40)_5795



99%_OCB_NVNT_ANT2_802_11ac(VHT80)_5775



-26BW_NVNT_ANT2_802_11ac(VHT80)_5775

