

TDE台德 部品承认书

PART FOR APPROVAL

文件编号File No: JX-RD-04-036 Ver: 1.0 No:

原厂名称（品牌名称）Vendor Name: Shenzhen HamyWe Technology Co., Ltd.

原厂型号 Vendor Part P/N: X2938-WBT1032B-ANT5

原厂规格描述 Part Description: FPC L=355MM

供应商确认签章Supplier: Shenzhen HamyWe Technology Co., Ltd.

台德适用机型 Model: WBT1032B

台德 ERP 料号 Part No:E110002923

台德部品名称 Part Name: FPC Antenna

台德规格描述 Part Description:

X2938-WBT1032B-ANT5 , FPC (X2115-WBT1032-ANT5-V1.0)
L=355MM, ROHS2.0+REACH

备注 Remarks:

RD/研发中心	QA/品质中心	APPROVED/批准



天线承认书

Parts Approval Sheet

Customer	台德	Project	WBT1032B
Band	ANT5	Color	BLACK
PN	X2938	Version	V1
Customer material number	THE CORD LENGTH WAS UPDATED FROM 310MM TO 355MM		

DATE: 2024/08/02

R&D			QC
Issued by	Checked by	Confirmed by	Checked by
伍海沅	项念	项念	蔡枝
Customer Confirm			


Environmental requirements: ☒ ROHS ☐ REACH ☐ 无

Contents

Contents	2
1.Summary	3
2.General Description	3
2.1Antenna Components/Part revisions	3
2.2Definitions	3
3.Electrical Performance	4
3.1 Matching Circuit Description	4
3.2 VSWR(Test in free space)	5
3.3 Gain&Efficiency	6
3.4 2D &3D Radiation Pattern	7
3.5 Environment treatment	8
4. Antenna Engineer drawing	9
5.Reliability Testing Report	10

1.Summary

This report summarizes the electrical results of the our antenna to support the project WBT1032B. The test fixture is made for further testing, which is show below:



2.General Description

2.1Antenna Components/Part revisions

The antenna part number is T: A

2.2Definitions

VSWR: Voltage Standing Wave Rate

TRP: total radiated power

TIS: total isotropic sensitivity

3.Electrical Performance

3.1 Matching Circuit Description

ANT5天线匹配电路

匹配是否有改动

无

天线	
Element	Value
E1 (0201)	
E2 (0201)	
E3 (0201)	

RF Module


E2

E3

E1

Antenna


3.2 VSWR(Test in free space)




3.3 Gain&Efficiency

ANT5			
Freq (MHZ)	efficiency_db	Gain	efficiency (%)
2400	-1.29	5.04	74.33
2410	-1.33	4.62	73.66
2420	-1.44	3.83	71.8
2430	-1.42	3.49	72.1
2440	-1.4	3.57	72.4
2450	-1.43	3.68	71.89
2460	-1.36	3.8	73.13
2470	-1.39	4.11	72.61
2480	-1.23	4.72	75.32
2490	-1.23	4.87	75.4
2500	-1.32	4.84	73.79


3.4 2D & 3D Radiation Pattern



3.5 Environment treatment



4. Antenna Engineer drawing



5. Reliability Testing Report

customer	台德	part number	FPC	Work Date	2024.07.26
Test item	Test requirement			Test result	Evaluation
neutral Salt-Fog test	Hydrochloric fog through neutral testing: In the time of 24 hours, no rust corrosion, color fading or solder peel off to the antenna fpc sop in Nacl 5% ± 1% PH value 6.5-7.2, above 85% humidity. and 35°C ± 2°C Seals environment.			Norust corrosion, color fading or solder peel off on the antenna surface after testing	pass
tester: 伍海沅			approval: 伍海沅		