



Shenzhen CTA Testing Technology Co., Ltd.
Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai
Street, Bao'an District, Shenzhen, China

FCC PART 15 SUBPART C TEST REPORT

FCC PART 15.407

Report Reference No.: **CTA24071501904**

FCC ID.: **2BCRN-SHELLS1**

Compiled by

(position+printed name+signature) : File administrators Jinghua Xiao

Jinghua Xiao

Supervised by

(position+printed name+signature) : Test Engineer Lushan Kong

Lushan Kong

Approved by

(position+printed name+signature) : Manager Eric Wang

Eric Wang

Date of issue : Aug. 13, 2024

Representative Laboratory Name.: **Shenzhen CTA Testing Technology Co., Ltd.**

Address : Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name.: **Dongguan Aika Electronic Technology Co., Ltd.**

Address : Room 201, Building 2, No. 388, Bihu Road, Fenggang Town, Dongguan City, Guangdong Province, China

Test specification :

Standard : **FCC Part 15.407: General technical requirements**

TRF Originator : Shenzhen Global Test Service Co.,Ltd.

Master TRF : Dated 2014-12

Shenzhen CTA Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTA Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTA Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description : **Smart Karaoke Speaker**

Trade Mark : Ikarao

Manufacturer : Guangdong Taide Zhilian Technology Co., Ltd

Model/Type reference : Shell S1

Listed Models : Shell S2

Operation Frequency : From 5180MHz to 5240MHz/ 5260MHz to 5320MHz/ 5500MHz to 5700MHz/ 5745MHz to 5825MHz

Hardware Version : V1.1

Software Version : V2.1

Rating : Input: DC 5.0 - 20.0V

Result : **PASS**

TEST REPORT

Test Report No.:	CTA24071501904	Aug. 13, 2024
		Date of issue

Equipment under Test : Smart Karaoke Speaker

Model /Type : Shell S1

Listed model : Shell S2

Applicant : **Dongguan Aika Electronic Technology Co., Ltd.**

Address : Room 201, Building 2, No. 388, Bihu Road, Fenggang Town, Dongguan City, Guangdong Province, China

Manufacturer : **Guangdong Taide Zhilian Technology Co., Ltd**

Address : No. 388, Bihu Road, Fenggang Town, Dongguan City, Guangdong Province, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. TEST STANDARDS	4
2. SUMMARY	5
2.1. General Remarks	5
2.2. Product Description	5
2.3. Equipment Under Test	5
2.4. Short description of the Equipment under Test (EUT)	7
2.5. EUT operation mode	7
2.6. Block Diagram of Test Setup	8
2.7. Related Submittal(s) / Grant (s)	8
2.8. EUT Exercise Software	8
2.9. Special Accessories	8
2.10. External I/O Cable	8
2.11. Modifications	8
3. TEST ENVIRONMENT	9
3.1. Address of the test laboratory	9
3.2. Test Facility	9
3.3. Environmental conditions	9
3.4. Statement of the measurement uncertainty	9
3.5. Test Description	10
3.6. Equipments Used during the Test	12
4. TEST CONDITIONS AND RESULTS	13
4.1. AC Power Conducted Emission	13
4.2. Radiated Emission	14
4.3. Duty Cycle	29
4.4. Maximum Average Output Power	30
4.5. Power Spectral Density	31
4.6. 99% and 6dB Bandwidth	32
4.7. 99% and 26dBc Bandwidth	33
4.8. Conducted Spurious Emissions and Band Edge Compliance	34
4.9. Frequency Stability	36
4.10. Antenna Requirement	40
5. TEST SETUP PHOTOS OF THE EUT	41
6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT	41

1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.407](#): General technical requirements.

[ANSI C63.10-2020](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 789033 D02 General U-NII Test Procedures New Rules v02r01](#): UNII, U-NII, U-NII Test Procedures

2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	:	Jun. 20, 2024
Testing commenced on	:	Jun. 20, 2024
Testing concluded on	:	Aug. 12, 2024

2.2. Product Description

Product Name:	Smart Karaoke Speaker
Trade Mark:	Ikarao
Model/Type reference:	Shell S1
List Model:	Shell S2
Model Declaration	PCB board, structure and internal of these model(s) are the same, only the speaker, power amplifier chip, screen size, antenna and appearance are different.
Power supply:	Input: DC 5.0 - 20.0V
Hardware Version	V1.1
Software Version	V2.1
Sample ID	CTA240715019-S0001-1# CTA240715019-1-S0001-2#
Chip1: JL7034A6	
Bluetooth	
Frequency Range	2402MHz ~ 2480MHz
Channel Number	79 channels for Bluetooth (BR/EDR)
Channel Spacing	1MHz for Bluetooth (BR/EDR)
Modulation Type	GFSK, $\pi/4$ -DQPSK for Bluetooth (BR/EDR)
Antenna Description	Internal Antenna 1, 3.87dBi(Max.) for Shell S1 Internal Antenna 1, 7.87dBi(Max.) for Shell S2
Chip2: AC7066D4	
Bluetooth	
Frequency Range	2402MHz ~ 2480MHz
Channel Number	40 channels for Bluetooth (BT LE) 40 channels for Bluetooth (BT 2LE)
Channel Spacing	2MHz for Bluetooth (BT LE) 2MHz for Bluetooth (BT 2LE)
Modulation Type	GFSK for Bluetooth (BT LE) GFSK for Bluetooth (BT 2LE)
Antenna Description	Internal Antenna 3, 3.96dBi(Max.) for Shell S1 Internal Antenna 3, 7.87dBi(Max.) for Shell S2
Chip3: AC7066D4	
Bluetooth	
Frequency Range	2402MHz ~ 2480MHz
Channel Number	40 channels for Bluetooth (BT LE) 40 channels for Bluetooth (BT 2LE)
Channel Spacing	2MHz for Bluetooth (BT LE) 2MHz for Bluetooth (BT 2LE)
Modulation Type	GFSK for Bluetooth (BT LE) GFSK for Bluetooth (BT 2LE)
Antenna Description	Internal Antenna 4, 3.97dBi(Max.) for Shell S1

	Internal Antenna 4, 7.87dBi(Max.) for Shell S2
Module:RTL8821CS	
2.4GWLAN	
WLAN Operation frequency	IEEE 802.11b:2412-2462MHz IEEE 802.11g:2412-2462MHz IEEE 802.11n HT20:2412-2462MHz IEEE 802.11n HT40:2422-2452MHz
WLAN Modulation Type	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK)
Channel number:	11 Channel for IEEE 802.11b/g/n (HT20) 7 Channel for IEEE 802.11n (HT40)
Channel separation:	5MHz
WIFI (5.2G/5.3G/5.7G/5.8G Band)	
Frequency Range	5180-5240MHz/ 5260MHz to 5320MHz/ 5500MHz to 5700MHz/ 5745MHz to 5825MHz
Channel Number	4 Channels for 20MHz bandwidth(5180-5240MHz) 4 Channels for 20MHz bandwidth(5260-5320MHz) 11 Channels for 20MHz bandwidth(5500-5700MHz) 5 channels for 20MHz bandwidth(5745-5825MHz) 2 channels for 40MHz bandwidth(5190~5230MHz) 2 channels for 40MHz bandwidth(5270~5310MHz) 5 Channels for 40MHz bandwidth(5510-5670MHz) 2 channels for 40MHz bandwidth(5755~5795MHz) 1 channels for 80MHz bandwidth(5210MHz) 1 channels for 80MHz bandwidth(5290MHz) 2 Channels for 80MHz bandwidth(5530-5610MHz) 1 channels for 80MHz bandwidth(5775MHz)
Modulation Type	IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac VHT20: OFDM (256QAM,64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac VHT40: OFDM (256QAM,64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac VHT80: OFDM (256QAM,64QAM, 16QAM, QPSK, BPSK)
Antenna Description	Shell S1: Internal Antenna 2, 4.72 dBi(Max.) for 2.4G Band and 5.26dBi(Max.) for 5G Band Shell S2: Internal Antenna 2, 5.26 dBi(Max.) for 2.4G Band and 5.33 dBi(Max.) for 5G Band
Note: Models Shell S1 and Shell S2 use different antennas of the same type and are tested using maximum antenna gain.	

2.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	<input type="radio"/>	230V / 50 Hz	<input type="radio"/>	120V / 60Hz
		<input type="radio"/>	12 V DC	<input type="radio"/>	24 V DC
		<input checked="" type="radio"/>	Other (specified in blank below)		

DC 20.0V

2.4. Short description of the Equipment under Test (EUT)

This is a Smart Karaoke Speaker.

For more details, refer to the user's manual of the EUT.

2.5. EUT operation mode

The application provider specific test software to control sample in continuous TX and RX.

Antenna	Chain0 (ANT0)			Chain1 (ANT1)			Simultaneously
Bandwidth Mode	20MHz	40MHz	80MHz	20MHz	40MHz	80MHz	/
IEEE 802.11a	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
IEEE 802.11n	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
IEEE 802.11ac	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

IEEE 802.11a/ac20/ac40/ac80/n20/n40:

UNII-1		UNII-1		UNII-1	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190	42	5210
40	5200	46	5230		
44	5220				
48	5240				

U-NI-2A		U-NI-2A		U-NI-2A	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	54	5270	58	5290
56	5280	62	5310		
60	5300				
64	5320				

U-NI-2C		U-NI-2C		U-NI-2C	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	102	5510	106	5530
104	5520	110	5550	122	5610
108	5540	118	5590		
112	5560	126	5630		
116	5580	134	5670		
120	5600				
124	5620				
128	5640				
132	5660				
136	5680				
140	5700				

U-NI-3		U-NI-3		U-NI-3	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755	155	5775
153	5765	159	5795		
157	5785				
161	5805				
165	5825				

The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in X position. AC conducted emission pre-test at both at AC 120V/60Hz and AC 240V/50Hz modes, recorded worst case(AC 120V/60Hz).

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be IEEE 802.11ac VHT20 mode (HCH).

2.6. Block Diagram of Test Setup



2.7. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2BCRN-SHELLS1** filing to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.

2.8. EUT Exercise Software

The system was configured for testing in a continuous transmits condition and change test channels by software (MTK Mode) provided by application.

2.9. Special Accessories

Manufacturer	Description	Model	Serial Number	Certificate
LANTO ELECTRONNIC LIMITED	Adapter	191106C	--	SDOC

Note: The Adapter only used for auxiliary testing.

2.10. External I/O Cable

I/O Port Description	Quantity	Cable
DC IN Port	1	1.0M, Unscreened Cable
AV Port	3	N/A
Type-c Port	1	N/A
USB Port	1	N/A
HDMI Port	1	N/A

2.11. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 517856 Designation Number: CN1318

Shenzhen CTA Testing Technology Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA-Lab Cert. No.: 6534.01

Shenzhen CTA Testing Technology Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 °C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen CTA Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device. Hereafter the best measurement capability for Shenzhen CTA Testing Technology Co., Ltd. :

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	9KHz~30MHz	3.02 dB	(1)
Radiated Emission	30~1000MHz	4.06 dB	(1)
Radiated Emission	1~18GHz	5.14 dB	(1)
Radiated Emission	18-40GHz	5.38 dB	(1)
Conducted Disturbance	0.15~30MHz	2.14 dB	(1)
Output Peak power	30MHz~18GHz	0.55 dB	(1)
Power spectral density	/	0.57 dB	(1)
Spectrum bandwidth	/	1.1%	(1)
Radiated spurious emission (30MHz-1GHz)	30~1000MHz	4.10 dB	(1)
Radiated spurious emission (1GHz-18GHz)	1~18GHz	4.32 dB	(1)
Radiated spurious emission (18GHz-40GHz)	18-40GHz	5.54 dB	(1)

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.5. Test Description

Applied Standard: FCC Part 15 Subpart E				
FCC Rules	Description of Test	Test Sample	Result	Remark
/	On Time and Duty Cycle	CTA240715019-S0001-1#	Compliant	Appendix D Appendix E Appendix F Appendix G
§15.407(a)	Maximum Conducted Output Power	CTA240715019-S0001-1#	Compliant	Appendix D Appendix E Appendix F Appendix G
§15.407(a)	Power Spectral Density	CTA240715019-S0001-1#	Compliant	Appendix D Appendix E Appendix F Appendix G
§15.407(a)	26dB&6dB Bandwidth and 99% Bandwidth	CTA240715019-S0001-1#	Compliant	Appendix D Appendix E Appendix F Appendix G
§15.209, §15.407(b)	Radiated Emissions	CTA240715019-S0001-1# CTA240715019-S0001-2#	Compliant	Note 1
§15.209, §15.407(b)	Conducted Spurious Emissions and Band Edges Test	CTA240715019-S0001-1#	Compliant	Appendix D Appendix E Appendix F Appendix G
§15.209, §15.407(b)	Emissions at Restricted Band	CTA240715019-S0001-1#	Compliant	Appendix D Appendix E Appendix F Appendix G
§15.407(g)	Frequency Stability	CTA240715019-S0001-1#	Compliant	Note 1
§15.207(a)	AC Mians Line Conducted Emissions	CTA240715019-S0001-2#	Compliant	Note 1
§15.203 §15.407(h)	Antenna Requirements	CTA240715019-S0001-1#	Compliant	Note 1
§15.407 §2.1091	RF Exposure	/	Compliant	Note 2

Remark:

1. The measurement uncertainty is not included in the test result.
2. NA = Not Applicable; NP = Not Performed
3. Note 1 – Test results inside test report;
4. Note 2 – Test results in other test report (MPE Report).
5. We tested all test mode and recorded worst case in report

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate
Maximum Peak Conducted Output Power	802.11a	6 Mbps
Power Spectral Density		
6dB Bandwidth		
26dB Bandwidth	802.11ac20/ac40/ac80 802.11n HT20/40	MCS0
Radiated Emission 30M~1GHz &		
Radiated Emission 1GHz~10 th Harmonic		
Band Edge	802.11a	6 Mbps
	802.11ac20/ac40/ac80 802.11n HT20/40	MCS0

3.6. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Equipment No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	CTA-308	2024/08/02	2025/08/01
LISN	R&S	ENV216	CTA-314	2024/08/02	2025/08/01
EMI Test Receiver	R&S	ESPI	CTA-307	2024/08/02	2025/08/01
EMI Test Receiver	R&S	ESCI	CTA-306	2024/08/02	2025/08/01
Spectrum Analyzer	Agilent	N9020A	CTA-301	2024/08/02	2025/08/01
Spectrum Analyzer	R&S	FSP	CTA-337	2024/08/02	2025/08/01
Vector Signal generator	Agilent	N5182A	CTA-305	2024/08/02	2025/08/01
Analog Signal Generator	R&S	SML03	CTA-304	2024/08/02	2025/08/01
Universal Radio Communication	CMW500	R&S	CTA-302	2024/08/02	2025/08/01
Temperature and humidity meter	Chigo	ZG-7020	CTA-326	2024/08/02	2025/08/01
Ultra-Broadband Antenna	Schwarzbeck	VULB9163	CTA-310	2023/10/17	2024/10/16
Horn Antenna	Schwarzbeck	BBHA 9120D	CTA-309	2023/10/13	2024/10/12
Loop Antenna	Zhinan	ZN30900C	CTA-311	2023/10/17	2024/10/16
Horn Antenna	Beijing Hangwei Dayang	OBH100400	CTA-336	2024/08/02	2025/08/01
Antenna Tower	Suzhou Keletuo electronic Technology Co., LTD	BK-*AT-BS	N/A	N/A	N/A
Amplifier	Schwarzbeck	BBV 9745	CTA-312	2024/08/02	2025/08/01
Amplifier	Taiwan chengyi	EMC051845B	CTA-313	2024/08/02	2025/08/01
Directional coupler	NARDA	4226-10	CTA-303	2024/08/02	2025/08/01
High-Pass Filter	XingBo	XBLBQ-GTA18	CTA-402	2024/08/02	2025/08/01
High-Pass Filter	XingBo	XBLBQ-GTA27	CTA-403	2024/08/02	2025/08/01
Automated filter bank	Tonscend	JS0806-F	CTA-404	2024/08/02	2025/08/01
Power Sensor	Agilent	U2021XA	CTA-405	2024/08/02	2025/08/01
Amplifier	Schwarzbeck	BBV9719	CTA-406	2024/08/02	2025/08/01

Note:


1. The Cal.Interval was one year.

2. All devices whose calibration expired on Aug.02, 2024 were calibrated from Aug.03, 2023 to Aug.02, 2024.

4. TEST CONDITIONS AND RESULTS

4.1. AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2020.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2020
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2020
- 4 The EUT received DC 20.0V power, the adapter received AC120V/60Hz or AC 240V/50Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.
- 9 The LISN is greater than 40 cm from the vertical reference plane.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

DISTURBANCE Calculation

The AC mains conducted disturbance is calculated by adding the 10dB Pulse Limiter and Cable Factor and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$CD (\text{dBuV}) = RA (\text{dBuV}) + PL (\text{dB}) + CL (\text{dB})$$


Where CD = Conducted Disturbance	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	PL = 10 dB Pulse Limiter Factor

TEST RESULTS

Remark: We measured Conducted Emission at all mode in AC 120V/60Hz, the worst case was recorded .


Temperature	25°C	Humidity	60%
Test Engineer	Lushan Kong	Configurations	BT

Model:Shell S1

Power supply:	AC 120V/60Hz	Polarization	L									
Test Graph												
												
Final Data List												
NO.	Frequency	QP Reading	AVG. Reading	Factor	QP Result	Avg. Result	QP Limit	Avg. Limit	QP Margin	Avg. Margin	Line	Remark
1	0.15	40.24	31.17	10.35	50.59	41.52	66.00	56.00	15.41	14.48	L1	PASS
2	0.222	36.87	24.27	10.14	47.01	34.41	62.74	52.74	15.73	18.33	L1	PASS
3	0.294	33.17	17.46	10.10	43.27	27.56	60.41	50.41	17.14	22.85	L1	PASS
4	0.519	30.58	18.61	10.24	40.82	28.85	56.00	46.00	15.18	17.15	L1	PASS
5	0.9015	39.46	25.04	10.23	49.69	35.27	56.00	46.00	6.31	10.73	L1	PASS
6	2.301	29.51	12.27	10.29	39.80	22.56	56.00	46.00	16.20	23.44	L1	PASS

Note: 1. Result (dB μ V) = Reading (dB μ V) + Factor (dB).



2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Power supply:	AC 120V/60Hz	Polarization	N									
Test Graph												
												
Final Data List												
NO.	Frequency	QP Reading	AVG. Reading	Factor	QP Result	Avg. Result	QP Limit	Avg. Limit	QP Margin	Avg. Margin	Line	Remark
1	0.15	40.11	25.99	10.35	50.46	36.34	66.00	56.00	15.54	19.66	N	PASS
2	0.2265	36.19	22.13	10.14	46.33	32.27	62.58	52.58	16.25	20.31	N	PASS
3	0.681	32.40	17.26	10.22	42.62	27.48	56.00	46.00	13.38	18.52	N	PASS
4	0.888	41.20	23.97	10.23	51.43	34.20	56.00	46.00	4.57	11.80	N	PASS
5	1.2525	38.68	23.20	10.22	48.90	33.42	56.00	46.00	7.10	12.58	N	PASS
6	7.6785	30.79	11.86	10.55	41.34	22.41	60.00	50.00	18.66	27.59	N	PASS

Note: 1. Result (dB μ V) = Reading (dB μ V) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).


Model:Shell S2

Power supply:	AC 120V/60Hz	Polarization	L																																																																																																																				
Test Graph																																																																																																																							
																																																																																																																							
<table border="1"><caption>Final Data List</caption><thead><tr><th rowspan="2">NO.</th><th rowspan="2">Frequency</th><th colspan="2">QP</th><th colspan="2">AVG.</th><th colspan="2">Factor</th><th colspan="2">QP</th><th colspan="2">AVG.</th><th colspan="2">QP</th><th colspan="2">AVG.</th><th rowspan="2">Line</th><th rowspan="2">Remark</th></tr><tr><th>Reading</th><th>Result</th><th>Reading</th><th>Result</th><th>Factor</th><th>Result</th><th>QP</th><th>Limit</th><th>AVG.</th><th>Limit</th><th>QP</th><th>Margin</th><th>AVG.</th><th>Margin</th></tr></thead><tbody><tr><td>1</td><td>0.15</td><td>39.15</td><td>49.50</td><td>26.24</td><td>36.59</td><td>10.35</td><td>66.00</td><td>56.00</td><td>56.00</td><td>16.50</td><td>19.41</td><td>L1</td><td>PASS</td></tr><tr><td>2</td><td>0.2175</td><td>36.40</td><td>46.54</td><td>22.13</td><td>32.27</td><td>10.14</td><td>62.91</td><td>52.91</td><td>52.91</td><td>16.37</td><td>20.64</td><td>L1</td><td>PASS</td></tr><tr><td>3</td><td>0.303</td><td>32.23</td><td>42.34</td><td>20.42</td><td>30.53</td><td>10.11</td><td>60.16</td><td>50.16</td><td>50.16</td><td>17.82</td><td>19.63</td><td>L1</td><td>PASS</td></tr><tr><td>4</td><td>0.672</td><td>31.72</td><td>41.93</td><td>20.05</td><td>30.26</td><td>10.21</td><td>56.00</td><td>46.00</td><td>46.00</td><td>14.07</td><td>15.74</td><td>L1</td><td>PASS</td></tr><tr><td>5</td><td>0.906</td><td>37.34</td><td>47.56</td><td>19.16</td><td>29.38</td><td>10.22</td><td>56.00</td><td>46.00</td><td>46.00</td><td>8.44</td><td>16.62</td><td>L1</td><td>PASS</td></tr><tr><td>6</td><td>2.6295</td><td>29.45</td><td>39.76</td><td>8.46</td><td>18.77</td><td>10.31</td><td>56.00</td><td>46.00</td><td>46.00</td><td>16.24</td><td>27.23</td><td>L1</td><td>PASS</td></tr></tbody></table>				NO.	Frequency	QP		AVG.		Factor		QP		AVG.		QP		AVG.		Line	Remark	Reading	Result	Reading	Result	Factor	Result	QP	Limit	AVG.	Limit	QP	Margin	AVG.	Margin	1	0.15	39.15	49.50	26.24	36.59	10.35	66.00	56.00	56.00	16.50	19.41	L1	PASS	2	0.2175	36.40	46.54	22.13	32.27	10.14	62.91	52.91	52.91	16.37	20.64	L1	PASS	3	0.303	32.23	42.34	20.42	30.53	10.11	60.16	50.16	50.16	17.82	19.63	L1	PASS	4	0.672	31.72	41.93	20.05	30.26	10.21	56.00	46.00	46.00	14.07	15.74	L1	PASS	5	0.906	37.34	47.56	19.16	29.38	10.22	56.00	46.00	46.00	8.44	16.62	L1	PASS	6	2.6295	29.45	39.76	8.46	18.77	10.31	56.00	46.00	46.00	16.24	27.23	L1	PASS
NO.	Frequency	QP				AVG.		Factor		QP		AVG.		QP		AVG.		Line	Remark																																																																																																				
		Reading	Result	Reading	Result	Factor	Result	QP	Limit	AVG.	Limit	QP	Margin	AVG.	Margin																																																																																																								
1	0.15	39.15	49.50	26.24	36.59	10.35	66.00	56.00	56.00	16.50	19.41	L1	PASS																																																																																																										
2	0.2175	36.40	46.54	22.13	32.27	10.14	62.91	52.91	52.91	16.37	20.64	L1	PASS																																																																																																										
3	0.303	32.23	42.34	20.42	30.53	10.11	60.16	50.16	50.16	17.82	19.63	L1	PASS																																																																																																										
4	0.672	31.72	41.93	20.05	30.26	10.21	56.00	46.00	46.00	14.07	15.74	L1	PASS																																																																																																										
5	0.906	37.34	47.56	19.16	29.38	10.22	56.00	46.00	46.00	8.44	16.62	L1	PASS																																																																																																										
6	2.6295	29.45	39.76	8.46	18.77	10.31	56.00	46.00	46.00	16.24	27.23	L1	PASS																																																																																																										
Note: 1. Result (dB μ V) = Reading (dB μ V) + Factor (dB). 2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).																																																																																																																							
Power supply:	AC 120V/60Hz	Polarization	N																																																																																																																				
Test Graph																																																																																																																							
																																																																																																																							
<table border="1"><caption>Final Data List</caption><thead><tr><th rowspan="2">NO.</th><th rowspan="2">Frequency</th><th colspan="2">QP</th><th colspan="2">AVG.</th><th colspan="2">Factor</th><th colspan="2">QP</th><th colspan="2">AVG.</th><th colspan="2">QP</th><th colspan="2">AVG.</th><th rowspan="2">Line</th><th rowspan="2">Remark</th></tr><tr><th>Reading</th><th>Result</th><th>Reading</th><th>Result</th><th>Factor</th><th>Result</th><th>QP</th><th>Limit</th><th>AVG.</th><th>Limit</th><th>QP</th><th>Margin</th><th>AVG.</th><th>Margin</th></tr></thead><tbody><tr><td>1</td><td>0.15</td><td>39.22</td><td>49.57</td><td>26.46</td><td>36.81</td><td>10.35</td><td>66.00</td><td>56.00</td><td>56.00</td><td>16.43</td><td>19.19</td><td>N</td><td>PASS</td></tr><tr><td>2</td><td>0.222</td><td>36.11</td><td>46.25</td><td>23.62</td><td>33.76</td><td>10.14</td><td>62.74</td><td>52.74</td><td>52.74</td><td>16.49</td><td>18.98</td><td>N</td><td>PASS</td></tr><tr><td>3</td><td>0.681</td><td>33.36</td><td>43.58</td><td>20.41</td><td>30.63</td><td>10.22</td><td>56.00</td><td>46.00</td><td>46.00</td><td>12.42</td><td>15.37</td><td>N</td><td>PASS</td></tr><tr><td>4</td><td>0.897</td><td>42.75</td><td>52.98</td><td>26.66</td><td>36.89</td><td>10.23</td><td>56.00</td><td>46.00</td><td>46.00</td><td>3.02</td><td>9.11</td><td>N</td><td>PASS</td></tr><tr><td>5</td><td>1.194</td><td>38.28</td><td>48.49</td><td>20.74</td><td>30.95</td><td>10.21</td><td>56.00</td><td>46.00</td><td>46.00</td><td>7.51</td><td>15.05</td><td>N</td><td>PASS</td></tr><tr><td>6</td><td>7.989</td><td>30.60</td><td>41.17</td><td>10.22</td><td>20.79</td><td>10.57</td><td>60.00</td><td>50.00</td><td>50.00</td><td>18.83</td><td>29.21</td><td>N</td><td>PASS</td></tr></tbody></table>				NO.	Frequency	QP		AVG.		Factor		QP		AVG.		QP		AVG.		Line	Remark	Reading	Result	Reading	Result	Factor	Result	QP	Limit	AVG.	Limit	QP	Margin	AVG.	Margin	1	0.15	39.22	49.57	26.46	36.81	10.35	66.00	56.00	56.00	16.43	19.19	N	PASS	2	0.222	36.11	46.25	23.62	33.76	10.14	62.74	52.74	52.74	16.49	18.98	N	PASS	3	0.681	33.36	43.58	20.41	30.63	10.22	56.00	46.00	46.00	12.42	15.37	N	PASS	4	0.897	42.75	52.98	26.66	36.89	10.23	56.00	46.00	46.00	3.02	9.11	N	PASS	5	1.194	38.28	48.49	20.74	30.95	10.21	56.00	46.00	46.00	7.51	15.05	N	PASS	6	7.989	30.60	41.17	10.22	20.79	10.57	60.00	50.00	50.00	18.83	29.21	N	PASS
NO.	Frequency	QP				AVG.		Factor		QP		AVG.		QP		AVG.		Line	Remark																																																																																																				
		Reading	Result	Reading	Result	Factor	Result	QP	Limit	AVG.	Limit	QP	Margin	AVG.	Margin																																																																																																								
1	0.15	39.22	49.57	26.46	36.81	10.35	66.00	56.00	56.00	16.43	19.19	N	PASS																																																																																																										
2	0.222	36.11	46.25	23.62	33.76	10.14	62.74	52.74	52.74	16.49	18.98	N	PASS																																																																																																										
3	0.681	33.36	43.58	20.41	30.63	10.22	56.00	46.00	46.00	12.42	15.37	N	PASS																																																																																																										
4	0.897	42.75	52.98	26.66	36.89	10.23	56.00	46.00	46.00	3.02	9.11	N	PASS																																																																																																										
5	1.194	38.28	48.49	20.74	30.95	10.21	56.00	46.00	46.00	7.51	15.05	N	PASS																																																																																																										
6	7.989	30.60	41.17	10.22	20.79	10.57	60.00	50.00	50.00	18.83	29.21	N	PASS																																																																																																										
Note: 1. Result (dB μ V) = Reading (dB μ V) + Factor (dB). 2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).																																																																																																																							


4.2. Radiated Emission

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz; the EUT was placed on a turn table which is 1.5m above ground plane when testing above 1GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT minimum operation frequency was 24MHz and maximum operation frequency was 5825MHz. so radiated emission test frequency band from 9KHz to 40GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Anternna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

$$Transd=AF + CL - AG$$

RADIATION LIMIT

According to §15.407 (b): Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits

Frequency (MHz)	EIRP Limit (dBm)	Equivalent Field Strength at 3m (dB μ V/m)
5150-5250	-27	68.2
5250-5350	-27	68.2
5470-5725	-27	682
5725-5850	-27 (beyond 10MHz of the bandedge)	68.2
	-17 (within 10 MHz of band edge)	78.2

Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark: We measured Radiated Emission at all mode from 9KHz to 25GHz in AC 120V/60Hz and the worst case was recorded.

Temperature	23.4°C	Humidity	54.5%
Test Engineer	Lushan Kong	Configurations	IEEE 802.11ac20 HCH

For 9 KHz~30MHz

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Over Limit (dBuV)	Remark
-	-	-	-	See Note


Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

Model:Shell S1
For 30MHz-1GHz



Model:Shell S2
For 30MHz-1GHz



For 1GHz to 40GHz

Model:Shell S1

5150-5250MHz:

IEEE 802.11a (Worst Case)

802.11a Mode Channel 36 5180 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10360	39.17	38.55	33.13	11.26	55.85	68.20	-12.35	Peak	Horizontal
1	10360	30.16	38.55	33.13	11.26	46.84	54.00	-7.16	AV	Horizontal
1	10360	41.95	38.55	33.13	11.26	58.63	68.20	-9.57	Peak	Vertical
1	10360	29.22	38.55	33.13	11.26	45.90	54.00	-8.10	AV	Vertical

802.11a Mode Channel 40 5200 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10400	39.47	38.55	33.13	11.26	56.15	68.20	-12.05	Peak	Horizontal
1	10400	31.64	38.55	33.13	11.26	48.32	54.00	-5.68	AV	Horizontal
1	10400	40.67	38.55	33.13	11.26	57.35	68.20	-10.85	Peak	Vertical
1	10400	28.26	38.55	33.13	11.26	44.94	54.00	-9.06	AV	Vertical

802.11a Mode Channel 48 5240 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10480	39.30	38.55	33.13	11.26	55.98	68.20	-12.22	Peak	Horizontal
1	10480	31.43	38.55	33.13	11.26	48.11	54.00	-5.89	AV	Horizontal
1	10480	41.14	38.55	33.13	11.26	57.82	68.20	-10.38	Peak	Vertical
1	10480	29.96	38.55	33.13	11.26	46.64	54.00	-7.36	AV	Vertical

5260-5320MHz:

IEEE 802.11a (Worst Case)

802.11a Mode_Channel 52_5260 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10520	40.02	38.55	33.13	11.26	56.70	68.20	-11.50	Peak	Horizontal
1	10520	30.63	38.55	33.13	11.26	47.31	54.00	-6.69	AV	Horizontal
1	10520	41.93	38.55	33.13	11.26	58.61	68.20	-9.59	Peak	Vertical
1	10520	28.63	38.55	33.13	11.26	45.31	54.00	-8.69	AV	Vertical

802.11a Mode_Channel 56_5280 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10560	39.81	38.55	33.13	11.26	56.49	68.20	-11.71	Peak	Horizontal
1	10560	30.76	38.55	33.13	11.26	47.44	54.00	-6.56	AV	Horizontal
1	10560	41.11	38.55	33.13	11.26	57.79	68.20	-10.41	Peak	Vertical
1	10560	28.22	38.55	33.13	11.26	44.90	54.00	-9.10	AV	Vertical

802.11a Mode_Channel 64_5320 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10640	40.38	38.55	33.13	11.26	57.06	68.20	-11.14	Peak	Horizontal
1	10640	30.78	38.55	33.13	11.26	47.46	54.00	-6.54	AV	Horizontal
1	10640	41.63	38.55	33.13	11.26	58.31	68.20	-9.89	Peak	Vertical
1	10640	28.04	38.55	33.13	11.26	44.72	54.00	-9.28	AV	Vertical

5500-5700MHz:

IEEE 802.11a (Worst Case)

802.11a Mode_Channel 100_5500 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11000	40.56	38.55	33.13	11.26	57.24	68.20	-10.96	Peak	Horizontal
1	11000	30.96	38.55	33.13	11.26	47.64	54.00	-6.36	AV	Horizontal
1	11000	40.61	38.55	33.13	11.26	57.29	68.20	-10.91	Peak	Vertical
1	11000	28.67	38.55	33.13	11.26	45.35	54.00	-8.65	AV	Vertical

802.11a Mode_Channel 120_5580 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11160	39.87	38.55	33.13	11.26	56.55	68.20	-11.65	Peak	Horizontal
1	11160	31.79	38.55	33.13	11.26	48.47	54.00	-5.53	AV	Horizontal
1	11160	41.58	38.55	33.13	11.26	58.26	68.20	-9.94	Peak	Vertical
1	11160	28.53	38.55	33.13	11.26	45.21	54.00	-8.79	AV	Vertical

802.11a Mode_Channel 140_5700 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11400	39.44	38.55	33.13	11.26	56.12	68.20	-12.08	Peak	Horizontal
1	11400	30.69	38.55	33.13	11.26	47.37	54.00	-6.63	AV	Horizontal
1	11400	40.33	38.55	33.13	11.26	57.01	68.20	-11.19	Peak	Vertical
1	11400	28.97	38.55	33.13	11.26	45.65	54.00	-8.35	AV	Vertical

5725-5850MHz:

IEEE 802.11a (Worst Case)

802.11a Mode_Channel 149_5745 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11490	40.93	38.55	33.13	11.26	57.61	68.20	-10.59	Peak	Horizontal
1	11490	30.07	38.55	33.13	11.26	46.75	54.00	-7.25	AV	Horizontal
1	11490	41.11	38.55	33.13	11.26	57.79	68.20	-10.41	Peak	Vertical
1	11490	29.57	38.55	33.13	11.26	46.25	54.00	-7.75	AV	Vertical

802.11a Mode_Channel 157_5785 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11570	39.91	38.55	33.13	11.26	56.59	68.20	-11.61	Peak	Horizontal
1	11570	31.24	38.55	33.13	11.26	47.92	54.00	-6.08	AV	Horizontal
1	11570	41.73	38.55	33.13	11.26	58.41	68.20	-9.79	Peak	Vertical
1	11570	28.36	38.55	33.13	11.26	45.04	54.00	-8.96	AV	Vertical

802.11a Mode_Channel 165_5825 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11650	39.97	38.55	33.13	11.26	56.65	68.20	-11.55	Peak	Horizontal
1	11650	30.92	38.55	33.13	11.26	47.60	54.00	-6.40	AV	Horizontal
1	11650	41.56	38.55	33.13	11.26	58.24	68.20	-9.96	Peak	Vertical
1	11650	29.68	38.55	33.13	11.26	46.36	54.00	-7.64	AV	Vertical

Model:Shell S2
5150-5250MHz:

IEEE 802.11a (Worst Case)

802.11a Mode Channel 36 5180 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10360	40.12	38.55	33.13	11.26	56.80	68.20	-11.40	Peak	Horizontal
1	10360	31.64	38.55	33.13	11.26	48.32	54.00	-5.68	AV	Horizontal
1	10360	40.24	38.55	33.13	11.26	56.92	68.20	-11.28	Peak	Vertical
1	10360	28.58	38.55	33.13	11.26	45.26	54.00	-8.74	AV	Vertical

802.11a Mode Channel 40 5200 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10400	40.11	38.55	33.13	11.26	56.79	68.20	-11.41	Peak	Horizontal
1	10400	30.77	38.55	33.13	11.26	47.45	54.00	-6.55	AV	Horizontal
1	10400	40.91	38.55	33.13	11.26	57.59	68.20	-10.61	Peak	Vertical
1	10400	28.56	38.55	33.13	11.26	45.24	54.00	-8.76	AV	Vertical

802.11a Mode Channel 48 5240 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10480	40.27	38.55	33.13	11.26	56.95	68.20	-11.25	Peak	Horizontal
1	10480	31.57	38.55	33.13	11.26	48.25	54.00	-5.75	AV	Horizontal
1	10480	41.46	38.55	33.13	11.26	58.14	68.20	-10.06	Peak	Vertical
1	10480	28.43	38.55	33.13	11.26	45.11	54.00	-8.89	AV	Vertical

5260-5320MHz:

IEEE 802.11a (Worst Case)

802.11a Mode_Channel 52_5260 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10520	39.64	38.55	33.13	11.26	56.32	68.20	-11.88	Peak	Horizontal
1	10520	31.54	38.55	33.13	11.26	48.22	54.00	-5.78	AV	Horizontal
1	10520	41.54	38.55	33.13	11.26	58.22	68.20	-9.98	Peak	Vertical
1	10520	28.21	38.55	33.13	11.26	44.89	54.00	-9.11	AV	Vertical

802.11a Mode_Channel 56_5280 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10560	40.72	38.55	33.13	11.26	57.40	68.20	-10.80	Peak	Horizontal
1	10560	31.02	38.55	33.13	11.26	47.70	54.00	-6.30	AV	Horizontal
1	10560	40.60	38.55	33.13	11.26	57.28	68.20	-10.92	Peak	Vertical
1	10560	29.90	38.55	33.13	11.26	46.58	54.00	-7.42	AV	Vertical

802.11a Mode_Channel 64_5320 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10640	39.94	38.55	33.13	11.26	56.62	68.20	-11.58	Peak	Horizontal
1	10640	31.35	38.55	33.13	11.26	48.03	54.00	-5.97	AV	Horizontal
1	10640	40.45	38.55	33.13	11.26	57.13	68.20	-11.07	Peak	Vertical
1	10640	29.20	38.55	33.13	11.26	45.88	54.00	-8.12	AV	Vertical

5500-5700MHz:

IEEE 802.11a (Worst Case)

802.11a Mode_Channel 100_5500 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11000	40.29	38.55	33.13	11.26	56.97	68.20	-11.23	Peak	Horizontal
1	11000	30.02	38.55	33.13	11.26	46.70	54.00	-7.30	AV	Horizontal
1	11000	41.17	38.55	33.13	11.26	57.85	68.20	-10.35	Peak	Vertical
1	11000	28.60	38.55	33.13	11.26	45.28	54.00	-8.72	AV	Vertical

802.11a Mode_Channel 120_5580 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11160	40.61	38.55	33.13	11.26	57.29	68.20	-10.91	Peak	Horizontal
1	11160	31.64	38.55	33.13	11.26	48.32	54.00	-5.68	AV	Horizontal
1	11160	40.12	38.55	33.13	11.26	56.80	68.20	-11.40	Peak	Vertical
1	11160	29.50	38.55	33.13	11.26	46.18	54.00	-7.82	AV	Vertical

802.11a Mode_Channel 140_5700 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11400	40.88	38.55	33.13	11.26	57.56	68.20	-10.64	Peak	Horizontal
1	11400	30.87	38.55	33.13	11.26	47.55	54.00	-6.45	AV	Horizontal
1	11400	40.89	38.55	33.13	11.26	57.57	68.20	-10.63	Peak	Vertical
1	11400	28.54	38.55	33.13	11.26	45.22	54.00	-8.78	AV	Vertical

5725-5850MHz:

IEEE 802.11a (Worst Case)

802.11a Mode_Channel 149_5745 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11490	40.36	38.55	33.13	11.26	57.04	68.20	-11.16	Peak	Horizontal
1	11490	30.81	38.55	33.13	11.26	47.49	54.00	-6.51	AV	Horizontal
1	11490	42.00	38.55	33.13	11.26	58.68	68.20	-9.52	Peak	Vertical
1	11490	29.47	38.55	33.13	11.26	46.15	54.00	-7.85	AV	Vertical

802.11a Mode_Channel 157_5785 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11570	39.79	38.55	33.13	11.26	56.47	68.20	-11.73	Peak	Horizontal
1	11570	30.19	38.55	33.13	11.26	46.87	54.00	-7.13	AV	Horizontal
1	11570	40.54	38.55	33.13	11.26	57.22	68.20	-10.98	Peak	Vertical
1	11570	29.73	38.55	33.13	11.26	46.41	54.00	-7.59	AV	Vertical

802.11a Mode_Channel 165_5825 MHz


Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11650	40.62	38.55	33.13	11.26	57.30	68.20	-10.90	Peak	Horizontal
1	11650	31.12	38.55	33.13	11.26	47.80	54.00	-6.20	AV	Horizontal
1	11650	41.31	38.55	33.13	11.26	57.99	68.20	-10.21	Peak	Vertical
1	11650	28.88	38.55	33.13	11.26	45.56	54.00	-8.44	AV	Vertical

REMARKS:

1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. Margin = Result Level - Limit
3. The other emission levels were very low against the limit.
4. Detector AV is setting spectrum/receiver. RBW=1MHz/VBW=10Hz/Sweep time=Auto/Detector=Peak;

4.3. Duty Cycle

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General U-NII Test Procedures New Rules v02r01 Duty Cycle (x), Transmission Duration (T):

- a. A diode detector and an oscilloscope that together have sufficiently short response time to permit accurate measurements of the on and off times of the transmitted signal
- b. The zero-span mode on a spectrum analyzer or EMI receiver, if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW \geq EBW if possible; otherwise, set RBW to the largest available value. Set VBW \geq RBW. Set detector = peak or average. The zerospan measurement method shall not be used unless both RBW and VBW are $> 50/T$, where T is defined in section II.B.1.a), and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

TEST RESULTS

For reporting purpose only.

Please refer to Appendix D.3.


Please refer to Appendix E.3.

Please refer to Appendix F.3.

Please refer to Appendix G.3.

4.4. Maximum Average Output Power

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General U-NII Test Procedures New Rules v02r01 Measurement using a Power Meter (PM):

- a. Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied
 1. The EUT is configured to transmit continuously or to transmit with a constant duty cycle
 2. At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.
 3. The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b. If the transmitter does not transmit continuously, measure the duty cycle, x, of the transmitter output signal as described in section II.B
- c. Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

Adjust the measurement in dBm by adding $10 \log(1/x)$ where x is the duty cycle (e.g., $10 \log(1/0.25)$ if the duty cycle is 25 percent).

LIMIT

According to §15.407(a): The maximum output power should be not exceed follow:

Frequency Range (MHz)	Limit
5150-5250	Fixed: 1 Watt (30dBm) Mobile and portable: 250mW (24dBm)
5250-5350	250mW (24dBm)
5470-5725	250mW (24dBm)
5725-5850	1 Watt (30dBm)

Note: The maximum e.i.r.p at anyelevation angle above 30 degrees as measured from the horizon must not exceed 125mW(21dBm)

TEST RESULTS

For reporting purpose only.

Please refer to Appendix D.4.

Please refer to Appendix E.4.

Please refer to Appendix F.4.

Please refer to Appendix G.4.

4.5. Power Spectral Density

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General U-NII Test Procedures New Rules v02r01: The rules requires "maximum power spectral density" measurements where the intent is to measure the maximum value of the time average of the power spectral density measured during a period of continuous transmission

- a. Create an average power spectrum for the EUT operating mode being tested by following the instructions in section II.E.2. for measuring maximum conducted output power using a spectrum analyzer or EMI receiver: select the appropriate test method (SA-1, SA-2, SA-3, or alternatives to each) and apply it up to, but not including, the step labeled, "Compute power...". (This procedure is required even if the maximum conducted output power measurement was performed using a power meter, method PM.)
- b. Use the peak search function on the instrument to find the peak of the spectrum and record its value.
- c. Make the following adjustments to the peak value of the spectrum, if applicable:
 1. If Method SA-2 or SA-2 Alternative was used, add $10 \log(1/x)$, where x is the duty cycle, to the peak of the spectrum.
 2.) If Method SA-3 Alternative was used and the linear mode was used in step II.E.2.g)(viii), add 1 dB to the final result to compensate for the difference between linear averaging and power averaging.
- d. The result is the Maximum PSD over 1 MHz reference bandwidth.
- e. For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, "provided that the measured power is integrated over the full reference bandwidth" to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 kHz bandwidth, the following adjustments to the procedures apply:
 1. Set RBW $\geq 1/T$, where T is defined in section II.B.I.a).
 2. Set VBW ≥ 3 RBW.
 3. If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log(500\text{kHz}/\text{RBW})$ to the measured result, whereas RBW (< 500 kHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
 4. If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10 \log(1\text{MHz}/\text{RBW})$ to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
 5. Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 kHz for the sections 5.c) and 5.d) above, since RBW=100 kHz is available on nearly all spectrum analyzers.

- f. Adjust the measurement in dBm by adding $10 \log(1/x)$ where x is the duty cycle (e.g., $10 \log(1/0.25)$ if the duty cycle is 25 percent).

LIMIT

According to §15.407(a): The maximum output power should be not exceed follow:

Frequency Range (MHz)	Limit
5150-5250	Other then Mobile and portable:17dBm/MHz Mobile and portable:11dBm/MHz
5250-5350	11dBm/MHz
5470-5725	11dBm/MHz
5725-5850	30dBm/500kHz

TEST RESULTS

For reporting purpose only.

Please refer to Appendix D.5.


Please refer to Appendix E.5.

Please refer to Appendix F.5.

Please refer to Appendix G.5.

4.6. 99% and 6dB Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General U-NII Test Procedures New Rules v02r01 for one of the following procedures may be used for section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The $RBW = 1\% - 3\%$ of occupied bandwidth, $VBW = 3 * RBW$ for 99% occupied bandwidth;
3. The $RBW = 100K$, $VBW = 3 * RBW$ for 6dB occupied bandwidth;
4. Measured the spectrum width with power higher than 6dB below carrier.
5. Measured the 99% and 6dB occupied bandwidth by related function of the spectrum analyzer.

LIMIT

For Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.725-5.85 GHz

TEST RESULTS


For reporting purpose only.

Please refer to Appendix G.1.

Please refer to Appendix G.2.

4.7. 99% and 26dBc Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The RBW = 1% - 3% of occupied bandwidth, VBW = 3*RBW;
3. Measured the spectrum width with power higher than 26dB below carrier.
4. Measured the 99% and 26dB occupied bandwidth by related function of the spectrum analyzer.

LIMIT

No Limits for 26dBc Bandwidth

TEST RESULTS

For reporting purpose only.

Please refer to Appendix D.1.

Please refer to Appendix D.2.

Please refer to Appendix E.1.


Please refer to Appendix E.2.

Please refer to Appendix F.1.

Please refer to Appendix F.2.

4.8. Conducted Spurious Emissions and Band Edge Compliance

TEST CONFIGURATION



LIMIT

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
0.009-0.49	3	$20\log(2400/F(\text{MHz}))+40\log(300/3)$	$2400/F(\text{MHz})$
0.49-1.705	3	$20\log(24000/F(\text{MHz}))+40\log(30/3)$	$24000/F(\text{MHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

According to §15.407 (b): Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits

Frequency (MHz)	EIRP Limit (dBm)	Equivalent Field Strength at 3m (dB μ V/m)
5150-5250	-27	68.2
5250-5350	-27	68.2
5470-5725	-27	68.2
5725-5850	-27 (beyond 10MHz of the bandedge)	68.2
	-17 (within 10 MHz of band edge)	78.2

TEST PROCEDURE

1. The EUT was placed on a turn table which is 1.5m above 1GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed..
5. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
1GHz-18GHz	Double Ridged Horn Antenna	3

6. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
1GHz-18GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$\mathbf{FS = RA + AF + CL - AG}$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude		AG = Amplifier Gain
AF = Antenna Factor		

TEST RESULTS

Remark:For radiated bandedge We measured at both mode, recorded worst case in antenna 0's 802.11 ac20 mode;

For Conducted at Restricted Band Measurement

For reporting purpose only.

Please refer to Appendix D.8.

Please refer to Appendix E.8.

Please refer to Appendix F.8.

Please refer to Appendix G.8.

For Conducted Band edge Measurement

For reporting purpose only.

Please refer to Appendix D.6.

Please refer to Appendix E.6.

Please refer to Appendix F.6.

Please refer to Appendix G.6.

For Conducted Spurious Emissions Measurement

For reporting purpose only.

Please refer to Appendix D.7.

Please refer to Appendix E.7.

Please refer to Appendix F.7.

Please refer to Appendix G.7.

4.9. Frequency Stability


Standard Applicable

According to FCC §15.407(g) "Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user manual."

According to FCC §2.1055(a) "The frequency stability shall be measured with variation of ambient temperature as follows:"

- (1) From -30° to + 50° centigrade for all equipment except that specified in paragraphs (a) (2) and (3) of this section.
- (2) From -20° to + 50° centigrade for equipment to be licensed for use in the Maritime Services under part 80 of this chapter, except for Class A, B, and S Emergency Position Indicating Radiobeacons (EPIRBS), and equipment to be licensed for use above 952 MHz at operational fixed stations in all services, stations in the Local Television Transmission Service and Point-to-Point Microwave Radio Service under part 21 of this chapter, equipment licensed for use aboard aircraft in the Aviation Services under part 87 of this chapter, and equipment authorized for use in the Family Radio Service under part 95 of this chapter.
- (3) From 0° to + 50° centigrade for equipment to be licensed for use in the Radio Broadcast Services under part 73 of this chapter.

Test Configuration



Test Procedure

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20 degree operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30 degree. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10 degree increased per stage until the highest temperature of +50 degree reached.

Test Results

PASS

Remark:

1. Measured all conditions and recorded worst case.

IEEE 802.11a Mode / 5180 – 5240 MHz / 5180 MHz

Enviroment Temperature (Dregree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 22.0V	5171.529444	5150 – 5250	PASS
20	DC 18.0V	5171.587832	5150 – 5250	PASS
50	DC 20.0V	5171.596598	5150 – 5250	PASS
40	DC 20.0V	5171.648338	5150 – 5250	PASS
30	DC 20.0V	5171.685991	5150 – 5250	PASS
20	DC 20.0V	5171.579461	5150 – 5250	PASS
10	DC 20.0V	5171.549529	5150 – 5250	PASS
0	DC 20.0V	5171.645655	5150 – 5250	PASS
-10	DC 20.0V	5171.629703	5150 – 5250	PASS
-20	DC 20.0V	5171.517857	5150 – 5250	PASS
-30	DC 20.0V	5171.660299	5150 – 5250	PASS

IEEE 802.11a Mode / 5180 – 5240 MHz / 5240 MHz

Enviroment Temperature (Dregree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 22.0V	5248.593399	5150 – 5250	PASS
20	DC 18.0V	5248.510552	5150 – 5250	PASS
50	DC 20.0V	5248.559547	5150 – 5250	PASS
40	DC 20.0V	5248.629856	5150 – 5250	PASS
30	DC 20.0V	5248.556288	5150 – 5250	PASS
20	DC 20.0V	5248.671909	5150 – 5250	PASS
10	DC 20.0V	5248.645823	5150 – 5250	PASS
0	DC 20.0V	5248.699087	5150 – 5250	PASS
-10	DC 20.0V	5248.523874	5150 – 5250	PASS
-20	DC 20.0V	5248.543578	5150 – 5250	PASS
-30	DC 20.0V	5248.598673	5150 – 5250	PASS

IEEE 802.11a Mode / 5260 – 5320 MHz / 5260 MHz

Enviroment Temperature (Dregree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 22.0V	5251.543517	5250 – 5350	PASS
20	DC 18.0V	5251.538615	5250 – 5350	PASS
50	DC 20.0V	5251.572129	5250 – 5350	PASS
40	DC 20.0V	5251.552778	5250 – 5350	PASS
30	DC 20.0V	5251.648509	5250 – 5350	PASS
20	DC 20.0V	5251.598824	5250 – 5350	PASS
10	DC 20.0V	5251.536960	5250 – 5350	PASS
0	DC 20.0V	5251.659565	5250 – 5350	PASS
-10	DC 20.0V	5251.542386	5250 – 5350	PASS
-20	DC 20.0V	5251.572169	5250 – 5350	PASS
-30	DC 20.0V	5251.611033	5250 – 5350	PASS

IEEE 802.11a Mode / 5260 – 5320 MHz / 5320 MHz

Enviroment Temperature (Dregree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 22.0V	5328.519247	5250 – 5350	PASS
20	DC 18.0V	5328.629540	5250 – 5350	PASS
50	DC 20.0V	5328.540036	5250 – 5350	PASS
40	DC 20.0V	5328.556698	5250 – 5350	PASS
30	DC 20.0V	5328.522968	5250 – 5350	PASS
20	DC 20.0V	5328.532018	5250 – 5350	PASS
10	DC 20.0V	5328.507683	5250 – 5350	PASS
0	DC 20.0V	5328.695483	5250 – 5350	PASS
-10	DC 20.0V	5328.637539	5250 – 5350	PASS
-20	DC 20.0V	5328.681097	5250 – 5350	PASS
-30	DC 20.0V	5328.573611	5250 – 5350	PASS

IEEE 802.11a Mode / 5500 – 5700 MHz / 5500 MHz

Enviroment Temperature (Dregree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 22.0V	5491.514444	5470 – 5725	PASS
20	DC 18.0V	5491.555611	5470 – 5725	PASS
50	DC 20.0V	5491.586335	5470 – 5725	PASS
40	DC 20.0V	5491.554403	5470 – 5725	PASS
30	DC 20.0V	5491.550919	5470 – 5725	PASS
20	DC 20.0V	5491.634474	5470 – 5725	PASS
10	DC 20.0V	5491.540753	5470 – 5725	PASS
0	DC 20.0V	5491.656543	5470 – 5725	PASS
-10	DC 20.0V	5491.657134	5470 – 5725	PASS
-20	DC 20.0V	5491.621061	5470 – 5725	PASS
-30	DC 20.0V	5491.516945	5470 – 5725	PASS

IEEE 802.11a Mode / 5500 – 5700 MHz / 5700 MHz

Enviroment Temperature (Dregree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 22.0V	5708.646016	5470 – 5725	PASS
20	DC 18.0V	5708.606923	5470 – 5725	PASS
50	DC 20.0V	5708.639368	5470 – 5725	PASS
40	DC 20.0V	5708.634826	5470 – 5725	PASS
30	DC 20.0V	5708.633476	5470 – 5725	PASS
20	DC 20.0V	5708.566839	5470 – 5725	PASS
10	DC 20.0V	5708.608993	5470 – 5725	PASS
0	DC 20.0V	5708.671639	5470 – 5725	PASS
-10	DC 20.0V	5708.535882	5470 – 5725	PASS
-20	DC 20.0V	5708.596548	5470 – 5725	PASS
-30	DC 20.0V	5708.669211	5470 – 5725	PASS

IEEE 802.11a Mode / 5745 – 5825 MHz / 5745 MHz

Enviroment Temperature (Dregree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 22.0V	5736.555416	5725 – 5850	PASS
20	DC 18.0V	5736.696547	5725 – 5850	PASS
50	DC 20.0V	5736.541030	5725 – 5850	PASS
40	DC 20.0V	5736.513092	5725 – 5850	PASS
30	DC 20.0V	5736.621543	5725 – 5850	PASS
20	DC 20.0V	5736.564317	5725 – 5850	PASS
10	DC 20.0V	5736.571745	5725 – 5850	PASS
0	DC 20.0V	5736.664155	5725 – 5850	PASS
-10	DC 20.0V	5736.555434	5725 – 5850	PASS
-20	DC 20.0V	5736.667651	5725 – 5850	PASS
-30	DC 20.0V	5736.601455	5725 – 5850	PASS

IEEE 802.11a Mode / 5745 – 5825 MHz / 5825 MHz

Enviroment Temperature (Dregree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 22.0V	5833.695340	5725 – 5850	PASS
20	DC 18.0V	5833.632301	5725 – 5850	PASS
50	DC 20.0V	5833.616732	5725 – 5850	PASS
40	DC 20.0V	5833.646580	5725 – 5850	PASS
30	DC 20.0V	5833.539254	5725 – 5850	PASS
20	DC 20.0V	5833.517459	5725 – 5850	PASS
10	DC 20.0V	5833.567516	5725 – 5850	PASS
0	DC 20.0V	5833.639147	5725 – 5850	PASS
-10	DC 20.0V	5833.649766	5725 – 5850	PASS
-20	DC 20.0V	5833.587227	5725 – 5850	PASS
-30	DC 20.0V	5833.529104	5725 – 5850	PASS

4.10. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.407 (a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Antenna Information

The antenna is Internal Aantenna, through the buckle stretched out, The directional gains of antenna used for transmitting is 5.33dBi.

Reference to the Test Report: **CTA24071501901**.

5. TEST SETUP PHOTOS OF THE EUT

Reference to the test report No. **CTA24071501901**.

6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT

Reference to the test report No. **CTA24071501901**.

.....**End of Report**.....