

FCC Test Report

Report No.: AGC16840241201FR04

FCC ID : 2BCRN-SHELLS3

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION: Smart Karaoke Machine

BRAND NAME : Ikarao

MODEL NAME : Shell S3

APPLICANT: Dongguan Aika Electronic Technology Co., Ltd.

DATE OF ISSUE : Feb. 05, 2025

STANDARD(S) : FCC Part 15 Subpart E §15.407

REPORT VERSION: V1.0

Attestation of Global Conclance (Shenzhen) Co., Ltd



Page 2 of 121


Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Feb. 05, 2025	Valid	Initial Release




Table of Contents

1. General Information	5
2. Product Information	6
2.1 Product Technical Description	6
2.2 Table of Carrier Frequency	7
2.3 IEEE 802.11n Modulation Scheme	8
2.4 Related Submittal(S) / Grant (S)	9
2.5 Test Methodology	9
2.6 Special Accessories	9
2.7 Equipment Modifications	9
2.8 Antenna Requirement	9
2.9 Description of Test Software	10
3. Test Environment	11
3.1 Address of The Test Laboratory	11
3.2 Test Facility	11
3.3 Environmental Conditions	12
3.4 Measurement Uncertainty	12
3.5 List of Equipment Used	13
4.System Test Configuration	15
4.1 EUT Configuration	15
4.2 EUT Exercise	15
4.3 Configuration of Tested System	15
4.4 Equipment Used in Tested System	15
4.5 Summary of Test Results	16
5. Description of Test Modes	17
6. Duty Cycle Measurement	20
7. RF Output Power Measurement	
7.1 Provisions Applicable	23
7.2 Measurement Procedure	23
7.3 Measurement Setup (Block Diagram of Configuration)	23
7.4 Measurement Result	24
8. 6dB&26dB Bandwidth Measurement	26
8.1 Provisions Applicable	26
8.2 Measurement Procedure	26
8.3 Measurement Setup (Block Diagram of Configuration)	26
8.4 Measurement Results	27





9. Power Spectral Density Measurement	50
9.1 Provisions Applicable	50
9.2 Measurement Procedure	50
9.3 Measurement Setup (Block Diagram of Configuration)	50
9.4 Measurement Result	51
10. Conducted Band Edge and Out-of-Band Emissions	67
10.1 Provisions Applicable	67
10.2 Measurement Procedure	67
10.3 Measurement Setup (Block Diagram of Configuration)	68
10.4 Measurement Results	69
11. Radiated Spurious Emission	95
11.1 Measurement Limit	95
11.2 Measurement Procedure	96
11.3 Measurement Setup (Block Diagram of Configuration)	98
11.4 Measurement Result	99
12. AC Power Line Conducted Emission Test	117
12.1 Measurement limit	117
12.2 Block Diagram of Line Conducted Emission Test	117
12.3 Preliminary Procedure of Line Conducted Emission Test	118
12.4 Final Procedure of Line Conducted Emission Test	118
12.5 Test Result of Line Conducted Emission Test	119
Appendix I: Photographs of Test Setup	121
Appendix II: Photographs of EUT	121





1. General Information

Applicant	Dongguan Aika Electronic Technology Co., Ltd.		
Address	Room 201, Building 2, No. 388, Bihu Road, Fenggang Town, Dongguan City, Guangdong Province, China		
Manufacturer	Dongguan Aika Electronic Technology Co., Ltd.		
Address	Room 201, Building 2, No. 388, Bihu Road, Fenggang Town, Dongguan City, Guangdong Province, China		
Factory	Dongguan Aika Electronic Technology Co., Ltd.		
Address	Room 201, Building 2, No. 388, Bihu Road, Fenggang Town, Dongguan City, Guangdong Province, China		
Product Designation	Smart Karaoke Machine		
Brand Name	Ikarao		
Test Model	Shell S3		
Series Model(s)	N/A		
Difference Description	N/A		
Date of receipt of test item	Dec. 31, 2024		
Date of Test	Dec. 31, 2024~Jan. 21, 2025		
Deviation from Standard	No any deviation from the test method		
Condition of Test Sample	Normal		
Test Result	Pass		
Test Report Form No	AGCER-FCC-5G WLAN-V1		

Note: The test results of this report relate only to the tested sample identified in this report.

Prepared By	Bibo zhang	
	Bibo Zhang (Project Engineer)	Feb. 05, 2025
Reviewed By	Calvin Lin	
	Calvin Liu (Reviewer)	Feb. 05, 2025
Approved By	Angole li	
	Angela Li (Authorized Officer)	Feb. 05, 2025



Page 6 of 121

2. Product Information

2.1 Product Technical Description

Equipment Type	☐ Outdoor access points☐ Fixed P2P access points☐ Client devices		
Operation Frequency	☑ U-NII 1:5150MHz~5250MHz ☐ U-NII 2A: 5250MHz~5350MHz ☐ U-NII 2C:5470MHz~5725MHz ☒ U-NII 3: 5725MHz~5850MHz		
DFS Design Type	☐ Master ☐ Slave with radar detection ☐ Slave without radar detection		
TPC Function	☐ Yes ☐ No		
Hardware Version	V1		
Software Version	V1.1.1		
Test Frequency Range	For 802.11a/n-HT20/ac-VHT20: 5180~5240MHz/5745~5825MHz; For 802.11n-HT40/ac-VHT40: 5190~5230MHz/5755~5795MHz; For 802.11ac-VHT80: 5210MHz/5775MHz		
RF Output Power	802.11a:14.69dBm,802.11n(HT20):13.35dBm; 802.11n(HT40):13.66dBm; 802.11ac (VHT20):13.32dBm;802.11ac (VHT40):13.60dBm; 802.11ac (VHT80):13.51dBm		
Modulation	802.11a/n:(64-QAM, 16-QAM, QPSK, BPSK) OFDM 802.11ac :(256-QAM, 64-QAM, 16-QAM, QPSK, BPSK) OFDM		
Data Rate	802.11a:6/9/12/18/24/36/48/54Mbps; 802.11n: up to 300Mbps; 802.11ac: up to 866.6Mbps;		
Number of channels	7 channels of U-NII-1 Band;8 channels of U- NII 3 Band		
Antenna Designation	FPC Antenna		
Antenna Gain	4.30dBi		
Power Supply	DC7.3V by battery or DC 5V by adapter		



Page 7 of 121

2.2 Table of Carrier Frequency

For 5180~5240MHz:

4 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

Channel	Frequency	Channel	Frequency
36	5180 MHz	44	5220 MHz
40	5200 MHz	48	5240 MHz

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz

1 channel is provided for 802.11ac (VHT80):

Channel	Frequency	Channel	Frequency
42	5210 MHz		

For 5745~5825MHz:

5 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

Channel	Frequency	Channel	Frequency
149	5745 MHz	161	5805 MHz
153	5765 MHz	165	5825 MHz
157	5785 MHz		

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

Channel	Frequency	Channel	Frequency
151	5755 MHz	159	5795 MHz

1 channel is provided for 802.11ac (VHT80):

Channel	Frequency	Channel	Frequency
155	5775 MHz		



Page 8 of 121

2.3 IEEE 802.11n Modulation Scheme

MCS Index	Nss	Modulation	R	N _{BPSC}	N _C	BPS	N _{DBPS}		Data rate (Mbps) 800nsGI	
					20MHz	40MHz 20MHz		40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0
6	1	64-QAM	3/4	6	312	648	234	489	58.5	121.5
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	Guard interval



Page 9 of 121

2.4 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: 2BCRN-SHELLS3 filing to comply with the FCC Part 15 requirements.

2.5 Test Methodology

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
4	KDB 789033	789033 D02 General U-NII Test Procedures New Rules v02r01

2.6 Special Accessories

Refer to section 4.4.

2.7 Equipment Modifications

Not available for this EUT intended for grant.

2.8 Antenna Requirement

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 4.30dBi.



2.9 Description of Test Software

For IEEE 802.11 mode:

The test utility software used during testing was "adb"

Software Setting Diagram

```
画 管理员: C:\Windows\System32\cmd.exe - adb shell
                                                                                                          П
                                                                                                                ×
       mp start:mp start ok
k3326_tgo:/ # rtwpriv wlan0 mp_bandwidth 40M=0,shortGI=0
fname = wlan0
input = mp_bandwidth 40M=0, shortGI=0
       mp_bandwidth:No change current BW 0
k3326_tgo:/ # rtwpriv wlan0 mp_channel 36
fname = w1an0
input = mp_channe1 36
w1an0 πp_channe1:No
fname = wlan0
inname wiano
input = mp_ant_tx a
wlan0 mp_ant_tx:switch Tx antenna to a
rk3326_tgo:/ # rtwpriv wlan0 mp_rate 12
ifname = wlan0
fname = wlan0
nput = mp_txpower patha=45, pathb=45
πp_ctx:
tart continuous DA=ffffffffffff 1en=1500 count=0
k3326_tgo:/ # 🕳
```

Test Mode	Channel	Power Index
802.11a	L/M/H	46
802.11n(HT20)	L/M/H	43
802.11n(HT40)	L/M/H	41
802.11ac(VHT20)	L/M/H	43
802.11ac(VHT40)	L/M/H	41
802.11ac(VHT80)	L/M/H	40



Page 11 of 121

3. Test Environment

3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories.)

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



Page 12 of 121


3.3 Environmental Conditions

	Normal Conditions
Temperature range (°C)	15 - 35
Relative humidity range	20% - 75%
Pressure range (kPa)	86 - 106
Power supply	DC7.3V by battery or DC 5V by adapter

3.4 Measurement Uncertainty

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Measurement Uncertainty
$U_c = \pm 2.9 \text{ dB}$
$U_c = \pm 3.9 \text{ dB}$
$U_c = \pm 4.9 \text{ dB}$
$U_c = \pm 0.8 \text{ dB}$
$U_c = \pm 2.6 \text{ dB}$
$U_c = \pm 2 \%$
$U_c = \pm 2.7 \%$






3.5 List of Equipment Used

• F	RF Conducted Test System							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
	AGC-ER-E036	Spectrum Analyzer	Agilent	N9020A	MY49100060	2024-05-24	2025-05-23	
\boxtimes	AGC-ER-E062	Power Sensor	Agilent	U2021XA	MY54110007	2024-02-01	2025-01-31	
\boxtimes	AGC-ER-E063	Power Sensor	Agilent	U2021XA	MY54110009	2024-02-01	2025-01-31	
\boxtimes	AGC-ER-A007	6dBFixed Attenuator	Mini circuits	Bw-S6-2W263A+	N/A	2024-02-01	2025-01-31	
\boxtimes	AGC-ER-A008	6dBFixed Attenuator	Mini circuits	BW-K6-2W44+	N/A	2024-02-01	2025-01-31	
\boxtimes	N/A	RF Connection Cable	N/A	1#	N/A	Each time	N/A	
\boxtimes	N/A	RF Connection Cable	N/A	2#	N/A	Each time	N/A	
\boxtimes	AGC-EM-E061	EXA Signal Analyzer	Aglient	N9010A	MY53470504	2024-05-28	2025-05-27	

• F	Radiated Spurious Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2024-02-01	2025-01-31	
\boxtimes	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23	
\boxtimes	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2024-05-28	2025-05-27	
\boxtimes	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04	
\boxtimes	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10	
	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2024-03-31	2025-03-30	
\boxtimes	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-09-24	2025-09-23	
\boxtimes	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2024-07-24	2026-07-23	
\boxtimes	AGC-EM-A118	5G Filter	SongYi	N/A	N/A	2024-05-23	2025-05-22	
\boxtimes	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08	
	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08	

• A	AC Power Line Conducted Emission								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)		
\boxtimes	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2024-05-28	2025-05-27		
\boxtimes	AGC-EM-A171	Attenuator	Mini-Circuits	UNAT-10A+	N/A	2024-02-01	2026-01-31		
	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2024-05-28	2025-05-27		





• Tes	Test Software								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information				
\boxtimes	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71				
	AGC-EM-S003	RE Test System	FARA	EZ-EMC	VRA-03A				
\boxtimes	AGC-EM-S004	RE Test System	Tonscend	TS+Ver2.1(JS32-RE)	4.0.0.0				
\boxtimes	AGC-ER-S012	BT/WIFI Test System	Tonscend	JS1120-2	2.6				
\boxtimes	AGC-EM-S011	RSE Test System	Tonscend	TS+-Ver2.1(JS36-RSE)	4.0.0.0				



Page 15 of 121

4. System Test Configuration

4.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System

Radiated Emission Configure:

EUT (Power by battery)

Conducted Emission Configure:

EUT

AC adapter

4.4 Equipment Used in Tested System

The following peripheral devices and interface cables were connected during the measurement:

☐ Test Accessories Come From The Laboratory

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1	Adapter	Xiaomi	MDY-11-EF	Input: 100-240V 50/60Hz 0.7A Output: 5V3A/9V3A/12V2.25A/20V1.35A/10V3A	
2	Redmi Notebook PC	Redmi	XMA2002-AB		
3	Control Box	RISYM	USB-TTL		

☐ Test Accessories Come From The Manufacturer

No	. Equipment	Manufacturer	Model No.	Specification Information	Cable
1					-



Page 16 of 121

4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	§15.203	Antenna Equipment	Pass
2	§15.407(a/1/3)	RF Output Power	Pass
3	§15.407(e)	6 dB Bandwidth	Pass
4	§15.403(i)	99% Occupied Bandwidth	Pass
5	§15.407(a/1/3)	Power Spectral Density	Pass
6	§15.407(g)	Frequency Stability	Pass (See Note 1)
7	§15.407(c)	Transmission Discontinuation Requirement	Pass (See Note 2)
8	§15.407(b)(1/4)	Conducted Band Edge and Out-of-Band Emissions	Pass
9	§15.209,§15.407(b)(1/4)	Radiated Spurious Emission	Pass
10	§15.207	AC Power Line Conducted Emission	Pass

Note:

- 1. Refer to the manufacturer's declaration in the user manual.
- 2. The device operates without the transmission of information.



Page 17 of 121

5. Description of Test Modes

EUT Configure Mode	Applicable To				Description
201 Configure Mode	RE > 1G	RE<1G	PLC	APCM	Description
А	\boxtimes	\boxtimes	\boxtimes	\boxtimes	Powered by Adapter with WIFI(5G) Link
В	\boxtimes	\boxtimes		\boxtimes	Powered by Battery with WIFI(5G) Link
С					Powered by USB with WIFI(5G) Link

Where. RE > 1G: Radiated Emission above 1GHz PLC: Power Line Conducted Emission

NOTE 1: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane.

NOTE 2: "--"means no effect.

• Radiated Emission Test (Above 1GHz):

\boxtimes	Pre-Scan has been conducted to determine the worst-case mode from all possible combinations be Meer
	available modulations, data rates and antenna ports (IF EUT with antenna diversity architecture).

☐ Support 802.11ax, device debugging is tested in Full RU state

☐ The device under test has multiple antennas. The mode that supports MIMO technology records the worst data, and the mode that does not support MIMO technology records antenna 1 as the worst data.

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Freq. Band (MHz)	Available Channel	Tested Channel	Modulation	Data Rate (Mbps)
В	802.11a	5180-5240	36 to 48	36, 40, 48	OFDM	6.0
В	802.11a	5745-5825	149 to 165	149, 157, 165	OFDM	6.0



Page 18 of 121

Radiated Emission Test (Below 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations be Meen available modulations, data rates and antenna ports (If EUT with antenna diversity architecture).

The device under test has multiple antennas. The mode that supports MIMO technology records the worst data, and the mode that does not support MIMO technology records antenna 1 as the worst data.

⊠ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Freq. Band (MHz)	Available Channel	Tested Channel	Modulation	Data Rate (Mbps)
В	802.11a	5745-5825	149 to 165	157	OFDM	MCS0

• Power Line Conducted Emission Test:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations be Meen available modulations, data rates and antenna ports (If EUT with antenna diversity architecture).

☐ The device under test has multiple antennas. The mode that supports MIMO technology records the worst data, and the mode that does not support MIMO technology records antenna 1 as the worst data.

☐ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Freq. Band (MHz)	Available Channel	Tested Channel	Modulation	Data Rate (Mbps)
Α	802.11a	5745-5825	149 to 165	157	OFDM	MCS0

Band edge Measurement:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations be Meen available modulations, data rates and antenna ports (If EUT with antenna diversity architecture).

Support 802.11ax, device debugging is tested in Full RU state

The device under test has multiple antennas. The mode that supports MIMO technology records the worst data, and the mode that does not support MIMO technology records antenna 1 as the worst data.

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Freq. Band (MHz)	Available Channel	Tested Channel	Modulation	Data Rate (Mbps)
Α	802.11a		36 to 48	36	OFDM	6.0
Α	802.11n (40MHz)	5180-5240	38 to 46	38	OFDM	MCS0
Α	802.11ac (80MHz)		42	42	OFDM	MCS0
A	802.11n (20MHz)	5745-5825	149 to 165	149, 165	OFDM	MCS0



Page 19 of 121

• Antenna Port Conducted Measurement:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations be Meen available modulations, data rates and antenna ports (If EUT with antenna diversity architecture).

☐ Support 802.11ax, device debugging is tested in Full RU state

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Freq. Band (MHz)	Available Channel	Tested Channel	Modulation	Data Rate (Mbps)
В	802.11a		36 to 48	36, 40, 48	OFDM	6.0
В	802.11n (20MHz)		36 to 48	36, 40, 48	OFDM	MCS0
В	802.11n (40MHz)	5180-5240	38 to 46	38, 46	OFDM	MCS0
В	802.11ac (20MHz)	5160-5240	36 to 48	36, 40, 48	OFDM	MCS0
В	802.11ac (40MHz)		38 to 46	38, 46	OFDM	MCS0
В	802.11ac (80MHz)		42	42	OFDM	MCS0
В	802.11a		149 to 165	149, 157, 165	OFDM	6.0
В	802.11n (20MHz)		149 to 165	149, 157, 165	OFDM	MCS0
В	802.11n (40MHz)	5745-5825	151 to 159	151, 159	OFDM	MCS0
В	802.11ac (20MHz)	0740-0620	149 to 165	149, 157, 165	OFDM	MCS0
В	802.11ac (40MHz)		151 to 159	151, 159	OFDM	MCS0
В	802.11ac (80MHz)		155	155	OFDM	MCS0



Page 20 of 121


6. Duty Cycle Measurement

5GHz WLAN (NII) operation is possible in 20MHz, 40MHz and 80MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = Average. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Operating mode	Data rates (Mbps)	Duty Cycle (%)	Duty Cycle Factor (dB)					
Band U-NII1:5150MHz-5250MHz								
802.11a	6	93.87	0.27					
802.11n_HT20	MCS0	93.75	0.28					
802.11n_HT40	MCS0	90.53	0.43					
802.11ac_VHT20	MCS0	92.67	0.33					
802.11ac_VHT40	MCS0	91.38	0.39					
802.11ac_VHT80	MCS0	87.80	0.57					
	Band U-NII 3:5725M	MHz-5850MHz						
802.11a	6	94.94	0.23					
802.11n_HT20	MCS0	91.87	0.37					
802.11n_HT40	MCS0	89.58	0.48					
802.11ac_VHT20	MCS0	92.68	0.33					
802.11ac_VHT40	MCS0	92.12	0.35					
802.11ac_VHT80	MCS0	89.41	0.49					

Remark:


- Duty Cycle factor = 10 * log (1/ Duty cycle)
- 2. The duty cycle of each frequency band mode reflects the determination requirements of the low channel measurement value.
- 3. Involving the test items of duty cycle compensation coefficient, the final results have been added and calculated by the software and presented.






The test plots as follows:











Page 23 of 121

7. RF Output Power Measurement

7.1 Provisions Applicable

Operation Band	EUT Category		LIMIT	
U-NII-1		Outdoor Access Point	1 Watt (30 dBm) (Max. e.i.r.p < 125mW(21 dBm) at any elevation angle above 30 degrees as measured from the horizon)	
0 14 1	Fixed point-to-point Access Point		1 Watt (30 dBm)	
	☐ Indoor Access Point		1 Watt (30 dBm)	
	\boxtimes	Client devices	250mW (23.98 dBm)	
U-NII-2A		/	250mW (23.98 dBm) or 11 dBm+10 log B*	
U-NII-2C		/ 250mW (23.98 dBm) or 11 dBm+10 le		
U-NII-3		/	1 Watt (30 dBm)	


Note: Where B is the 26dB emission bandwidth in MHz.

7.2 Measurement Procedure

☑Method PM is Measurement using an RF average power meter. The procedure for this method is as follows:

- 1. The testing follows the ANSI C63.10 Section 12.3.3.1
- Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the following conditions are satisfied:
- 3. The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
- 4. At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
- 5. The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- 6. Determine according to the duty cycle of the equipment: when it is less than 98%, follow the steps below.
- Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
- 8. Adjust the measurement in dBm by adding [10 log (1 / D)], where D is the duty cycle {e.g., [10 log (1 / 0.25)], if the duty cycle is 25%}.
- 9. The final test results have been increased by the duty cycle factor and recorded in the report.

7.3 Measurement Setup (Block Diagram of Configuration)






Page 24 of 121

7.4 Measurement Result

	Test Data of Conducted Output Power for band 5.15-5.25 GHz							
Test Mode	Test Channel (MHz)	Average Power (dBm)	Limits (dBm)	Pass or Fail				
	5180	14.06	23.98	Pass				
802.11a	5200	14.24	23.98	Pass				
	5240	14.46	23.98	Pass				
	5180	12.55	23.98	Pass				
802.11n20	5200	12.70	23.98	Pass				
	5240	13.16	23.98	Pass				
000 11 5 10	5190	12.08	23.98	Pass				
802.11n40	5230	12.46	23.98	Pass				
	5180	12.61	23.98	Pass				
802.11ac20	5200	12.83	23.98	Pass				
	5240	13.15	23.98	Pass				
802.11ac40	5190	12.05	23.98	Pass				
002.11ac40	5230	12.34	23.98	Pass				
802.11ac80	5210	11.93	23.98	Pass				





	Test Data of Conducted Output Power for band 5.725-5.850 GHz							
Test Mode	Test Channel (MHz)	Average Power (dBm)	Limits (dBm)	Pass or Fail				
	5745	14.49	30	Pass				
802.11a	5785	14.69	30	Pass				
	5825	14.47	30	Pass				
	5745	13.33	30	Pass				
802.11n20	5785	13.35	30	Pass				
	5825	13.07	30	Pass				
000 44 = 40	5755	13.63	30	Pass				
802.11n40	5795	13.66	30	Pass				
	5745	13.26	30	Pass				
802.11ac20	5785	13.32	30	Pass				
	5825	13.11	30	Pass				
902 44 5540	5755	13.54	30	Pass				
802.11ac40	5795	13.60	30	Pass				
802.11ac80	5775	13.51	30	Pass				



Page 26 of 121

8. 6dB&26dB Bandwidth Measurement

8.1 Provisions Applicable

The minimum 6dB bandwidth shall be at least 500 kHz.

8.2 Measurement Procedure

◆ -6dB bandwidth (DTS bandwidth) Test setting:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on operation frequency individually.
- 3. Set RBW = 100kHz.
- 4. Set the VBW $\geq 3*RBW$. Detector = Peak. Trace mode = max hold.
- 5. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.

♦ 99% occupied bandwidth test setting:


- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 1.5 to 5 times the OBW, centered on a nominal channel
 The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video
 bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.

-26dB Bandwidth test setting:

- 1. Set RBW = approximately 1% of the emission bandwidth.
- 2. Set the VBW > RBW.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

Note: The EUT was tested according to KDB 789033 for compliance to FCC 47CFR 15.407 requirements.

8.3 Measurement Setup (Block Diagram of Configuration)






Page 27 of 121


8.4 Measurement Results

Test Data of Occupied Bandwidth and -26dB Bandwidth for band 5.15-5.25 GHz						
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (MHz)	-26dB Bandwidth (MHz)	Limits (MHz)	Pass or Fail	
802.11a	5180	16.574	21.248	N/A	Pass	
	5200	16.583	22.845	N/A	Pass	
	5240	16.507	20.235	N/A	Pass	
802.11n20	5180	17.625	20.336	N/A	Pass	
	5200	17.618	21.348	N/A	Pass	
	5240	17.623	20.317	N/A	Pass	
802.11n40	5190	36.149	41.450	N/A	Pass	
	5230	36.124	41.206	N/A	Pass	
802.11ac20	5180	17.666	21.372	N/A	Pass	
	5200	17.647	20.962	N/A	Pass	
	5240	17.631	20.466	N/A	Pass	
802.11ac40	5190	36.061	40.552	N/A	Pass	
	5230	36.148	40.714	N/A	Pass	
802.11ac80	5210	75.217	80.039	N/A	Pass	







Test Data of Occupied Bandwidth and DTS Bandwidth for band 5.725-5.85 GHz							
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (MHz)	DTS Bandwidth (MHz)	Limits (MHz)	Pass or Fail		
802.11a	5745	16.558	16.324	0.5	Pass		
	5785	16.644	16.331	0.5	Pass		
	5825	16.531	16.328	0.5	Pass		
802.11n20	5745	17.626	17.551	0.5	Pass		
	5785	17.605	16.567	0.5	Pass		
	5825	17.624	16.317	0.5	Pass		
802.11n40	5755	36.103	34.873	0.5	Pass		
	5795	36.124	35.451	0.5	Pass		
802.11ac20	5745	17.619	17.072	0.5	Pass		
	5785	17.667	17.554	0.5	Pass		
	5825	17.607	16.691	0.5	Pass		
802.11ac40	5755	36.164	35.173	0.5	Pass		
	5795	36.065	34.511	0.5	Pass		
802.11ac80	5775	75.141	75.211	0.5	Pass		







Test Graphs of Occupied Bandwidth and -26dB Bandwidth for band 5.15-5.25 GHz

























































Test Graphs of Occupied Bandwidth and -26dB Bandwidth for band 5.745-5.825 GHz

























































Test Graphs of DTS Bandwidth for band 5.725-5.85 GHz


















































9. Power Spectral Density Measurement

9.1 Provisions Applicable


Operation Band	EUT Category		LIMIT	
U-NII-1		Outdoor Access Point	17dBm/ MHz	
		Fixed point-to-point Access Point	17dBm/ MHz	
		Indoor Access Point	17dBm/ MHz	
	\boxtimes	Client devices	11dBm/ MHz	
U-NII-2A	/		11dBm/ MHz	
U-NII-2C	/		11dBm/ MHz	
U-NII-3	/		30 dBm/500kHz	


9.2 Measurement Procedure

⊠For Average power spectral density test:

- Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator.
- 2. Span was set to encompass the entire 26dB EBW of the signal.
- 3. RBW = 1MHz.
- 4. If measurement bandwidth of Maximum PSD is specified in 500 kHz, RBW = 100KHz
- 5. Set VBW≥[3×RBW].
- 6. Sweep Time=Auto couple.
- 7. Detector function=RMS (i.e., power averaging).
- 8. Trace average at least 100 traces in power averaging (rms) mode.
- 9. When the measurement bandwidth of Maximum PSD is specified in 100 kHz, add a constant factor 10*log(500kHz/100kHz) = 6.99 dB to the measured result.
- 10. Determine according to the duty cycle of the equipment: when it is less than 98%, follow the steps below.
- 11. Add [10 log (1/D)], where D is the duty cycle, to the measured power to compute the average power during the actual transmission times (because the measurement represents an average over both the ON and OFF times of the transmission). For example, add [10 log (1/0.25)] = 6 dB if the duty cycle is 25%.
- 12. The final test results have been increased by the duty cycle factor and recorded in the report

9.3 Measurement Setup (Block Diagram of Configuration)







9.4 Measurement Result

Test Data of Conducted Output Power Density for band 5.15-5.25 GHz								
Test Mode	Test Channel (MHz)	Average Power Density (dBm/MHz)	Limits (dBm/MHz)	Pass or Fail				
802.11a	5180	3.163	11	Pass				
	5200	3.255	11	Pass				
	5240	3.701	11	Pass				
802.11n20	5180	1.499	11	Pass				
	5200	1.511	11	Pass				
	5240	2.140	11	Pass				
802.11n40	5190	-2.241	11	Pass				
	5230	-1.895	11	Pass				
802.11ac20	5180	1.323	11	Pass				
	5200	1.724	11	Pass				
	5240	1.806	11	Pass				
802.11ac40	5190	-2.063	11	Pass				
	5230	-1.888	11	Pass				
802.11ac80	5210	-4.106	11	Pass				




Report No.: AGC16840241201FR04

Page 52 of 121

Test Data of Conducted Output Power Density for band 5.725-5.85 GHz							
Test Mode	Test Channel (MHz)	Average Power Density (dBm/100kHz)	Average Power Density (dBm/500kHz)	Limits (dBm/500kHz)	Pass or Fail		
802.11a	5745	-4.958	2.032	30	Pass		
	5785	-5.312	1.678	30	Pass		
	5825	-5.393	1.597	30	Pass		
802.11n20	5745	-6.918	0.072	30	Pass		
	5785	-6.566	0.424	30	Pass		
	5825	-7.096	-0.106	30	Pass		
802.11n40	5755	-9.800	-2.810	30	Pass		
	5795	-9.695	-2.705	30	Pass		
802.11ac20	5745	-6.842	0.148	30	Pass		
	5785	-6.830	0.160	30	Pass		
	5825	-7.050	-0.060	30	Pass		
802.11ac40	5755	-9.456	-2.466	30	Pass		
	5795	-9.702	-2.712	30	Pass		
802.11ac80	5775	-11.650	-4.660	30	Pass		

Note:1.Power density(dBm/500kHz) = Power density(dBm/100kHz)+10*log(500/100).





Test Graphs of Conducted Output Power Spectral Density for band 5.15-5.25 GHz

