



■ Report No.: DDT-RE23082411-2E04

■ Issued Date: Sep. 28, 2023

RF EXPOSURE REPORT

FOR

Applicant	:	FIRST TECHNOLOGY GROUP, LLC
Address	:	401 Hawthorne Ln, Suite 110-185 c/o Tedesco JSN, Charlotte North Carolina, United State
Equipment under Test	:	Multimedia
Model No.	:	Kansas City 100
Trade Mark	:	Blaupunkt
FCC ID	:	2BCRZ-KANSAS100
Manufacturer	:	Huizhou Foryou General Electronics Co., Ltd.
Address	:	No.2 District A, Foryou Industry Park, No. 1 North Shangxia Road, Dongjiang Hi tech Industry Park, 516005 Huizhou city, Guangdong Province, China (PROC)

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,
Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

Test report declares.....	3
1. General Information	5
1.1. Description of equipment	5
1.2. Assess laboratory.....	6
2. RF Exposure Evaluation	7
2.1. Requirement.....	7
2.2. Calculation method	7
2.3. Estimation result.....	8

Test Report Declare

Applicant	:	FIRST TECHNOLOGY GROUP, LLC
Address	:	401 Hawthorne Ln, Suite 110-185 c/o Tedesco JSN, Charlotte North Carolina, United State
Equipment under Test	:	Multimedia
Model No.	:	Kansas City 100
Trade mark	:	Blaupunkt
Manufacturer	:	Huizhou Foryou General Electronics Co., Ltd.
Address	:	No.2 District A, Foryou Industry Park, No. 1 North Shangxia Road, Dongjiang Hi tech Industry Park, 516005 Huizhou city, Guangdong Province, China (PROC)

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No.:	DDT-RE23082411-2E04		
Date of Receipt:	Aug. 31, 2023	Date of Test:	Aug. 31, 2023~ Sep. 27, 2023

Prepared By:



Jacky Huang/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Sep. 28, 2023	

1. General Information

1.1. Description of equipment

EUT Name	: Multimedia
Model Number	: Kansas City 100
EUT function description	: Please reference user manual of this device
Power supply	: DC 12V
Radio Specification	: Bluetooth V5.0, IEEE802.11b/g/n/a/ac
Operation frequency	: Bluetooth: 2402MHz-2480MHz IEEE802.11b/g/n/a/ac: 2412MHz-2462MHz, 5180MHz-5320MHz, 5745MHz-5825MHz
Modulation	: Bluetooth: GFSK, $\pi/4$ -DQPSK, 8DPSK IEEE 802.11b: DSSS (CCK, QPSK, BPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20, HT40: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: VHT20, VHT40, VHT80: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)
Transmitter rate	: Bluetooth: 1Mbps, 2Mbps, 3Mbps IEEE 802.11b: up to 11 Mbps IEEE 802.11g/a: up to 54 Mbps IEEE 802.11n HT20: up to 72.2 Mbps IEEE 802.11n HT40: up to 150 Mbps IEEE 802.11ac VHT20: up to 86.7 Mbps IEEE 802.11ac VHT40: up to 200 Mbps IEEE 802.11ac VHT80: up to 433.3 Mbps
Antenna Gain	: 2.4G band maximum PK gain: 0.75 dBi, 5G band maximum PK gain: 3.47 dBi
Sample Number	: S23082411-03 for conducted, S23082411-02 for radiated.

1.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
USB Cable	/	/	EMIFIL
RCA Cable	/	/	EMIFIL
DC Cable	/	/	EMIFIL
Speaker out Cable	/	/	EMIFIL

1.3. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2. RF Exposure Evaluation

2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2. Calculation method

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(mW/cm^2) = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)=

d = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d= 0.2 m, as well as the gain of the used antenna, the RF power density can be obtained.

2.3. Estimation result

Mode	PK Output power (dBm)	Output power (mW)	tune up power (dBm)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm ²)	MPE Limit (mW/cm ²)
BT	9.06	8.05	10.50	0.75	1.19	0.00191	1
2.4G WIFI	10.46	11.11	12.00	0.75	1.19	0.00263	1
5G WIFI	9.30	8.51	11.00	3.47	2.22	0.00376	1

Simultaneous (worst case):

$$\text{Bluetooth+5G WIFI} = 0.00191/1 + 0.00376/1 = 0.00567 < 1$$

Note: The estimation distance is 20 cm, EUT does not support simultaneous transmission of 2.4G WIFI and 5G WIFI or 2.4G WIFI and Bluetooth.

Conclusion: The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

END OF REPORT