



FCC ID:2BCSS-OPENFREEI

RF Exposure Evaluation

According to KDB 447498 and part 2.1093, Unless specifically required by the *published RF exposure KDB procedures*, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding *SAR Test Exclusion Threshold* condition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances \leq 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

$f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Tune-up Power

| Modulation Type | Frequency (MHz) | Output Power to antenna (dBm) | Output Power to antenna (mW) | Tune-up Power(dBm) ± 1 | Maxmum Tune-up Power(dBm) |
|-----------------|-----------------|-------------------------------|------------------------------|-------------------------------|---------------------------|
| GFSK | 2402 | -0.46 | 0.90 | -1 | 0 |
| | 2441 | -1.17 | 0.76 | -2 | -1 |
| | 2480 | -1.76 | 0.67 | -2 | -1 |
| $\pi/4$ -DQPSK | 2402 | 0.20 | 1.05 | 0 | 1 |
| | 2441 | -0.53 | 0.86 | -1 | 0 |
| | 2480 | -1.07 | 0.77 | -2 | -1 |
| 8-DPSK | 2402 | 0.40 | 1.10 | 0 | 1 |
| | 2441 | -0.30 | 0.93 | -1 | 0 |
| | 2480 | -0.82 | 0.83 | -1 | 0 |

| Frequency (MHz) | Mode | Maximum Output power to antenna (dBm) | Output power to antenna (mW) | Calculation Value | limit |
|-----------------|----------------|---------------------------------------|------------------------------|-------------------|-------|
| 2402MHz | GFSK | 0 | 1.00 | 0.310 | 3.0 |
| 2402MHz | $\pi/4$ -DQPSK | 1 | 1.26 | 0.390 | 3.0 |
| 2402MHz | 8-DPSK | 1 | 1.26 | 0.390 | 3.0 |

Antenna Gain:1.95 dBi

Min. Distance 5mm

So a SAR test is not required

Shenzhen ZKT Technology Co., Ltd.

1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

+86-400-000-9970

+86-755-2233 6688

zkt@zkt-lab.com

www.zkt-lab.com