

SPECIFICATION

| | |
|---------------|--|
| Manufacturer | Dongguan Taishen Electronics Co., Ltd. |
| Address | 4th Floor, No. 1, Alley 5, Dihao Street, Baiguodong, Zhangmutou Town, Dongguan, Guangdong, China |
| Product name: | MPA2-10uH |
| Model name: | MPA2-10uH |
| DATE: | 2023/06/06 |
| Version: | A.0 |

Version Change History

SPECIFICATION

三、 Winding Specification:

| NO. | TERMINAL | WIRE | Turns | Winding Direction |
|-----|----------|------|---------------------------|-------------------|
| 1 | S | F | Hot air line 0.1*24PX2 | 10Ts |

四、 ELECTRICAL CHARACTERISTICS:

TEMPERATURE:25±10°C, RELATIVE HUMIDITY:65±20%

| NO. | ITEM | TERMINAL | SPECIFICATION | TEST FREQUENCY | TEST EQUIPMENTS |
|-----|------|----------|---------------------------------|----------------|-----------------|
| 1 | IND. | S-F | 3.8uH ±20%Individual coil | 100KHz/1.0V | LCZ METER 1062B |
| 2 | IND. | S-F | 6.5uH ±10%Adding magnetic disks | 100KHz/1.0V | LCZ METER 1062B |
| 3 | DCR | S-F | ≤90mΩ | 100KHz/1.0V | LCZ METER 502B |
| 4 | Q | S-F | ≥39 | 100KHz/1.0V | LCZ METER 502B |

PREPARED BY/DATE

2023/06/06

CHECKED BY/DATE

2023/06/06