

FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID: 2BCUR-V3

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: f is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

Test Result of RF Exposure Evaluation

	Modes& Channel Freq. (MHz)	Tune up Produce power	Maximu m peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm2)	Limit (mW / cm2)	Result
BLE	GFSK&HC H	4±1	5	3.1623	2.0749 (3.17dBi)	0.0013	1	Pass
EDR	8DPSK &LCH	4±1	5	3.1623	2.0749 (3.17dBi)	0.0013	1	Pass
2.4G WIFI ANT1	802.11b&2 412	14±1	15	31.6228	2.0749 (3.17dBi)	0.013	1	Pass
2.4G WIFI ANT2	802.11b&2 462	14±1	15	31.6228	2.0749 (3.17dBi)	0.013	1	Pass
5.2G WIFI ANT1	802.11a&5 240	13±1	14	25.1189	2.6792 (4.28dBi)	0.0134	1	Pass
5.2G WIFI ANT2	802.11a&5 200	12±1	13	19.9526	2.6792 (4.28dBi)	0.0106	1	Pass
5.3G WIFI ANT1	802.11n(H T40)& 5270	14±1	15	31.6228	2.6792 (4.28dBi)	0.0169	1	Pass
5.3G WIFI ANT2	802.11a&5 280	13±1	14	25.1189	2.6792 (4.28dBi)	0.0134	1	Pass
5.6G WIFI ANT1	802.11a&5 580	14±1	15	31.6228	2.5177 (4.01dBi)	0.0158	1	Pass
5.6G WIFI ANT2	802.11a&5 700	14±1	15	31.6228	2.5177 (4.01dBi)	0.0158	1	Pass
5.8G WIFI ANT1	802.11a&5 785	11±1	12	15.8489	2.4889 (3.96dBi)	0.0079	1	Pass
5.8G WIFI ANT2	802.11ac4 0&5755	12±1	13	19.9526	2.4889 (3.96dBi)	0.0099	1	Pass

Technology	Tune up Produce power(dBm)		Maximum Tune-up (dBm)		Antenna Gain(ANT 1/ANT 2) (numeric)	Power Density (S) (mW/ cm2)		MPE Limit (mW/ cm2)	Σ MPE Ratio	Σ MPE Ratio Limit	Result
	ANT 1	ANT 2	ANT 1	ANT 2		ANT 1	ANT 2				
2.4G WIFI MIMO	14 $\pm$ 1	14 $\pm$ 1	15	15	2.0749 (3.17dBi)	0.013	0.013	1	0.026	1	Pass

Technology	Tune up Produce power(dBm)		Maximum Tune-up (dBm)		Antenna Gain(ANT 1/ANT 2) (numeric)	Power Density (S) (mW/ cm2)		MPE Limit (mW/ cm2)	Σ MPE Ratio	Σ MPE Ratio Limit	Result
	ANT 1	ANT 2	ANT 1	ANT 2		ANT 1	ANT 2				
5G WIFI MIMO	14 $\pm$ 1	13 $\pm$ 1	15	14	2.6792 (4.28dBi)	0.0169	0.0134	1	0.0303	1	Pass

BT+WIFI supported simultaneous transmission:
BLE + 2.4GWIFI MIMO+5GWIFI MIMO: Σ MPE Ratio
=0.0013/1+0.026/1+0.0303/1=0.0576 $\leq$ 1, So passed.