

TEST REPORT

FCC ID. :	2BCUX-V0102	
Test Report No..... :	TCT230817E014	
Date of issue..... :	Aug. 25, 2023	
Testing laboratory	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name..... :	Shen Zhen Shi Ai Mei Ke Ke Ji You Xian Gong Si	
Address..... :	Room 1615, Building C, Huangdu Plaza, No.3008 Yitian Road, Huanggang Community, Futian Street, Futian District, Shenzhen 518000 China	
Manufacturer's name ... :	Dong guan Utopia-Originality Technology co., Ltd	
Address..... :	NO.2, moushan Road, Chan'an Town, Dongguan City, Guangdong Province, China	
Standard(s)	FCC CFR Title 47 Part 15 Subpart C	
Product Name..... :	Portable Charger	
Trade Mark	VEGER	
Model/Type reference..... :	V0102	
Rating(s)..... :	Type-C Input: DC 5V, 1.0A Rechargeable Li-ion Battery DC 3.7V	
Date of receipt of test item	Aug. 17, 2023	
Date (s) of performance of test..... :	Aug. 17, 2023 - Aug. 25, 2023	
Tested by (+signature) ... :	Ronaldo LUO	
Check by (+signature).... :	Beryl ZHAO	
Approved by (+signature):	Tomsin	

General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Table of Contents

1. General Product Information	3
1.1. EUT description	3
1.2. Model(s) list.....	3
2. Test Result Summary	4
3. General Information.....	5
3.1. Test environment and mode.....	5
3.2. Description of Support Units.....	5
4. Facilities and Accreditations	6
4.1. Facilities	6
4.2. Location	6
4.3. Measurement Uncertainty.....	6
5. Test Results and Measurement Data	7
5.1. Antenna requirement	7
5.2. Conducted Emission.....	8
5.3. Radiated Spurious Emission Measurement.....	12
Appendix A: Photographs of Test Setup	
Appendix B: Photographs of EUT	

1. General Product Information

1.1. EUT description

Product Name.....:	Portable Charger
Model/Type reference.....:	V0102
Sample Number.....:	TCT230817E014-0101
Operation Frequency	325.72kHz
Modulation Technology	Load modulation
Max. Wireless Output Power:	2.5 W
Antenna Type.....:	Inductive loop coil Antenna
Rating(s).....:	Type-C Input: DC 5V, 1.0A Rechargeable Li-ion Battery DC 3.7V

1.2. Model(s) list

None.

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203	PASS
AC Power Line Conducted Emission	§15.207	PASS
Spurious Emission	§15.209(a)(f)	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

3. General Information

3.1. Test environment and mode

Operating Environment:		
Condition	Conducted Emission	Radiated Emission
Temperature:	24.6 °C	25.3 °C
Humidity:	51 % RH	56 % RH
Atmospheric Pressure:	1010 mbar	1010 mbar
Test Mode:		
AC mode	Keep the EUT in three different wireless output modes (99% load, 50% load,1% load).	
Internal Battery Mode	Keep the EUT in three different wireless output modes (99% load, 50% load,1% load).	
The sample was placed 0.8m for the measurement below above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case(Z axis) are shown in Test Results of the following pages.		

3.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
Adapter	WC065A11JH	J121083BA1003016	/	OnePlus
Apple Watch	A1757	GGFX909MHDX9	/	Apple

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4. Facilities and Accreditations

4.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

4.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

4.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	± 3.10 dB
2	RF power, conducted	± 0.12 dB
3	Spurious emissions, conducted	± 0.11 dB
4	All emissions, radiated(<1 GHz)	± 4.56 dB
5	All emissions, radiated(1 GHz - 18 GHz)	± 4.22 dB
6	All emissions, radiated(18 GHz- 40 GHz)	± 4.36 dB

5. Test Results and Measurement Data

5.1. Antenna requirement

Standard requirement:


FCC Part15 C Section 15.203

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

E.U.T Antenna:

The antennas are inductive loop coil antenna which permanently attached.



5.2. Conducted Emission

5.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	Reference Plane 40cm 80cm E.U.T AC power LISN Filter AC power EMI Receiver Test table/Insulation plane Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m														
Test Mode:	AC mode(The battery of the Apple watch is less than 1%)														
Test Procedure:	1. The E.U.T is connected to an adapter through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.														
Test Result:	PASS														


5.2.2. Test Instruments

Conducted Emission Shielding Room Test Site (843)				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCI3	100898	Jun. 29, 2024
Line Impedance Stabilisation Newtork(LISN)	Schwarzbeck	NSLK 8126	8126453	Feb. 20, 2024
Line-5	TCT	CE-05	/	Jul. 03, 2024
EMI Test Software	Shurple Technology	EZ-EMC	/	/

5.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room

Phase: **L1**

Temperature: 24.6 (°C)

Humidity: 51 %

Limit: FCC Part 15C Conduction(QP)

Power: DC 5 V(Adapter Input AC 120 V/60 Hz)

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1900	31.71	10.14	41.85	64.04	-22.19	QP	
2		0.1900	21.70	10.14	31.84	54.04	-22.20	AVG	
3		0.3019	26.30	9.64	35.94	60.19	-24.25	QP	
4		0.3019	17.35	9.64	26.99	50.19	-23.20	AVG	
5		0.9779	13.83	9.01	22.84	56.00	-33.16	QP	
6		0.9779	13.06	9.01	22.07	46.00	-23.93	AVG	
7		2.2780	21.18	10.04	31.22	56.00	-24.78	QP	
8		2.2780	20.75	10.04	30.79	46.00	-15.21	AVG	
9		4.8819	25.56	10.12	35.68	56.00	-20.32	QP	
10	*	4.8819	25.30	10.12	35.42	46.00	-10.58	AVG	
11		20.5019	22.73	10.39	33.12	60.00	-26.88	QP	
12		20.5019	21.74	10.39	32.13	50.00	-17.87	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard


Margin (dB) = Measurement (dBμV) – Limits (dBμV)

Q.P. =Quasi-Peak

AVG =average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room

Phase: **N**

Temperature: 24.6 (°C)

Humidity: 51 %

Limit: FCC Part 15C Conduction(QP)

Power: DC 5 V(Adapter Input AC 120 V/60 Hz)

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1539	31.77	10.09	41.86	65.79	-23.93	QP	
2		0.1539	19.03	10.09	29.12	55.79	-26.67	AVG	
3		0.3260	31.64	9.61	41.25	59.55	-18.30	QP	
4	*	0.3260	31.13	9.61	40.74	49.55	-8.81	AVG	
5		1.3020	16.77	10.01	26.78	56.00	-29.22	QP	
6		1.3020	15.91	10.01	25.92	46.00	-20.08	AVG	
7		3.5819	23.60	10.08	33.68	56.00	-22.32	QP	
8		3.5819	23.39	10.08	33.47	46.00	-12.53	AVG	
9		6.1859	25.99	10.13	36.12	60.00	-23.88	QP	
10		6.1859	25.73	10.13	35.86	50.00	-14.14	AVG	
11		20.5138	23.42	10.39	33.81	60.00	-26.19	QP	
12		20.5138	22.32	10.39	32.71	50.00	-17.29	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard


Margin (dB) = Measurement (dBμV) – Limits (dBμV)

Q.P. =Quasi-Peak AVG =average


* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz

5.3. Radiated Spurious Emission Measurement

5.3.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10: 2013				
Frequency Range:	9 kHz to 25 GHz				
Measurement Distance:	3 m				
Antenna Polarization:	Horizontal & Vertical				
Operation mode:	Refer to item 3.1				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
Limit:	Frequency		Field Strength (microvolts/meter)		Measurement Distance (meters)
	0.009-0.490		2400/F(KHz)		300
	0.490-1.705		24000/F(KHz)		30
	1.705-30		30		30
	30-88		100		3
	88-216		150		3
	216-960		200		3
	Above 960		500		3
Test setup:	For radiated emissions below 30MHz				
					
	30MHz to 1GHz				

30MHz to 1GHz



Test Procedure:

1. For the radiated emission test below 1GHz:
The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
For the radiated emission test above 1GHz:
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
2. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
3. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

	4. Use the following spectrum analyzer settings: (1) Span shall wide enough to fully capture the emission being measured; (2) Set RBW=120 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold; (3) Set RBW = 1 MHz, VBW= 3MHz for $f \square 1$ GHz for peak measurement. For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Test mode:	Refer to section 3.1 for details
Test results:	PASS

5.3.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESIB7	100197	Jun. 29, 2024
Spectrum Analyzer	R&S	FSQ40	200061	Jun. 29, 2024
Pre-amplifier	SKET	LNPA_0118G-45	SK2021012102	Feb. 20, 2024
Pre-amplifier	SKET	LNPA_1840G-50	SK202109203500	Feb. 20, 2024
Pre-amplifier	HP	8447D	2727A05017	Jun. 27, 2024
Loop antenna	Schwarzbeck	FMZB1519B	00191	Jul. 02, 2024
Broadband Antenna	Schwarzbeck	VULB9163	340	Jul. 01, 2024
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Jul. 01, 2024
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Feb. 24, 2024
Antenna Mast	Keleto	RE-AM	/	/
Coaxial cable	SKET	RC-18G-N-M	/	Feb. 24, 2024
Coaxial cable	SKET	RC_40G-K-M	/	Feb. 24, 2024
EMI Test Software	Shurple Technology	EZ-EMC	/	/


5.3.3. Test Data

Please refer to following diagram for individual

9KHz-30MHz

9KHz-150KHz:

coaxial



Site: #3 3m Anechoic Chamber

Polarization: **Coaxial**

Temperature: 25.3(°C)


Humidity: 50 %

Limit: FCC Part15.209(9K-30M)

Power:DC 3.7 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	0.0102	42.22	20.73	62.95	127.43	-64.48	peak	P	
2 *	0.0154	42.18	20.67	62.85	123.85	-61.00	peak	P	
3	0.0239	34.45	20.54	54.99	120.04	-65.05	peak	P	
4	0.0399	31.08	20.54	51.62	115.59	-63.97	peak	P	
5	0.0561	29.35	20.76	50.11	112.63	-62.52	peak	P	
6	0.0722	28.19	21.05	49.24	110.43	-61.19	peak	P	

Coplanar



Site: #3 3m Anechoic Chamber

Polarization: **Coplanar**

Temperature: 25.3(°C)

Humidity: 50 %


Limit: FCC Part 15.209(9K-30M)

Power: DC 3.7 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	0.0094	40.89	20.87	61.76	128.14	-66.38	peak	P	
2	0.0116	38.67	20.71	59.38	126.32	-66.94	peak	P	
3	0.0153	39.82	20.67	60.49	123.91	-63.42	peak	P	
4	0.0197	32.46	20.60	53.06	121.72	-68.66	peak	P	
5	0.0399	30.55	20.54	51.09	115.59	-64.50	peak	P	
6 *	0.0559	28.50	20.76	49.26	112.66	-63.40	peak	P	

150KHz-30MHz:

coaxial



Site: #3 3m Anechoic Chamber

Polarization: **Coaxial**

Temperature: 25.3(°C)


Humidity: 50 %

Limit: FCC Part15.209(9K-30M)

Power:DC 3.7 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	0.1529	34.92	20.72	55.64	103.92	-48.28	peak	P	
2	0.1707	35.35	20.77	56.12	102.96	-46.84	peak	P	
3	0.3266	47.28	21.14	68.42	97.32	-28.90	peak	P	
4	0.4731	23.27	21.47	44.74	94.10	-49.36	peak	P	
5 *	1.0809	18.39	22.82	41.21	66.95	-25.74	peak	P	
6	2.4102	14.41	25.57	39.98	69.50	-29.52	peak	P	

coplanar



Site: #3 3m Anechoic Chamber

Polarization: **Conplanar**

Temperature: 25.3(°C)

Humidity: 50 %


Limit: FCC Part15.209(9K-30M)

Power:DC 3.7 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	0.2323	30.19	20.91	51.10	100.28	-49.18	peak	P	
2	0.3251	44.34	21.14	65.48	97.36	-31.88	peak	P	
3	0.9044	21.51	22.44	43.95	68.49	-24.54	peak	P	
4 *	0.9857	21.17	22.64	43.81	67.75	-23.94	peak	P	
5	3.3644	11.96	27.48	39.44	69.50	-30.06	peak	P	
6	5.6878	7.18	31.95	39.13	69.50	-30.37	peak	P	

30MHz-1GHz

Horizontal:



Site #2 3m Anechoic Chamber

Polarization: **Horizontal**

Temperature: 25.3(C)


Humidity: 56 %

Limit: FCC Part 15C RE_3m

Power: DC 3.7 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	43.3534	5.79	13.84	19.63	40.00	-20.37	QP	P	
2	61.1315	6.65	13.02	19.67	40.00	-20.33	QP	P	
3	149.4857	5.60	14.88	20.48	43.50	-23.02	QP	P	
4	218.3085	9.35	11.83	21.18	46.00	-24.82	QP	P	
5	326.7395	6.78	15.46	22.24	46.00	-23.76	QP	P	
6 *	539.4775	9.95	20.06	30.01	46.00	-15.99	QP	P	

Vertical:



Site #2 3m Anechoic Chamber

Polarization: **Vertical**

Temperature: 25.3(C) Humidity: 56 %

Limit: FCC Part 15C RE_3m

Power: DC 3.7 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	40.8446	5.40	14.35	19.75	40.00	-20.25	QP	P	
2	56.7916	4.68	13.43	18.11	40.00	-21.89	QP	P	
3	119.4360	6.67	12.92	19.59	43.50	-23.91	QP	P	
4	158.6677	5.87	14.91	20.78	43.50	-22.72	QP	P	
5	256.5210	5.02	13.22	18.24	46.00	-27.76	QP	P	
6 *	485.6091	7.06	19.15	26.21	46.00	-19.79	QP	P	

Note:

1: Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
Both AC mode and Internal Battery Mode have been tested, only the worse mode(Internal Battery Mode) reported.

2: The battery of the Apple watch is less than 1%

Appendix A: Photographs of Test Setup


Product: Portable Charger

Model: V0102

Radiated Emission



Conducted Emission



Appendix B: Photographs of EUT

Product: Portable Charger

Model: V0102

External Photos















Product: Portable Charger



Model: V0102



Internal Photos











*******END OF REPORT*******