



**RF Exposure Evaluation  
For  
Guangdong Pisen Electronics Co., Ltd.  
PISEN StandBy 120W Desktop Charger  
Test Model: TP-C119**

Prepared for : Guangdong Pisen Electronics Co., Ltd.  
Address : Building 5, 1st Floor, No. 9, Qinfu 1st Street, Liuyue Nan  
Community, Henggang Town, Longgang District, Shenzhen City, Guangdong Province, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.  
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street, Baoan District, Shenzhen, China  
Tel : (+86)755-82591330  
Fax : (+86)755-82591332  
Web : [www.LCS-cert.com](http://www.LCS-cert.com)  
Mail : [webmaster@LCS-cert.com](mailto:webmaster@LCS-cert.com)

Date of receipt of test sample : March 04, 2025  
Number of tested samples : 2  
Sample No. : A250303092-1, A250303092-2  
Serial number : Prototype  
Date of Test : March 04, 2025 ~ May 14, 2025  
Date of Report : May 14, 2025



Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel: +(86) 0755-82591330 | E-mail: [webmaster@lcs-cert.com](mailto:webmaster@lcs-cert.com) | Web: [www.lcs-cert.com](http://www.lcs-cert.com)  
Scan code to check authenticity



RF Exposure Evaluation		
Report Reference No.	: LCSA03035176EB	
Date Of Issue	: May 14, 2025	
Testing Laboratory Name	: Shenzhen LCS Compliance Testing Laboratory Ltd.	
Address	: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street, Baoan District, Shenzhen, China	
Testing Location/ Procedure	: <input checked="" type="checkbox"/> Full application of Harmonised standards <input type="checkbox"/> Partial application of Harmonised standards <input type="checkbox"/> Other standard testing method	
Applicant's Name	: Guangdong Pisen Electronics Co., Ltd.	
Address	: Building 5, 1st Floor, No. 9, Qinfu 1st Street, Liuyue Nan Community, Henggang Town, Longgang District, Shenzhen City, Guangdong Province, China	
<b>Test Specification</b>		
Standard	: FCC KDB publication 680106 D01 Wireless Power Transfer v04 FCC CFR 47 part1 1.1310 FCC CFR 47 part2 2.1091 FCC CFR 47 part 18.107	
Test Report Form No.	: TRF-4-E-214 A/0	
TRF Originator	: Shenzhen LCS Compliance Testing Laboratory Ltd.	
Master TRF	: Dated 2011-03	
<b>Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.</b>		
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.		
Test Item Description	: PISEN StandBy 120W Desktop Charger	
Trade Mark	: PISEN	
Test Model	: TP-C119	
Power Supply	: Please Refer to Page 6	
Result	: Positive	

Compiled by:

Nadia Zhou/ Administrator

Supervised by:

Jack Liu/ Technique principal

Approved by:

Gavin Liang/ Manager



Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
Scan code to check authenticity



## FCC TEST REPORT

<b>Test Report No. :</b>	<b>LCSA03035176EB</b>	<u>May 14, 2025</u>
		Date of issue

Test Model.....	: TP-C119
EUT.....	: PISEN StandBy 120W Desktop Charger
<b>Applicant.....</b>	<b>: Guangdong Pisen Electronics Co., Ltd.</b>
Address.....	: Building 5, 1st Floor, No. 9, Qinfu 1st Street, Liuyue Nan Community, Henggang Town, Longgang District, Shenzhen City, Guangdong Province, China
Telephone.....	: /
Fax.....	: /
<b>Manufacturer.....</b>	<b>: Guangdong Pisen Electronics Co., Ltd.</b>
Address.....	: Building 5, 1st Floor, No. 9, Qinfu 1st Street, Liuyue Nan Community, Henggang Town, Longgang District, Shenzhen City, Guangdong Province, China
Telephone.....	: /
Fax.....	: /
<b>Factory.....</b>	<b>: HUNAN C-SMARTLINK TECHNOLOGY CO.,LTD</b>
Address.....	: Building 5-6-7-8, Chengnan Electronic Information Industrial Park, Chenxi Industrial Development Zone, Chenxi County, Huaihua, Hunan Province
Telephone.....	: /
Fax.....	: /

<b>Test Result</b>	<b>Positive</b>
--------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
Scan code to check authenticity



## Revision History

Report Version	Issue Date	Revision Content	Revised By
000	May 14, 2025	Initial Issue	--



Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
Scan code to check authenticity



## TABLE OF CONTENTS

Description	Page
1. PRODUCT INFORMATION.....	6
2. EVALUATION METHOD .....	7
3. EVALUATION LIMIT .....	10
4. TEST SETUP DIAGRAM.....	12
5. TEST EQUIPMENT.....	12
6. MEASUREMENT PROCEDURE.....	12
7. EQUIPMENT APPROVAL CONSIDERATIONS.....	13
8. E AND H FIELD STRENGTH.....	14
9. TEST SETUP PHOTOS .....	17
10. CONCLUSION.....	20
11. DESCRIPTION OF TEST FACILITY .....	20
12. MEASUREMENT UNCERTAINTY.....	20



Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
Scan code to check authenticity



## 1. Product Information

Product Name	PISEN StandBy 120W Desktop Charger
Model Number	TP-C119
Ratings	<p>Input:100-240V~ 50/60Hz 2.5A MAX</p> <p>Output:USB-C1/C2:5V---3A 9V---3A 12V---3A 15V---3A 20V---5A(100W Max)</p> <p>USB-C3:5V---3A 9V---3A 12V---2.5A 15V---2A 20V---1.5A(30W Max)</p> <p>USB-A:5V---2A(10W Max)</p> <p>Phone Wireless Charging:5W/7.5W/10W/15W</p> <p>Watch/Earphone Wireless Charging:5W Max</p> <p>USB-C1+USB-C2:65W+45W(110W Max)</p> <p>USB-C1/C2+USB-C3:65W+30W(95W Max)</p> <p>USB-C1/C2+Phone Wireless Charging:100W+15W(115W Max)</p> <p>USB-C1/C2+Watch/Earphone Wireless Charging:100W+ 5W(105W Max)</p> <p>USB-C3+Phone Wireless Charging:30W+15W(45W Max)</p> <p>USB-C1+USB-C2+USB-C3:45W+45W+20W(110W Max)</p> <p>USB-C2+USB-C3+USB-A:65W+30W+10W(105W Max)</p> <p>USB-C3+USB-A+Phone Wireless Charging:30W+10W+15W(55W Max)</p> <p>USB-A+Phone Wireless Charging+Watch/Earphone Wireless Charging:10W+15W+5W(30W Max)</p> <p>USB-C1+USB-C2+USB-A:65W+30W+10W(105W Max)</p> <p>USB-C1+USB-C2+Phone Wireless Charging:65W+30W+15W(110W Max)</p> <p>USB-C1+USB-C2+Watch/Earphone Wireless Charging:65W+45W+5W(115W Max)</p> <p>USB-C2+USB-C3+Phone Wireless Charging:65W+30W+15W(110W Max)</p> <p>USB-C2+USB-C3+Watch/Earphone Wireless Charging:65W+30W+5W(100W Max)</p> <p>USB-C1+USB-C2+USB-C3+USB-A:45W+30W+30W+10W(115W Max)</p> <p>USB-C1+USB-C2+USB-A+Phone Wireless Charging:65W+30W+10W+15W(120W Max)</p> <p>USB-C1+USB-C2/C3+Phone Wireless Charging+Watch/Earphone Wireless Charging: 65W+30W+15W+5W(115W Max)</p> <p>USB-C1+USB-C2+USB-A+Watch/Earphone Wireless Charging:65W+30W+10W+5W(110W Max)</p> <p>USB-C2+USB-C3+USB-A+Phone Wireless Charging:65W+30W+10W+15W(120W Max)</p> <p>USB-C3+USB-A+Phone Wireless Charging+Watch/Earphone Wireless Charging: 30W+10W+15W+5W(60W Max)</p> <p>USB-C1+USB-C3+USB-A+Phone Wireless</p>



	Charging:45W+30W+10W+15W(100W Max) USB-C1+USB-C2+USB-C3+USB-A+Phone Wireless Charging:45W+30W+20W+10W+15W(120W Max) USB-C2+USB-C3+USB-A+Phone Wireless Charging+Watch/Earphone Wireless Charging: 30W+30W+10W+15W+5W(90W Max) USB-C1+USB-C2+USB-A+Phone Wireless Charging+Watch/Earphone Wireless Charging: 45W+30W+10W+15W+5W(105W Max) USB-C1+USB-C2+USB-C3+Phone Wireless Charging+ Watch/Earphone Wireless Charging: 45W+30W+20W+15W+5W (115W Max) USB-C1+USB-C2+USB-C3+USB-A+ Phone Wireless Charging+Watch/Earphone Wireless Charging:45W+20W+7.5W+5W+15W+5W (97.5W Max)
Wireless Charging	
Operating Frequency	110.0~205.0KHz
Modulation Type	ASK
Antenna Type	Coil Antenna
SRD	
Operating Frequency	275-285KHz
Modulation Type	ASK
Antenna Type	Coil Antenna
Hardware version	/
Software version	/
Accessories	Phone*1+Watch*1
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Mobile Device

## 2. Evaluation Method

Per KDB 680106 D01 Section 3. RF Exposure Requirements;

- 1) Wireless power transfer devices must comply with RF exposure requirements for all design configurations in which they can operate. At a minimum, RF exposure must be evaluated for the worst-case scenario, typically when the transmitter, while delivering energy to a client device, is operating at maximum output power. RF exposure compliance for equipment authorization must be determined following the guidance of KDB447498, which includes consideration of the different test requirements for *Mobile Device* and *Portable Device* exposure categories, as defined in §§ 2.1091 and 2.1093 of the Rules.
- 2) The RF exposure limits, as set forth in § 1.1310, do not cover the frequency range below 100 kHz for Specific Absorption Rate (SAR) and below 300 kHz for Maximum Permitted Exposure (MPE). In addition, present limitations of RF exposure evaluation systems prevent an accurate evaluation of SAR below 4 MHz. For these reasons, a specific MPE-based RF Exposure compliance procedure for devices operating in the aforementioned low-frequency ranges has been set in place. This procedure is applicable to Equipment Authorization of all RF devices, thus including, but not limited to, Part 18 and WPT devices. Accordingly, for § 2.1091-*Mobile* devices, the MPE limits between 100 kHz to 300 kHz are to be considered the same as those at



Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
Scan code to check authenticity

300 kHz in Table 1 of § 1.1310, that is, 614 V/m and 1.63 A/m, for the electric field and magnetic field, respectively. For § 2.1093-Portable devices below 4 MHz and down to 100 kHz, the MPE limits in § 1.1310 (with the 300 kHz limit applicable all the way down to 100 kHz) can be used for the purpose of equipment authorization in lieu of SAR evaluations.

Furthermore, consistent with FCC's equipment authorization RF exposure guidance, any device (both portable and mobile) operating at frequencies below 100 kHz is considered compliant for the purpose of equipment authorization when the external (unperturbed) temporal peak field strengths do not exceed the following reference levels:

83 V/m for the electric field strength ( $E$ )


and 90 A/m for the magnetic field strength ( $H$ )

These data may be provided through measurements and/or numerical simulations, and for all the positions in space relevant for any possible body exposure.

3) "Large size" probes may prevent the measurement of E- and/or H-fields near the surface of the radiating structure (e.g., a WPT source coil), as in the example shown in Figure 1.

If the center of the probe sensing element is located more than 5 mm from the probe outer surface, the field strengths need to be estimated through modeling for those positions that are not reachable. The estimates may be done either via numerical calculation, or via analytic model: e.g., approximated formulas for circular coils, dipoles, etc., may be acceptable if it is shown that the model is applicable for the design parameters considered. A typical example is the use of a quasi-static approximation formula for a low-frequency magnetic field source. These estimates shall include points spaced no more than 2 cm from each other. Thus, in the example of

Figure 1, at least the estimates at 0 cm<sup>2</sup> and 2 cm are required, while only one point would not be sufficient. In addition, the model needs to be validated through the probe measurements for the two closest points to the device surface, and with 2-cm increments, as indicated in Figure 1. In that example, the same model must also be applied to the 4 cm and 6 cm positions, and then compared with the measured data, for validation purposes. The validation is considered sufficient if a 30% agreement between the model and the (E- and/or H-field) probe measurements is demonstrated. If such a level of agreement cannot be shown, a more accurate model (and/or a smaller probe) shall be used.




**Figure 1. Example of probe (in yellow) measurements in points close to the WPT device (in red/brown). The probe radius is 4 cm, thus the closest point to the device where the field can be measured is at 4 cm from the surface (this example assumes that the probe calibration refers to the center of the sensing element structure, in this case a sphere of 4 cm radius). Data at 0 cm and 2 cm must be estimated through a model, and then the same model must be validated via comparison with the actual measurements at 4 cm and 6 cm, where the probe center can be positioned and collect valid data.**

#### 4) Part 18 Wireless Power Transfer up to One-Meter Distance. This section applies only to WPT




transmitters that, by design, can provide power to a load located at a distance no greater than one meter. This distance shall be measured between the closest points between the transmitter and the receiver enclosure surfaces. For instance, two coils positioned as in Figure 2-a may be operated and considered under the provisions of this section, because both receivers are within one-meter distance from the transmitter. However, the case in Figure 2-b cannot be considered in the same way, and it is treated according to the prescription of Section 5.3.

For WPT designs with more than one radiating structure the distance to the load shall be considered as in Figure 3, thus measured between the receiver and the closest transmitting structure.




*a) Not considered as WPT  
“at-a-distance”*



*b) WPT “at-a-distance”  
because RX2 position*

*Figure 2-a) For multiple-receiver systems (here shown with two receivers, indicated with RX1 and RX2) the one-meter distance limit must apply for all the receivers that are engaged in the charging process. b) The WPT system is considered “at-a-distance” because it can function when the RX2 is further away than one meter from the transmitter.*





**Figure 3. For multiple-coil transmitter systems, the one-meter distance limit is measured from the closest coil edge. A WPT within one meter operates with loads configured as those labeled in green font, if a load can be powered beyond one meter (in red), then it shall be considered “at-a-distance”**

There might be situations where the WPT RF emissions are limited enough that even operations in a “crowded” environment, where many similar WPT devices are present, do not pose significant EMC and RF exposure concerns. In this scenario, and for devices operating within a one-meter distance from the receiver, as defined above, a manufacturer will not have to submit an “Equipment Compliance Review” KDB, and receive FCC concurrence before proceeding with equipment authorization. This exception to the requirement of submitting the ECR to obtain FCC concurrence only applies when all the following criteria (1) through (6) are met:

- (1) The power transfer frequency is below 1 MHz.
- (2) The output power from each transmitting element (e.g., coil) is less than or equal to 15 watts.
- (3) A client device providing the maximum permitted load is placed in physical contact with the transmitter (i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact)
- (4) Only § 2.1091- Mobile exposure conditions apply (i.e., this provision does not cover § 2.1093 – Portable exposure conditions).
- (5) The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1. These measurements shall be taken along the principal axes of the device, with one axis oriented along the direction of the estimated maximum field strength, and for three points per axis or until a 1/d (inverse distance from the emitter structure) field strength decay is observed. Symmetry considerations may be used for test reduction purposes. The device shall be operated in documented worst-case compliance scenarios (i.e., the ones that lead to the maximum field components), and while all the radiating structures (e.g., coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power.
- 5) For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the design allows one or more radiating structures to be powered at a higher level while other radiating structures are not powered, then those cases must be tested as well. For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested

### 3. Evaluation Limit

#### 3.1 Refer evaluation method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 680106 D01 RF Exposure Wireless Charging Apps v04](#): RF Exposure Considerations for Low Power Consumer Wireless Power Transfer Applications

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

[FCC CFR 47 part 18.107](#): Industrial, Scientific, and Medical Equipment





### 3.2 Limit

#### Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500	/	/	f/300	6
1,500-100,000	/	/	5	6

#### Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500	/	/	f/1500	30
1,500-100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

According to FCC KDB 680106 D01 Section 3. RF Exposure Requirements clause 3 the Emission-Limits in the frequency range from 100 KHz to 300 KHz should be assessed versus the limits at 300 KHz in Table 1 of CFR 47 – Section1.310 as following (measured distance shall be 15cm from the center of the probe to the edge of the device):


	E-Field	*/*	B-Field
Frequency	V/m	A/m	uT
0.3 MHz – 3.0 MHz	614	1.613	2.0
3.0 MHz – 30 MHz	824/f (=27.5 <sub>30MHz</sub> )	2.19/f (=0.073 <sub>30MHz</sub> )	--

A KDB inquire was required to determine/confirm the applicable limits below 100 KHz.



Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
Scan code to check authenticity

#### 4. Test Setup Diagram



#### 5. Test Equipment

Equipment	Manufacturer	Model	Serial no.	Calibrated date	Calibrated Due
Exposure Level Tester	Narda	ELT-400	N-0713	2024-11-11	2025-11-10
B-Field Probe	Narda	ELT-400	M-1154	2024-10-08	2025-10-07
Electric field probe	Narda	EP601	611WX70332	N/A	N/A

#### Support equipment List

Manufacturer	Description	Model	Serial Number	Certificate
Huawei	Mobile phone	FRD-AL10	FRD-AL10C00B 373	FCC
--	Smart Watch	G2	--	FCC

Note: Auxiliary equipment is provided by the laboratory.

#### 6. Measurement Procedure

- The RF exposure test was performed on 360 degree turn table in anechoic chamber.
- The measurement probe was placed at test distance (15cm and 20cm) which is between the edges of the charger and the geometric center of probe.
- The turn table was rotated 360d degree to search of highest strength.
- The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
- The EUT were measured according to the dictates of KDB 680106 D01v04.





## 7. Equipment Approval Considerations

The EUT does comply with item 5.2 of KDB 680106 D01v04 as follows table;

Requirements of KDB 680106 D01	Yes / No	Description
Power transfer frequency is less than 1 MHz	Yes	The device operates in the frequency range 110.0 KHz - 205 KHz, 275-285KHz
The output power from each transmitting element (e.g., coil) is less than or equal to 15 watts.	Yes	The maximum output power of the primary coil is 15W.
A client device providing the maximum permitted load is placed in physical contact with the transmitter (i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact)	Yes	Client device is placed directly in contact with the transmitter.
Only § 2.1091- Mobile exposure conditions apply (i.e., this provision does not cover § 2.1093-Portable exposure conditions).	Yes	Mobile exposure conditions only
The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1. These measurements shall be taken along the principal axes of the device, with one axis oriented along the direction of the estimated maximum field strength, and for three points per axis or until a 1/d (inverse distance from the emitter structure) field strength decay is observed. Symmetry considerations may be used for test reduction purposes. The device shall be operated in documented worst-case compliance scenarios (i.e., the ones that lead to the maximum field components), and while all the radiating structures (e.g., coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power.	Yes	The EUT H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.
For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the design allows one or more radiating structures to be powered at a higher level while other radiating structures are not powered, then those cases must be tested as well.	Yes	Only two radiating structure and tested at maximum Output Power



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity

For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested

There might be situations where the WPT RF emissions are limited enough that even operations in a “crowded” environment, where many similar WPT devices are present, do not pose significant EMC and RF exposure concerns. In this scenario, and for devices operating within a one-meter distance from the receiver, as defined above, a manufacturer will not have to submit an “Equipment Compliance Review” KDB, and receive FCC concurrence before proceeding with equipment authorization. This exception to the requirement of submitting the ECR to obtain FCC concurrence only applies when all the following criteria (1) through (6) are met.

## 8. E and H field Strength

Test Modes		
Mode 1	AC power supply + EUT + Phone + Watch (Battery Status: <1%)	Record
Mode 2	AC power supply + EUT + Phone + Watch (Battery Status: <50%)	Record
Mode 3	AC power supply + EUT + Phone + Watch (Battery Status: 100%)	Record

Note: All test modes were pre-tested for ac and dc mode, but we only recorded the worst case in this report for ac mode.

### For Phone:

Field Strength at 15 cm from the edges surrounding the EUT and 15cm from the top surface of the EUT

Load mode	Frequency Range (kHz)	Field Strength	Measured Field Strength Values					50% Limits	Limits
			Test Position A	Test Position B	Test Position C	Test Position D	Test Position E		
Mode 1	110.0~205.0	uT	0.125	0.137	0.144	0.129	0.138	--	--
Mode 1	110.0~205.0	A/m	0.100	0.109	0.115	0.104	0.111	0.815	1.63
Mode 1	110.0~205.0	V/m	37.461	41.105	43.355	38.908	41.563	307.0	614.0
Mode 2	110.0~205.0	uT	0.123	0.129	0.142	0.132	0.144	--	--
Mode 2	110.0~205.0	A/m	0.099	0.103	0.114	0.106	0.115	0.815	1.63
Mode 2	110.0~205.0	V/m	37.042	38.896	42.775	39.710	43.381	307.0	614.0
Mode 3	110.0~205.0	uT	0.119	0.137	0.139	0.132	0.144	--	--
Mode 3	110.0~205.0	A/m	0.095	0.109	0.111	0.106	0.115	0.815	1.63
Mode 3	110.0~205.0	V/m	35.816	41.062	41.844	39.762	43.234	307.0	614.0



**For Watch:**

Field Strength at 15 cm from the edges surrounding the EUT and 15cm from the top surface of the EUT

Load mode	Frequency Range (kHz)	Field Strength	Measured Field Strength Values					50% Limits	Limits
			Test Position A	Test Position B	Test Position C	Test Position D	Test Position E		
Mode 1	275-285	uT	0.124	0.135	0.136	0.128	0.143	--	--
Mode 1	275-285	A/m	0.099	0.108	0.109	0.102	0.115	0.815	1.63
Mode 1	275-285	V/m	37.379	40.698	40.958	38.429	43.059	307.0	614.0
Mode 2	275-285	uT	0.127	0.131	0.142	0.129	0.145	--	--
Mode 2	275-285	A/m	0.101	0.105	0.114	0.103	0.116	0.815	1.63
Mode 2	275-285	V/m	38.096	39.500	42.793	38.663	43.624	307.0	614.0
Mode 3	275-285	uT	0.119	0.130	0.139	0.129	0.141	--	--
Mode 3	275-285	A/m	0.095	0.104	0.111	0.103	0.113	0.815	1.63
Mode 3	275-285	V/m	35.796	39.125	41.702	38.851	42.527	307.0	614.0

**For Phone:**

Field Strength at 20 cm from the edges surrounding the EUT and 20cm from the top surface of the EUT

Load mode	Frequency Range (kHz)	Field Strength	Measured Field Strength Values		50% Limits	Limits
			Test Position E	Test Position E		
Mode 1	110.0~205.0	uT	0.146	0.146	--	--
Mode 1	110.0~205.0	A/m	0.117	0.117	0.815	1.63
Mode 1	110.0~205.0	V/m	43.948	43.948	307	614
Mode 2	110.0~205.0	uT	0.138	0.138	--	--
Mode 2	110.0~205.0	A/m	0.111	0.111	0.815	1.63
Mode 2	110.0~205.0	V/m	41.540	41.540	307	614
Mode 3	110.0~205.0	uT	0.148	0.148	--	--
Mode 3	110.0~205.0	A/m	0.119	0.119	0.815	1.63
Mode 3	110.0~205.0	V/m	44.552	44.552	307	614



**For Watch:**


Field Strength at 20 cm from the edges surrounding the EUT and 20cm from the top surface of the EUT

Load mode	Frequency Range (kHz)	Field Strength	Measured Field Strength Values	50% Limits	Limits
			Test Position E		
Mode 1	275-285	uT	0.139	--	--
Mode 1	275-285	A/m	0.111	0.815	1.63
Mode 1	275-285	V/m	41.830	307	614
Mode 2	275-285	uT	0.139	--	--
Mode 2	275-285	A/m	0.111	0.815	1.63
Mode 2	275-285	V/m	41.813	307	614
Mode 3	275-285	uT	0.141	--	--
Mode 3	275-285	A/m	0.113	0.815	1.63
Mode 3	275-285	V/m	42.289	307	614

Note:  $V/m = 10(((20\lg(A/m \cdot 10^6) + 51.5) - 120)/20)$ Note:  $A/m = uT/1.25$ 

## 9. Test Setup Photos

### 9.1. Test Position A - Exposure photo from side edge surface-Rear(15cm)





(TM1)



### 9.2. Test Position B - Exposure photo from side edge surface-Left(15cm)



(TM1)



**9.3. Test Position C - Exposure photo from side edge surface-Front(15cm)****(TM1)****9.4. Test Position D - Exposure photo from side edge surface-Right(15cm)****(TM1)**

**9.5. Test Position E - Exposure photo from top surface (20cm)****(TM1)****9.6. Test Position E- Exposure photo from top surface (15cm)****(TM1)**



## 10. Conclusion

A minimum safety distance of at 15 cm surrounding the device and 20 cm above the top surface of the device is required when the device is charging a smart phone. The detected emissions with a distance of 15 cm surrounding the device and 20 cm above the top surface of the device are below the limitations according to FCC KDB 680106 D01 Section 3. RF Exposure Requirement Clause 3.

## 11. Description of Test Facility

NVLAP Accreditation Code is 600167-0.  
FCC Designation Number is CN5024.  
CAB identifier is CN0071.  
CNAS Registration Number is L4595.  
Test Firm Registration Number: 254912.

## 12. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Field Strength Uncertainty	1Hz~400KHz	1%	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

.....END OF REPORT.....



Shenzhen LCS Compliance Testing Laboratory Ltd.  
Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China  
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com  
Scan code to check authenticity