

## QI2 Magnetic Wireless Charger

### QI2磁吸无线充电器

#### Specification

Model / 型号	OJD-Q203
Input / 输入	9V/2.22A
Output / 输出	5W/7.5W/15W
Interface / 接口	Type-c
Conversion rate / 充电转换率	≥73%
colour / 颜色	White / Black

#### Note

1. Please do not disassemble the product at will.  
请勿随意拆卸本产品。
2. Please do not use this product in high temperature, damp environment.  
请勿在高温、潮湿环境下使用本产品。
3. To charging contact surface on the back of the mobile phone cannot carry metal materials such as iron sheets, finger rings, metal protective shells, etc.  
手机背面充电接触面不能带有金属物质,如铁片、指环、金属保护壳等。



#### Packaging List

QI2 Magnetic Wireless Charger\*1  
QI2磁吸无线充电器\*1  
User Manual\*1  
用户手册\*1



## 产品外观

### Product Appearance



充电无指示灯

Charging no working indicator light



Made in China

### FCC Warning

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radiofrequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

-Reorient or relocate the receiving antenna.

-Increase the separation between the equipment and receiver.

-Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

-Consult the dealer or an experienced radio/TV technician for help.

The FCC certification of this device refers to RF exposure testing performed in typical operating conditions, where a person is no closer than 20 centimeters from the device surface at all times, except for non-repetitive patterns with transient time intervals in the order of a second. Only in the stated conditions, the device is shown to fully comply with the FCC RF Exposure requirements of KDB 447498.