

Description: WIFI 3 AUX LEFT




Series: SY AICAM

CUSTOMER P/N:

PULSE P/N: TZ2727W

Features:

- WLAN antenna
- Flexible Printed Circuit
- 1.13mm LLS cable with IPEX4
- RoHS Compliant



Applications:

AI CAM



In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe. Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden. For more information:



Description: WIFI 3 AUX LEFT



Series: SY AICAM CUSTOMER P/N:

PULSE P/N: TZ2727W

ELECTRICAL SPECIFICATIONS

Antenna Type FPC Dipole

Frequency 2.4-2.5 GHz

5.15-5.85 GHz

Nominal Impedance 50 Ω Radiation Pattern Omni

Gain Refer to below table

Polarization Linear

Power Withstanding 1W

MECHANICAL SPECIFICATIONS

Overall Length 77.57x20.6x0.15mm

Antenna Color / Material

Connector type

See table, P3

Cable type

See table, P3

Cable length

See table, P3

Adhesive tape

See table, P3

See table, P3

See table, P3

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature $-40 \sim +85^{\circ}\text{C}$ Storage Temperature $-40 \sim +85^{\circ}\text{C}$

RoHS Compliant Yes





Description: WIFI 3 AUX LEFT




Series: SY AICAM

CUSTOMER P/N:

PULSE P/N: TZ2727W

MECHANICAL DRAWING







Description: WIFI 3 AUX LEFT





Series: SY AICAM

CUSTOMER P/N: PULSE P/N: TZ2727W

TEST SETUP

SII of WIFI3









Description: WIFI 3 AUX LEFT




Series: SY AICAM

CUSTOMER P/N: PULSE P/N: TZ2727W

TEST SETUP

Efficiency of WIFI3





Description: WIFI 3 AUX LEFT



Series: SY AICAM

CUSTOMER P/N:

PULSE P/N: TZ2727W

TEST SETUP

Efficiency of WIFI3

	WIFI3		
Freq	Eff.(dB)	Eff.(%)	Peak Gain
(MHz)	En.(uD)	LII.(/0)	(dBi)
2400	-2.84	52.0	2.07
2450	-2.16	60.8	2.54
2500	-2.61	54.8	2.36
5150	-2.22	60.0	5.07
5250	-1.63	68.7	5.60
5350	-1.65	68.4	5.50
5470	-2.37	57.9	5.71
5600	-1.58	69.5	6.30
5725	-1.64	68.5	6.18
5785	-2.00	63.1	5.28
5850	-1.85	65.3	4.81



Description: WIFI 3 AUX LEFT



Series: SY AICAM

CUSTOMER P/N: PULSE P/N: TZ2727W

CHARTS

Radiation Pattern of WIFI3

