

Portable Power Station

Model: **TTPS3000W-US**

Battery: 2560Wh, 51.2V

Power Input/Output: 40-58.8V=50A charge, 70A discharge(max.)

Discharge temperature range: -20-45°C

Charge temperature range: 0-45°C

AC Input: 220-240V~, 50/60Hz, 10A max., 2300W max.

Solar/Car input x2: 13-45V=12A max., 800W max.

AC socket x3 : 220-240V~, 50/60Hz, 16A max., 3000W max.

AC socket [Bypass Mode] x3 : 220-240V~, 50/60Hz, 10A max., 2300W max.

Cigarette lighter output/DC 5521 total: max. 126W

Cigarette lighter output: 12.6V=10A max., 126W max.

DC 5521 output x2: 12.6V=3A, 40.8W max.

Anderson terminal output: 12.6V=30A max., 378W max.

USB-C1/C2 output: 5/9/12/15V=3A, 20V=5A, 100W max.

USB-A1/A2 output: 5V=3A, 9V=2A, 12V=1.5A, 18W max.

USB-A3/A4 output: 5V=2.4A, 12W max.

Made in China

FCC ID: **2BCX4-3KV**

IC: 31342-3KV

Portable Power Station

Model: TTPS3000W-US

Battery: 2560Wh, 51.2V

Power Input/Output: 40-58.8V, 50A charge, 70A discharge(max.)

Discharge temperature range: -20-45°C

Charge temperature range: 0-45°C

AC Input: 220-240V~, 50/60Hz, 10A max., 2300W max.

Solar/Car input x2: 13-45V, 12A max., 800W max.

AC socket x3 : 220-240V~, 50/60Hz, 16A max., 3000W max.

AC socket (Bypass Mode) x3 : 220-240V~, 50/60Hz, 10A max., 2300W max.

Cigarette lighter output/DC 5521 total: max. 126W

Cigarette lighter output: 12.6V, 10A max., 126W max.

DC 5521 output x2: 12.6V, 3A, 40.8W max.

Anderson terminal output: 12.6V, 30A max., 37.8W max.

USB-C1/C2 output: 5/9/12/15V, 3A, 20V, 5A, 100W max.

USB-A1/A2 output: 5V, 3A, 9V, 2A, 12V, 1.5A, 18W max.

USB-A3/A4 output: 5V, 2.4A, 12W max.

Made in China

FCC ID: 2BCK4-3KV

IC: 31342-3KV

