

## FCC RF Exposure

EUT Description: Wireless IR Repeater System

Model No.: SLIWIRO04, SLIWIRO03, SLIWIRO01, SLIWIRO02, SLIWIRO05, SLIWIRO06, SLIWIRO11, SLIWIRO12, SLIWIRO13, SLIWIRO14, SLIWIRO15, SLIWIRO16, SLIWIRO21, SLIWIRO22, SLIWIRO23, SLIWIRO24, SLIWIRO25, SLIWIRO26, SLIWIRO31, SLIWIRO32, SLIWIRO33, SLIWIRO34, SLIWIRO35, SLIWIRO41, SLIWIRO42, SLIWIRO43, SLIWIRO45, SLIWIRO51, SLIWIRO52, SLIWIRO53, SLIWIRO54, SLIWIRO55

FCC ID: 2BCXL-SLIWIRO04

Equipment type: mobile equipment

### 1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F = frequency in MHz

Formula:  $Pd = (Pout * G) / (4 * \pi * r^2)$

Where :

Pd = power density in mW/cm<sup>2</sup>,

Pout = output power to antenna in mW;

G = gain of antenna in linear scale,

$\pi = 3.14$ ;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 3. Test Result of RF Exposure Evaluation

$$\text{EIRP} = \text{EMeas} + 20\log(\text{dmeas}) - 104.7$$

EIRP is the equivalent isotropically radiated power,

EMeas in dBm is the field strength of the emission at the measurement distance, in dB u V/m

dmeas is the measurement distance, in m

Field strength(dBuV/m)	EIRP(dBm)	Max tune-up(mW)	Antenna Gain(dBi)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
72.36	-22.7976	0.0053	2.0	0.000002	0.289	Pass

Conclusion: No SAR is required