

---

# SAR Test Report

---

Report No.: AGC13676230901FH01

**FCC ID** : 2BCYIA1010S

**PRODUCT DESIGNATION** : BEEBEST Walkie-Talkie LITO

**BRAND NAME** : BEEBEST

**MODEL NAME** : A1010S

**APPLICANT** : HONGKONG BEEBEST INFORMATION TECHNOLOGY CO., LIMITED

**DATE OF ISSUE** : Oct. 27, 2023

**STANDARD(S)** : IEEE Std. 1528:2013  
FCC 47 CFR Part 2§2.1093  
IEEE Std C95.1™-2005

**REPORT VERSION** : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd.



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>



**Report Revise Record**

| Report Version | Revise Time | Issued Date   | Valid Version | Notes           |
|----------------|-------------|---------------|---------------|-----------------|
| V1.0           | /           | Oct. 27, 2023 | Valid         | Initial Release |


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

| Test Report                  |                                                                                              |
|------------------------------|----------------------------------------------------------------------------------------------|
| Applicant Name               | HONGKONG BEEBEST INFORMATION TECHNOLOGY CO., LIMITED                                         |
| Applicant Address            | WORKSHOP 60, 3F, BLOCK A,EAST SUN INDUSTRIAL CENTRE NO.16 SHING YIP STREET, KOWLOON, China.  |
| Manufacturer Name            | Xi'an Fengyu Information Technology Co., Ltd                                                 |
| Manufacturer Address         | Room A-506, SSTRC, No. 10, Zhangba Subdistrict Office, High-tech Zone, Xi'an, Shaanxi, China |
| Factory Name                 | N/A                                                                                          |
| Factory Address              | N/A                                                                                          |
| Product Designation          | BEEBEST Walkie-Talkie LITO                                                                   |
| Brand Name                   | BEEBEST                                                                                      |
| Model Name                   | A1010S                                                                                       |
| EUT Voltage                  | DC3.8 V                                                                                      |
| Applicable Standard          | IEEE Std. 1528:2013<br>FCC 47 CFR Part 2§2.1093<br>IEEE Std C95.1™-2005                      |
| Date of receipt of test item | Sep. 25, 2023                                                                                |
| Test Date                    | Sep. 25, 2023                                                                                |
| Report Template              | AGCRT- US -PTT/SAR (2021-04-20)                                                              |

Note: The results of testing in this report apply to the product/system which was tested only.

Prepared By



Bibo Zhang  
(Project Engineer)

Sep. 25, 2023

Reviewed By



Calvin Liu  
(Reviewer)

Oct. 27, 2023

Approved By



Max Zhang  
(Authorized Officer)

Oct. 27, 2023

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std &amp; Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

## TABLE OF CONTENTS

|                                                                                              |           |
|----------------------------------------------------------------------------------------------|-----------|
| <b>1. SUMMARY OF MAXIMUM SAR VALUE .....</b>                                                 | <b>5</b>  |
| <b>2. GENERAL INFORMATION.....</b>                                                           | <b>6</b>  |
| 2.1. EUT DESCRIPTION.....                                                                    | 6         |
| <b>3. SAR MEASUREMENT SYSTEM.....</b>                                                        | <b>7</b>  |
| 3.1. THE DASY5 SYSTEM USED FOR PERFORMING COMPLIANCE TESTS CONSISTS OF FOLLOWING ITEMS ..... | 7         |
| 3.2. DASY5 E-FIELD PROBE.....                                                                | 8         |
| 3.3. DATA ACQUISITION ELECTRONICS DESCRIPTION .....                                          | 8         |
| 3.4. ROBOT.....                                                                              | 9         |
| 3.5. LIGHT BEAM UNIT .....                                                                   | 9         |
| 3.6. DEVICE HOLDER .....                                                                     | 10        |
| 3.7. MEASUREMENT SERVER.....                                                                 | 10        |
| 3.8. PHANTOM.....                                                                            | 11        |
| <b>4. SAR MEASUREMENT PROCEDURE .....</b>                                                    | <b>12</b> |
| 4.1. SPECIFIC ABSORPTION RATE (SAR).....                                                     | 12        |
| 4.2. SAR MEASUREMENT PROCEDURE .....                                                         | 13        |
| <b>5. TISSUE SIMULATING LIQUID .....</b>                                                     | <b>15</b> |
| 5.1. THE COMPOSITION OF THE TISSUE SIMULATING LIQUID.....                                    | 15        |
| 5.2. TISSUE DIELECTRIC PARAMETERS FOR HEAD AND BODY PHANTOMS .....                           | 15        |
| 5.3. TISSUE CALIBRATION RESULT .....                                                         | 16        |
| <b>6. SAR SYSTEM CHECK PROCEDURE .....</b>                                                   | <b>17</b> |
| 6.1. SAR SYSTEM CHECK PROCEDURES .....                                                       | 17        |
| <b>7. EUT TEST POSITION.....</b>                                                             | <b>19</b> |
| 7.1. BODY WORN POSITION .....                                                                | 19        |
| <b>8. SAR EXPOSURE LIMITS .....</b>                                                          | <b>20</b> |
| <b>9. TEST FACILITY .....</b>                                                                | <b>21</b> |
| <b>10. TEST EQUIPMENT LIST .....</b>                                                         | <b>22</b> |
| <b>11. MEASUREMENT UNCERTAINTY .....</b>                                                     | <b>23</b> |
| <b>12. POWER MEASUREMENT .....</b>                                                           | <b>27</b> |
| <b>13. TEST RESULTS.....</b>                                                                 | <b>28</b> |
| 13.1. SAR TEST RESULTS SUMMARY .....                                                         | 28        |
| <b>APPENDIX A. SAR SYSTEM CHECK DATA .....</b>                                               | <b>31</b> |
| <b>APPENDIX B. SAR MEASUREMENT DATA.....</b>                                                 | <b>32</b> |
| <b>APPENDIX C. TEST SETUP PHOTOGRAPHS.....</b>                                               | <b>38</b> |
| <b>APPENDIX D. CALIBRATION DATA .....</b>                                                    | <b>41</b> |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

## 1. SUMMARY OF MAXIMUM SAR VALUE

The maximum results of Specific Absorption Rate (SAR) found during testing for EUT are as follows:

### Highest Report standalone SAR Summary (50% duty cycle)

| Frequency Band              | Type of signal | Separation | Highest Reported 1g-SAR(W/kg)  |                                 |
|-----------------------------|----------------|------------|--------------------------------|---------------------------------|
|                             |                |            | Face Up (with 25mm separation) | Back Touch with all accessories |
| 462.5500-462.7250MHz(2W)    | Analog         | 12.5KHz    | 0.126                          | 0.674                           |
| 467.5625-467.7125MHz (0.5W) |                |            | 0.106                          | 0.497                           |

This device is compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure environment limits(1.6W/kg) specified in 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1, and had been tested in accordance with measurement methods and procedures specified in IEEE 1528-2013 and the following specific FCC Test Procedures:

KDB 447498 D01 General RF Exposure Guidance v06

KDB 865664 D01 SAR Measurement 100MHz to 6GHz v01r04

KDB 643646 D01 SAR Test for PTT Radios v01r03

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

## 2. GENERAL INFORMATION

### 2.1. EUT Description

| General Information     |                                                                                        |
|-------------------------|----------------------------------------------------------------------------------------|
| Product Name            | BEEBEST Walkie-Talkie LITO                                                             |
| Test Model              | A101OS                                                                                 |
| Hardware Version        | 3.1                                                                                    |
| Software Version        | 0.2.6                                                                                  |
| Exposure Category       | General Population/Uncontrolled Environments                                           |
| Device Category         | FM Portable Transceiver                                                                |
| Modulation Type         | F3E                                                                                    |
| TX Frequency Range      | 462.5500-462.7250MHz(2W); 467.5625-467.7125MHz (0.5W)                                  |
| Rated Power             | 2W/0.5W (It was fixed by the manufacturer, any individual can't arbitrarily change it) |
| Max. Output Power       | 32.78dBm                                                                               |
| Channel Spacing         | 12.5 KHz                                                                               |
| Antenna Type            | Inseparable                                                                            |
| Antenna Gain            | 1.85dBi                                                                                |
| Body-Worn Accessories   | Belt Clip and headset                                                                  |
| Face-Head Accessories   | None                                                                                   |
| Battery Type (s) Tested | DC3.8V, 2190mAh (by battery)                                                           |
| Bluetooth               |                                                                                        |
| Operation Frequency     | 2402~2480MHz                                                                           |
| Antenna Gain            | -3.4dBi                                                                                |
| Bluetooth Version       | V4.2                                                                                   |
| Type of modulation      | <b>BR/EDR:</b> GFSK, $\Pi/4$ -DQPSK, 8-DPSK; <b>BLE:</b> GFSK                          |
| EIRP                    | <b>BR/EDR:</b> -0.694dBm; <b>BLE:</b> 7.319dBm                                         |

Note: 1. The sample used for testing is end product.

2. The test sample has no any deviation to the test method of standard mentioned in page 1.

|         |                                                                                                  |
|---------|--------------------------------------------------------------------------------------------------|
| Product | Type                                                                                             |
|         | <input checked="" type="checkbox"/> Production unit <input type="checkbox"/> Identical Prototype |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

### 3. SAR MEASUREMENT SYSTEM

#### 3.1. The DASY5 system used for performing compliance tests consists of following items



- A standard high precision 6-axis robot with controller, teach pendant and software.
- Data acquisition electronics (DAE) which attached to the robot arm extension. The DAE consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock
- A dosimetric probe equipped with an optical surface detector system.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital Communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- A Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- Phantoms, device holders and other accessories according to the targeted measurement.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



### 3.2. DASY5 E-Field Probe

The SAR measurement is conducted with the dosimetric probe manufactured by SPEAG. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. SPEAG conducts the probe calibration in compliance with international and national standards (e.g. IEEE 1528 etc.) Under ISO17025. The calibration data are in Appendix D.

#### Isotropic E-Field Probe Specification

|               |                                                                                                                                                                                                            |                                                                                     |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Model         | ES3DV3-SN:3337                                                                                                                                                                                             |                                                                                     |
| Manufacture   | SPEAG                                                                                                                                                                                                      |                                                                                     |
| frequency     | 0.15GHz-0.45 GHz<br>Linearity:±0.6%dB(K=2)(0.15MHz-0.45 GHz)                                                                                                                                               |  |
| Dynamic Range | 0.01W/kg-100W/kg<br>Linearity:±0.6%dB(K=2)                                                                                                                                                                 |                                                                                     |
| Dimensions    | Overall length:337mm<br>Tip diameter:4mm<br>Typical distance from probe tip to dipole centers:2mm                                                                                                          |                                                                                     |
| Application   | High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 3 GHz with precision of better 30%. |                                                                                     |

### 3.3. Data Acquisition Electronics description

The data acquisition electronics (DAE) consist if a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement sever is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

#### DAE4

|                              |                          |                                                                                      |
|------------------------------|--------------------------|--------------------------------------------------------------------------------------|
| <b>Input Impedance</b>       | 200MOhm                  |  |
| <b>The Inputs</b>            | Symmetrical and floating |                                                                                      |
| <b>Common mode rejection</b> | above 80 dB              |                                                                                      |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



### 3.4. Robot

The DASY system uses the high precision robots (DASY5:TX60) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version form is used.

The XL robot series have many features that are important for our application:

- ☐ High precision (repeatability 0.02 mm)
- ☐ High reliability (industrial design)
- ☐ Jerk-free straight movements
- ☐ Low ELF interference (the closed metallic construction shields against motor control fields)
- ☐ 6-axis controller



### 3.5. Light Beam Unit

The light beam switch allows automatic “tooling” of the probe. During the process, the actual position of the probe tip with respect to the robot arm is measured, as well as the probe length and the horizontal probe offset. The software then corrects all movements, such that the robot coordinates are valid for the probe tip.

The repeatability of this process is better than 0.1 mm. If a position has been taught with an aligned probe.1 mm, even if the other probe has different dimensions. During probe rotations, the probe tip will keep its actual position. e, the same position will be reached with another aligned probe within 0



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: [agc@agccert.com](mailto:agc@agccert.com) Web: <http://www.agccert.com/>

### 3.6. Device Holder

The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR).

Thus the device needs no repositioning when changing the angles.

The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon=3$  and loss tangent  $\delta = 0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



### 3.7. Measurement Server

The measurement server is based on a PC/104 CPU board with CPU (DASY5: 400 MHz, Intel Celeron), chip-disk (DASY5: 128MB), RAM (DASY5: 128MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DAYS I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all the real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operations.



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: [agc@agccert.com](mailto:agc@agccert.com) Web: <http://www.agccert.com/>

### 3.8. PHANTOM SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region where shell thickness increases to 6mm). It has three measurement areas:

- ☐ Left head
- ☐ Right head
- ☐ Flat phantom



The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

### ELI4 Phantom

- ☐ Flat phantom a fiberglass shell flat phantom with 2mm $\pm$  0.2 mm shell thickness. It has only one measurement area for Flat phantom



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

## 4. SAR MEASUREMENT PROCEDURE

### 4.1. Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and occupational/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of given mass density ( $\rho$ ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dV} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR can be obtained using either of the following equations:

$$SAR = \frac{\sigma E^2}{\rho}$$

$$SAR = c_h \left. \frac{dT}{dt} \right|_{t=0}$$

Where

|          |                                                                                      |
|----------|--------------------------------------------------------------------------------------|
| SAR      | is the specific absorption rate in watts per kilogram;                               |
| E        | is the r.m.s. value of the electric field strength in the tissue in volts per meter; |
| $\sigma$ | is the conductivity of the tissue in siemens per metre;                              |
| $\rho$   | is the density of the tissue in kilograms per cubic metre;                           |
| $c_h$    | is the heat capacity of the tissue in joules per kilogram and Kelvin;                |

$\left. \frac{dT}{dt} \right|_{t=0}$  is the initial time derivative of temperature in the tissue in kelvins per second

## 4.2. SAR Measurement Procedure

### Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurement are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface is 2.7mm This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties,

### Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in db) is specified in the standards for compliance testing. For example, a 2db range is required in IEEE Standard 1528 standards, whereby 3db is a requirement when compliance is assessed in accordance with the ARIB standard (Japan) If one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximum are detected, the number of Zoom Scan has to be increased accordingly.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100MHz to 6GHz

|                                                                                                        | $\leq 3 \text{ GHz}$                                                                                                                                                                                                                                                   | $> 3 \text{ GHz}$                                                                  |
|--------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface | $5 \pm 1 \text{ mm}$                                                                                                                                                                                                                                                   | $\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$                         |
| Maximum probe angle from probe axis to phantom surface normal at the measurement location              | $30^\circ \pm 1^\circ$                                                                                                                                                                                                                                                 | $20^\circ \pm 1^\circ$                                                             |
| Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$                 | $\leq 2 \text{ GHz}: \leq 15 \text{ mm}$<br>$2 - 3 \text{ GHz}: \leq 12 \text{ mm}$                                                                                                                                                                                    | $3 - 4 \text{ GHz}: \leq 12 \text{ mm}$<br>$4 - 6 \text{ GHz}: \leq 10 \text{ mm}$ |
|                                                                                                        | When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device. |                                                                                    |

### Step 3: Zoom Scan

Zoom Scan are used to assess the peak spatial SAR value within a cubic average volume containing 1g abd 10g of simulated tissue. The Zoom Scan measures points(refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1g and 10g and displays these values next to the job's label.



#### Zoom Scan Parameters extracted from KDB865664 D01 SAR Measurement 100MHz to 6GHz

|                                                                                                                                                                                                                                                                                                                                               |                                    |                                                                                      |                                                                                     |                                                                                                                               |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|--------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Maximum zoom scan spatial resolution: $\Delta x_{Zoom}$ , $\Delta y_{Zoom}$                                                                                                                                                                                                                                                                   |                                    |                                                                                      | $\leq 2 \text{ GHz}: \leq 8 \text{ mm}$<br>$2 - 3 \text{ GHz}: \leq 5 \text{ mm}^*$ | $3 - 4 \text{ GHz}: \leq 5 \text{ mm}^*$<br>$4 - 6 \text{ GHz}: \leq 4 \text{ mm}^*$                                          |
| Maximum zoom scan spatial resolution, normal to phantom surface                                                                                                                                                                                                                                                                               | uniform grid: $\Delta z_{Zoom}(n)$ |                                                                                      | $\leq 5 \text{ mm}$                                                                 | $3 - 4 \text{ GHz}: \leq 4 \text{ mm}$<br>$4 - 5 \text{ GHz}: \leq 3 \text{ mm}$<br>$5 - 6 \text{ GHz}: \leq 2 \text{ mm}$    |
|                                                                                                                                                                                                                                                                                                                                               | graded grid                        | $\Delta z_{Zoom}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface | $\leq 4 \text{ mm}$                                                                 | $3 - 4 \text{ GHz}: \leq 3 \text{ mm}$<br>$4 - 5 \text{ GHz}: \leq 2.5 \text{ mm}$<br>$5 - 6 \text{ GHz}: \leq 2 \text{ mm}$  |
|                                                                                                                                                                                                                                                                                                                                               |                                    | $\Delta z_{Zoom}(n>1)$ : between subsequent points                                   | $\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$                                               |                                                                                                                               |
| Minimum zoom scan volume                                                                                                                                                                                                                                                                                                                      | x, y, z                            |                                                                                      | $\geq 30 \text{ mm}$                                                                | $3 - 4 \text{ GHz}: \geq 28 \text{ mm}$<br>$4 - 5 \text{ GHz}: \geq 25 \text{ mm}$<br>$5 - 6 \text{ GHz}: \geq 22 \text{ mm}$ |
| Note: $\delta$ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.                                                                                                                                                                                             |                                    |                                                                                      |                                                                                     |                                                                                                                               |
| * When zoom scan is required and the <u>reported</u> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is $\leq 1.4 \text{ W/kg}$ , $\leq 8 \text{ mm}$ , $\leq 7 \text{ mm}$ and $\leq 5 \text{ mm}$ zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz. |                                    |                                                                                      |                                                                                     |                                                                                                                               |

#### Step 4: Power Drift Measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the same settings. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

## 5. TISSUE SIMULATING LIQUID

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15cm. For head SAR testing the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15cm For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 10% are listed in 6.2

### 5.1. The composition of the tissue simulating liquid

| Ingredient<br>(% Weight)<br>Frequency<br>(MHz) | Water | NaCl | Sugar | HEC  | Bactericide | DGBE | 1,2-<br>Propanediol | Triton<br>X-100 |
|------------------------------------------------|-------|------|-------|------|-------------|------|---------------------|-----------------|
| 450 Head (100%)                                | 38.56 | 3.95 | 56.32 | 0.98 | 0.19        | 0.0  | 0.0                 | 0.0             |

### 5.2. Tissue Dielectric Parameters for Head and Body Phantoms

The head and body tissue dielectric parameters recommended by the IEEE Std. 1528 have been incorporated in the following table.

| Target Frequency<br>(MHz) | head         |                | body         |                |
|---------------------------|--------------|----------------|--------------|----------------|
|                           | $\epsilon_r$ | $\sigma$ (S/m) | $\epsilon_r$ | $\sigma$ (S/m) |
| 150                       | 52.3         | 0.76           | 52.3         | 0.76           |
| 300                       | 45.3         | 0.87           | 45.3         | 0.87           |
| <b>450</b>                | <b>43.5</b>  | <b>0.87</b>    | <b>43.5</b>  | <b>0.87</b>    |
| 835                       | 41.5         | 0.90           | 41.5         | 0.90           |
| 900                       | 41.5         | 0.97           | 41.5         | 0.97           |
| 915                       | 41.5         | 0.98           | 41.5         | 0.98           |
| 1450                      | 40.5         | 1.20           | 40.5         | 1.20           |
| 1610                      | 40.3         | 1.29           | 40.3         | 1.29           |
| 1800 – 2000               | 40.0         | 1.40           | 40.0         | 1.40           |
| 2450                      | 39.2         | 1.80           | 39.2         | 1.80           |
| 3000                      | 38.5         | 2.40           | 38.5         | 2.40           |

( $\epsilon_r$  = relative permittivity,  $\sigma$  = conductivity and  $\rho = 1000 \text{ kg/m}^3$ )

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>



### 5.3. Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using DASY5 Dielectric Probe Kit and R&S Network Analyzer ZVL6.

| Tissue Stimulant Measurement for 450MHz |                              |                           |                        |               |
|-----------------------------------------|------------------------------|---------------------------|------------------------|---------------|
| Fr.<br>(MHz)                            | Dielectric Parameters (±10%) |                           | Tissue<br>Temp<br>[°C] | Test time     |
|                                         | Head                         |                           |                        |               |
|                                         | εr43.50(39.150 - 47.850)     | δ[s/m]0.87(0.783 - 0.957) |                        |               |
| 450                                     | 43.20                        | 0.88                      | 20.3                   | Sep. 25, 2023 |
| 462.6500                                | 42.31                        | 0.91                      |                        |               |
| 467.6375                                | 41.26                        | 0.93                      |                        |               |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>


## 6. SAR SYSTEM CHECK PROCEDURE

### 6.1. SAR System Check Procedures

SAR system check is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are re-measured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.

Each DASY system is equipped with one or more system check kits. These units, together with the predefined measurement procedures within the DASY software, enable the user to conduct the system check and system validation. System kit includes a dipole, and dipole device holder.


The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system check setup is shown as below.



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).

## 6.2. SAR System Check

### 6.2.1. Dipoles

|                                                                                   |                                                                                                                                                                                                                                                                    |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <p>The dipoles used is based on the IEEE-1528 standard, and is complied with mechanical and electrical specifications in line with the requirements of IEEE. the table below provides details for the mechanical and electrical specifications for the dipoles</p> |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

| Frequency | R/L (mm) | R/h (mm) | d (mm) |
|-----------|----------|----------|--------|
| 450MHz    | 290      | 166.7    | 6.35   |

### 6.2.2. System Check Result

| System Performance Check at 450MHz |                    |      |                          |             |                        |      |                   |               |
|------------------------------------|--------------------|------|--------------------------|-------------|------------------------|------|-------------------|---------------|
| Validation Kit: D450V3 SN:1113     |                    |      |                          |             |                        |      |                   |               |
| Frequency [MHz]                    | Target Value(W/kg) |      | Reference Result (± 10%) |             | Normalized to 1W(W/kg) |      | Tissue Temp. [°C] | Test time     |
|                                    | 1g                 | 10g  | 1g                       | 10g         | 1g                     | 10g  |                   |               |
| 450                                | 4.61               | 3.09 | 4.149-5.071              | 2.781-3.399 | 4.42                   | 2.98 | 20.3              | Sep. 25, 2023 |

Note:

(1) We use a CW signal of 18dBm(450MHz)for system check, and then all SAR value are normalized to 1W forward power. The result must be within ±10% of target value.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

## 7. EUT TEST POSITION

This EUT was tested in **Front Face and Rear Face**.

### 7.1. Body Worn Position

- (1) To position the EUT parallel to the phantom surface.
- (2) To adjust the EUT parallel to the flat phantom.
- (3) To adjust the distance between the EUT surface and the flat phantom to **25mm** while used in front of face, and body back touch with all accessories.



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

## 8. SAR EXPOSURE LIMITS

### Limits for General population/Uncontrolled exposure Environment

| Type Exposure Limits                             | general population/uncontrolled exposure limits (W/kg) |
|--------------------------------------------------|--------------------------------------------------------|
| Spatial Peak<br>(averaged over any 1g of tissue) | 1.6                                                    |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

## 9. TEST FACILITY

|                                          |                                                                                                                                          |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Test Site</b>                         | Attestation of Global Compliance (Shenzhen) Co., Ltd                                                                                     |
| <b>Location</b>                          | 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China |
| <b>Designation Number</b>                | CN1259                                                                                                                                   |
| <b>FCC Test Firm Registration Number</b> | 975832                                                                                                                                   |
| <b>A2LA Cert. No.</b>                    | 5054.02                                                                                                                                  |
| <b>Description</b>                       | Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by A2LA                                                                |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>



## 10. TEST EQUIPMENT LIST

| Equipment description                             | Manufacturer/ Model   | Identification No. | Software version | Current calibration date | Next calibration date |
|---------------------------------------------------|-----------------------|--------------------|------------------|--------------------------|-----------------------|
| Stäubli Robot                                     | Stäubli-TX60          | F13/5Q2UD1/A/01    | N/A              | N/A                      | N/A                   |
| Robot Controller                                  | Stäubli-CS8           | 139522             | N/A              | N/A                      | N/A                   |
| E-Field Probe                                     | Speag- ES3DV3         | SN:3337            | N/A              | Sep. 26, 2022            | Sep. 25, 2023         |
| SAM Twin Phantom                                  | Speag-SAM             | 1790               | N/A              | N/A                      | N/A                   |
| ELI4 Phantom                                      | ELI V5.0              | 1210               | N/A              | N/A                      | N/A                   |
| Device Holder                                     | Speag-SD 000 H01 KA   | SD 000 H01 KA      | N/A              | N/A                      | N/A                   |
| DAE4                                              | Speag-SD 000 D04 BM   | 1398               | N/A              | May 17, 2023             | May 16, 2024          |
| SAR Software                                      | Speag-DASY5           | DASY52.8.7.1 137   | N/A              | N/A                      | N/A                   |
| Liquid                                            | SATIMO                | N/A                | N/A              | N/A                      | N/A                   |
| Dipole                                            | Speag-D450V3          | SN:1113            | N/A              | Feb. 05, 2021            | Feb. 04, 2024         |
| Signal Generator                                  | Agilent-E4438C        | US41461365         | V5.03            | Jun. 01, 2023            | May 31, 2024          |
| EXA Signal Analyzer                               | Agilent / N9010A      | MY53470504         | N/A              | Jun. 01, 2023            | May 31, 2024          |
| Network Analyzer                                  | Rhode & Schwarz ZVL6  | 101443             | 3.2              | Sep. 21, 2023            | Sep. 20, 2024         |
| Attenuator                                        | Warison /WATT-6SR1211 | S/N:WRJ34A YM2F1   | N/A              | Jun. 07, 2023            | Jun. 06, 2024         |
| Amplifier                                         | AS0104-55_55          | 1004793            | N/A              | N/A                      | N/A                   |
| Directional Couple                                | Werlatone/ C5571-10   | SN99463            | N/A              | Mar. 10, 2022            | Mar. 09, 2024         |
| Power Sensor                                      | NRP-Z21               | 1137.6000.02       | N/A              | Sep. 05, 2023            | Sep. 04, 2024         |
| Power Sensor                                      | NRP-Z23               | 100323             | N/A              | Feb. 15, 2023            | Feb. 14, 2024         |
| Power Viewer                                      | R&S                   | V2.3.1.0           | N/A              | N/A                      | N/A                   |
| Calibration standard parts for network sub - port | R&S/ ZV-Z132          | N/A                | V2.3.1.0         | Nov. 15, 2022            | Nov. 14, 2023         |

Note: Per KDB 865664 Dipole SAR Validation, AGC Lab has adopted 3 years calibration intervals. On annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole;
2. System validation with specific dipole is within 10% of calibrated value;
3. Return-loss is within 20% of calibrated measurement;
4. Impedance is within 5Ω of calibrated measurement.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

## 11. MEASUREMENT UNCERTAINTY

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in Table as follow.

| Uncertainty Distributions | Normal   | Rectangular  | Triangular   | U-Shape      |
|---------------------------|----------|--------------|--------------|--------------|
| Multiplying Factor(a)     | $1/k(b)$ | $1/\sqrt{3}$ | $1/\sqrt{6}$ | $1/\sqrt{2}$ |

(a) Standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b)  $k$  is the coverage factor

**Table 13.1 Standard Uncertainty for Assumed Distribution (above table)**

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

| DASY Uncertainty- ES3DV3<br>Measurement uncertainty for Dipole averaged over 1 gram / 10 gram. |       |              |                |             |              |              |               |                |    |
|------------------------------------------------------------------------------------------------|-------|--------------|----------------|-------------|--------------|--------------|---------------|----------------|----|
| a                                                                                              | b     | c            | d              | e<br>f(d,k) | f            | g            | h<br>c×f/e    | i<br>c×g/e     | k  |
| Uncertainty Component                                                                          | Sec.  | Tol<br>(± %) | Prob.<br>Dist. | Div.        | Ci (1g)      | Ci (10g)     | 1g Ui<br>(±%) | 10g Ui<br>(±%) | vi |
| <b>Measurement System</b>                                                                      |       |              |                |             |              |              |               |                |    |
| Probe calibration                                                                              | E.2.1 | 6.65         | N              | 1           | 1            | 1            | 6.65          | 6.65           | ∞  |
| Axial Isotropy                                                                                 | E.2.2 | 0.25         | R              | $\sqrt{3}$  | $\sqrt{0.5}$ | $\sqrt{0.5}$ | 0.10          | 0.10           | ∞  |
| Hemispherical Isotropy                                                                         | E.2.2 | 1.3          | R              | $\sqrt{3}$  | $\sqrt{0.5}$ | $\sqrt{0.5}$ | 0.53          | 0.53           | ∞  |
| Boundary effect                                                                                | E.2.3 | 1            | R              | $\sqrt{3}$  | 1            | 1            | 0.58          | 0.58           | ∞  |
| Linearity                                                                                      | E.2.4 | 0.3          | R              | $\sqrt{3}$  | 1            | 1            | 0.17          | 0.17           | ∞  |
| System detection limits                                                                        | E.2.4 | 1.0          | R              | $\sqrt{3}$  | 1            | 1            | 0.58          | 0.58           | ∞  |
| Modulation response                                                                            | E.2.5 | 3.3          | R              | $\sqrt{3}$  | 1            | 1            | 1.91          | 1.91           | ∞  |
| Readout Electronics                                                                            | E.2.6 | 0.15         | N              | 1           | 1            | 1            | 0.15          | 0.15           | ∞  |
| Response Time                                                                                  | E.2.7 | 0            | R              | $\sqrt{3}$  | 1            | 1            | 0             | 0              | ∞  |
| Integration Time                                                                               | E.2.8 | 1.7          | R              | $\sqrt{3}$  | 1            | 1            | 0.98          | 0.98           | ∞  |
| RF ambient conditions-Noise                                                                    | E.6.1 | 3.0          | R              | $\sqrt{3}$  | 1            | 1            | 1.73          | 1.73           | ∞  |
| RF ambient conditions-reflections                                                              | E.6.1 | 3.0          | R              | $\sqrt{3}$  | 1            | 1            | 1.73          | 1.73           | ∞  |
| Probe positioner mechanical tolerance                                                          | E.6.2 | 0.4          | R              | $\sqrt{3}$  | 1            | 1            | 0.23          | 0.23           | ∞  |
| Probe positioning with respect to phantom shell                                                | E.6.3 | 6.7          | R              | $\sqrt{3}$  | 1            | 1            | 3.87          | 3.87           | ∞  |
| Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation              | E.5   | 4            | R              | $\sqrt{3}$  | 1            | 1            | 2.31          | 2.31           | ∞  |
| <b>Test sample Related</b>                                                                     |       |              |                |             |              |              |               |                |    |
| Test sample positioning                                                                        | E.4.2 | 2.9          | N              | 1           | 1            | 1            | 2.90          | 2.90           | ∞  |
| Device holder uncertainty                                                                      | E.4.1 | 3.6          | N              | 1           | 1            | 1            | 3.60          | 3.60           | ∞  |
| Output power variation—SAR drift measurement                                                   | E.2.9 | 5            | R              | $\sqrt{3}$  | 1            | 1            | 2.89          | 2.89           | ∞  |
| SAR scaling                                                                                    | E.6.5 | 5            | R              | $\sqrt{3}$  | 1            | 1            | 2.89          | 2.89           | ∞  |
| <b>Phantom and tissue parameters</b>                                                           |       |              |                |             |              |              |               |                |    |
| Phantom shell uncertainty—shape, thickness, and permittivity                                   | E.3.1 | 6.6          | R              | $\sqrt{3}$  | 1            | 1            | 3.81          | 3.81           | ∞  |
| Uncertainty in SAR correction for deviations in permittivity and conductivity                  | E.3.2 | 1.9          | N              | 1           | 1            | 0.84         | 1.90          | 1.60           | ∞  |
| Liquid conductivity measurement                                                                | E.3.3 | 4            | N              | 1           | 0.78         | 0.71         | 3.12          | 2.84           | M  |
| Liquid permittivity measurement                                                                | E.3.3 | 5            | N              | 1           | 0.23         | 0.26         | 1.15          | 1.30           | M  |
| Liquid conductivity—temperature uncertainty                                                    | E.3.4 | 2.5          | R              | $\sqrt{3}$  | 0.78         | 0.71         | 1.13          | 1.02           | ∞  |
| Liquid permittivity—temperature uncertainty                                                    | E.3.4 | 2.5          | R              | $\sqrt{3}$  | 0.23         | 0.26         | 0.33          | 0.38           | ∞  |
| Combined Standard Uncertainty                                                                  |       |              | RSS            |             |              |              | 11.79         | 11.62          |    |
| Expanded Uncertainty (95% Confidence interval)                                                 |       |              | K=2            |             |              |              | 23.58         | 23.25          |    |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

| DASY Uncertainty- ES3DV3                                                          |         |              |                |             |         |          |               |                |    |
|-----------------------------------------------------------------------------------|---------|--------------|----------------|-------------|---------|----------|---------------|----------------|----|
| System Check uncertainty for Dipole averaged over 1 gram / 10 gram.               |         |              |                |             |         |          |               |                |    |
| a                                                                                 | b       | c            | d              | e<br>f(d,k) | f       | g        | h<br>cxf/e    | i<br>cxg/e     | k  |
| Uncertainty Component                                                             | Sec.    | Tol<br>(± %) | Prob.<br>Dist. | Div.        | Ci (1g) | Ci (10g) | 1g Ui<br>(±%) | 10g Ui<br>(±%) | vi |
| <b>Measurement System</b>                                                         |         |              |                |             |         |          |               |                |    |
| Probe calibration drift                                                           | E.2.1   | 0.5          | N              | 1           | 1       | 1        | 0.5           | 0.5            | ∞  |
| Axial Isotropy                                                                    | E.2.2   | 0.25         | R              | $\sqrt{3}$  | 0       | 0        | 0.00          | 0.00           | ∞  |
| Hemispherical Isotropy                                                            | E.2.2   | 1.3          | R              | $\sqrt{3}$  | 0       | 0        | 0.00          | 0.00           | ∞  |
| Boundary effect                                                                   | E.2.3   | 1            | R              | $\sqrt{3}$  | 0       | 0        | 0.00          | 0.00           | ∞  |
| Linearity                                                                         | E.2.4   | 0.3          | R              | $\sqrt{3}$  | 0       | 0        | 0.00          | 0.00           | ∞  |
| System detection limits                                                           | E.2.4   | 1.0          | R              | $\sqrt{3}$  | 0       | 0        | 0.00          | 0.00           | ∞  |
| Modulation response                                                               | E.2.5   | 3.3          | R              | $\sqrt{3}$  | 0       | 0        | 0.00          | 0.00           | ∞  |
| Readout Electronics                                                               | E.2.6   | 0.15         | N              | 1           | 0       | 0        | 0.00          | 0.00           | ∞  |
| Response Time                                                                     | E.2.7   | 0            | R              | $\sqrt{3}$  | 0       | 0        | 0.00          | 0.00           | ∞  |
| Integration Time                                                                  | E.2.8   | 1.7          | R              | $\sqrt{3}$  | 0       | 0        | 0.00          | 0.00           | ∞  |
| RF ambient conditions-Noise                                                       | E.6.1   | 3.0          | R              | $\sqrt{3}$  | 0       | 0        | 0.00          | 0.00           | ∞  |
| RF ambient conditions-reflections                                                 | E.6.1   | 3.0          | R              | $\sqrt{3}$  | 0       | 0        | 0.00          | 0.00           | ∞  |
| Probe positioner mechanical tolerance                                             | E.6.2   | 0.4          | R              | $\sqrt{3}$  | 1       | 1        | 0.23          | 0.23           | ∞  |
| Probe positioning with respect to phantom shell                                   | E.6.3   | 6.7          | R              | $\sqrt{3}$  | 1       | 1        | 3.87          | 3.87           | ∞  |
| Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation | E.5     | 4            | R              | $\sqrt{3}$  | 0       | 0        | 0.00          | 0.00           | ∞  |
| <b>System check source (dipole)</b>                                               |         |              |                |             |         |          |               |                |    |
| Deviation of experimental dipoles                                                 | E.6.4   | 2.0          | N              | 1           | 1       | 1        | 2.00          | 2.00           | ∞  |
| Input power and SAR drift measurement                                             | 8,6.6.4 | 5.0          | R              | $\sqrt{3}$  | 1       | 1        | 2.89          | 2.89           | ∞  |
| Dipole axis to liquid distance                                                    | 8,E.6.6 | 2.0          | R              | $\sqrt{3}$  | 1       | 1        | 1.15          | 1.15           | ∞  |
| <b>Phantom and tissue parameters</b>                                              |         |              |                |             |         |          |               |                |    |
| Phantom shell uncertainty—shape, thickness, and permittivity                      | E.3.1   | 6.6          | R              | $\sqrt{3}$  | 1       | 1        | 3.81          | 3.81           | ∞  |
| Uncertainty in SAR correction for deviations in permittivity and conductivity     | E.3.2   | 1.9          | N              | 1           | 1       | 0.84     | 1.90          | 1.60           | ∞  |
| Liquid conductivity measurement                                                   | E.3.3   | 4            | N              | 1           | 0.78    | 0.71     | 3.12          | 2.84           | M  |
| Liquid permittivity measurement                                                   | E.3.3   | 5            | N              | 1           | 0.23    | 0.26     | 1.15          | 1.30           | M  |
| Liquid conductivity—temperature uncertainty                                       | E.3.4   | 2.5          | R              | $\sqrt{3}$  | 0.78    | 0.71     | 1.13          | 1.02           | ∞  |
| Liquid permittivity—temperature uncertainty                                       | E.3.4   | 2.5          | R              | $\sqrt{3}$  | 0.23    | 0.26     | 0.33          | 0.38           | ∞  |
| Combined Standard Uncertainty                                                     |         |              | RSS            |             |         |          | 7.34          | 7.07           |    |
| Expanded Uncertainty (95% Confidence interval)                                    |         |              | K=2            |             |         |          | 14.67         | 14.14          |    |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

| DASY Uncertainty- ES3DV3                                                          |         |             |                |             |         |          |               |                |    |
|-----------------------------------------------------------------------------------|---------|-------------|----------------|-------------|---------|----------|---------------|----------------|----|
| System Validation uncertainty for Dipole averaged over 1 gram / 10 gram.          |         |             |                |             |         |          |               |                |    |
| a                                                                                 | b       | c           | d              | e<br>f(d,k) | f       | g        | h<br>cxf/e    | i<br>cxg/e     | k  |
| Uncertainty Component                                                             | Sec.    | Tol<br>(±%) | Prob.<br>Dist. | Div.        | Ci (1g) | Ci (10g) | 1g Ui<br>(±%) | 10g Ui<br>(±%) | vi |
| <b>Measurement System</b>                                                         |         |             |                |             |         |          |               |                |    |
| Probe calibration                                                                 | E.2.1   | 6.65        | N              | 1           | 1       | 1        | 6.65          | 6.65           | ∞  |
| Axial Isotropy                                                                    | E.2.2   | 0.25        | R              | $\sqrt{3}$  | 1       | 1        | 0.14          | 0.14           | ∞  |
| Hemispherical Isotropy                                                            | E.2.2   | 1.3         | R              | $\sqrt{3}$  | 0       | 0        | 0.00          | 0.00           | ∞  |
| Boundary effect                                                                   | E.2.3   | 1           | R              | $\sqrt{3}$  | 1       | 1        | 0.58          | 0.58           | ∞  |
| Linearity                                                                         | E.2.4   | 0.3         | R              | $\sqrt{3}$  | 1       | 1        | 0.17          | 0.17           | ∞  |
| System detection limits                                                           | E.2.4   | 1.0         | R              | $\sqrt{3}$  | 1       | 1        | 0.58          | 0.58           | ∞  |
| Modulation response                                                               | E.2.5   | 3.3         | R              | $\sqrt{3}$  | 0       | 0        | 0.00          | 0.00           | ∞  |
| Readout Electronics                                                               | E.2.6   | 0.15        | N              | 1           | 1       | 1        | 0.15          | 0.15           | ∞  |
| Response Time                                                                     | E.2.7   | 0           | R              | $\sqrt{3}$  | 0       | 0        | 0.00          | 0.00           | ∞  |
| Integration Time                                                                  | E.2.8   | 1.7         | R              | $\sqrt{3}$  | 0       | 0        | 0.00          | 0.00           | ∞  |
| RF ambient conditions-Noise                                                       | E.6.1   | 3.0         | R              | $\sqrt{3}$  | 1       | 1        | 1.73          | 1.73           | ∞  |
| RF ambient conditions-reflections                                                 | E.6.1   | 3.0         | R              | $\sqrt{3}$  | 1       | 1        | 1.73          | 1.73           | ∞  |
| Probe positioner mechanical tolerance                                             | E.6.2   | 0.4         | R              | $\sqrt{3}$  | 1       | 1        | 0.37          | 0.37           | ∞  |
| Probe positioning with respect to phantom shell                                   | E.6.3   | 6.7         | R              | $\sqrt{3}$  | 1       | 1        | 3.87          | 3.87           | ∞  |
| Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation | E.5     | 4           | R              | $\sqrt{3}$  | 1       | 1        | 2.31          | 2.31           | ∞  |
| <b>System check source (dipole)</b>                                               |         |             |                |             |         |          |               |                |    |
| Deviation of experimental dipole from numerical dipole                            | E.6.4   | 5.0         | N              | 1           | 1       | 1        | 5.00          | 5.00           | ∞  |
| Input power and SAR drift measurement                                             | 8,6.6.4 | 5.0         | R              | $\sqrt{3}$  | 1       | 1        | 2.89          | 2.89           | ∞  |
| Dipole axis to liquid distance                                                    | 8,E.6.6 | 2.0         | R              | $\sqrt{3}$  | 1       | 1        | 1.15          | 1.15           | ∞  |
| <b>Phantom and tissue parameters</b>                                              |         |             |                |             |         |          |               |                |    |
| Phantom shell uncertainty—shape, thickness, and permittivity                      | E.3.1   | 6.6         | R              | $\sqrt{3}$  | 1       | 1        | 3.81          | 3.81           | ∞  |
| Uncertainty in SAR correction for deviations in permittivity and conductivity     | E.3.2   | 1.9         | N              | 1           | 1       | 0.84     | 1.90          | 1.60           | ∞  |
| Liquid conductivity measurement                                                   | E.3.3   | 4           | N              | 1           | 0.78    | 0.71     | 3.12          | 2.84           | M  |
| Liquid permittivity measurement                                                   | E.3.3   | 5           | N              | 1           | 0.23    | 0.26     | 1.15          | 1.30           | M  |
| Liquid conductivity—temperature uncertainty                                       | E.3.4   | 2.5         | R              | $\sqrt{3}$  | 0.78    | 0.71     | 1.13          | 1.02           | ∞  |
| Liquid permittivity—temperature uncertainty                                       | E.3.4   | 2.5         | R              | $\sqrt{3}$  | 0.23    | 0.26     | 0.33          | 0.38           | ∞  |
| Combined Standard Uncertainty                                                     |         |             | RSS            |             |         |          | 11.44         | 11.27          |    |
| Expanded Uncertainty (95% Confidence interval)                                    |         |             | K=2            |             |         |          | 22.88         | 22.54          |    |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

## 12. POWER MEASUREMENT

| Frequency (MHz)                    | Channel | ERP (dBm)    |
|------------------------------------|---------|--------------|
| <b>462.5625-462.7125MHz(2W)</b>    |         |              |
| 462.5625                           | 1       | 32.69        |
| 462.6375                           | 4       | 32.77        |
| 462.7125                           | 7       | 32.71        |
| <b>467.5625-467.7125MHz (0.5W)</b> |         |              |
| 467.5625                           | 8       | 26.81        |
| 467.6375                           | 11      | 26.85        |
| 467.7125                           | 14      | 26.73        |
| <b>462.5500-462.7250MHz(2W)</b>    |         |              |
| 462.5500                           | 15      | 32.66        |
| 462.6500                           | 19      | <b>32.78</b> |
| 462.7250                           | 22      | 32.73        |

### Bluetooth\_V4.2

| Modulation     | Channel | Frequency(MHz) | Avg. Burst Power (dBm) |
|----------------|---------|----------------|------------------------|
| <b>BR/EDR</b>  |         |                |                        |
| GFSK           | 0       | 2402           | -1.643                 |
|                | 39      | 2441           | <b>-0.694</b>          |
|                | 78      | 2480           | -0.769                 |
| $\pi/4$ -DQPSK | 0       | 2402           | -1.968                 |
|                | 39      | 2441           | -1.756                 |
|                | 78      | 2480           | -2.403                 |
| 8-DPSK         | 0       | 2402           | -2.003                 |
|                | 39      | 2441           | -1.724                 |
|                | 78      | 2480           | -2.379                 |
| <b>BLE</b>     |         |                |                        |
| GFSK 1M        | 0       | 2402           | 7.197                  |
|                | 19      | 2440           | <b>7.319</b>           |
|                | 39      | 2480           | 6.613                  |

Note 1:

**BR/EDR:** Calculation Value  $=[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f}(\text{GHz})]. = -0.694/5 \cdot \sqrt{2.441} = 0.266 \leq 3.0$

**GFSK 1M:** Calculation Value  $=[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f}(\text{GHz})]. = 7.319/5 \cdot \sqrt{2.440} = 1.685 \leq 3.0$

According to KDB447498 D01 V06, threshold at which no SAR required is  $\leq 3.0$  for 1-g SAR, separation distance is 5mm, and no simultaneous SAR measurement is required.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



## 13. TEST RESULTS

### 13.1. SAR Test Results Summary

#### 13.1.1. Test position and configuration

Face up SAR was performed with the device configured in the positions according to KDB 643646 and Body SAR was performed with the device configured with all accessories close to the Flat Phantom.

#### 13.1.2. Operation Mode

- Set the EUT to maximum output power level and transmit on lower, middle and top channel with 100% duty cycle individually during SAR measurement.
- Per KDB 643646 D01, Passive body-worn and audio accessories generally do not apply to the head SAR of PTT radios. Head SAR is measured with the front surface of the radio positioned at 2.5 cm parallel to a flat phantom.

Per KDB 865664 D01 v01r04, for each frequency band, if the measured SAR is  $\geq 0.8\text{W/kg}$ , testing for repeated SAR measurement is required, that the highest measured SAR is only to be tested. When the SAR results are near the limit, the following procedures are required for each device to verify these types of SAR measurement related variation concerns by repeating the highest measured SAR configuration in each frequency band.


- a. When the original highest measured SAR is  $\geq 0.8\text{W/kg}$ , repeat that measurement once.
  - b. Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $>1.20$  or when the original or repeated measurement is  $\geq 1.45\text{ W/kg}$ .
  - c. Perform a third repeated measurement only if the original, first and second repeated measurement is  $\geq 1.5\text{ W/kg}$  and ratio of largest to smallest SAR for the original, first and second measurement is  $\geq 1.20$ .
- Per KDB 643646 D01, Body SAR is measured with the radio placed in a body-worn accessory, positioned against a flat phantom, representative of the normal operating conditions expected by users and typically with a standard default audio accessory supplied with the radio.

When testing antennas with the default battery: the same test measurement with head part.

- The EUT only contains the Testing antenna, Standard battery and default body-worn accessory specified by customer. The earphone is only for testing



### 13.1.3. Antenna Location: ( back view )



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

### 13.1.4. SAR Test Results Summary

| SAR MEASUREMENT                                                                       |             |                  |                      |                                    |                                   |                          |                          |                   |            |
|---------------------------------------------------------------------------------------|-------------|------------------|----------------------|------------------------------------|-----------------------------------|--------------------------|--------------------------|-------------------|------------|
| Depth of Liquid (cm):>15                                                              |             |                  |                      |                                    | Relative Humidity (%): 54.4       |                          |                          |                   |            |
| Product: BEEBEST Walkie-Talkie LITO                                                   |             |                  |                      |                                    |                                   |                          |                          |                   |            |
| Test Mode: Hold to Face with 2.5 cm separation & body back touch with all accessories |             |                  |                      |                                    |                                   |                          |                          |                   |            |
| Position                                                                              | Freq. (MHz) | Separation (KHz) | Power Drift (±0.2dB) | SAR 1g with 100% duty Cycle (W/kg) | SAR 1g with 50% duty cycle (W/kg) | Max. Tune-up Power (dBm) | Meas. output Power (dBm) | Scaled SAR (W/kg) | Limit W/kg |
| 462.5500-462.7250MHz(2W)                                                              |             |                  |                      |                                    |                                   |                          |                          |                   |            |
| Face Up                                                                               | 462.6500    | 12.5             | 0.03                 | 0.237                              | 0.1185                            | 33.01                    | 32.78                    | 0.126             | 1.6        |
| Back Touch +Belt Clip + headset                                                       | 462.6500    |                  | -0.17                | 1.23                               | 0.615                             | 33.01                    | 32.78                    | 0.674             | 1.6        |
| 467.5625-467.7125MHz (0.5W)                                                           |             |                  |                      |                                    |                                   |                          |                          |                   |            |
| Face Up                                                                               | 467.6375    | 12.5             | -0.11                | 0.201                              | 0.1005                            | 26.99                    | 26.85                    | 0.106             | 1.6        |
| Back Touch +Belt Clip + headset                                                       | 467.6375    |                  | -1.35                | 0.705                              | 0.3525                            | 26.99                    | 26.85                    | 0.497             | 1.6        |

Note:

- During the test, EUT power is 2W&0.5W with 100% duty cycle;
- There is just default battery and antenna in this project;
- $$\text{Max\_Scaled} = \text{SAR\_meas} * 10^{\frac{|\text{Drift}|}{10}} * \frac{P_{\text{max}}}{P_{\text{int}}} * \text{DC}$$

$P_{\text{max}}$  = Maximum Power(W)  
 $P_{\text{int}}$  = Initial Power(W)  
Drift = DASY drift results(dB)  
SAR\_meas=Measured 10-g or 1-g Avg.SAR(W/kg)  
DC = Transmission mode duty cycle in % where applicable 50% duty cycle is applied for PTT operation.  
For conservative results, the following are applied:  
If  $P_{\text{int}} > P_{\text{max}}$ , then  $P_{\text{max}}/P_{\text{int}} = 1$ . Drift = 1 for positive drift

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

## APPENDIX A. SAR SYSTEM CHECK DATA

Test Laboratory: AGC Lab

Test date: Sep. 25, 2023

System Check Head 450MHz

DUT: Dipole 450 MHz Type: D450V3

Communication System: CW; Communication System Band: CW; Duty Cycle: 1:1;

Frequency: 450MHz; Medium parameters used:  $f = 450\text{MHz}$ ;  $\sigma = 0.88 \text{ mho/m}$ ;  $\epsilon_r = 43.20$ ;  $\rho = 1000 \text{ kg/m}^3$ ;

Phantom Type: Elliptical Phantom; Input Power=18dBm

Ambient temperature ( $^{\circ}\text{C}$ ): 20.6, Liquid temperature ( $^{\circ}\text{C}$ ): 20.3

DASY Configuration:

- Probe: ES3DV3-SN:3337; ConvF(7.23, 7.23, 7.23); Calibrated: Sep. 26, 2022;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0$ ,
- Electronics: DAE4 SN1398; Calibrated: May 17, 2023
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1108
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**Configuration/System Check 450MHz Head/Area Scan (8x23x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
Maximum value of SAR (measured) = 0.313 W/kg


**Configuration/System Check 450MHz Head/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 17.242 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 0.419 W/kg

**SAR(1 g) = 0.279 W/kg; SAR(10 g) = 0.188 W/kg**

Maximum value of SAR (measured) = 0.317 W/kg



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: [agc@agccert.com](mailto:agc@agccert.com) Web: <http://www.agccert.com/>

## APPENDIX B. SAR MEASUREMENT DATA

462.5500-462.7250MHz(2W)

Test Laboratory: AGC Lab

Date: Sep. 25, 2023

450 Mid- face up 2.5cm (12.5 KHz)

DUT: BEEBEST Walkie-Talkie LITO; Type: A101OS

Communication System: 450; Communication System Band: D450 (450.0 MHz); Duty Cycle: 1:1;  
Frequency: 462.6500 MHz; Medium parameters used:  $f = 450\text{MHz}$ ;  $\sigma = 0.91\text{ mho/m}$ ;  $\epsilon_r = 42.31$ ;  $\rho = 1000\text{ kg/m}^3$  ;  
Phantom Type: Elliptical Phantom  
Ambient temperature ( $^{\circ}\text{C}$ ): 20.6, Liquid temperature ( $^{\circ}\text{C}$ ): 20.3

DASY Configuration:

- Probe: ES3DV3-SN:3337; ConvF(7.23, 7.23, 7.23); Calibrated: Sep. 26, 2022;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0$ ,
- Electronics: DAE4 SN1398; Calibrated: May 17, 2023
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1108
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**HOLD TO FACE/A-12.5K-FACE UP-25MM/Area Scan (7x17x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.263 W/kg


**HOLD TO FACE/A-12.5K-FACE UP-25MM/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 15.060 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.306 W/kg

**SAR(1 g) = 0.237 W/kg; SAR(10 g) = 0.177 W/kg**

Maximum value of SAR (measured) = 0.262 W/kg



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: [agc@agccert.com](mailto:agc@agccert.com) Web: <http://www.agccert.com/>

**Test Laboratory: AGC Lab**  
**450 Mid -Body-Back with all accessories 0mm (12.5 KHz)**  
**DUT: BEEBEST Walkie-Talkie LITO; Type: A1010S**

**Date: Sep. 25, 2023**

Communication System: 450; Communication System Band: D450 (450.0 MHz); Duty Cycle: 1:1;  
Frequency: 462.6500 MHz; Medium parameters used:  $f = 450$  MHz;  $\sigma = 0.91$  mho/m;  $\epsilon_r = 42.31$ ;  $\rho = 1000$  kg/m;  
Phantom Type: Elliptical Phantom  
Ambient temperature ( $^{\circ}\text{C}$ ): 20.6, Liquid temperature ( $^{\circ}\text{C}$ ): 20.3

DASY Configuration:

- Probe: ES3DV3-SN:3337; ConvF(7.23, 7.23, 7.23); Calibrated: Sep. 26, 2022;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0$ ,
- Electronics: DAE4 SN1398; Calibrated: May 17, 2023
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1108
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**BODY/A-12.5K-BACK+CLIP/Area Scan (7x17x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 1.39 W/kg


**BODY/A-12.5K-BACK+CLIP/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 36.179 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 1.62 W/kg

**SAR(1 g) = 1.23 W/kg; SAR(10 g) = 0.910 W/kg**

Maximum value of SAR (measured) = 1.37 W/kg




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: [agc@agccert.com](mailto:agc@agccert.com) Web: <http://www.agccert.com/>



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



**462.5500-462.7250MHz(2W)**

**Test Laboratory: AGC Lab**

**Date: Sep. 25, 2023**

**450 Mid- face up 2.5cm (12.5 KHz)**

**DUT: BEEBEST Walkie-Talkie LITO; Type: A101OS**

Communication System: 450; Communication System Band: D450 (450.0 MHz); Duty Cycle: 1:1;  
Frequency: 467.6375 MHz; Medium parameters used:  $f = 450\text{MHz}$ ;  $\sigma = 0.93\text{ mho/m}$ ;  $\epsilon_r = 41.26$ ;  $\rho = 1000\text{ kg/m}^3$  ;  
Phantom Type: Elliptical Phantom  
Ambient temperature ( $^{\circ}\text{C}$ ): 20.6, Liquid temperature ( $^{\circ}\text{C}$ ): 20.3

DASY Configuration:

- Probe: ES3DV3-SN:3337; ConvF(7.23, 7.23, 7.23); Calibrated: Sep. 26, 2022;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0$ ,
- Electronics: DAE4 SN1398; Calibrated: May 17, 2023
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1108
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**HOLD TO FACE /A-12.5K-FACE UP-25MM/Area Scan (7x17x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.226 W/kg


**HOLD TO FACE/A-12.5K-FACE UP-25MM/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 14.118 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.258 W/kg

**SAR(1 g) = 0.201 W/kg; SAR(10 g) = 0.152 W/kg**

Maximum value of SAR (measured) = 0.223 W/kg



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: [agc@agccert.com](mailto:agc@agccert.com) Web: <http://www.agccert.com/>

**Test Laboratory: AGC Lab**  
**450 Mid -Body-Back with all accessories 0mm (12.5 KHz)**  
**DUT: BEEBEST Walkie-Talkie LITO; Type: A1010S**

**Date: Sep. 25, 2023**

Communication System: 450; Communication System Band: D450 (450.0 MHz); Duty Cycle: 1:1;  
Frequency: 467.6375 MHz; Medium parameters used:  $f = 450$  MHz;  $\sigma = 0.93$  mho/m;  $\epsilon_r = 41.26$ ;  $\rho = 1000$  kg/m;  
Phantom Type: Elliptical Phantom  
Ambient temperature ( $^{\circ}\text{C}$ ): 20.6, Liquid temperature ( $^{\circ}\text{C}$ ): 20.3

DASY Configuration:

- Probe: ES3DV3-SN:3337; ConvF(7.23, 7.23, 7.23); Calibrated: Sep. 26, 2022;
- Sensor-Surface: 3mm (Mechanical Surface Detection),  $z = 1.0$ ,
- Electronics: DAE4 SN1398; Calibrated: May 17, 2023
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1108
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

**BODY/A-12.5K-BACK+CLIP/Area Scan (7x17x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 1.02 W/kg


**BODY/A-12.5K-BACK+CLIP/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 31.390 V/m; Power Drift = -1.35 dB

Peak SAR (extrapolated) = 0.915 W/kg


**SAR(1 g) = 0.705 W/kg; SAR(10 g) = 0.527 W/kg**

Maximum value of SAR (measured) = 0.778 W/kg



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: [agc@agccert.com](mailto:agc@agccert.com) Web: <http://www.agccert.com/>




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

**APPENDIX C. TEST SETUP PHOTOGRAPHS**

Face Up with 2.5 cm Separation Distance.



Body Back Touch with all accessories



The thickness of EUT is 1.4 cm

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std &amp; Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: [agc@agccert.com](mailto:agc@agccert.com) Web: <http://www.agccert.com/>



Note : The headset is just for testing. This tested and electrically similar headsets may be used.


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: [agc@agccert.com](mailto:agc@agccert.com) Web: <http://www.agccert.com/>



### DEPTH OF THE LIQUID IN THE PHANTOM—ZOOM IN

Note: The position used in the measurement was according to IEEE 1528-2013



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd  
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd  
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>



## APPENDIX D. CALIBRATION DATA

Refer to Attached files.

-----END OF REPORT-----

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: [agc@agccert.com](mailto:agc@agccert.com) Web: <http://www.agccert.com/>



## Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the “Company”) solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the “Clients”).
2. Any report issued by Company as a result of this application for testing services (the “Report”) shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: [agc@agccert.com](mailto:agc@agccert.com) Web: <http://www.agccert.com/>