

Test Report

Product: Smart watch

Trade Mark: Wavefun

Model Number: Wave 70

FCC ID: 2BCYV-WAVE

Prepared for

Shenzhen Whale Wave Technology Co., Ltd
A8-103 Yuanchuangyuan 6th, Xintang Village 8th, Jutang Community,
Fucheng Street, Longhua District, Shenzhen, Guangdong, China

Prepared by

Shenzhen HongBiao Certification& Testing Co., Ltd
Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan
Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen,
China
Tel.: +86-755-2998 9321 Fax.: +86-755-2998 5110
Website: <http://www.sz-hongbiao.com>

Table of Contents

1	GENERAL DESCRIPTION	6
1.1	DESCRIPTION OF EUT.....	6
1.2	TEST MODE.....	6
1.3	OPERATION CHANNEL LIST.....	6
1.4	TEST SETUP	7
1.5	ANCILLARY EQUIPMENT	7
1.6	SUMMARY OF TEST RESULT	8
2	TEST FACILITIES AND ACCREDITATIONS	9
2.1	TEST LABORATORY	9
2.2	ENVIRONMENTAL CONDITIONS	9
2.3	MEASUREMENT UNCERTAINTY	9
2.4	TEST SOFTWARE	9
3	LIST OF TEST EQUIPMENT	10
4	TEST ITEM AND RESULTS	12
4.1	ANTENNA REQUIREMENT	12
4.1.1	<i>Standard Requirement</i>	12
4.1.2	<i>Test Result</i>	12
4.2	CONDUCTED EMISSION.....	13
4.2.1	<i>Limits</i>	13
4.2.2	<i>Test Procedures</i>	13
4.2.3	<i>Test Setup</i>	14
4.2.4	<i>Test Result</i>	14
4.3	RADIATED EMISSION	17
4.3.1	<i>Limits</i>	17
4.3.2	<i>Test Procedures</i>	17
4.3.3	<i>Test Setup</i>	17
4.3.4	<i>Test Result</i>	18
4.3.5	<i>Band Edge - Radiated</i>	23
4.4	PEAK OUTPUT POWER.....	24
4.4.1	<i>Limit</i>	24
4.4.2	<i>Test Procedure</i>	24
4.4.3	<i>Test Setup</i>	24
4.4.4	<i>Test Results</i>	24
4.5	POWER SPECTRAL DENSITY.....	25
4.5.1	<i>Limit</i>	25
4.5.2	<i>Test Procedure</i>	25
4.5.3	<i>Test Setup</i>	25
4.5.4	<i>Test Results</i>	25
4.6	6dB BANDWIDTH	27
4.6.1	<i>Limit</i>	27
4.6.2	<i>Test Procedure</i>	27
4.6.3	<i>Test Setup</i>	27
4.6.4	<i>Test Results</i>	27
4.7	DUTY CYCLE	29
4.7.1	<i>Limit</i>	29
4.7.2	<i>Test Procedure</i>	29
4.7.3	<i>Test Setup</i>	29
4.7.4	<i>Test Results</i>	29
4.8	CONDUCTED BAND EDGE.....	31
4.8.1	<i>Limit</i>	31
4.8.2	<i>Test Procedure</i>	31

4.8.3	Test Setup	31
4.8.4	Test Results	31
4.9	SPURIOUS RF CONDUCTED EMISSIONS	33
4.9.1	Limit	33
4.9.2	Measuring Instruments	33
4.9.3	Test Procedure	33
4.9.4	Test Setup	33
4.9.5	Test Results	33
5	PHOTOGRAPHS OF THE TEST SETUP	35
6	PHOTOGRAPHS OF THE EUT	36

TEST RESULT CERTIFICATION

Applicant's Name..... : Shenzhen Whale Wave Technology Co., Ltd
A8-103 Yuanchuangyuan 6th, Xintang Village 8th, Jutang
Address : Community, Fucheng Street, Longhua District, Shenzhen,
Guangdong, China
Manufacturer's Name : Shenzhen Whale Wave Technology Co., Ltd
A8-103 Yuanchuangyuan 6th, Xintang Village 8th, Jutang
Address : Community, Fucheng Street, Longhua District, Shenzhen,
Guangdong, China

Product description

Product name : Smart watch
Model Number : Wave 70
Standards : FCC Part 15.247
Test procedure..... : IEEE/ANSI C63.10-2020

This device described above has been tested by Shenzhen HongBiao Certification& Testing Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the EMC requirements. And it is applicable only to the tested sample identified in the report.

Date of Test


Date (s) of performance of tests: September 12, 2023 ~ September 22, 2023
Test Result.....: **Pass**

Testing Engineer :




(Z o e S u)

Technical Manager :



(G a r y L u)

Authorized Signatory :



(L e o S u)

[illegible]

1 General Description

1.1 Description of EUT

Product name:	Smart watch
Model name:	Wave 70
Series Model:	Wavefun Wave 20, Wavefun Wave 30, Wavefun Wave 40, Wavefun Wave 50, Wavefun Wave 60, Wavefun Wave 80, Wavefun Wave 90, Wavefun Wave 100, Wavefun Wave 200, Wavefun Wave 300, Wavefun Play 20, Wavefun Play 30, Wavefun Play 40, Wavefun Play 50, Wavefun Play 60, Wavefun Play 70, Wavefun Play 80, Wavefun Play 90, Wavefun Play 100, Wavefun Play 200, Wavefun Play 300
Different of series model:	The color of appearance and model name of series models listed are different from the main model, but the circuit and the electronic construction are the same, declared by the manufacturer.
Operation frequency:	2402-2480MHz
Modulation type:	GFSK
Bit Rate of transmitter:	1 Mbps
Antenna type:	Internal Antenna
Antenna gain:	-6.08dBi
Max. output power:	5.41dBm
Hardware version:	2.1.1
Software version:	3.1.1
Battery:	DC 3.8V/410mAh
Power supply:	DC 3.8V by battery, USB 5V charging
Adapter information:	N/A

1.2 Test Mode

Test Mode	Channel	Frequency (MHz)
1	00	2402
2	19	2440
3	39	2480

1.3 Operation Channel list

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

1.4 Test Setup

See photographs of the test setup in the report for the actual setup and connections between EUT and support equipment.

1.5 Ancillary Equipment

Equipment	Model	S/N	Manufacturer
Adapter	HW-100225C00	/	Huawei

Equipment	Length (cm)	Shielded/Unshielded	With/Without Ferrite

1.6 Summary of Test Result

No.	Standard Section	Test Item	Result	Remark
1	15.203	Antenna Requirement	Pass	
2	15.247 (b)	Peak Output Power	Pass	
3	15.207	Conducted Emission	Pass	
4	15.247 (d) & 15.209	Radiated Spurious Emission	Pass	
5	15.247 (e)	Power Spectral Density	Pass	
6	15.247 (a)(2)	6dB Bandwidth	Pass	
7	558074 D01 15.247 Meas Guidance v05r02 Chapter 6	Duty Cycle	Pass	
8	15.205	Band Edge Emission	Pass	
9	15.247(d)	Spurious RF Conducted Emissions	Pass	

2 Test Facilities and Accreditations

2.1 Test Laboratory

Test Site	Shenzhen HongBiao Certification& Testing Co., Ltd
Test Site Location	Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen, China
Telephone:	(86-755) 2998 9321
Fax:	(86-755) 2998 5110
FCC Registration No.:	CN1341
A2LA Certificate No.:	6765.01

2.2 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C~35°C
Relative Humidity:	20%~75%
Air Pressure:	98kPa~101kPa

2.3 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Measurement Frequency Range	U, (dB)	Note
RF frequency	2×10^{-5}	
RF power, conducted	± 0.57 dB	
Conducted emission(150kHz~30MHz)	± 2.5 dB	
Radiated emission(30MHz~1GHz)	± 4.2 dB	
Radiated emission (above 1GHz)	± 4.7 dB	
Temperature	± 1 degree	
Humidity	± 5 %	

2.4 Test Software

Software name	Manufacturer	Model	Version
EMI Measurement	Farad	EZ-EMC	V1.1.4.2
Conducted test system	MWRF-test	MTS 8310	V2.0.0

3 List of Test Equipment

Radiation emission							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E001	Horn Antenna	Schwarzbeck	BBHA 9120D	02592	2022-04-02	2024-04-01
2	HB-E002	Biconical log-periodic composite antenna	Schwarzbeck	VULB 9168	01340	2022-04-06	2024-04-05
3	HB-E003	SHF-EHF Horn	Schwarzbeck	BBHA 91270	01193	2022-04-02	2024-04-01
4	HB-E004	Preamplifier	Noyetec	LAN-0910	NYCM1420101	2023-05-11	2024-05-10
5	HB-E005	Preamplifier	Noyetec	LAN-0118	NYCM1420102	2023-05-12	2024-05-11
6	HB-E006	Preamplifier	Noyetec	LAN-1840	NYCM1420103	2023-06-11	2024-06-10
7	HB-E007	EMI TEST RECEIVER	R&S	ESR7	102520	2023-05-12	2024-05-11
8	HB-E009	POSITINAL COTROLLE R	Noyetec	N/A	N/A	/	/
9	HB-E013	RF switch	Noyetec	NY-RF4	NY0CM1420204	/	/
10	HB-E066	Illuminance Tester	TASI	TA8121	N/A	2023-05-11	2024-05-10
11	HB-E075	Active loop antenna	Schwarzbeck	FMZB 1519B	1519B-245	2022-07-24	2024-07-23
Conduction emission							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E014	4 Path V-LISN	Schwarzbeck	NNLK 8121	00770	2023-05-12	2024-05-11
2	HB-E015	Pulse Limiter	Schwarzbeck	VTSD 9561-F	00949	2023-05-12	2024-05-11
3	HB-E016	ZN23201	Noyetec	ZN23201	N/A	2023-05-11	2024-05-10
4	HB-E059	Attenuator	Xianghua	TS2-6-1	220215166	2023-05-12	2024-05-11
5	HB-E069	EMI TEST RECEIVER	R&S	ESCI	N/A	2023-05-12	2024-05-11
RF							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E041	MXG AnaioG Signal Generator	Agilent	N5181A	MY47070421	2023-05-11	2024-05-10
2	HB-E042	WIDEBAND RADIO COMMUNICA	R&S	CMW500	132108	2023-05-11	2024-05-10

		TION TESTER					
3	HB-E043	MXG Anaio Signal Generator	Agilent	N5182A	US46240335	2023-05-11	2024-05-10
4	HB-E044	Signal& spectrum Analyzer	R&S	FSV3044	101264	2023-05-11	2024-05-10
5	HB-E045	RF Control Box	Noyetec	NY100-R FCB	N/A	/	/
6	HB-E058	Thermometer Clock Humidity Monitor	N/A	HTC-1	N/A	/	/
7	HB-E077	PXA Signal Analyzer	Agilent	N9030A	N/A	2023-05-11	2024-05-10

Note: the calibration interval of the above test instruments is 12&24 months and the calibrations are traceable to international system unit (SI).

4 Test Item And Results

4.1 Antenna Requirement

4.1.1 Standard Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device

4.1.2 Test Result

The EUT antenna is Internal Antenna. It comply with the standard requirement. In case of replacement of broken antenna the same antenna type must be used.

4.2 Conducted Emission

4.2.1 Limits

Limits – Class B		
Frequency (MHz)	Limit (dBμV)	
	Quasi-Peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50

Note:

- the tighter limit applies at the band edges.
- the limit of "*" marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

4.2.2 Test Procedures

a) EUT Operating Conditions


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b) The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item – photographs of the test setup.

4.2.3 Test Setup



4.2.4 Test Result

EUT:	Smart watch	Model Name:	Wave 70
Test Mode:	Working	Phase :	L
Test Voltage:	AC 120V/60Hz		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1815	32.38	9.02	41.40	64.42	-23.02	QP	P	
2	0.1815	15.88	9.02	24.90	54.42	-29.52	AVG	P	
3	0.3704	27.34	9.85	37.19	58.49	-21.30	QP	P	
4	0.3704	14.79	9.85	24.64	48.49	-23.85	AVG	P	
5 *	0.6134	32.23	9.94	42.17	56.00	-13.83	QP	P	
6	0.6134	16.54	9.94	26.48	46.00	-19.52	AVG	P	
7	1.2750	26.42	10.03	36.45	56.00	-19.55	QP	P	
8	1.2750	12.27	10.03	22.30	46.00	-23.70	AVG	P	
9	1.9320	25.18	10.05	35.23	56.00	-20.77	QP	P	
10	1.9320	10.20	10.05	20.25	46.00	-25.75	AVG	P	
11	6.4365	22.62	10.25	32.87	60.00	-27.13	QP	P	
12	6.4365	7.82	10.25	18.07	50.00	-31.93	AVG	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. All test modes were pre-tested, but we only recorded the worst case in this report.

EUT:	Smart watch	Model Name:	Wave 70
Test Mode:	Working	Phase :	N
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1874	31.70	9.41	41.11	64.15	-23.04	QP	P	
2	0.1874	16.30	9.41	25.71	54.15	-28.44	AVG	P	
3	0.2265	29.65	9.63	39.28	62.58	-23.30	QP	P	
4	0.2265	15.01	9.63	24.64	52.58	-27.94	AVG	P	
5 *	0.6134	29.90	9.70	39.60	56.00	-16.40	QP	P	
6	0.6134	13.68	9.70	23.38	46.00	-22.62	AVG	P	
7	1.0455	24.27	9.75	34.02	56.00	-21.98	QP	P	
8	1.0455	9.93	9.75	19.68	46.00	-26.32	AVG	P	
9	1.8015	22.25	10.04	32.29	56.00	-23.71	QP	P	
10	1.8015	9.03	10.04	19.07	46.00	-26.93	AVG	P	
11	5.0100	17.24	10.22	27.46	60.00	-32.54	QP	P	
12	5.0100	2.40	10.22	12.62	50.00	-37.38	AVG	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. All test modes were pre-tested, but we only recorded the worst case in this report.

4.3 Radiated Emission

4.3.1 Limits

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.3.2 Test Procedures


- The radiated emission tests were performed in the 3 meters.
- The EUT was placed on the top of a rotating table 0.8 meters above the ground. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the test antenna shall vary between 1m to 4m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- If the peak mode measured value compliance with and lower than quasi peak mode limit, the EUT shall be deemed to meet QP limits and then no additional QP mode measurement performed.
- If the peak mode measured value compliance with and lower than average mode limit, the EUT shall be deemed to meet average limits and then no additional average mode measurement performed.
- For the actual test configuration, please refer to the related item – EUT test photos.

4.3.3 Test Setup


Radiated Emission Test-Up Frequency Below 30MHz



Radiated Emission Test-Up Frequency 30MHz~1GHz



Radiated emission test-up frequency above 1GHz



4.3.4 Test Result

Below 30MHz

EUT:	Smart watch	Model Name:	Wave 70
Pressure:	1010 hPa	Test Voltage:	DC 3.8V from battery
Test Mode:	Working	Polarization:	--


Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	Pass
--	--	--	--	Pass

Note:

1. For 9kHz-30MHz, the amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);
3. Limit line = specific limits (dBuV) + distance extrapolation factor.

Frequency range (30MHz – 1GHz)

EUT:	Smart watch	Model Name:	Wave 70
Test Mode:	Working	Phase :	Vertical
Test Voltage:	DC 3.8V from battery		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	47.4917	25.85	-9.08	16.77	40.00	-23.23	QP	100	125	P	
2	62.4313	26.60	-10.17	16.43	40.00	-23.57	QP	100	352	P	
3	95.7622	26.95	-12.99	13.96	43.50	-29.54	QP	100	216	P	
4	148.4410	25.39	-8.83	16.56	43.50	-26.94	QP	100	238	P	
5	339.5887	28.23	-7.80	20.43	46.00	-25.57	QP	100	232	P	
6 *	665.8034	26.14	-0.11	26.03	46.00	-19.97	QP	100	314	P	

Remarks:

1. Measurement Level = Reading level + Correct Factor, Margin = Measurement Level – Limit.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. All test modes were pre-tested, but we only recorded the worst case in this report.

EUT:	Smart watch	Model Name:	Wave 70
Test Mode:	Working	Phase :	Horizontal
Test Voltage:	DC 3.8V from battery		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	34.5172	27.35	-8.92	18.43	40.00	-21.57	QP	100	360	P	
2	49.7066	26.72	-8.78	17.94	40.00	-22.06	QP	100	46	P	
3	160.3455	26.93	-9.06	17.87	43.50	-25.63	QP	100	154	P	
4	277.0935	26.98	-8.96	18.02	46.00	-27.98	QP	100	315	P	
5	515.4373	26.96	-3.29	23.67	46.00	-22.33	QP	100	217	P	
6 *	687.1506	26.01	0.39	26.40	46.00	-19.60	QP	100	240	P	

Remarks:

1. Mesurement Level = Reading level + Correct Factor, Margin = Mesurement Level – Limit.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. All test modes were pre-tested, but we only recorded the worst case in this report.

Frequency range (1GHz-25GHz)

Frequency	Read Level	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
Low Channel (2402 MHz) --Above 1G									
4804	65.99	5.21	35.59	44.30	62.49	74.00	-11.51	Pk	Vertical
4804	50.52	5.21	35.59	44.30	47.02	54.00	-6.98	AV	Vertical
7206	59.37	6.48	36.27	44.60	57.52	74.00	-16.48	Pk	Vertical
7206	44.92	6.48	36.27	44.60	43.07	54.00	-10.93	AV	Vertical
4804	67.21	5.21	35.55	44.30	63.67	74.00	-10.33	Pk	Horizontal
4804	52.10	5.21	35.55	44.30	48.56	54.00	-5.44	AV	Horizontal
7206	58.63	6.48	36.27	44.52	56.86	74.00	-17.14	Pk	Horizontal
7206	44.66	6.48	36.27	44.52	42.89	54.00	-11.11	AV	Horizontal
Middle Channel (2440 MHz) --Above 1G									
4880	66.93	5.21	35.66	44.20	63.60	74.00	-10.40	Pk	Vertical
4880	51.49	5.21	35.66	44.20	48.16	54.00	-5.84	AV	Vertical
7320	58.83	7.10	36.50	44.43	58.00	74.00	-16.00	Pk	Vertical
7320	45.40	7.10	36.50	44.43	44.57	54.00	-9.43	AV	Vertical
4880	64.90	5.21	35.66	44.20	61.57	74.00	-12.43	Pk	Horizontal
4880	51.45	5.21	35.66	44.20	48.12	54.00	-5.88	AV	Horizontal
7320	59.57	7.10	36.50	44.43	58.74	74.00	-15.26	Pk	Horizontal
7320	43.86	7.10	36.50	44.43	43.03	54.00	-10.97	AV	Horizontal
High Channel (2480 MHz) --Above 1G									
4960	64.30	5.21	35.52	44.21	60.82	74.00	-13.18	Pk	Vertical
4960	49.12	5.21	35.52	44.21	45.64	54.00	-8.36	AV	Vertical
7440	59.07	7.10	36.53	44.60	58.10	74.00	-15.90	Pk	Vertical
7440	45.11	7.10	36.53	44.60	44.14	54.00	-9.86	AV	Vertical
4960	66.73	5.21	35.52	44.21	63.25	74.00	-10.75	Pk	Horizontal
4960	49.90	5.21	35.52	44.21	46.42	54.00	-7.58	AV	Horizontal
7440	59.81	7.10	36.53	44.60	58.84	74.00	-15.16	Pk	Horizontal
7440	44.29	7.10	36.53	44.60	43.32	54.00	-10.68	AV	Horizontal

Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
 (2) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor
 (3) All other emissions more than 20dB below the limit.

4.3.5 Band Edge - Radiated

Frequency	Meter Reading	Cable Loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
GFSK									
2310.00	57.03	2.40	27.70	40.40	46.73	74.00	-27.27	Pk	Horizontal
2310.00	42.38	2.40	27.70	40.40	32.08	54.00	-21.92	AV	Horizontal
2310.00	57.55	2.40	27.70	40.40	47.25	74.00	-26.75	Pk	Vertical
2310.00	42.94	2.40	27.70	40.40	32.64	54.00	-21.36	AV	Vertical
2390.00	58.11	2.44	28.30	40.10	48.75	74.00	-25.25	Pk	Vertical
2390.00	41.55	2.44	28.30	40.10	32.19	54.00	-21.81	AV	Vertical
2390.00	57.50	2.44	28.30	40.10	48.14	74.00	-25.86	Pk	Horizontal
2390.00	42.60	2.44	28.30	40.10	33.24	54.00	-20.76	AV	Horizontal
2483.50	59.83	2.48	28.70	39.80	51.21	74.00	-22.79	Pk	Vertical
2483.50	43.39	2.48	28.70	39.80	34.77	54.00	-19.23	AV	Vertical
2483.50	58.14	2.48	28.70	39.80	49.52	74.00	-24.48	Pk	Horizontal
2483.50	42.93	2.48	28.70	39.80	34.31	54.00	-19.69	AV	Horizontal

4.4 Peak Output Power


4.4.1 Limit

FCC Part15 Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(b)(3)	Peak output power	1 watt or 30dBm	2400-2483.5

4.4.2 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
 RBW=1MHz, VBW=3MHz, Detector=Peak (If 20dB BW ≤1 MHz)
 RBW=3MHz, VBW=8MHz, Detector=Peak (If 20dB BW > 1 MHz)
- (3) The EUT was set to continuously transmitting in the max power during the test.

4.4.3 Test Setup



4.4.4 Test Results

EUT:	Smart watch	Model Name:	Wave 70
Test Mode:	TX Mode /CH00, CH19, CH39	Test Voltage:	DC 3.8V from battery

GFSK

Test Channel	Frequency (MHz)	Maximum Peak Output Power(dBm)	Limit (dBm)
CH00	2402	5.32	30
CH19	2440	4.83	30
CH39	2480	5.41	30

4.5 Power Spectral Density


4.5.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247	Power Spectral Density	8 dBm (in any 3kHz)	2400-2483.5

4.5.2 Test Procedure

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW ≥ 3 kHz.
4. Set the VBW $\geq 3 \times$ RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


4.5.3 Test Setup



4.5.4 Test Results

EUT:	Smart watch	Model Name:	Wave 70
Pressure:	1015 hPa	Test Voltage:	DC 3.8V from battery
Test Mode:	TX Mode /CH00, CH19, CH39		

Frequency	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2402 MHz	-10.24	8	PASS
2440 MHz	-10.2	8	PASS
2480 MHz	-10.96	8	PASS



4.6 6dB Bandwidth


4.6.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(a)(2)	Bandwidth	$\geq 500\text{kHz}$ (6dB bandwidth)	2400-2483.5

4.6.2 Test Procedure

1. Set RBW= 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.6.3 Test Setup




4.6.4 Test Results

EUT:	Smart watch	Model Name:	Wave 70
Pressure:	1012 hPa	Test Voltage:	DC 3.8V from battery
Test Mode:	TX Mode /CH00, CH19, CH39		

Channel	Frequency (MHz)	6dB bandwidth (kHz)	99% bandwidth (MHz)	6dB bandwidth Limit (kHz)	Result
Low	2402	652.1	1.0313	500	Pass
Middle	2440	641.1	1.0408	500	Pass
High	2480	650.3	1.0391	500	Pass

Test plots



4.7 Duty Cycle

4.7.1 Limit

No limit requirement.

4.7.2 Test Procedure

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value. Set $VBW \geq RBW$. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

The transmitter output is connected to the Spectrum Analyzer. We tested according to the zero-span measurement method, 6.0(b) in KDB 558074 D01 DTS Meas Guidance v05r02.

The largest available value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = Zero Span

RBW = 8MHz (the largest available value)

VBW = 8MHz ($\geq$ RBW)

Number of points in Sweep >100


Detector function = peak

Trace = Clear write

Measure Total and Ton

Calculate Duty Cycle = $Ton / Total$


4.7.3 Test Setup




4.7.4 Test Results

EUT:	Smart watch	Model Name:	Wave 70
Pressure:	1012 hPa	Test Voltage:	DC 3.8V from battery
Test Mode:	TX Mode /CH00, CH19, CH39		


GFSK on Channel 00



GFSK on Channel 19



GFSK on Channel 39



4.8 Conducted Band Edge


4.8.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

4.8.2 Test Procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- Repeat above procedures until all measured frequencies were complete.


4.8.3 Test Setup




4.8.4 Test Results

EUT:	Smart watch	Model Name:	Wave 70
Pressure:	1012 hPa	Test Voltage:	DC 3.8V from battery
Test Mode:	TX Mode /CH00, CH39		

BLE: Band Edge, Left Side



BLE: Band Edge, Right Side



4.9 Spurious RF Conducted Emissions

4.9.1 Limit

Below -20dB of the highest emission level in operating band.


4.9.2 Measuring Instruments

The Measuring equipment is listed in the section 4 of this test report.

4.9.3 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW=300kHz to measure the peak field strength, and measure frequency range from 9kHz to 26.5GHz.

4.9.4 Test Setup




4.9.5 Test Results


Note:

- 1: The measurement frequency range is from 9kHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and band edge measurement data.
- 2: The worst mode is GFSK mode, and the report only show the worst mode data.


GFSK on Channel 00




GFSK on Channel 00




GFSK on Channel 19




GFSK on Channel 19



GFSK on Channel 39



GFSK on Channel 39



5 Photographs of the Test Setup

Reference to the appendix Test Setup Photos for details.

6 Photographs of the EUT

Reference to the appendix External Photos and Internal Photos for details.

******* END OF REPORT *******