

FCC RF Exposure

EUT Description:TPMS

ModelNo.:BY-PTCP

Series Model:N/A

FCC ID: 2BD2D-DXTY1N

Equipment type: Mobile equipment

1. Limits

Test procedures according to the technical standards: KDB 447498 D01 V06 and FCC 2.1091.

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposures | | | | |
| 0.3–3.0 | 614 | 1.63 | *(100) | 6 |
| 3.0–30 | 1842/f | 4.89/f | *(900/f ²) | 6 |
| 30–300 | 61.4 | 0.163 | 1.0 | 6 |
| 300–1500 | | | f/300 | 6 |
| 1500–100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3–1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34–30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30–300 | 27.5 | 0.073 | 0.2 | 30 |
| 300–1500 | | | f/1500 | 30 |
| 1500–100,000 | | | 1.0 | 30 |

F = frequency in MHz

Formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where :

P_d = power density in mW/cm^2 ,

P_{out} = output power to antenna in mW ;

G = gain of antenna in linear scale,

$\pi = 3.14$;

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm^2 . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Test Result of RF Exposure Evaluation

$$\text{EIRP} = \text{EMeas} + 20 \log(\text{dmeas}) - 104.7$$

EIRP is the equivalent isotropically radiated power,

EMeas in dBm is the field strength of the emission at the measurement distance, in dB u V/m

dmeas is the measurement distance, in m

433.92MHz

| Modulation | Channel Freq. (MHz) | Field strength(dBuV/m) | EIRP(dB m) | Max tune-up(m W) | Antenna Gain (dBi) | Antenna gain numeric | Evaluation result (mW/cm ²) | Power density Limits (mW/cm ²) |
|------------|---------------------|------------------------|------------|------------------|--------------------|----------------------|---|--|
| ASK | 433.92 | 58.87 | -36.33 | 0.0002 | 0.8 | 1.20 | 0.00000047 | 0.28928 |

Conclusion: the max result : $0.00000047 \leq 0.28928$ compliance with FCC's RF Exposure.