

Tire pressure sensor user manual

No: BOYOTY

Statement: There is a button battery in the sensor. The sensor send the signal by radio signal, pls make sure the sensor is suit for your car. The sensor works in the 315MHz

Pls make sure your replaced sensor OE No. is one of them:1472547/1472547G/1490701-01-C/1490701-01-B/1490700-00-B. If not, pls contact your seller to confirm the OE No.

1.For tire pressure sensor installation, we recommend user to go to tire repair shop or other experienced shop to change the sensor.

2.After changing, mandatory requirement that the tire pressure should be set at the required value like 280KPa .

Drive for 10min, tire pressure alarm lamp will disappear. If not, pls contact with your seller for help.

FCC Warning Statement

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- - Reorient or relocate the receiving antenna.
- - Increase the separation between the equipment and receiver.
- - Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- - Consult the dealer or an experienced radio/TV technician for help.

*RF warning for Mobile device:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.