



Shenzhen CTL Testing Technology Co., Ltd.
Tel: +86-755-89486194 E-mail: ctl@ctl-lab.com

TEST REPORT

47 CFR Part 15, Subpart C 15.247

Report Reference No.: **CTL2411257011-WF03**

Compiled by:
(position+printed name+signature)

Happy Guo
(File administrators)

Tested by:
(position+printed name+signature)

Jack Wang
(Test Engineer)

Approved by:
(position+printed name+signature)

Ivan Xie
(Manager)



Product Name: CORDLESS ROBOTIC POOL CLEANER

Model/Type reference: PRT1P

List Model(s): N/A

Trade Mark: Aiper

FCC ID: 2BD5N-SCUBAX1PRO

Applicant's name: Shenzhen Aiper Intelligent Co.,Ltd.

Address of applicant: 32nd floor, Block C, Phase 2 Galaxy World, Minle community, Minzhi street, Longhua district, Shenzhen, China

Test Firm: Shenzhen CTL Testing Technology Co., Ltd.

Address of Test Firm: Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China 518055

Test specification:

Standard: 47 CFR Part 15, Subpart C 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz.

TRF Originator: Shenzhen CTL Testing Technology Co., Ltd.

Master TRF: Dated 2011-01

Date of receipt of test item: Dec. 19, 2024

Date of Test Date: Dec. 19, 2024-Jan. 18, 2025

Date of Issue: Jan. 21, 2025

Result: **Pass**

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

TEST REPORT

Test Report No. :	CTL2411257011-WF03	Jan. 21, 2025
Date of issue		

Equipment under Test : CORDLESS ROBOTIC POOL CLEANER

Sample No : CTL2411257011

Model /Type : PRT1P

Listed Models : N/A

Applicant : **Shenzhen Aiper Intelligent Co.,Ltd.**

Address : 32nd floor, Block C, Phase 2 Galaxy World, Minle community, Minzhi street, Longhua district, Shenzhen, China

Manufacturer : **Shenzhen Aiper Intelligent Co.,Ltd.**

Address : 32nd floor, Block C, Phase 2 Galaxy World, Minle community, Minzhi street, Longhua district, Shenzhen, China

Test result	Pass *
--------------------	---------------

* In the configuration tested, the EUT complied with the standards specified page 5.

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.

** Modified History **

	Table of Contents	Page
1. SUMMARY		5
1.1. TEST STANDARDS		5
1.2. TEST DESCRIPTION		5
1.3. TEST FACILITY		6
1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY		6
2. GENERAL INFORMATION		8
2.1. ENVIRONMENTAL CONDITIONS		8
2.2. GENERAL DESCRIPTION OF EUT		8
2.3. DESCRIPTION OF TEST MODES AND TEST FREQUENCY		9
2.4. EQUIPMENTS USED DURING THE TEST		10
2.5. RELATED SUBMITTAL(S) / GRANT (S)		10
2.6. MODIFICATIONS		11
3. TEST CONDITIONS AND RESULTS		12
3.1. CONDUCTED EMISSIONS TEST		12
3.2. RADIATED EMISSIONS AND BAND EDGE		15
3.3. MAXIMUM CONDUCTED OUTPUT POWER		25
3.4. POWER SPECTRAL DENSITY		26
3.5. 6dB BANDWIDTH		27
3.6. OUT-OF-BAND EMISSIONS		28
3.7. ANTENNA REQUIREMENT		29
4. TEST SETUP PHOTOS OF THE EUT		30
5. PHOTOS OF THE EUT		32

1. SUMMARY

1.1. TEST STANDARDS

The tests were performed according to following standards:

[47 CFR Part 15, Subpart C 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

[ANSI C63.10: 2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 558074 D01 v05r02](#): KDB558074 D01 15.247 Meas Guidance v05r02

1.2. Test Description

47 CFR Part 15, Subpart C 15.247		
47 CFR Part 15, Subpart C 15.207	AC Power Conducted Emission	PASS
47 CFR Part 15, Subpart C 15.247(a)(2)	6dB Bandwidth	PASS
47 CFR Part 15, Subpart C 15.247(d)	Spurious RF Conducted Emission	PASS
47 CFR Part 15, Subpart C 15.247(b)	Maximum Conducted Output Power	PASS
47 CFR Part 15, Subpart C 15.247(e)	Power Spectral Density	PASS
47 CFR Part 15, Subpart C 15.109/ 15.205/ 15.209	Radiated Emissions	PASS
47 CFR Part 15, Subpart C 15.247(d)	Band Edge	PASS
47 CFR Part 15, Subpart C 15.203/15.247 (b)	Antenna Requirement	PASS

1.3. Test Facility

1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co.,Ltd.
Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Nanshan District, Shenzhen, China
518055

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.10 and CISPR 32/EN 55032 requirements.

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L7497

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No. 4343.01

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

IC Registration No.: 9618B

CAB identifier: CN0041

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Registration No.: 9618B.

FCC-Registration No.: 399832

Designation No.: CN1216

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 399832.

1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Measurement Uncertainty	Notes
Transmitter power conducted	±0.57 dB	(1)
Transmitter power Radiated	±2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	±2.20 dB	(1)
Occupied Bandwidth	±0.01ppm	(1)
Radiated Emission9KHz~30MHz	±3.66dB	(1)
Radiated Emission 30~1000MHz	±4.08dB	(1)
Radiated Emission Above 1GHz	±4.32dB	(1)
20dB Emission Bandwidth	±1.9%	(1)
Carrier Frequency Separation	±1.9%	(1)
Maximum Power Spectral Density Level	±0.98 dB	(1)
Number of Hopping Channel	±1.9%	(1)
Time of Occupancy	±0.11%	(1)
Max Peak Conducted Output Power	±0.98 dB	(1)
Band-edge Spurious Emission	±1.21dB	(1)
Conducted RF Spurious Emission	9kHz-7GHz:±1.09dB 7GHz-26.5GHz: ±3.27dB	(1)
Conducted Disturbance0.15~30MHz	±2.96dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

2. GENERAL INFORMATION

2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

2.2. General Description of EUT

Product Name:	CORDLESS ROBOTIC POOL CLEANER
Model/Type reference:	PRT1P
Power supply:	DC 21.6V from battery, charged by Charging base from AC adapter
Adapter information	Model: GM95-252300-1FGN Input: 100-240V~50/60Hz 2.5A Output: 25.2V == 3.0A 75.6W

2.4G Wi-Fi

Supported type:	IEEE 802.11 b/g/n
Modulation:	IEEE 802.11 b: DSSS IEEE 802.11 g/IEEE 802.11 n(HT20)
Operation frequency:	IEEE 802.11 b/IEEE 802.11 g/IEEE 802.11 n(HT20): 2412MHz~2462MHz
Channel number:	IEEE 802.11 b/IEEE 802.11 g/IEEE 802.11 n(HT20): 11
Channel separation:	5MHz
Antenna type:	FPC Antenna
Antenna gain:	-1.12 dBi

Note1: For more details, please refer to the user's manual of the EUT.

Note2: Antenna gain provided by the applicant.

2.3. Description of Test Modes and Test Frequency

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing.

There are 11 channels provided to the EUT and Channel 01/06/11 were selected for Wi-Fi test.

Operation Frequency Wi-Fi :

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432		
6	2437		
7	2442		

Note: The line display in grey were the channel selected for testing

Data Rate Used:

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
Maximum Conducted Output Power Power Spectral Density 6dB Bandwidth Spurious RF conducted emission Radiated Emission 9kHz~1GHz& Radiated Emission 1GHz~10th Harmonic	11b/DSSS	1 Mbps	1/6/11
	11g/OFDM	6 Mbps	1/6/11
	11n(20MHz)/OFDM	6.5Mbps	1/6/11
Band Edge	11b/DSSS	1 Mbps	1/11
	11g/OFDM	6 Mbps	1/11
	11n(20MHz)/OFDM	6.5Mbps	1/11

2.4. Equipments Used during the Test

Conducted Emission						
Test Equipment	Manufacturer	Model No.	Serial No.	Previous calibration	Last Cal.	Cal.Due
EMI Test Receiver	ROHDE & SCHWARZ	ESCI	1166.5950.03	2023/05/04	2024/04/30	2025/04/29
LISN	ROHDE & SCHWARZ	ESH2-Z5	860014/010	2023/05/04	2024/04/30	2025/04/29
Limitator	ROHDE & SCHWARZ	ESH3-Z2	100408	2023/05/04	2024/04/30	2025/04/29
Software:						
Name of Software:			Version:			
ES-K1			V1.71			

Radiated Emission						
Test Equipment	Manufacturer	Model No.	Serial No.	Previous calibration	Last Cal.	Cal.Due
Active Loop Antenna	Da Ze	ZN30900A	/	2021/05/13	2024/04/30	2025/04/29
Double cone logarithmic antenna	Schwarzbeck	VULB 9168	824	/	2023/02/13	2026/02/12
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	/	2024/11/25	2027/11/24
Horn Antenna	Ocean Microwave	OBH100400	26999002	/	2024/12/21	2027/12/20
Amplifier	MRT-AP01M06	MRT	S-001	2023/05/04	2024/04/30	2025/04/29
Amplifier	Agilent	8449B	3008A02306	2023/05/04	2024/04/30	2025/04/29
Amplifier	Brief&Smart	LNA-4018	2104197	2023/05/05	2024/05/03	2025/05/02
EMI Test Receiver	ROHDE & SCHWARZ	ESCI	1166.5950.03	2023/05/04	2024/04/30	2025/04/29
Spectrum Analyzer	RS	FSP	1164.4391.38	2023/05/05	2024/05/03	2025/05/02
Software:						
Name of Software:			Version:			
EZ EMC(Below 1GHz)			V1.1.4.2			
EZ EMC(Above 1GHz)			V1.1.4.2			

RF Conducted						
Test Equipment	Manufacturer	Model No.	Serial No.	Previous calibration	Last Cal.	Cal.Due
Spectrum Analyzer	Keysight	N9020A	MY53420874	2023/05/04	2024/05/01	2025/04/30
Temperature/Humidity Meter	Ji Yu	MC501	/	2023/05/09	2024/05/04	2025/05/03
Software:						
Name of Software:			Version:			
TST-PASS			V2.0			

2.5. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.6. Modifications

No modifications were implemented to meet testing criteria.

3. TEST CONDITIONS AND RESULTS

3.1. Conducted Emissions Test


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION





TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a a landing system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10:2013.
2. Support equipment, if needed, was placed as per ANSI C63.10:2013.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2013.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST RESULTS

Remark:802.11b/802.11g/802.11n(HT20) mode all have been tested ,only worse case is reported.

Test Mode	802.11b	Line:	L																																																								
Start of Test:	1/7/2025 / 9:19:48AM																																																										
SCAN TABLE: "Voltage (9K-30M) FIN"																																																											
Short Description: 150K-30M Voltage																																																											
																																																											
MEASUREMENT RESULT: "CTL241226945_fin" 1/7/2025 9:22AM <table> <thead> <tr> <th>Frequency MHz</th> <th>Level dBμV</th> <th>Transd dB</th> <th>Limit dBμV</th> <th>Margin dB</th> <th>Detector</th> <th>Line</th> <th>PE</th> </tr> </thead> <tbody> <tr> <td>0.154500</td> <td>45.40</td> <td>10.0</td> <td>66</td> <td>20.4</td> <td>QP</td> <td>L1</td> <td>GND</td> </tr> <tr> <td>0.186000</td> <td>50.00</td> <td>10.0</td> <td>64</td> <td>14.2</td> <td>QP</td> <td>L1</td> <td>GND</td> </tr> <tr> <td>2.062500</td> <td>39.10</td> <td>10.1</td> <td>56</td> <td>16.9</td> <td>QP</td> <td>L1</td> <td>GND</td> </tr> <tr> <td>2.157000</td> <td>38.80</td> <td>10.1</td> <td>56</td> <td>17.2</td> <td>QP</td> <td>L1</td> <td>GND</td> </tr> <tr> <td>17.097000</td> <td>48.60</td> <td>11.2</td> <td>60</td> <td>11.4</td> <td>QP</td> <td>L1</td> <td>GND</td> </tr> </tbody> </table>				Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE	0.154500	45.40	10.0	66	20.4	QP	L1	GND	0.186000	50.00	10.0	64	14.2	QP	L1	GND	2.062500	39.10	10.1	56	16.9	QP	L1	GND	2.157000	38.80	10.1	56	17.2	QP	L1	GND	17.097000	48.60	11.2	60	11.4	QP	L1	GND								
Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE																																																				
0.154500	45.40	10.0	66	20.4	QP	L1	GND																																																				
0.186000	50.00	10.0	64	14.2	QP	L1	GND																																																				
2.062500	39.10	10.1	56	16.9	QP	L1	GND																																																				
2.157000	38.80	10.1	56	17.2	QP	L1	GND																																																				
17.097000	48.60	11.2	60	11.4	QP	L1	GND																																																				
MEASUREMENT RESULT: "CTL241226945_fin2" 1/7/2025 9:22AM <table> <thead> <tr> <th>Frequency MHz</th> <th>Level dBμV</th> <th>Transd dB</th> <th>Limit dBμV</th> <th>Margin dB</th> <th>Detector</th> <th>Line</th> <th>PE</th> </tr> </thead> <tbody> <tr> <td>0.181500</td> <td>31.70</td> <td>10.0</td> <td>54</td> <td>22.7</td> <td>AV</td> <td>L1</td> <td>GND</td> </tr> <tr> <td>0.190500</td> <td>32.10</td> <td>10.0</td> <td>54</td> <td>21.9</td> <td>AV</td> <td>L1</td> <td>GND</td> </tr> <tr> <td>2.125500</td> <td>28.00</td> <td>10.1</td> <td>46</td> <td>18.0</td> <td>AV</td> <td>L1</td> <td>GND</td> </tr> <tr> <td>2.274000</td> <td>28.40</td> <td>10.1</td> <td>46</td> <td>17.6</td> <td>AV</td> <td>L1</td> <td>GND</td> </tr> <tr> <td>5.784000</td> <td>32.00</td> <td>10.2</td> <td>50</td> <td>18.0</td> <td>AV</td> <td>L1</td> <td>GND</td> </tr> <tr> <td>16.975500</td> <td>43.10</td> <td>11.2</td> <td>50</td> <td>6.9</td> <td>AV</td> <td>L1</td> <td>GND</td> </tr> </tbody> </table>				Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE	0.181500	31.70	10.0	54	22.7	AV	L1	GND	0.190500	32.10	10.0	54	21.9	AV	L1	GND	2.125500	28.00	10.1	46	18.0	AV	L1	GND	2.274000	28.40	10.1	46	17.6	AV	L1	GND	5.784000	32.00	10.2	50	18.0	AV	L1	GND	16.975500	43.10	11.2	50	6.9	AV	L1	GND
Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE																																																				
0.181500	31.70	10.0	54	22.7	AV	L1	GND																																																				
0.190500	32.10	10.0	54	21.9	AV	L1	GND																																																				
2.125500	28.00	10.1	46	18.0	AV	L1	GND																																																				
2.274000	28.40	10.1	46	17.6	AV	L1	GND																																																				
5.784000	32.00	10.2	50	18.0	AV	L1	GND																																																				
16.975500	43.10	11.2	50	6.9	AV	L1	GND																																																				

Test Mode	802.11b	Line:	N																																																								
Start of Test: 1/7/2025 / 9:28:49AM																																																											
SCAN TABLE: "Voltage (9K-30M) FIN"																																																											
Short Description: 150K-30M Voltage																																																											
																																																											
MEASUREMENT RESULT: "CTL241226948_fin" 1/7/2025 9:31AM <table> <thead> <tr> <th>Frequency MHz</th> <th>Level dBμV</th> <th>Transd dB</th> <th>Limit dBμV</th> <th>Margin dB</th> <th>Detector</th> <th>Line</th> <th>PE</th> </tr> </thead> <tbody> <tr><td>0.483000</td><td>42.10</td><td>10.0</td><td>56</td><td>14.2</td><td>QP</td><td>N</td><td>GND</td></tr> <tr><td>0.852000</td><td>42.80</td><td>10.1</td><td>56</td><td>13.2</td><td>QP</td><td>N</td><td>GND</td></tr> <tr><td>1.896000</td><td>43.70</td><td>10.1</td><td>56</td><td>12.3</td><td>QP</td><td>N</td><td>GND</td></tr> <tr><td>2.440500</td><td>43.60</td><td>10.1</td><td>56</td><td>12.4</td><td>QP</td><td>N</td><td>GND</td></tr> <tr><td>16.953000</td><td>48.10</td><td>11.2</td><td>60</td><td>11.9</td><td>QP</td><td>N</td><td>GND</td></tr> <tr><td>23.901000</td><td>41.40</td><td>10.7</td><td>60</td><td>18.6</td><td>QP</td><td>N</td><td>GND</td></tr> </tbody> </table>				Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE	0.483000	42.10	10.0	56	14.2	QP	N	GND	0.852000	42.80	10.1	56	13.2	QP	N	GND	1.896000	43.70	10.1	56	12.3	QP	N	GND	2.440500	43.60	10.1	56	12.4	QP	N	GND	16.953000	48.10	11.2	60	11.9	QP	N	GND	23.901000	41.40	10.7	60	18.6	QP	N	GND
Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE																																																				
0.483000	42.10	10.0	56	14.2	QP	N	GND																																																				
0.852000	42.80	10.1	56	13.2	QP	N	GND																																																				
1.896000	43.70	10.1	56	12.3	QP	N	GND																																																				
2.440500	43.60	10.1	56	12.4	QP	N	GND																																																				
16.953000	48.10	11.2	60	11.9	QP	N	GND																																																				
23.901000	41.40	10.7	60	18.6	QP	N	GND																																																				
MEASUREMENT RESULT: "CTL241226948_fin2" 1/7/2025 9:31AM <table> <thead> <tr> <th>Frequency MHz</th> <th>Level dBμV</th> <th>Transd dB</th> <th>Limit dBμV</th> <th>Margin dB</th> <th>Detector</th> <th>Line</th> <th>PE</th> </tr> </thead> <tbody> <tr><td>0.622500</td><td>27.90</td><td>10.0</td><td>46</td><td>18.1</td><td>AV</td><td>N</td><td>GND</td></tr> <tr><td>0.852000</td><td>28.70</td><td>10.1</td><td>46</td><td>17.3</td><td>AV</td><td>N</td><td>GND</td></tr> <tr><td>2.053500</td><td>33.50</td><td>10.1</td><td>46</td><td>12.5</td><td>AV</td><td>N</td><td>GND</td></tr> <tr><td>2.292000</td><td>34.40</td><td>10.1</td><td>46</td><td>11.6</td><td>AV</td><td>N</td><td>GND</td></tr> <tr><td>8.227500</td><td>33.20</td><td>10.5</td><td>50</td><td>16.8</td><td>AV</td><td>N</td><td>GND</td></tr> <tr><td>17.304000</td><td>42.10</td><td>11.2</td><td>50</td><td>7.9</td><td>AV</td><td>N</td><td>GND</td></tr> </tbody> </table>				Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE	0.622500	27.90	10.0	46	18.1	AV	N	GND	0.852000	28.70	10.1	46	17.3	AV	N	GND	2.053500	33.50	10.1	46	12.5	AV	N	GND	2.292000	34.40	10.1	46	11.6	AV	N	GND	8.227500	33.20	10.5	50	16.8	AV	N	GND	17.304000	42.10	11.2	50	7.9	AV	N	GND
Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE																																																				
0.622500	27.90	10.0	46	18.1	AV	N	GND																																																				
0.852000	28.70	10.1	46	17.3	AV	N	GND																																																				
2.053500	33.50	10.1	46	12.5	AV	N	GND																																																				
2.292000	34.40	10.1	46	11.6	AV	N	GND																																																				
8.227500	33.20	10.5	50	16.8	AV	N	GND																																																				
17.304000	42.10	11.2	50	7.9	AV	N	GND																																																				

3.2. Radiated Emissions and Band Edge

Limit

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission out of authorized band shall not exceed the following table at a 3 meters measurement distance.


In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



Test Procedure


1. Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.


TEST RESULTS

Remark:

1. All three channels (lowest/middle/highest) of each mode were measured below 1GHz and recorded worst case at 802.11b low channel.
2. All three channels (lowest/middle/highest) of each mode were measured above 1GHz and recorded worst case at 802.11b mode.
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, Found the emission level are attenuated 20dB below the limits from 9 kHz to 30MHz, so it does not recorded in report.

For 30MHz-1GHz

Test mode:	Wi-Fi	Polarization:	Horizontal								
	Shenzhen CTL Testing Technology Co., Ltd Tel: +86-755-89486194										
Radiated Emission Measurement											
File :RF_1	Data :#521	Date: 2025/01/14	Time: 23:32:46								
80.0 dBuV/m											
70											
60											
50											
40											
30											
20											
10											
0.0											
30.000	60.00	[MHz]	300.00								
			1000.000								
											
Site LAB Chamber 2	Polarization: Horizontal	Temperature: 25(C)									
Limit: FCC Part15 RE-Class C_30-1000MHz	Power:	Humidity: 50 %									
EUT:	Distance: 3m										
M/N: PRT1P											
Mode: Wi-Fi2.4G 2412MHz											
Note: Shenzhen Aiper Intelligent Co.,Ltd. ?											
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	100.7571	13.54	11.61	25.15	43.50	18.35	QP	100	0	P	
2	102.0015	15.17	12.00	27.17	43.50	16.33	QP	100	0	P	
3	103.2156	24.42	11.79	36.21	43.50	7.29	peak	100	70	P	
4	104.4901	27.63	12.16	39.79	43.50	3.71	peak	100	8	P	
5	114.7155	25.08	13.03	38.11	43.50	5.39	peak	100	8	P	
6	117.7210	22.63	13.34	35.97	43.50	7.53	peak	100	8	P	

Test mode:	Wi-Fi	Polarization:	Vertical								
	Shenzhen CTL Testing Technology Co., Ltd Tel: +86-755-89486194										
Radiated Emission Measurement											
File :RF_1 80.0 dBuV/m	Data :#522	Date: 2025/01/14	Time: 23:33:49								
											
Site LAB Chamber 2 Limit: FCC Part15 RE-Class C_30-1000MHz EUT: M/N: PRT1P Mode: Wi-Fi2.4G 2412MHz Note: Shenzhen Aiper Intelligent Co.,Ltd. ?	Polarization: Vertical	Temperature: 25(C)									
Power: Distance: 3m		Humidity: 50 %									
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	100.8897	16.86	11.60	28.46	43.50	15.04	QP	100	0	P	
2	101.7703	18.48	11.91	30.39	43.50	13.11	QP	100	0	P	
3	112.2288	16.46	12.72	29.18	43.50	14.32	QP	100	0	P	
4	113.6645	26.60	12.95	39.55	43.50	3.95	peak	100	13	P	
5	134.4413	24.22	14.15	38.37	43.50	5.13	peak	100	239	P	
6	136.1014	25.04	14.26	39.30	43.50	4.20	peak	100	115	P	

For 1GHz to 25GHz

Note: 802.11b/802.11g/802.11n (HT20) all have been tested, only worse case 802.11b is reported

802.11b Mode (above 1GHz)

Horizontal



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194


Radiated Emission Measurement

File :RF_12
80.0 dBuV/m

Data #:2645

Date: 2024/12/31

Time: 18:54:19



Site LAB Chamber 2

Polarization: **Horizontal**

Temperature: 25(C)

Limit: FCC Part15 RE-Class C_Above 1GHz_PK

Power:

Humidity: 50 %

EUT:

Distance: 3m

M/N: PRT1P

Mode: Wi-Fi2.4G 2412MHz

Note: Shenzhen Aiper Intelligent Co.,Ltd.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	1996.625	58.91	-18.82	40.09	74.00	33.91	peak	150	337	P	
2	4000.500	50.87	-10.30	40.57	74.00	33.43	peak	150	326	P	
3	8242.000	48.34	-2.33	46.01	74.00	27.99	peak	150	107	P	
4	10626.250	49.35	0.10	49.45	74.00	24.55	peak	150	33	P	
5	13388.750	46.98	3.47	50.45	74.00	23.55	peak	150	44	P	
6	16491.250	45.29	6.16	51.45	74.00	22.55	peak	150	64	P	

Vertical



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194


Radiated Emission Measurement

File :RF_12
80.0 dBuV/m

Data :#2646

Date: 2024/12/31

Time: 18:55:23



Site LAB Chamber 2
Limit: FCC Part15 RE-Class C_Above 1GHz_PK
EUT:
M/N: PRT1P
Mode: Wi-Fi2.4G 2412MHz
Note: Shenzhen Aiper Intelligent Co.,Ltd.

Polarization: **Vertical**

Temperature: 25(C)

Power:

Humidity: 50 %

Distance: 3m


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	1996.625	60.99	-18.82	42.17	74.00	31.83	peak	150	45	P	
2	4803.750	50.42	-8.09	42.33	74.00	31.67	peak	150	358	P	
3	6916.000	48.65	-3.96	44.69	74.00	29.31	peak	150	171	P	
4	10231.000	47.49	0.26	47.75	74.00	26.25	peak	150	76	P	
5	11965.000	47.84	2.08	49.92	74.00	24.08	peak	150	23	P	
6	17498.500	42.36	9.16	51.52	74.00	22.48	peak	150	317	P	


REMARKS:


1. 18GHz-26GHz not recorded for no spurious point have a margin of less than 6 dB with respect to the limits.
2. PK detector measurement value is lower than the average limit. Therefore, there is no need to test AV detector measurements.


Results of Band Edges Test (Radiated)

Note: 802.11b/802.11g/802.11n (HT20) all have been tested, only worse case 802.11n (HT20) is reported.









3.3. Maximum Conducted Output Power

Limit


The Maximum Peak Output Power Measurement is 30dBm.

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum.

1. Measure the duty cycle D of the transmitter output signal as described in 11.6.
2. Set span to at least 1.5 times the OBW.
3. Set RBW = 1% to 5% of the OBW, not to exceed 1 MHz.
4. Set VBW $\geq [3 \times \text{RBW}]$.
5. Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
6. Sweep time = auto.
7. Detector = RMS (i.e., power averaging), if available. Otherwise, use the sample detector mode.
8. Do not use sweep triggering. Allow the sweep to "free run."
9. Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the ON and OFF periods of the transmitter.
10. Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function with band limits set equal to the OBW band edges. If the instrument does not have a band power function, then sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
11. Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured power to compute the average power during the actual transmission times (because the measurement represents an average over both the ON and OFF times of the transmission). For example, add $[10 \log (1/0.25)] = 6 \text{ dB}$ if the duty cycle is 25%.

Test Configuration



Test Results

Raw data reference to Section 3 of document No. CTL2411257011-WF03_2.4G_Wi-Fi_Appendix.

3.4. Power Spectral Density

Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Test Procedure

12. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance.
13. Set the RBW \geq 3 kHz.
14. Set the VBW $\geq 3 \times$ RBW.
15. Set the span to 1.5 times the DTS channel bandwidth.
16. Detector = Average.
17. Sweep points = 40001
18. Trace mode = max hold.
19. Allow trace to fully stabilize.
20. Use the peak marker function to determine the maximum power level.
21. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
22. The resulting PSD level must be 8dBm.

Test Configuration



Test Results

Raw data reference to Section 4 of document No. CTL2411257011-WF03_2.4G Wi-Fi_Appendix.

3.5. 6dB Bandwidth

Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

Test Configuration



Test Results

Raw data reference to Section 2 of document No. CTL2411257011-WF03_2.4G_Wi-Fi_Appendix.

3.6. Out-of-band Emissions

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector , and max hold. Measurements utilizing these setting are made of the in-band reference level, bandedge and out-of-band emissions.

Test Configuration



Test Results

Raw data reference to Section 5 of document No. CTL2411257011-WF03_2.4G Wi-Fi_Appendix.

3.7. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

FCC CFR Title 47 Part 15 Subpart C Section 15.247(b) (4):

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


Test Result:

The maximum gain of antenna was -1.12dBi.



4. Test Setup Photos of the EUT





5. Photos of the EUT

Reference to the test report No. CTL2411257011-WF01.

***** End of Report *****