### **RF Exposure Evaluation**

FCC ID: 2BD8F-PS4290

## **Limits for Maximum Permissible Exposure (MPE)**

#### SAR EVALUATION

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

Limits for SAR evaluation

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [ $\sqrt{f(GHz)}$ ]  $\leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation17
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $\leq$  5 mm, a distance of 5 mm is applied to determine SAR test exclusion



# **RF Exposure Evaluation**

FCC ID: 2BD8F-PS4290

## **Measurement Result**

Operation Mode:	Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated	Exclusion
				(dBm)	(mW)	value	threshold
GFSK	Lowest (2402MHz)	0.871	0±1	1	1.26	0.39	
	Middle (2441MHz)	0.070	0±1	1	1.26	0.39	
	Highest (2480MHz)	-1.309	-1±1	0	1.00	0.31	
Pi4-DQPSK	Lowest (2402MHz)	3.123	3±1	4	2.51	0.78	
	Middle (2441MHz)	2.128	2±1	3	2.00	0.62	3.0
	Highest (2480MHz)	0.647	0±1	1	1.26	0.40	
8DPSK	Lowest (2402MHz)	3.583	3±1	4	2.51	0.78	
	Middle (2441MHz)	2.567	2±1	3	2.00	0.62	
	Highest (2480MHz)	1.035	1±1	2	1.58	0.50	
	Conclusion: the	calculated value ≤3.	0, SAR is exem	pted.			

Prepared by:

Jerry Hu/ Engineer

Approved & Authorized Signer:

Frank Offering SERVICE

Issue Date: August 19, 2024

---END----